

Vectorial Cyclic Codes and Their Structure

Sümeysra Bedir

Thesis Supervisor: Assoc. Prof. Dr. Bayram Ali ERSOY

Yıldız Technical University
Department of Mathematics

PhD Thesis Report - II
30.12.2016

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes

as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary

Rank Metric Spaces

Construction of

Optimal Codes in M_{2n}

Code Construction

Proposition and

Examples

Future Studies

References

- ▶ Pseudo-cyclic codes over finite fields were first introduced in (Peterson, 1972).

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes
as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary

Rank Metric Spaces

Construction of
Optimal Codes in $M_{\mathbb{F}_q}$

Code Construction
Proposition and
Examples

Future Studies

References

- ▶ Pseudo-cyclic codes over finite fields were first introduced in (Peterson, 1972).
- ▶ Although every pseudo-cyclic code corresponds to a shortened cyclic code over finite fields, researches have showned that the method not only provides a direct construction for many linear codes but also may be a fruitful way to construct many good codes over different algebraic structures for which a construction is not introduced yet (Lopez et al., 2009; Alahamdi et al., 2016).

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes

as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Tern

Rank Metric Spaces

Construction of
Optimal Codes in M_{2n}

Code Construction
Proposition and
Examples

Future Studies

References

- ▶ Pseudo-cyclic codes over finite fields were first introduced in (Peterson, 1972).
- ▶ Although every pseudo-cyclic code corresponds to a shortened cyclic code over finite fields, researches have showned that the method not only provides a direct construction for many linear codes but also may be a fruitful way to construct many good codes over different algebraic structures for which a construction is not introduced yet (Lopez et al., 2009; Alahamdi et al., 2016).
- ▶ In the first section we give the definitions for the pseudo-cyclic shift and pseudo-cyclic codes.

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Term
Rank Metric Spaces

Construction of
Optimal Codes in M_{2n}

Code Construction
Proposition and
Examples

Future Studies

References

- ▶ Pseudo-cyclic codes over finite fields were first introduced in (Peterson, 1972).
- ▶ Although every pseudo-cyclic code corresponds to a shortened cyclic code over finite fields, researches have showned that the method not only provides a direct construction for many linear codes but also may be a fruitful way to construct many good codes over different algebraic structures for which a construction is not introduced yet (Lopez et al., 2009; Alahamdi et al., 2016).
- ▶ In the first section we give the definitions for the pseudo-cyclic shift and pseudo-cyclic codes.
- ▶ In the second section we mention about our previous studies briefly.

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary
Rank Metric Spaces

Construction of
Optimal Codes in M_{2n}

Code Construction
Proposition and
Examples

Future Studies

References

- ▶ Pseudo-cyclic codes over finite fields were first introduced in (Peterson, 1972).
- ▶ Although every pseudo-cyclic code corresponds to a shortened cyclic code over finite fields, researches have showned that the method not only provides a direct construction for many linear codes but also may be a fruitful way to construct many good codes over different algebraic structures for which a construction is not introduced yet (Lopez et al., 2009; Alahamdi et al., 2016).
- ▶ In the first section we give the definitions for the pseudo-cyclic shift and pseudo-cyclic codes.
- ▶ In the second section we mention about our previous studies briefly.
- ▶ Finally, we introduce our recent study on pseudo-cyclic code constructions over different metric spaces.

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary Codes (ICCC, 2015)

Pseudo-cyclic Codes with Applications to DNA (ICFAS, 2016)

Ongoing Research

Codes over Term

Rank Metric Spaces

Construction of Optimal Codes in M_q

Code Construction Proposition and Examples

Future Studies

References

Pseudo-cyclic Shift

Let $F = GF(q)$ be a finite field with q elements and let F^n be the n -dimensional vector space over F .

Let $c = (c_0, c_1, \dots, c_{n-1})$ be any vector in F^n . We fix a shift vector $v = (v_0, v_1, \dots, v_{n-1})$ and define the following transformation

$$\begin{aligned}\tau_v: F^n &\rightarrow F^n \\ (c_0, c_1, \dots, c_{n-1}) &\mapsto (v_0 c_{n-1}, c_0 + v_1 c_{n-1}, \dots, c_{n-2} + v_{n-1} c_{n-1})\end{aligned}$$

- It has the following representation matrix as $\tau_v(c) = T_v c$, and T_v is exactly the companion matrix for $f(x) = x^n - v(x)$.

$$T_v = \begin{bmatrix} 0 & \cdots & \cdots & 0 & v_0 \\ 1 & 0 & \cdots & 0 & v_1 \\ 0 & 1 & \ddots & \vdots & \vdots \\ \vdots & \ddots & \ddots & 0 & \vdots \\ 0 & \cdots & 0 & 1 & v_{n-1} \end{bmatrix}_{n \times n}$$

Example

Let $c = (c_0, c_1, c_2)$ be a vector in some vector space F^3 . Let $v = (v_0, v_1, v_2)$ be the shift vector.

Thus we have the following shift representation matrix;

$$T_v = \begin{bmatrix} 0 & 0 & v_0 \\ 1 & 0 & v_1 \\ 0 & 1 & v_2 \end{bmatrix}$$

And the transformation τ_v moves $c = (c_0, c_1, c_2)$ to the vector $\tau_v(c) = (v_0c_2, c_0 + v_1c_2, c_1 + v_2c_2)$ as follows;

$$\tau_v(c) = T_v c = \begin{bmatrix} 0 & 0 & v_0 \\ 1 & 0 & v_1 \\ 0 & 1 & v_2 \end{bmatrix} \begin{bmatrix} c_0 \\ c_1 \\ c_2 \end{bmatrix} = \begin{bmatrix} v_0c_2 \\ c_0 + v_1c_2 \\ c_1 + v_2c_2 \end{bmatrix}$$

- T_v is the companion matrix for $f(x) = x^3 - (v_0 + v_1x + v_2x^2)$.

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes

as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary

Codes (ICCC, 2015)

Pseudo-cyclic Codes

with Applications to

DNA (ICFAS, 2016)

Ongoing Research

Codes over Tern

Rank Metric Spaces

Construction of

Optimal Codes in $M_{n,k}$

Code Construction

Proposition and

Examples

Future Studies

References

Different Notations of the shift and Related Structures

Vectorial Cyclic Codes and Their Structure

Sümeysra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

- ▶ Pseudo-cyclic shift, Pseudo-cyclic codes
- ▶ Polycyclic shift, Polycyclic codes
- ▶ $p(x)$ —circulants, Generalized cyclic codes
- ▶ v —vector cyclic shift, v —vector based codes

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes
as Invariant
Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary
Rank Metric Spaces

Construction of
Optimal Codes in M_{25}

Code Construction
Proposition and
Examples

Future Studies

References

Definition

A linear code C with length n over a finite field F is called *pseudo-cyclic* with respect to the polynomial $v(x) = v_0 + v_1x + \cdots + v_{n-1}x^{n-1}$, if whenever $c = (c_0, c_1, \dots, c_{n-1})$ is in C , so is its v -pseudo-cyclic shift $(v_0c_{n-1}, c_0 + v_1c_{n-1}, \dots, c_{n-2} + v_{n-1}c_{n-1})$.

- ▶ A pseudo-cyclic code with respect to v is invariant under τ_v .

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes

as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary
Rank Metric Spaces

Construction of
Optimal Codes in M_{2n}

Code Construction
Proposition and
Examples

Future Studies

References

Definition

A linear code C with length n over a finite field F is called *pseudo-cyclic* with respect to the polynomial $v(x) = v_0 + v_1x + \cdots + v_{n-1}x^{n-1}$, if whenever $c = (c_0, c_1, \dots, c_{n-1})$ is in C , so is its v -pseudo-cyclic shift $(v_0c_{n-1}, c_0 + v_1c_{n-1}, \dots, c_{n-2} + v_{n-1}c_{n-1})$.

- ▶ A pseudo-cyclic code with respect to v is invariant under τ_v .
- ▶ Any cyclic code is *pseudo-cyclic* with respect to $v = (1, 0, \dots, 0) \cdot (v(x) = 1)$

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary

Rank Metric Spaces

Construction of
Optimal Codes in M_{2n}

Code Construction
Proposition and
Examples

Future Studies

References

Definition

A linear code C with length n over a finite field F is called *pseudo-cyclic* with respect to the polynomial $v(x) = v_0 + v_1x + \cdots + v_{n-1}x^{n-1}$, if whenever $c = (c_0, c_1, \dots, c_{n-1})$ is in C , so is its v -pseudo-cyclic shift $(v_0c_{n-1}, c_0 + v_1c_{n-1}, \dots, c_{n-2} + v_{n-1}c_{n-1})$.

- ▶ A pseudo-cyclic code with respect to v is invariant under τ_v .
- ▶ Any cyclic code is *pseudo-cyclic* with respect to $v = (1, 0, \dots, 0) \cdot (v(x) = 1)$
- ▶ Any constacyclic code with respect to α , is *pseudo-cyclic* with respect to $v = (\alpha, 0, \dots, 0) \cdot (v(x) = \alpha)$

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary

Rank Metric Spaces

Construction of
Optimal Codes in M_{2n}

Code Construction
Proposition and
Examples

Future Studies

References

- In terms of the usual correspondance to the polynomial ring $F[x]/(x^n - v(x))$, multiplying a polynomial by x corresponds to a pseudo-cyclic shift with respect to v , therefore a *pseudo-cyclic* code over F^n corresponds to an ideal in $F[x]/(x^n - v(x))$.

Example

Consider $c(x) = c_0 + c_1x + c_2x^2$. Let $v(x) = v_0 + v_1x + v_2x^2$, and we are in $F_q[x]/(x^3 - v(x))$.

Multiplying $c(x)$ by x , we get;

$$\begin{aligned}(c_0 + c_1x + c_2x^2).x &= c_0x + c_1x^2 + c_2x^3 \\ &= c_0x + c_1x^2 + c_2(v(x)) \\ &= c_0x + c_1x^2 + c_2(v_0 + v_1x + v_2x^2) \\ &= c_2v_0 + (c_0 + c_2v_1)x + (c_1 + c_2v_2)x^2\end{aligned}$$

So this gives us the pseudo-cyclic shift,

$$(c_0, c_1, c_2) \rightarrow (c_2v_0, c_0 + c_2v_1, c_1 + c_2v_2)$$

Pseudo-cyclic Codes as Invariant Submodules

Vectorial Cyclic
Codes and
Their Structure

Sümeýra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

- ▶ Pseudo-cyclic codes over finite chain rings are recently studied by (Lopez, et al., 2009).

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes
as Invariant
Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary
Rank Metric Spaces

Construction of
Optimal Codes in M_{2n}

Code Construction
Proposition and
Examples

Future Studies

References

Pseudo-cyclic Codes as Invariant Submodules

Vectorial Cyclic
Codes and
Their Structure

Sümeýra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

- ▶ Pseudo-cyclic codes over finite chain rings are recently studied by (Lopez, et al., 2009).
- ▶ Let $f(x) = x^n - v(x) = f_1 \cdot f_2 \cdots f_t$ be the factorization of a regular polynomial $f(x)$ over a finite chain ring R into pairwise coprime, monic, basic irreducible polynomial factors. In this case, we can apply the generalization of the Sun Zi Theorem;

$$R/(f(x)) = R/(f_1(x)) \oplus \cdots \oplus R/(f_t(x))$$

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes
as Invariant
Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Tern

Rank Metric Spaces

Construction of
Optimal Codes in M_{2n}

Code Construction
Proposition and
Examples

Future Studies

References

Theorem

Let C be a linear polycyclic code of length n over R . Then the following facts hold

(1) $C = \bigoplus_{j=1}^s U_{i_j}$ for some minimal τ_v -invariant submodules of R^n

and $\text{rank}(C) = \sum_{j=1}^s k_{i_j}$ where k_{i_j} is the rank of U_{i_j}

(2) $h(x) = f_{i_1}(x) \cdot f_{i_2}(x) \cdot \dots \cdot f_{i_s}(x)$ is the minimal polynomial of τ_v over C

(3) $\text{rank}(h(T_v)) = n - \text{rank}(C)$

(4) $c \in C$ if and only if $h(T_v)c = 0$.

- If $g(x) = f(x)/h(x)$ is the generating polynomial of a polycyclic code C , then $H = h(T_v)$ is a parity check matrix for C and $G = g(T_v^{tr})$ is a generator matrix for C . One may also notice that G is indeed a full vector-circulant matrix (Jitman, 2013) of $c = (g_0, g_1, \dots, g_{n-1})$ with respect to v .

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary Codes (ICCC, 2015)

Pseudo-cyclic Codes with Applications to DNA (ICFAS, 2016)

Ongoing Research

Codes over Term

Rank Metric Spaces

Construction of

Optimal Codes in M_{α}

Code Construction

Proposition and

Examples

Future Studies

References

Vector Circulant Matrices (p(x)-circulants)

Vectorial Cyclic Codes and Their Structure

Sümeysra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

The generator matrix of a pseudo-cyclic code is a vector circulant matrix.

Vector circulant matrices are obtained by applying recursively the vector cyclic shift to the generating vector in the first row.

Namely, if we have $g = (g_0, g_1, \dots, g_{n-1})$ as the generating vector (the coefficient vector for the generating polynomial $g(x)$), then the generating matrix is obtained as follows;

$$G = \begin{bmatrix} \dots & g & \dots \\ \dots & \tau_v(g) & \dots \\ \dots & \tau_v^2(g) & \dots \\ & \vdots & \\ \dots & \tau_v^{n-1}(g) & \dots \end{bmatrix}_{n \times n} = g(T_v^{tr})$$

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary

Codes (ICCC, 2015)

Pseudo-cyclic Codes

with Applications to

DNA (ICFAS, 2016)

Ongoing Research

Codes over Term

Rank Metric Spaces

Construction of

Optimal Codes in M_{TR}

Code Construction

Proposition and

Examples

Future Studies

References

Example

Consider the vector space F_7^4 .

Fix the shift vector $v = (2, 3, 0, 1)$ and construct the v -vector circulant matrix for $g = (1, 2, 3, 4)$.

$$\tau_v((g_0, g_1, g_2, g_3)) = (v_0 g_3, g_0 + v_1 g_3, g_1 + v_2 g_3, g_2 + v_3 g_3).$$

$$v = (2, 3, 0, 1);$$

$$T_v = \begin{bmatrix} 0 & 0 & 0 & 2 \\ 1 & 0 & 0 & 3 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 1 \end{bmatrix}, g = \begin{bmatrix} 1 \\ 2 \\ 3 \\ 4 \end{bmatrix};$$

$$Tg = \begin{bmatrix} 1 \\ 6 \\ 2 \\ 0 \end{bmatrix}, T^2g = \begin{bmatrix} 0 \\ 1 \\ 6 \\ 2 \end{bmatrix}, T^3g = \begin{bmatrix} 4 \\ 6 \\ 1 \\ 1 \end{bmatrix};$$

$$G = \begin{bmatrix} 1 & 2 & 3 & 4 \\ 1 & 6 & 2 & 0 \\ 0 & 1 & 6 & 2 \\ 4 & 6 & 1 & 1 \end{bmatrix}$$

Our Previous Studies

Polycyclic Quaternary Codes (ICCC, 2015)

- ▶ We pointed out the algebraic structure via submodule representation of quaternary pseudo-cyclic codes and their duals.

Vectorial Cyclic Codes and Their Structure

Sümeysra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary Codes (ICCC, 2015)

Pseudo-cyclic Codes with Applications to DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary

Rank Metric Spaces

Construction of

Optimal Codes in M_{2n}

Code Construction

Proposition and

Examples

Future Studies

References

Our Previous Studies

Polycyclic Quaternary Codes (ICCC, 2015)

- ▶ We pointed out the algebraic structure via submodule representation of quaternary pseudo-cyclic codes and their duals.
- ▶ We obtained good pseudo-cyclic codes over \mathbb{Z}_4 , most of which are new and optimal linear codes with respect to the existing database of quaternary codes (Asamov, 2007)

Our Previous Studies

Pseudo-cyclic Codes with Applications to DNA (ICFAS, 2016)

- ▶ We introduced the construction of polycyclic reversible DNA codes generated by polynomials of 4^k -lifted form

Vectorial Cyclic Codes and Their Structure

Sümeysra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary Codes (ICCC, 2015)

Pseudo-cyclic Codes with Applications to DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary

Rank Metric Spaces

Construction of

Optimal Codes in M_{2n}

Code Construction

Proposition and

Examples

Future Studies

References

Our Previous Studies

Pseudo-cyclic Codes with Applications to DNA (ICFAS, 2016)

- ▶ We introduced the construction of polycyclic reversible DNA codes generated by polynomials of 4^k -lifted form
- ▶ We gave some promising examples of these codes which are MDS and satisfy the Griesmer bound.

Vectorial Cyclic
Codes and
Their Structure

Sümeysra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes
as Invariant
Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary

Rank Metric Spaces

Construction of
Optimal Codes in M_{2n}

Code Construction
Proposition and
Examples

Future Studies

References

Term Rank Metric Spaces

The vector space of $m \times n$ matrices over a fixed finite field F_q of q elements become a metric space denoted by M_{TR} , with the term rank metric derived from the term rank weight defined below, given A as an $m \times n$ matrix with $\mathcal{I}(A)$ being the set of rows/columns of A which contains all the nonzero entries of A ;

$$\|A\|_{TR} = \min |\mathcal{I}(A)|$$

If A and B are two $m \times n$ matrices, the term rank distance is defined as;

$$d_{TR} = \|A - B\|_{TR}$$

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes

as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Term
Rank Metric Spaces

Construction of
Optimal Codes in M_{TR}

Code Construction
Proposition and
Examples

Future Studies

References

Examples

$$A = \begin{bmatrix} 0 & 0 & 0 & 0 \\ 1 & 0 & 1 & 1 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix} \Rightarrow \|A\|_{TR} = 1$$

$$A = \begin{bmatrix} 1 & 1 & 1 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \end{bmatrix} \Rightarrow \|A\|_{TR} = 2$$

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes

as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Term

Rank Metric Spaces

Construction of
Optimal Codes in $M_{r,n}$

Code Construction

Proposition and

Examples

Future Studies

References

Codes over Term Rank Metric Spaces

Vectorial Cyclic Codes and Their Structure

Sümeysra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

Codes over term rank metric spaces have applications in information transmission via memoryless matrix channels which appear in the data storage systems, memory cards and some wireless communication systems.

These codes are considered as k -dimensional vector subspaces of $F_q^{m \times n}$. The minimum distance of a code over term rank metric space, denoted by D_{TR} , should clearly be less than or equal to the minimum of $\{m, n\}$ and assuming without the loss of generality that $m \leq n$, we have;

$$D_{TR} = \min_{A \in C - \{0\}} \|A\|_{TR} \leq m$$

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary Codes (ICCC, 2015)

Pseudo-cyclic Codes with Applications to DNA (ICFAS, 2016)

Ongoing Research

Codes over Term Rank Metric Spaces

Construction of Optimal Codes in M_{TR}

Code Construction Proposition and Examples

Future Studies

References

Computing Term Rank Distance

Vectorial Cyclic Codes and Their Structure

Sümeyra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

It is proved that, the term rank weight of a matrix A is equal to the maximum size of a matching of the bipartite graph for which A is the bi-adjacency matrix (Bruualdi et al, 2012).

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary Codes (ICCC, 2015)

Pseudo-cyclic Codes with Applications to DNA (ICFAS, 2016)

Ongoing Research

Codes over Term

Rank Metric Spaces

Construction of Optimal Codes in $M_{r \times n}$

Code Construction

Proposition and Examples

Future Studies

References

Singleton Bound

The only known bound for codes over M_{TR} is the Singleton bound, which is expressed in the following version;

$$k \leq n(m - D_{TR} + 1)$$

If we have the equality, the code is considered to be optimal.

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes

as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Term

Rank Metric Spaces

Construction of

Optimal Codes in M_{TR}

Code Construction

Proposition and

Examples

Future Studies

References

Construction of Optimal Codes

Vectorial Cyclic Codes and Their Structure

Sümeysra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary Codes (ICCC, 2015)

Pseudo-cyclic Codes with Applications to DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary Rank Metric Spaces

Construction of Optimal Codes in M_{2n}

Code Construction Proposition and Examples

Future Studies

References

► Gabudilin Codes (in Rank Metric Spaces)

Construction of Optimal Codes

Vectorial Cyclic Codes and Their Structure

Sümeysra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

- ▶ Gabudilin Codes (in Rank Metric Spaces)
- ▶ by considering a set of all $p(x)$ – *circulant* $m \times n$ matrices over F_q (for $D_{TR} = m$).

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary Codes (ICCC, 2015)

Pseudo-cyclic Codes with Applications to DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary

Rank Metric Spaces

Construction of Optimal Codes in $M_{m,n}$

Code Construction

Proposition and

Examples

Future Studies

References

Construction of Optimal Codes

Vectorial Cyclic Codes and Their Structure

Sümeysra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

- ▶ Gabudilin Codes (in Rank Metric Spaces)
- ▶ by considering a set of all $p(x)$ – *circulant* $m \times n$ matrices over F_q (for $D_{TR} = m$).
- ▶ by Toeplitz-like matrices (for $D_{TR} = m$).

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary Codes (ICCC, 2015)

Pseudo-cyclic Codes with Applications to DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary

Rank Metric Spaces

Construction of Optimal Codes in M_{TR}

Code Construction

Proposition and

Examples

Future Studies

References

Construction of Optimal Codes

Vectorial Cyclic Codes and Their Structure

Sümeysra Bedir
Thesis Supervisor:
Assoc. Prof. Dr.
Bayram Ali ERSOY

- ▶ Gabudilin Codes (in Rank Metric Spaces)
- ▶ by considering a set of all $p(x)$ – *circulant* $m \times n$ matrices over F_q (for $D_{TR} = m$).
- ▶ by Toeplitz-like matrices (for $D_{TR} = m$).
- ▶ ???

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary Codes (ICCC, 2015)

Pseudo-cyclic Codes with Applications to DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary

Rank Metric Spaces

Construction of Optimal Codes in M_{TR}

Code Construction

Proposition and

Examples

Future Studies

References

Example

Let $F_q = GF(2^2) = \{0, 1, a, a^2\}$.

Let $p(x) = x^4 + a$, M_{TR} ; 4×4 F_q -matrix space

In this case, T = the companion matrix of $p(x)$ is considered.

And the subspace generated by the matrices $\{T, T^2, T^3, I_4\}$ constructs a $[4 \times 4, 4]$ code over M_{TR} .

$$C = \left\langle \left\{ \begin{bmatrix} 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ a & 0 & 0 & 0 \end{bmatrix}, \begin{bmatrix} 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ a & 0 & 0 & 0 \\ 0 & a & 0 & 0 \end{bmatrix}, \begin{bmatrix} 0 & 0 & 0 & 1 \\ a & 0 & 0 & 0 \\ 0 & a & 0 & 0 \\ 0 & 0 & a & 0 \end{bmatrix}, I_4 \right\} \right\rangle$$

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary

Codes (ICCC, 2015)

Pseudo-cyclic Codes with Applications to

DNA (ICFAS, 2016)

Ongoing Research

Codes over Tern

Rank Metric Spaces

Construction of

Optimal Codes in M_{TR}

Code Construction

Proposition and

Examples

Future Studies

References

Code Construction and Examples

Let $p(x) = a_0 + a_1x + \cdots + x^m$ be a monic divisor of degree m of a polynomial $f = x^n - 1$ of degree n and consider the following matrix P obtained from the companion matrix (bootom format) of p horizontally joined with an $m \times (n - m)$ block matrix of zeroes.

$$P = \begin{bmatrix} 0 & 1 & 0 & \cdots & 0 & \cdots & 0 \\ \vdots & \ddots & \ddots & \ddots & \ddots & \vdots & \vdots \\ 0 & \cdots & 0 & 1 & 0 & \cdots & 0 \\ -a_0 & -a_1 & \cdots & -a_{m-1} & 0 & \cdots & 0 \end{bmatrix}$$

We define a cyclic shift by vertically shifting the columns of P to the right hand side. We can obtain this shift by successive operations of the companion matrix of f to the matrix P .

The F_q sub matrix space spanned by n matrices of cyclic shifts of P construct a form of a cyclic code over M_{TR} .

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes
as Invariant
Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Tern

Rank Metric Spaces

Construction of
Optimal Codes in M_{TR}

Code Construction
Proposition and
Examples

Future Studies

References

We generalize this to the pseudo-cyclic case as follows;

Fact (Proposition)

Let F_q be a finite field with q elements and let f be a monic polynomial and p a divisor polynomial of f over $F_q[x]$, with $\deg f = n$ and $\deg p = m$. Let P be the matrix obtained from the companion matrix of p horizontally joined with an $m \times (n - m)$ block matrix of zeroes, and T be the companion matrix of f . The F_q -sub matrix space spanned by the following set of $m \times n$ matrices;

$$\{P, PT, PT^2, \dots, PT^{n-1}\}$$

constructs a pseudo-cyclic code over the term rank metric space M_{TR} .

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes
as Invariant
Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Term
Rank Metric Spaces

Construction of
Optimal Codes in M_{TR}

Code Construction
Proposition and
Examples

Future Studies

References

Example

Let F_q be the finite field with 4 elements; $F_4 = \{0, 1, a, a^2\}$.

Consider $f(x) = x^9 - 1$ and take $p(x) = x^3 + a^2$ as a divisor of f .

Therefore we have $m = 3$, $n = 9$, and

$$P = \begin{bmatrix} 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ a^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix},$$

$$T = \begin{bmatrix} 0 & 1 & 0 & \cdots & 0 \\ 0 & 0 & 1 & \ddots & \vdots \\ 0 & \vdots & \ddots & \ddots & 0 \\ 0 & 0 & \cdots & 0 & 1 \\ 1 & 0 & \cdots & \cdots & 0 \end{bmatrix}_{9 \times 9}$$

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary

Rank Metric Spaces

Construction of
Optimal Codes in M_{2n}

Code Construction
Proposition and
Examples

Future Studies

References

Example

Applying T to P , constructs the desired cyclic shift;

$$\begin{aligned} PT &= \begin{bmatrix} 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & a^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}, \\ PT^2 &= \begin{bmatrix} 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & a^2 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}, \\ &\vdots \\ PT^8 &= \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & a^2 \end{bmatrix} \end{aligned}$$

The subspace generated by the spanning set $\{P, PT, PT^2, \dots, PT^8\}$ becomes a cyclic $[3x9, 9]$ -code over the F_4 -matrix space of $3x9$ matrices.

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary

Codes (ICCC, 2015)

Pseudo-cyclic Codes

with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Ternary

Rank Metric Spaces

Construction of

Optimal Codes in M_{2n}

Code Construction

Proposition and

Examples

Future Studies

References

- ▶ We aim to find the restrictions and conditions for constructing optimal codes with the proposed construction method.
- ▶ New bounds (implementations of sphere packing-covering bounds) are to be explored as in the usual vector space case.

Introduction

Preliminaries

Pseudo-cyclic Shift

Pseudo-cyclic Codes

Pseudo-cyclic Codes

as Invariant

Submodules

Our Previous Studies

Polycyclic Quaternary
Codes (ICCC, 2015)

Pseudo-cyclic Codes
with Applications to
DNA (ICFAS, 2016)

Ongoing Research

Codes over Term

Rank Metric Spaces

Construction of
Optimal Codes in M_{2^n}


Code Construction

Proposition and


Examples


Future Studies


References


 A. Alahamdi, S. Dougherty, A. Leroy, P. Sole, (2016). On the duality and the direction of polycyclic codes, Adv. in Math. of Com., 10(4):921-929.


 A. Asamov, N. Aydın, (2007). The database for \mathbb{Z}_4 codes, <http://www.asamov.com/Z4Codes/>

 S. Jitman, (2013). Vector-circulant matrices over finite fields and related codes, arXiv:1408.2059 [math.RA]

 S.R. Lopez-Permouth, B.R. Parra-Avila, S. Szabo, (2009). Dual generalizations of the concept of cyclicity of codes, Adv. in Math. of Com. (2009) 227–234.

 William Wesley Peterson, E. J. Jr Weldon, Error Correcting codes: second edition, MIT Press (1972).

 D. Radkova, A.J. Van Zanten, Constacyclic codes as invariant subspaces, Linear Algebra and its Applications, 430(2009), 855-864.

 M. Wu, Free cyclic codes as invariant submodules over finite chain rings, International Mathematical Forum, 8-37(2013), 1835 - 1838.

 V. Gritsenko, A. Maevskiy, (2014). On a construction of optimal codes in term rank metric via $p(x)$ -circulants. Fourteenth