

Requirement:

Cast Noz-Chek Body

Valve Flange Size: 12"

Valve Body Size: 12"

Pressure Class: CL 900

Style1: Flanged Valve

Style: Non-integral Diffuser - API 6D Long Pattern

Body Material: ASTM A494 Gr CU5MCuC per ESBM-2128 Rev 8

Body Configuration: Double Flanged (3)

End Connection Type: Serrated Face (125-250 uin/3.2-6.3 Ra)

ECCN: SCOMET

Body Liquid Penetrant Test Sample Size: All Castings

Body Liquid Penetrant Test Coverage: Accessible Surfaces

Liquid Penetrant Test Acceptance Criteria: ASME BPVC VIII, D1, App 8

Liquid Penetrant Test Procedure: ASTM B165 Procedure B-2.

Body Radiography Sample Size: All Castings

Body Radiography Coverage: Critical Areas

Radiography Acceptance Criteria: ASME BPVC, Section VIII, Division 1, App 7

(upto 2" thick) Category A,B & CA Level 2, Category CB, CC & CD Level 3,

Category D,E & F Level 0. For wall thickness 2" to 4.5" comparable plates of

ASTM E186 shall be used. ASTM E94 and ASTM E142 shall be used for

recommended practice & controlling quality of radiography as guide.

Radiography Test Procedure: ASME Sec VIII, Div. I, App 7, Para 7-2 to

7-5

X-Ray Films Required for Review?: Yes

For Radiography, IQI selection shall be as per table 4 of ASTM E747.