



Grid Class	Column Width
.ym-g20	20 %
.ym-g25	25 %
.ym-g33	33.3333 %
.ym-g38	38.2 % (Golden Ratio)
.ym-g50	50 %
.ym-g60	60 %
.ym-g62	61.8 % (Golden Ratio)
.ym-g66	66.6666 %
.ym-g75	75 %
.ym-g80	80 %

Flexible Layouts	
.ym-wrapper	Separate values for width.
.ym-wbox	Paddings and borders.

Float Classes	
.ym-clearfix	Clearing floats without extra markup, avoids margin-collapsing problems in static containers.
.ym-contain-dt	Containing floats, to display oversized child-elements.
.ym-contain-oh	Containing floats, overflow, for clipping of oversized child-elements by the parent element without scrollbars.
.ym-contain-fl	Containing float, if relative positioning of the attached element is needed.

Grid	
.ym-grid	Parent class
	<b>Child Classes</b>
.ym-gl	Float direction is left.
.ym-gr	Correction of rounding errors – floating direction of last column to the right.
.ym-g[xx]	Independent control of column- and gutter-widths.
	<b>Optional classes</b>
.ym-equalize	Equalized column heights within a grid row.
.ym-gbox	Holds gutter vales (as padding or margin).
.ym-gbox-left	Aligned left.
.ym-gbox-right	Aligned right.
.linearize-level-1	Add to any grid module, you want to be linearized.

Buttons	
.ym-button	Default button style and size.
.ym-small	A smaller button.
.ym-xsmall	A very small button.
.ym-large	A more emphasized button.
.ym-xlarge	A very large button.
.ym-primary	Primary action button (purple).
.ym-success	Positive action button (green).
.ym-warning	“Take with care” action button (yellow).
.ym-danger	Dangerous action button (red).



[www.yaml.de](http://www.yaml.de)

Form	
.ym-form	Parent class
	<b>Row wrapper</b>
.ym-fbox	Creates box.
.ym-fbox-footer	Box positioned as footer.
.ym-fbox-wrap	Box wrapping.
	<b>IE6 helper classes</b>
.ym-fbox-text	For text input.
.ym-fbox-select	Select-box.
.ym-fbox-check	Check-box.
.ym-fbox-button	For custom or submit button.
	<b>Optional classes</b>
.ym-full	Provides a stacked view of labels and related form elements. Width of all form elements is normalized to 100& width.
.ym-columnar	Provides columnar arrangement of form elements.
.ym-inline	Creates inline.
.ym-required	Visually emphasizes as required.
.ym-error	Highlights form fields with invalid form elements.
.ym-message	For output messages that will be correctly aligned in all form styles.
.ym-fbox-heading	Use this before the button set for more consistent appearance of forms.
.ym-label	Forces any heading level to fit into your form theme.

Columns	
.ym-column	Parent class
	<b>Child classes</b>
.ym-col[1 2 3]	For independent control of column widths and paddings.
	<b>Optional classes</b>
.ym-cbox	Creates column box.
.ym-cbox-left	Aligned left.
.ym-cbox-right	Aligned right.
.linearize-level-1	Add to any column module, you want to be linearized.



Attribute-ShareAlike 3.0  
(CC-BY-SA 3.0)  
[www.creativecommons.org](http://www.creativecommons.org)



The FAU's IT provider  
[www.rrze.de](http://www.rrze.de)  
Created by: franziska.sponsel@fau.de

yaml/	<b><u>Stylesheet base.css</u></b>
--- add-ons/	
--- accessible-tabs/	
--- jquery.tabs.js	
__ tabs.css	
--- microformats/	
--- icons/	
__ microformats.css	
--- rtl-support/	
--- core/	
--- base-rtl.css	
__ base-rtl.min.css	
--- navigation/	
--- hlist-rtl.css	
__ vlist-rtl.css	
__ screen/	
__ typography-rtl.css	
__ microformats	
__ jquery.syncheights.css	
--- core/	
--- base.css	
--- base.min.css	
--- ie hacks.css	
__ ie hacks.min.css	
--- forms/	
__ gray-theme.css	
--- navigation/	
--- hlist.css	
__ vlist.css	
--- print/	
__ print.css	
__ screen/	
--- grid-960-12.css	
--- grid-960-16.css	
--- screen-FULLPAGE-layout.css	
--- screen-PAGE-layout.css	
__ typography.css	

Accessibility	
<b>.ym-skiplinks</b>	Parent class, controls the visual properties of the list. Unordered list.
<b>.ym-skip</b>	Child class. Each link in the list is marked up with this class. Required for skip anchors.
	<b>Optional classes</b>
<b>.ym-hideme</b>	Elements are visually hidden in browsers, but accessible for screen readers.
<b>.ym-print</b>	Elements are visually hidden in media screen, but accessible for screen readers and on media print.
<b>.ym-noprint</b>	Elements will not be printed, but are visible on any other media type.

Accessible Tabs	
.jquery_tabs	Specific elements become tab headings.
.tbody	Defines content (or its wrapper).

Tables	
<b>.bordertable</b>	Classic table style.
<b>.narrow</b>	Smaller table rows.

Typography	
	<div> <div>H1 Heading</div> <div>H2 Heading</div> <div>H3 Heading</div> <div>H4 Heading</div> <div>H5 Heading</div> <div>H6 Heading</div> </div>
	<b>Special Paragraphs</b>
<b>Class="highlight"</b>	Red.
<b>Class="dimmed"</b>	Grey.
<b>Class="box.info"</b>	Grey box.
<b>Class="box success"</b>	Green box.
<b>Class="box warning"</b>	Yellow box.
<b>Class="box error"</b>	Red box.
	<b>Misc. Elements</b>
<b>&lt;blockquote&gt;</b>	Paragraph text within <blockquote> element
<b>&lt;pre&gt;</b>	Preformatted text wrapped in <pre> element.
	<b>Inline semantic text decoration</b>
<b>&lt;a&gt;</b>	Anchor
<b>&lt;i&gt;, &lt;em&gt;</b>	Italics and emphasized.
<b>&lt;big&gt;, &lt;small&gt;</b>	Big and small.
<b>&lt;b&gt;, &lt;strong&gt;</b>	Bold and strong.
<b>&lt;acronym&gt;, &lt;abbr&gt;</b>	Acronym and abbreviation.
<b>&lt;cite&gt;, &lt;q&gt;</b>	Cite and quote.
<b>&lt;code&gt;, &lt;dfn&gt;</b>	Code and definition.
<b>&lt;tt&gt;, &lt;kdb&gt;</b>	Teletype and keyboard.
<b>&lt;var&gt;, &lt;samp&gt;</b>	Variable and sample.
<b>&lt;ins&gt;, &lt;del&gt;</b>	Inserted and deleted.
<b>&lt;sub&gt;, &lt;sup&gt;</b>	Subscript and superscript.
<b>&lt;mark&gt;</b>	Marked, highlighted.
	<b>Media</b>
<b>.flexible</b>	Flexible media (responsive)
<b>.bordered</b>	Add border to images or videos.