

Driver Initialization	
Firefox (Below v.47) Refer Part2-Page58	System.setProperty("webdriver.geck-o.driver", "PathTo\\geckodriver.exe");
Download from https://gith- ub.com/mozilla/geckodriv- er/releases	WebDriver driver = new FirefoxDr- iver();
Chrome Refer Part2-Page59	System.setProperty("WebDriver.chrome.driver", System.getProperty("user.dir")+"//BrowserDrivers//chromedriver.exe");
Download from https://site- s.google.com/a/chromium.o- rg/chromedriver/downloads	WebDriver driver = new ChromeDriver();
Internet Explorer ^{Refer} Part2-Page59	System.setProperty("WebDriver.ie.d-river", "PathTo//IEDriverServer.exe");
Download from The Internet Explorer Driver Server at http://docs.seleniumhq.org/- download/	WebDriver driver = new InternetExplorerDriver();
Safari Driver	WebDriver driver = new SafariDriver();

Selenium Locators	
Locating by ID Refer Part2 Page37	driver.findElement(By.id("q")).send- Keys("Selenium 3");
Locating by Name ^{Refer} Part2-Page37	<pre>driver.findElement(By.name("q")).se- ndKeys("Selenium 3");</pre>
Locating by Xpath Refer Part2-Page37/38	<pre>driver.findElement(By.xpath("//input[- @id='q']")).sendKeys("Selenium 3");</pre>
Locating Hyperlinks by Link Text Refer Part2-Pag- e38/39	<pre>driver.FindElement(By.LinkText("edit this page")).Click();</pre>

Selenium Locators (cont)		
Locating by DOM Refer Part2-Page39	dom =document.getElementById('sign-inForm')	
Locating by CSS ^{Refer} Part2-Page40-43	<pre>driver.FindElement(By.CssSelector("#r- ightbar > .menu > li:nth-of-type(2) > h4"));</pre>	
Locating by ClassN- ame ^{Refer Part2-Page37}	<pre>driver.findElement(By.className("prof- ile-header"));</pre>	
Locating by TagNam- e ^{Refer Part2-Page37}	<pre>driver.findElement(By.tagName("sel- ect")).Click();</pre>	
Locating by LinkTe- xtRefer Part2-Page37-40	<pre>driver.findElement(By.linkText("NextP- age")).click();</pre>	
Locating by PartialLi- nkText ^{Refer Part2-Pag-} e37-40	<pre>driver.findElement(By.partialLinkText("N- extP")).click();</pre>	

Selenium Exceptions	
'Server Exception : sessionId should not be null Refer Part2-Page160	Replace Chrome Driver with Latest Version
ERROR: No sessionId provided Refer Part2-Page160	Use Jenkins
UnreachableBrowserException Refer Part2-Page160	Registry Key Changes Recommended
Illegal state exception using Selenium 3Refer Part2-Page161	Get latest Firefox Gecko Driver

TestNG @BeforeSuite @AfterSuite @BeforeTest @AfterTest @BeforeGroups @AfterGroups @BeforeClass @AfterClass @BeforeMethod @AfterMethod JUnit @After @AfterClass @Before @BeforeClass @Ignore

@Test



By **Narayanan Palani** (Narayanan Palani)

cheatography.com/narayanan-palani/

www.udemy.com/user/narayanan-palani/

Published 15th November, 2016. Last updated 20th June, 2020. Page 1 of 5.



Execute Javascript	
Executes an asynchronous piece of JavaScript	executeAsyncScr-ipt()
Executes JavaScript	executeScript()
Code Example: if (driver instanceof JavascriptExecutor) { ((JavascriptExecutor)driver).executeScript("ale }	ert('hello world');");

Take screenshot	
Capture the screenshot and store	getScreenshotAs
getScreenshotAs — used to Capture the	e screenshot and store it in

the specified location. This method throws WebDriverException. copy() method from the File Handler class is used to store the screenshot in a destination folder.

Code Example:

TakesScreenshot screenShot =(TakesScreenshot)driver; FileHandler.copy(screenShot.getScreenshotAs(OutputType.FILE), new File("path/to/destination/folder/screenshot.png"));

nett i ne(patitite) decimale i nette e centerie i nette i nette e centerie i nette e cen	
Cookies	
addC- ook- ie(arg)	driver.manage().addCookie(new Cookie("foo", "bar"));
getC- ook- ies()	driver.manage().getCookies(); // to get all cookies
getC- ook- ieN- amed()	driver.manage().getCookieNamed("foo");
dele- teC- ook- ieN-	driver.manage().deleteCookieNamed("foo");

Cookie cookie1 = new Cookie("test2", "cookie2");

leteCookie(cookie1); // deleting cookie object

driver.manage().addCookie(cookie1); driver.manage().de-

driver.manage().deleteAllCookies(); // deletes all cookies

Page Loading Strategy	
normal	ChromeOptions chromeOptions = new ChromeOptions(); chromeOptions.setP- ageLoadStrategy(PageLoadStrategy.N- ORMAL); WebDriver driver = new ChromeDriver(chromeOptions);
eager: When setting to eager, Selenium WebDriver waits until DOMContentLoaded event fire is returned.	ChromeOptions chromeOptions = new ChromeOptions(); chromeOptions.setP- ageLoadStrategy(PageLoadStrategy.E- AGER); WebDriver driver = new Chrome- Driver(chromeOptions);
none: When set to none Selenium WebDriver only waits until the initial page is downloaded.	ChromeOptions chromeOptions = new ChromeOptions(); chromeOptions.setP- ageLoadStrategy(PageLoadStrategy.N- ONE); WebDriver driver = new Chrome- Driver(chromeOptions);

The document.readyState property of a document describes the loading state of the current document. By default, WebDriver will hold off on responding to a driver.get() (or) driver.navigate().to() call until the document ready state is complete

By default, when Selenium WebDriver loads a page, it follows the normal pageLoadStrategy.

Handle alerts: (Web-based alert pop-ups)	
driver.switchTO().alert.getText()	to retrieve the alert message
driver.switchTO().alert.accept()	to accept the alert box
driver.switchTO().alert.dismiss()	to cancel the alert box
driver.switchTO().alert.sendKeys("- Text")	to send data to the alert box



amed() dele-

teC-

ookie()

teAllCookies()

dele-

By Narayanan Palani (Narayanan Palani) cheatography.com/narayananpalani/

Published 15th November, 2016. Last updated 20th June, 2020. Page 2 of 5.



nts()

Selenium WebDriver Cheat Sheet Cheat Sheet by Narayanan Palani (Narayanan Palani) via cheatography.com/32112/cs/9838/

Find element VS Find elements	
driv- er.f- in- dEl- eme- nt()	When no match has found(0) throws NoSuchElementException when 1 match found returns a WebElement instance when 2+ matches found returns only the first matching web element
driv- er.f- in- dEl- eme-	when no macth has found (0) returns an empty list when 1 match found returns a list with one WebElement when 2+ matches found returns a list with all matching WebElements



ISTQB Advanced Test Automation Engineering | Compared | Compared

https://www.udemy.com/course/istqb-advanced/

Materials	
Selenium Certification	https://isqi.org/en/54-certified-seleniumtester-foundation.html
Selenium Certification Q&A	https://www.udemy.com/course/certified-selenium-tester-foundation/
Part1-Software Automation Testing Secrets Revealed	https://www.amazon.com/Software-Auto- mation-Testing-Secrets-Revealed/dp/1- 729432506/
Part2-Software Automation Testing Secrets Revealed	https://www.amazon.com/gp/product/17-29432379/

Materials (cont)	
Part3-Software Automation Testing Secrets Revealed	https://www.amazon.com/Advanced-Selenium-Web-Accessibility-Testing/dp/1949449432/
Udemy Course- Selenium	https://www.udemy.com/course/ctfl_syll2018/
Udemy Course- ISTQB Test Automation Engineering	https://www.udemy.com/course/istqb-adva- nced/
Useful Commands (Credits: Madhan K)	https://medium.com/@madhankumaravelu93/-selenium-cheat-sheet-a-comprehensive-list-of-selenium-commands-fa4c5c9d11ab
Useful Commands (Credits: Bijan Patel)	https://qascript.com/selenium-webdriver-co- mmands-cheat-sheet/

Practice Scripts	
Launch Webpage ^{Refer} Part2-Page60	driver.get("www.webdriverinselenium.com");
Click Button ⁻ Refer Part2-Page60	driver.findElement(By.id("submit")).click();
Store Text ^{Refer} Part2-Page60	String txtDropdown = driver.findElement(By.ID- ("select")).getText();
Enter Text ^{Refer} Part2-Page61	driver.findElement(By.xpath("//input[@name='Fi-rstName034']")).sendKeys("NarayananPalani");
Handle Alert ^{Refer Part2} Page62	Alert Alertpopup = driver.switchTo().alert();
(Mouse)Cli- ck ^{Refer Part2} Page62	<pre>driver.findElement(By.xpath("//input[@value='O- BJECT NAME']")).click();</pre>
Compare Text ^{Refer Part2} Page64	Assert.assertTrue(chkbox12.isSelected());



By **Narayanan Palani** (Narayanan Palani)

cheatography.com/narayanan-palani/

Published 15th November, 2016. Last updated 20th June, 2020. Page 3 of 5. Sponsored by **CrosswordCheats.com** Learn to solve cryptic crosswords! http://crosswordcheats.com

www.udemy.com/user/narayanan-palani/



actions.perform();

Practice Scripts	c (cont)
Disable a Field ^{Refer} Part2-Page64	$\label{lem:condition} driver.getElementsByName('')[0].setAttribute('disabled', ");$
Enable a Field ^{Refer} Part2-Page64	driver.getElementsByName(' <objectid>')[0].removeAttribute('disabled';</objectid>
Screenshot ⁻ Refer Part2 Page64	File snapshot = ((TakesScreenshot)driver).getS- creenshotAs(OutputType.FILE);
	FileUtils.copyFile(snapshot, new File("C:\\screenshot.jpg"));
Print the Title of the Page ^{Refer} Part2-Page68	String pagetitle = driver.getTitle();
	System.out.print(pagetitle);
Implicit Wait ^{Refer} Part2-Page69	driver.manage().timeouts().implicitlyWait(10, TimeUnit.SECONDS);
Explicit Wait ^{Refer} Part2-Page70	WebDriverWait wait = new WebDriverWait(driver, 20);
	wait.until(ExpectedConditions.textToBePresent-InElementLocated(By.xpath("//div[@id=' <object id="">']"), "Enter Your Personal Details"));</object>
Fluent Wait ^{Refer} Part2-Page70	Wait wait = new FluentWait(driver)
	.withTimeout(20, SECONDS)
Sleep ^{Refer}	Thread.Sleep(10);

Keyboard and Mouse events	
keyboard events	keyDown(); keyUp(); sendKeys()
Mouse events	clickAndHold(); contextClick()// — performs the mouse right-click action; doubleClick(); dragAndDrop(source,target); dragAndDropBy(source,xOffset,yOffset); moveBy-Offset(xOffset,yOffset); moveByElement(); release()
Code Example: Actions builder = new Actions(driver); Action actions = builder .moveToElement("login-textbox") .click() .keyDown("login-textbox", Keys.SHIFT) .sendKeys("login-textbox", "hello") .keyUp("login-textbox", Keys.SHIFT) .doubleClick("login-textbox") .contextClick() .build();	

Element validation	
isEnabl- ed()	determines if an element is enabled or not, returns a boolean.
isSelec- ted()	determines if an element is selected or not, returns a boolean.
isDispl- ayed()	determines if an element is displayed or not, returns a boolean.

Handle multiple windows and tabs		
getWindowHandle()	used to retrieve the handle of the current page (a unique identifier)	
getWindowHandles()	used to retrieve a set of handles of the all the pages available	
driver.switchTo().window- ("windowName/handle")	switch to a window	
driver.close()	closes the current browser window	
driver.quit();	This method Closes all windows opened by the WebDriver.	



Part2-Page70

By Narayanan Palani (Narayanan Palani)

cheatography.com/narayanan-palani/

www.udemy.com/user/narayanan-palani/

Published 15th November, 2016. Last updated 20th June, 2020. Page 4 of 5.



Switch Frames		
Mentioning the frame index number, the Driver will switch to that specific frame	driver.switchTo.frame(int frameNumber)	
Mentioning the frame element or ID, the Driver will switch to that specific frame	driver.switchTo.frame(- string frameNameOrID)	
Mentioning the frame web element, the Driver will switch to that specific frame	driver.switchTo.frame(- WebElement frameElement)	
Switching back to the main window	driver.switchTo().defa- ultContent()	

Get methods in Selenium		
getTitle()	used to retrieve the current title of the webpage	
getCurrentUrl()	used to retrieve the current URL of the webpage	
getPageSou- rce()	used to retrieve the current page source of the webpage	
getText()	used to retrieve the text of the specified web element	
getAttribute()	used to retrieve the value specified in the attribute	

Navigation	
Refresh Page	driver.navigate().refr- esh()
Navigate forwards in the browser history	driver.navigate().forw- ard()
Navigate backward in the browser history	driver.navigate().back()

Desired Capabilities-Chrome

 $\label{lem:decapabilities} Desired Capabilities (aps.set Capability ("browserName", "chrome"); caps.set Capability ("browserVersion", "80.0""); caps.set Capability ("platformName", "win10"); WebDriver driver = new ChromeDriver (caps); // Pass the capabilities as an argument to the driver object |$

Desired Capabilities-Firefox

 $\label{lem:decapabilities} Desired Capabilities (aps.set Capability ("browserName", "firefox"); caps.set Capability ("browserVersion", "81.0""); caps.set Capability ("platformName", "win10"); WebDriver driver = new FirefoxDriver (caps); // Pass the capabilities as an argument to the driver object |$



By Narayanan Palani (Narayanan Palani) cheatography.com/narayananpalani/

www.udemy.com/user/narayanan-palani/

Published 15th November, 2016. Last updated 20th June, 2020. Page 5 of 5.