



DEPARTMENT OF INFORMATICS

TECHNISCHE UNIVERSITÄT MÜNCHEN

Report

Black Box Testing Report

Alexis Engelke, Johannes Fischer, Ralph Schaumann,
Saurabh Nawalgaria





DEPARTMENT OF INFORMATICS

TECHNISCHE UNIVERSITÄT MÜNCHEN

Report

Black Box Testing Report

Author: Alexis Engelke, Johannes Fischer, Ralph Schaumann, Saurabh Nawalgaria
Team: 9
Lecture: Secure Coding, Phase 2
Submission Date: November 24, 2015



Executive Summary

Contents

Executive Summary	ii
1 Time Tracking	1
2 Vulnerabiliteis Overview	2
2.1 Online Banking	2
2.1.1 Stored XSS in Registration and Transaction Description	2
2.1.2 Missing check for amount in transactions from batch file	2
2.1.3 SQL injection in transaction batch file	2
2.1.4 Some critical vulnerability	3
2.2 SecureBank	3
3 Tools	4
3.1 Zed Attack Proxy (ZAP)	4
3.2 SQLmap	4
4 Detailed Report	5
4.1 Configuration and Deploy Management Testing	6
4.1.1 Test File Extensions Handling for Sensitive Information	6
4.1.2 Test HTTP Methods	8
4.1.3 Test HTTP Strict Transport Security	9
4.1.4 Test RIA cross domain policy	10
4.2 Identity Management Testing	11
4.2.1 Test Role Definitions	11
4.2.2 Test User Registration Process	13
4.2.3 Test Account Provisioning Process	15
4.2.4 Testing for Account Enumeration and Guessable User Account .	16
4.2.5 Testing for Weak or unenforced username policy	17
4.3 Authentcation Testing	18
4.3.1 Testing for Credentials Transported over Encrypted Channel . .	18
4.3.2 Testing for default credentials	19
4.3.3 Testing for Weak lock out mechanism	20

Contents

4.3.4	Testing for bypassing authentication schema	22
4.3.5	Testing for Vulnerable Remember Password	24
4.3.6	Testing for Browser Cache Weakness	25
4.3.7	Testing for Weak password policy	26
4.3.8	Testing for Weak security question/answer	27
4.3.9	Testing for Weak password change or reset functionalities	27
4.3.10	Testing for Weaker authentication in alternative channel	27
4.4	Authorization Testing	28
4.4.1	Testing Directory traversal/file include	28
4.4.2	Testing for bypassing authorization schema	28
4.4.3	Testing for Privilege Escalation	28
4.4.4	Testing for Insecure Direct Object References	28
4.5	Session Management Testing	28
4.6	Data Validation Testing	28
4.6.1	Testing for LDAP Injection	28
4.6.2	Testing for ORM Injection	28
4.6.3	Testing for XML Injection	28
4.6.4	Testing for SSI Injection	28
4.6.5	Testing for XPath Injection	28
4.6.6	Testing for SQL injection	29
4.7	Error Handling	32
4.7.1	Analysis of Error Codes	32
4.7.2	Testing for Stack Traces	34
4.8	Testing for weak Cryptography	34
4.9	Business Logic Testing	34
4.10	Client Side Testing	34
Acronyms		35

1 Time Tracking

If a task is prefixed with (o), it refers to the Online Banking web application, if a task is prefixed with (s), the task refers only to the SecureBank web application.

Table 1.1: Time Tracking Table

Name	Task	Time
Alexis Engelke	Setting up LaTeX template	1
Alexis Engelke	(o) Analyzing XSS vulnerabilities using ZAP	2
Alexis Engelke	(o) Analyzing SQL injection vulnerabilities in the web interface using SQLmap	1.5
Alexis Engelke	(o) Analyzing SQL injection vulnerabilities in the file upload	2
Alexis Engelke	(o) Exploiting the TAN verification in the file upload	2
Alexis Engelke	(o) Documenting SQL injection	1
Alexis Engelke	Testing and Documenting Configuration and Deploy Management Testing	2
Alexis Engelke	Testing and Documenting Identity Management Testing	1
Alexis Engelke	Testing and Documenting Authentication Testing	2
Foo	Fixing all issues	10

2 Vulnerabiliteis Overview

Through our testing, we identified the following vulnerabilities as the most critical for the Online Banking application and the SecureBank:

2.1 Online Banking

2.1.1 Stored XSS in Registration and Transaction Description

- Likelihood: high
- Implication: high
- Risk: high

With stored cross site scripting attacks it is possible to inject JavaScript code, which is run whenever an employee logs in and opens the list of unapproved accounts or transactions. It is also possible to inject script from other sites.

2.1.2 Missing check for amount in transactions from batch file

- Likelihood: medium
- Implication: high
- Risk: high

It is possible to get money from another client of the bank by filling in a negative number in the amount field of a transaction batch file. Therefore, one client can generate an infinite amount of money, while reducing the amount of money of other clients.

2.1.3 SQL injection in transaction batch file

- Likelihood: medium
- Implication: high

- Risk: high

The application is vulnerable to SQL injections in the transaction batch files. Therefore, it is possible to perform transactions while using any unused TAN in the system, which is not known to the attacker and might come from another client.

2.1.4 Some critical vulnerability

- Likelihood: high
- Implication: high
- Risk: high

The web application is vulnerable.

2.2 SecureBank

3 Tools

3.1 Zed Attack Proxy (ZAP)

Using the Zed Attack Proxy (ZAP), we were able to reveal significant parts of the directory structure in both web applications. In the *Online Banking* web application, we found a stored XSS vulnerability in the registration and the transaction description as well as a SQL injection vulnerability in the login form using the fuzzer. We were also be able to find a buffer overflow vulnerability for the transaction description in the transaction batch files.

3.2 SQLmap

Using SQLmap, we found the SQL injection vulnerability in the login form, which we found using ZAP earlier. SQLmap did not reveal further SQL injection possibilities.

4 Detailed Report

4.1 Configuration and Deploy Management Testing

4.1.1 Test File Extensions Handling for Sensitive Information

Online Banking

Observation	We found various files which are served as plain text but are PHP source files. One of these files contains the credentials of the mail server. We were also able to download the compiled executable as well as the source code of the batch file parser.
Discovery	Using the OWASP ZAP tool, we used the forced browse functionality on /InternetBanking/. We received a list of files which were found using this tool, see below.
Likelihood	This can be tested by anyone who enters specific strings into the address bar of a browser. However, the likelihood of this vulnerability is much higher if the attacker uses specific tools which test specific paths systematically.
Impact	The attacker can get sensitive information, e.g. credentials to the mail server or the database. He can analyze the source of the parser and find vulnerabilities there.
Access Vector	Network
Access Complexity	Low
Privileges Required	None
User Interaction	None
Scope	Unchanged
Confidentiality	High
Integrity	No Impact
Availability	No Impact

TODO: Forced browsing results.

SecureBank

Observation	We found some HTML snippets, which do not contain any sensitive information, and the compiled executable of the transaction file parser.
Discovery	Using the OWASP ZAP tool, we used the forced browse functionality on /seccoding-2015/. We received a list of files which were found using this tool, see below.
Likelihood	This can be tested by anyone who enters specific strings into the address bar of a browser. However, the likelihood of this vulnerability is much higher if the attacker uses specific tools which test specific paths systematically.
Impact	The attacker only has access to the parser executable, which might contain information about the database connection. He can analyze the parser and find vulnerabilities there.
Access Vector	Network
Access Complexity	Low
Privileges Required	None
User Interaction	None
Scope	Unchanged
Confidentiality	Low
Integrity	No Impact
Availability	No Impact

TODO: Forced browsing results.

Comparison

The web application of the SecureBank discloses less sensitive information. However, both applications disclose information which should not be available to unauthorized persons.

4.1.2 Test HTTP Methods

Online Banking

Observation	The server responded that the method POST, GET, OPTIONS and HEAD are supported.
Discovery	We submitted the request OPTIONS / HTTP/1.1 to the server via NetCat on port 80.
Impact	n/a
Likelihood	n/a
CVSS	n/a

SecureBank

Observation	The server responded that the method POST, GET, OPTIONS and HEAD are supported.
Discovery	We submitted the request OPTIONS / HTTP/1.1 to the server via NetCat on port 80.
Impact	n/a
Likelihood	n/a
CVSS	n/a

Comparison

There are no significant differences between both applications.

4.1.3 Test HTTP Strict Transport Security

Online Banking

Observation	The server did not send any Strict-Transport-Security header.
Discovery	Executing the command <code>curl -s -D-http://vm/InternetBanking/ grep Strict</code> resulted in no results.
Impact	n/a
Likelihood	n/a
CVSS	n/a

SecureBank

Observation	The server did not send any Strict-Transport-Security header.
Discovery	Executing the command <code>curl -s -D-http://vm/InternetBanking/ grep Strict</code> resulted in no results.
Impact	n/a
Likelihood	n/a
CVSS	n/a

Comparison

There are no significant differences between both applications.

4.1.4 Test RIA cross domain policy

Online Banking

Observation	No cross domain policy files were found.
Discovery	We scanned the traffic using ZAP.
Impact	n/a
Likelihood	n/a
CVSS	n/a

SecureBank

Observation	No cross domain policy files were found.
Discovery	We scanned the traffic using ZAP.
Impact	n/a
Likelihood	n/a
CVSS	n/a

Comparison

There are no significant differences between both applications.

4.2 Identity Management Testing

4.2.1 Test Role Definitions

Online Banking

Observation	We found the following functionality for the different roles:		
		Client	Employee
	View own account	×	×
	View own transaction history	×	—
	Create new transactions	×	—
	View account and transaction history of clients and employees	—	×
	Change account details and balance of clients and employees	—	×
	Approve transactions	—	×
Discovery	Approve registrations of clients and employees		
	We noticed that there are links to view the transaction history and change the account balance of employees, too.		
	We gathered the information by exploring the web application interface manually.		
Impact	n/a		
Likelihood	n/a		
CVSS	n/a		

SecureBank

Observation	We found the following functionality for the different roles:		
		Client	Employee
	View own account	×	–
	View own transaction history	×	–
	Create new transactions	×	–
	View account and transaction history of clients	–	×
	Approve transactions	–	×
	Approve registrations of clients and employees	–	×
Discovery	We gathered the information by exploring the web application interface manually.		
Impact	n/a		
Likelihood	n/a		
CVSS	n/a		

Comparison

The SecureBank web application does not offer a possibility for an employee to change the account balance of a client. However, the Online Banking application allows to view the transaction history and change the account balance also for employees, which have no account. This behaviour might be confusing.

4.2.2 Test User Registration Process

Online Banking

Observation	For registration, a username, an e-mail address, a password and whether the registrant is a client or an employee are needed. Anyone can register for access. The registration has to be approved by an employee before the registrant can use the account. A person can register only one time with the same e-mail address. However, a person can register many times with the same username. (The activation of such an account fails with a database error.) We could not find out, whether the registrants are verified personally before the approval.
Discovery	We tried to register several accounts with the same e-mail address and/or username using the web application.
Impact	n/a
Likelihood	n/a
CVSS	n/a

SecureBank

Observation	For registration, the full name, an e-mail address, a password and whether the registrant is a client or an employee are needed. Anyone can register for access. The registration has to be approved by an employee before the registrant can use the account. A person can register only one time with the same e-mail address. We could not find out, whether the registrants are verified personally before the approval.
Discovery	We tried to register several accounts with the same e-mail address and/or names using the web application.
Impact	n/a
Likelihood	n/a
CVSS	n/a

Comparison

The Online Banking web application allows the double-registration of the same username at first, it only fails at the activation. This behaviour is confusing. Also, the application should ask for the full name be able to verify the name. Otherwise, there are no significant differences between both applications.

4.2.3 Test Account Provisioning Process

Online Banking

Observation	There is no way to change the role of a user. Account requests (both, client and employee) must be approved by an employee.
Discovery	We followed the links in the user interface and tried to login as a non-verified user.
Impact	n/a
Likelihood	n/a
CVSS	n/a

SecureBank

Observation	There is no way to change the role of a user. Account requests (both, client and employee) must be approved by an employee.
Discovery	We followed the links in the user interface and tried to login as a non-verified user.
Impact	n/a
Likelihood	n/a
CVSS	n/a

Comparison

There are no significant differences between both applications.

4.2.4 Testing for Account Enumeration and Guessable User Account

Online Banking

Observation	There are no differences in the servers response for not activated accounts, valid usernames and invalid usernames.
Discovery	We tested the login for activated and non-activated accounts, existing and not-existing usernames and valid or invalid passwords.
Impact	n/a
Likelihood	n/a
CVSS	n/a

SecureBank

Observation	There are no differences in the servers response for not activated accounts, valid usernames and invalid usernames.
Discovery	We tested the login for activated and non-activated accounts, existing and not-existing usernames and valid or invalid passwords.
Impact	n/a
Likelihood	n/a
CVSS	n/a

Comparison

There are no significant differences between both applications.

4.2.5 Testing for Weak or unenforced username policy

Online Banking

Observation	We were not able to find a username policy.
Discovery	We tested various usernames.
Impact	n/a
Likelihood	n/a
CVSS	n/a

SecureBank

Observation	The username has to be a valid e-mail address of the client/employee. There is no policy regarding the e-mail address.
Discovery	We tested valid and invalid e-mail addresses.
Impact	n/a
Likelihood	n/a
CVSS	n/a

Comparison

The only difference between the applications is that the Online Banking application uses usernames, which might have less correlation to the user than the e-mail address.

4.3 Authentcation Testing

4.3.1 Testing for Credentials Transported over Encrypted Channel

TODO!

Online Banking

Observation	
Discovery	
Impact	
Likelihood	n/a
CVSS	n/a

SecureBank

Observation	
Discovery	
Impact	n/a
Likelihood	n/a
CVSS	n/a

Comparison

4.3.2 Testing for default credentials

We decided to not test for default credentials, because we are working with custom software and therefore assume that all users and administrators choose secure passwords.

4.3.3 Testing for Weak lock out mechanism

Online Banking

Observation	We were not able to find any lock out mechanism. Therefore, brute force attacks on passwords are possible.
Discovery	We entered a valid username and incorrect passwords 10 times, and always got the error message about an incorrect password. Afterwards, we were able to log in with a correct password.
Impact	An attacker can brute-force the password of any user and therefore take the user over.
Likelihood	High
Access Vector	Network
Access Complexity	Low
Privileges Required	None
User Interaction	None
Scope	Unchanged
Confidentiality	Low
Integrity	Low
Availability	No Impact

SecureBank

Observation	We were not able to find any lock out mechanism. Therefore, brute force attacks on passwords are possible.
Discovery	We entered a valid username and incorrect passwords 10 times, and always got the error message about the failed login. Afterwards, we were able to log in with a correct password.
Impact	An attacker can brute-force the password of any user and therefore take the user over.
Likelihood	High
Access Vector	Network
Access Complexity	Low
Privileges Required	None
User Interaction	None
Scope	Unchanged
Confidentiality	Low
Integrity	Low
Availability	No Impact

Comparison

Both applications do not provide any lock out mechanism.

4.3.4 Testing for bypassing authentication schema

Online Banking

Observation	We were able to bypass the authentication schema via a SQL injection. This gave us the ability to login as any user without knowing the password.
Discovery	Using the fuzzer jbrofuzz / SQL Injection of ZAP on the username field of the login page, we were able to login as admin or another user without knowing the password. We had no success with direct page requests, modifying the session ID and parameter modification.
Impact	An attacker can take over a user without knowing the valid access credentials.
Likelihood	High
Access Vector	Network
Access Complexity	Low
Privileges Required	None
User Interaction	None
Scope	Unchanged
Confidentiality	Low
Integrity	Low
Availability	No Impact

SecureBank

Observation	We were not able to bypass the authentication schema.
Discovery	Using the fuzzer jbrofuzz / SQL Injection of ZAP and SQLmap on the username field of the login page, we were not able to find SQL injection vulnerabilities to bypass the authentication schema. We also had no success with direct page requests, modifying the session ID and parameter modification.
Impact	n/a
Likelihood	n/a
CVSS	n/a

Comparison

The Online Banking web application provides a way to bypass the authentication schema via SQL injection. The SecureBank application does not offer such vulnerabilities.

4.3.5 Testing for Vulnerable Remember Password

We did not found a remember password functionality, so we decided to not further test on this.

4.3.6 Testing for Browser Cache Weakness

Online Banking

Observation	Clicking the back button in the browser does not cause a re-login. All sites have the header Cache-Control: no-store, no-cache, must-revalidate, post-check=0, pre-check=0 and the Pragma: no-cache as well as an Expires: <date in the past> header set.
Discovery	Using ZAP, we analyzed the response header for different pages which are only available when a user is logged in.
Impact	n/a
Likelihood	n/a
CVSS	n/a

SecureBank

Observation	Clicking the back button in the browser does not cause a re-login. All sites have the header Cache-Control: no-store, no-cache, must-revalidate, post-check=0, pre-check=0 and the Pragma: no-cache as well as an Expires: <date in the past> header set.
Discovery	Using ZAP, we analyzed the response header for different pages which are only available when a user is logged in.
Impact	n/a
Likelihood	n/a
CVSS	n/a

Comparison

There is no significant difference between both applications.

4.3.7 Testing for Weak password policy

Online Banking

Observation	There is a password policy enforced, which states that a password has have a length ≥ 6 and has to include at least one number, one lowercase character, one uppercase character and one symbol. There is no way to change the password. The password does not expire.
Discovery	We tested various passwords, like 123456. If a password does not match the policy, an error message is shown which informs the user about the policy.
Impact	n/a
Likelihood	n/a
CVSS	n/a

SecureBank

Observation	The password has to have a length ≥ 6 . There is no way to change the password. The password does not expire.
Discovery	We tested various passwords, like 123456. If a password does not match the policy, an error message is shown which informs the user about the policy.
Impact	n/a
Likelihood	n/a
CVSS	n/a

Comparison

The Online Banking application enforces a more strict password policy than the Secure-Bank application. This reduces the risk of brute force attacks.

4.3.8 Testing for Weak security question/answer

We could not find such functionality in both application. Therefore, we decidede to not proceed testing on this.

4.3.9 Testing for Weak password change or reset functionalities

We could not find such functionality in both application. Therefore, we decidede to not proceed testing on this.

4.3.10 Testing for Weaker authentication in alternative channel

We could not find an alternative channel for authentication. Therefore, we decidede to not proceed testing on this.

4.4 Authorization Testing

4.4.1 Testing Directory traversal/file include

TODO!

4.4.2 Testing for bypassing authorization schema

TODO!

4.4.3 Testing for Privilege Escalation

TODO!

4.4.4 Testing for Insecure Direct Object References

TODO!

4.5 Session Management Testing

TODO!

4.6 Data Validation Testing

TODO!

4.6.1 Testing for LDAP Injection

4.6.2 Testing for ORM Injection

4.6.3 Testing for XML Injection

4.6.4 Testing for SSI Injection

4.6.5 Testing for XPath Injection

We did not test any of these injection types as it appears that these techniques are not used in any of the two applications. Therefore, we decided to not further investigate in these types of injection.

4.6.6 Testing for SQL injection

Online Banking

Observation	We were able to log into the application as any user without knowing the password and to perform transactions with any unused TAN of any user when uploading a transaction batch file.
Discovery	<p>We used the fuzzer of ZAP on the username field of the login form, with the query parameters <code>username=admin&password=123</code>, where the fuzzing point was at the end of the username. We compared the answers of the server and found that in one case we got redirected to the employee page. We analyzed the login page also using SQLmap, which delivered a similar result. Additionally, we ran SQLmap on the fields of the perform transaction form, it returned that none of the four inputs were exploitable for SQL injection.</p> <p>We tested the fields of the transaction batch form manually by trying some standard SQL injection parts (e.g. ' ; - and " ; -). We noted that the application gives no usual feedback when uploading a transaction file where the username or the comment contains strings that apparently results in a syntactically erroneous SQL query. We continued to determine the table structure using a brute force script which tests for some expectable table and column names, the results can be found below. Finally, we were able to exploit the SQL injection vulnerability in the TAN field to use any unused TAN from any user.</p>
Impact	An attacker can log into any account, of which he knows the username, and perform transactions without knowing valid TANs for that account by uploading a transaction batch file. Furthermore, as an attacker can take over an administrator account, if he knows the username, he has access to all accounts and can change the account balances at will. Also, an attacker can analyze the structure of a database.
Likelihood	High

Access Vector	Network
Access Complexity	Low
Privileges Required	None
User Interaction	None
Scope	Unchanged
Confidentiality	High
Integrity	High
Availability	No Impact

Results of the brute-force script

Table payment: id, trancode, payer, receipt, amount, purpose
Table user: id, balance, email, username, password, isemployee
Table userrequest: id, email, username, password, isemployee
Table paymentrequest: id, trancode, payer, receipt, amount, purpose
Table trancode: id, clientid

SecureBank

TODO!	Observation	
	Discovery	
	Impact	
	Likelihood	Low
	Access Vector	Network
	Access Complexity	Low
	Privileges Required	None
	User Interaction	None
	Scope	Unchanged
	Confidentiality	Low
	Integrity	Low
	Availability	No Impact

Comparison

TODO!

4.7 Error Handling

4.7.1 Analysis of Error Codes

Online Banking

Observation	We were not able to get reveal any information about the database, but we were able to get usual error codes of an apache server. The error pages also revealed information about the version, which is 2.2.22 on an Ubuntu server.
Discovery	By using the fuzzer jbrofuzz / SQL Injection / MySQL Injection 101 of ZAP on the purpose field of the online transaction form, we got one response which simply stated Database error, but gave no further information. Using a browser, we requested the page /InternetBanking/foobar/, which returned a 404 error, with further information about the server operating system and the Apache version.
Impact	Using the apache version, an attacker can run known exploits for this specific version.
Likelihood	Medium
Access Vector	Network
Access Complexity	Low
Privileges Required	None
User Interaction	None
Scope	Unchanged
Confidentiality	No Impact
Integrity	No Impact
Availability	No Impact

SecureBank

Observation	We were not able to get reveal any information about the database, but we were able to get usual error codes of an apache server. The error pages also revealed information about the version, which is 2.2.22 on an Ubuntu server. On the login page, we found an error code if the login was unsuccessful. Apparently, the code is always 1, if the credentials are incorrect.
Discovery	By using the fuzzer jbrofuzz / SQL Injection / MySQL Injection 101 of ZAP on the purpose field of the on-line transaction form, we were not able to produce a databse error. Using a browser, we requested the page /seccoding-2015/foobar/, which returned a 404 error, with further information about the server operating system and the Apache version.
Impact	Using the apache version, an attacker can run known exploits for this specific version.
Likelihood	Medium
Access Vector	Network
Access Complexity	Low
Privileges Required	None
User Interaction	None
Scope	Unchanged
Confidentiality	No Impact
Integrity	No Impact
Availability	No Impact

Comparison

Although the Online Banking application produces an error message about a database error, they provide the similar information in error messages.

4.7.2 Testing for Stack Traces

We were not able to produce stack traces in both applications using invalid inputs (e.g. negative numbers), or SQL injection.

4.8 Testing for weak Cryptography

TODO!

4.9 Business Logic Testing

TODO!

4.10 Client Side Testing

TODO!

Acronyms

TUM Technische Universität München.