

Standard Operating Procedure — ARV-5 Brake System Inspection

Reference SOP-BRK-031 Revision A Unit: 12 Field Workshop

FICTIONAL CONTENT — generated for platform testing only.

1 Purpose

To define the first-line brake system inspection for the fictional ARV-5 recovery vehicle, carried out before any recovery task and at scheduled servicing.

2.4 Wheel Nut Torque

Wheel nuts shall be tightened to 620 Nm in a diagonal sequence. Re-check the torque after the first 50 km following any wheel removal, and again at the next scheduled service.

3.1 Air Pressure Check

With the engine at idle, system air pressure shall build to 8.2 bar within four minutes. A build time exceeding four minutes indicates compressor wear and shall be raised as a second-line demand.

4.1 Brake Fluid

The braking system uses DOT-4 fluid. Fluid shall be replaced every 24 months regardless of mileage, and always after any hydraulic component has been opened to atmosphere.

4.6 Pad Wear Limit

Friction material shall be replaced when the remaining thickness reaches 4.5 mm at any point across the pad. Pads worn unevenly by more than 2 mm across their width indicate caliper misalignment and require investigation.

6.1 Deferral

A brake defect may not be deferred. Any vehicle failing this inspection is declared non-task-worthy and immobilised until rectified.