

```
<!DOCTYPE html>

<html lang="en">

<head>

<meta charset="UTF-8">

<title>Form Validation Example</title>
```

```
<style>

  body {

    font-family: Arial, sans-serif;

    margin: 40px;

  }
```

```
  form {

    width: 300px;

  }
```

```
  input {

    width: 100%;

    padding: 8px;

    margin-top: 5px;

    margin-bottom: 10px;

  }
```

```
  .error {

    color: red;

    font-size: 14px;

  }
```

```
  button {

    padding: 8px 15px;

    cursor: pointer;
```

```
}
</style>
</head>

<body>

<h2>Registration Form</h2>

<form id="myForm" onsubmit="return validateForm()">

  <label>Name:</label>
  <input type="text" id="name">
  <div id="nameError" class="error"></div>

  <label>Email:</label>
  <input type="text" id="email">
  <div id="emailError" class="error"></div>

  <button type="submit">Submit</button>

</form>

<script>
function validateForm() {

  let name = document.getElementById("name").value.trim();
  let email = document.getElementById("email").value.trim();

  let nameError = document.getElementById("nameError");
  let emailError = document.getElementById("emailError");
```

```
// Clear previous errors

nameError.innerHTML = "";
emailError.innerHTML = "";


let valid = true;


// Name validation
if (name === "") {
    nameError.innerHTML = "Name cannot be empty";
    valid = false;
}

// Email validation
let emailPattern = /^[^\s@]+@[^\s@]+\.[^\s@]+$/;

if (email === "") {
    emailError.innerHTML = "Email cannot be empty";
    valid = false;
}
else if (!emailPattern.test(email)) {
    emailError.innerHTML = "Please enter a valid email address";
    valid = false;
}

return valid; // if false, form submission stops
}

</script>
</body>
</html>
```