

1. `read_csv()` : Read a comma-separated values (csv) file into DataFrame.
2. `columns` : It is an inbuilt variable , which returns column names from the dataframe
3. `info()` : used to get information about the DataFrame
4. `head()` : used to get top **N** rows (default **N=5**)
5. `tail()` : used to get bottom **N** rows (default **N=5**)
6. `fillna()` : used to fill the missing values (None,NaN)
7. `dropna()` : auto detects the rows and columns which are having missing values and removes them
axis=0 (remove the rows which are having missing values)
axis=1 (remove the columns which are having missing values)
8. `astype()` : used to convert dtype of columns (**dict** can be passed as argument)
9. `drop()` : used to remove the specific row/column
(index / columns) or (axis=0/ axis=1) can be used respectively.
10. `rename()` : used to change the name of the rows/columns
(index / columns) or (axis=0/ axis=1) can be used respectively.
11. `replace()` : used to replace one or more old_vals by new_vals
(**dict** can be passed as arg)
12. `replace()` : used to replace the all old_values by new_values
(if not then replaces by NaN/None)
(**dict** can be passed as arg)
13. `reset_index()`: used to reset the index which starts from ZERO
14. `drop_duplicates()` : Returns DataFrame with duplicate rows removed.
(if not used on DataFrame then duplicates are replcd by NaN/None)

- `df.info()` – Displays a summary of the DataFrame including data types, non-null counts, and memory usage.
- `df.head()` – Returns the first 5 rows of the DataFrame.
- `df.tail()` – Returns the last 5 rows of the DataFrame.
- `df.describe()` – Provides summary statistics for numeric columns.
- `df.duplicated()` – Returns a Boolean Series indicating duplicate rows.
- `df.drop_duplicates()` – Removes duplicate rows from the DataFrame.
- `df.astype()` – Converts the data type of one or more columns.
- `df.fillna()` – Replaces missing values with a specified value or method.
- `df.dropna()` – Removes rows (or columns) with missing values.
- `df.drop()` – Deletes specified rows or columns from the DataFrame.
- `df.map()` – Applies a function or mapping to each element in a Series.
- `df.replace()` – Replaces specific values in the DataFrame with others.
- `df.rename()` – Renames index or column labels.
- `df.set_index()` – Sets a column as the DataFrame index.
- `df.reset_index()` – Resets the index to the default integer index.
- `df.groupby()` – Groups data based on column values and enables aggregation.
- `df.sort_index()` – Sorts the DataFrame by its index.
- `df.sort_values()` – Sorts the DataFrame by the values in one or more columns.
- `df.corr()` – Computes pairwise correlation of numeric columns.
- `df.isnull()` – Returns a Boolean DataFrame indicating missing values.
- `df[col].nunique()` – Counts the number of unique values in a column.
- `df[col].unique()` – Returns the unique values in a column.
- `df[col].value_counts()` – Returns the count of each unique value in a column.

- `pd.read_csv()` – Reads a CSV file into a DataFrame.
- `pd.read_excel()` – Reads an Excel file into a DataFrame.
- `pd.read_json()` – Reads a JSON file or string into a DataFrame.
- `pd.Series()` – Creates a one-dimensional labeled array.
- `pd.DataFrame` – Creates a two-dimensional labeled data structure (table).
- `pd.to_datetime()` – Converts a column or value to datetime format.
- `pd.cut()` – Bins continuous data into discrete intervals.
- `pd.merge()` – Merges DataFrames using database-style join operations.
- `pd.concat()` – Concatenates pandas objects along a particular axis.
- `pd.pivot()` – Reshapes data based on column values (requires unique combinations).
- `pd.melt()` – Unpivots a DataFrame from wide to long format.
- `pd.pivot_table()` – Creates a pivot table with aggregation, similar to Excel pivot.
- `count()` – Returns the number of non-missing values in each column or row.
- `max()` – Returns the maximum value in each column or row.
- `min()` – Returns the minimum value in each column or row.
- `sum()` – Returns the sum of values for each column or row.
- `mean()` – Returns the mean (average) of values in each column or row.
- `idxmax()` – Returns the index of the first occurrence of the maximum value.
- `idxmin()` – Returns the index of the first occurrence of the minimum value.
- `agg()` – Applies one or more aggregation functions to a DataFrame or Series.

`df.info()`
`df.head()`
`df.tail()`
`df.describe()`
`df.duplicated()`
`df.drop_duplicates()`
`df.astype()`
`df.fillna()`
`df.dropna()`
`df.drop()`
`df.map()`
`df.replace()`
`df.rename()`
`df.set_index()`
`df.reset_index()`
`df.groupby()`
`df.sort_index()`
`df.sort_values()`
`df.corr()`
`df.isnull()`
`df[col].nunique()`
`df[col].unique()`
`df[col].value_counts`

`Pd.read_csv()`
`Pd.read_excel()`
`Pd.read_json()`
`Pd.Series()`
`Pd.DataFrame`
`Pd.to_datetime()`
`Pd.cut()`
`Pd.merge()`
`Pd.concat()`
`Pd.pivot()`
`Pd.melt()`
`Pd.pivot_table()`

`count()`
`max()`
`min()`
`sum()`
`mean()`
`idxmax()`
`idxmin()`
`agg()`

`shape`
`columns`
`index`
`values`
`loc[]`
`iloc[]`

`Str.` (built-in methods)