InfoMorph Installation Guide

Version 1.0 | 28 October 2026 | Baseline ade0695

This guide explains local installation, environment configuration, Supabase preparation and first-run checks for InfoMorph.

Prerequisites

Use a current Node.js 22.12+ or 24 release and npm. This is a conservative setup recommendation, not a verified minimum for every locked dependency. You need a Gemini account/key with access to a usable text model and a Supabase project for authentication and persistence. Registry and API network access are required.

Get the project

```
git clone https://github.com/snehakapilavayi/informorph1.0.git
cd informorph1.0
npm ci
```

For the supplied source archive, extract it and run npm ci in its project folder. package-lock.json is included. bun.lock also exists, but this guide uses npm consistently.

Configure the environment

Copy .env.example to .env and populate your own project values. On Windows use Copy-Item .env.example .env; on macOS/Linux use cp .env.example .env.

```
VITE_SUPABASE_URL=https://YOUR_PROJECT.supabase.co
VITE_SUPABASE_PUBLISHABLE_KEY=YOUR_PUBLIC_PUBLISHABLE_KEY
SUPABASE_URL=https://YOUR_PROJECT.supabase.co
SUPABASE_PUBLISHABLE_KEY=YOUR_PUBLIC_PUBLISHABLE_KEY
GEMINI_API_KEY=YOUR_PRIVATE_SERVER_KEY
INFOMORPH_MODEL=YOUR_ACCOUNT_ACCESSIBLE_GEMINI_TEXT_MODEL
```

The template also lists project IDs; set them to your Supabase project ID where required by your hosting integration. Optional INFOMORPH_TTS_MODEL and INFOMORPH_VIDEO_MODEL override media models. Choose model names accessible to your account; defaults in the code are not verified by this package. The same public Supabase endpoint/key should be used on both client and server for a conventional local setup. The client contains public deployment fallbacks; set explicit values to avoid using that existing project unintentionally.

Keep GEMINI_API_KEY and any SUPABASE_SERVICE_ROLE_KEY private and server-side. Never put them in VITE_ variables. Set SUPABASE_SERVICE_ROLE_KEY only if deploying server helpers that need it. LOVABLE_DB_MIGRATION_URL is for the included Drizzle database tooling, not a frontend variable.

Prepare Supabase

Use a fresh project or inspect existing tables before applying the initial migration. The first migration creates tables and policies without idempotent guards.

1. Create private Storage buckets named source-documents and generated-media in the Supabase dashboard.
2. Run drizzle/migrations/0000_migration.sql in the SQL editor once.
3. Run drizzle/migrations/0001_media_columns_policies.sql once.
4. Enable email/password authentication. Set the site URL and allowed redirect URLs to your local/deployed origin and /studio callback as appropriate.
5. Google login uses @lovable.dev/cloud-auth-js. Configure the supported Lovable OAuth integration if using it; generic Supabase Google settings alone do not replace that helper. Email login is a separate path.
6. Test owner isolation with two accounts. Check private bucket uploads and downloads.

Start and check

npm run dev

npm test

npm run build

npm run lint

Use the local URL printed by Vite. Visit /studio directly for the main workflow, /auth to sign in and / for the story page. Run npm run preview to inspect the build using the configured preview command. The preset includes Nitro with a Cloudflare default target; production deployment needs a compatible server runtime and private environment secrets. Uploading only the public folder will not deploy server functions.

First smoke test

Paste the example in 07_Demo_Script_and_Final_Checks.md. Generate WhatsApp, Instagram and email drafts. Check the deadline and claim quotes. Edit a date in a draft and re-verify. Compare the revised source. Sign in, save and reload. Test audio/video separately before including them in the pitch.

Troubleshooting

Missing key: set GEMINI_API_KEY in the server runtime and restart. Model/quota errors: verify account access, billing and the model override. Save errors: check session, migrations, buckets and policies. Empty PDF: use a selectable-text PDF or paste the text. URL import failure: paste page text if it is blocked, unreadable or JavaScript-rendered. Build failures: retain logs and resolve them before marking the submission validated.

This guide is based on source inspection. Dependency installation and deployment smoke tests have not been completed in this environment.

Demo source

Final-year undergraduate students can apply for the Innovation Showcase. Registration closes on 15 November 2026. Register using the student portal. There is no registration fee.

For revision testing, change the deadline to 20 November 2026, compare source versions and regenerate affected drafts.

Completion checklist

- Dependencies installed and environment configured
- Tables, policies and private storage buckets prepared
- Generation and revision workflow checked
- Sign-in, save and reload checked
- Tests, build and lint results recorded