React Quiz 3

Total points 9/11

Email *

snehakumarisah@gmail.com

0 of 0 points

Enter Your Name *

sneha kumari

Quiz

9 of 11 points

✕ What is the primary purpose of the React Compiler? 0/1

- (●) To transpile JSX into JavaScript using Babel ✕
- ( ) To automatically optimize React components by memoizing values and functions
- ( ) To bundle React applications for production
- ( ) To convert React code into WebAssembly

Correct answer

- (●) To automatically optimize React components by memoizing values and functions

✓ In the following code, what is the purpose of the useDispatch hook? 1/1

```
function Counter() {
  const dispatch = useDispatch();

  const increment = () => {
    dispatch({ type: 'INCREMENT' });
  };

  return (
    <button onClick={increment}>Increment</button>
  );
}
```

- ○ It synchronizes the redux state with the component state.
- ◉ It dispatches the action to the redux store ✓
- ○ It is used to update the local component state.
- ○ It saves the action lo the local storage

✓ What is the **purpose** of the **Redux store**? 1/1

- ○ To store the components' local state in React.
- ◉ To store and manage the entire state of the application in a central location. ✓
- ○ To execute asynchronous actions and update the DOM.
- ○ To create a connection between React components and their local state.

✓ Which of the following is the **main purpose** of using useSelector in a React component? 1/1

- ○ To dispatch actions to the Redux store.
- ◉ To subscribe to and retrieve state from the Redux store. ✓
- ○ To modify the state directly within the Redux store.
- ○ To trigger asynchronous actions like API calls.

✓ You are building a **dashboard** in React that displays data fetched from an API. The data needs to be **automatically refreshed** every minute. What is the best way to implement this functionality? 2/2

- ○ Use setTimeout inside a component to fetch data every minute.
- ◉ Use useEffect with setInterval to repeatedly fetch data every minute and clear the interval when the component unmounts. ✓
- ○ Use the onClick event of a refresh button to manually fetch data every time the user clicks.
- ○ Call the API in the render method to ensure the data is fetched on every re-render.

✓ What is the **primary purpose** of using the **React Context** API? 1/1

- ○ To fetch data from an external API.
- ◉ To manage global state and pass data deeply through the component tree without manually passing props at every level. ✓
- ○ To handle side effects in functional components.
- ○ To improve performance by memoizing functions.

✓ Which of the following is **true** about Redux reducers? 1/1

- ○ Reducers are responsible for handling side effects like API calls.
- ◉ Reducers must always return a new state object instead of modifying the current state directly. ✓
- ○ A reducer function can dispatch actions to update the state.
- ○ Reducers can directly manipulate the DOM based on the state changes.

What will happen when the PostData component is rendered and the button is clicked? 1/1

```
import React, { useState } from 'react';
import axios from 'axios';

function PostData() {
  const [title, setTitle] = useState('');
  const [response, setResponse] = useState(null);

  const handlePost = async () => {
    try {
      const res = await
axios.post('https://jsonplaceholder.typicode.com/posts', {
        title: title,
        body: 'Sample body',
        userId: 1
      });
      setResponse(res.data);
    } catch (error) {
      console.error('Error posting data', error);
    }
  };

  return (
    <div>
      <input
        type="text"
        value={title}
        onChange={(e) => setTitle(e.target.value)}
        placeholder="Enter title"
      />
      <button onClick={handlePost}>Post Data</button>
      {response && <p>Posted: {response.title}</p>}
    </div>
  );
}

export default PostData;
```

- (●) Clicking the button will post data to the API and display the posted title. ✓
- ( ) Clicking the button will throw an error because axios.post cannot be used inside an async function.
- ( ) Clicking the button will not post any data because the title input is empty by default.
- ( ) The response will always be null and nothing will be displayed.

✓ Which of the following is a correct rule when creating custom hooks? 1/1

- (●) Custom hooks use other hooks inside them ✓
- ( ) Custom hook's name can start with any word
- ( ) Custom hooks can only be used in SSR components
- ( ) Custom hooks can be used in class and functional components

✕ Which of the following is **true** about the following data-fetching component? 0/1

```
import React, { useState, useEffect } from 'react';
import axios from 'axios';

function FetchMultipleData() {
  const [users, setUsers] = useState([]);
  const [posts, setPosts] = useState([]);

  useEffect(() => {
    const fetchData = async () => {
      try {
        const [usersResponse, postsResponse] = await Promise.all([
          axios.get('https://jsonplaceholder.typicode.com/users'),
          axios.get('https://jsonplaceholder.typicode.com/posts')
        ]);
        setUsers(usersResponse.data);
        setPosts(postsResponse.data);
      } catch (error) {
        console.error('Error fetching data:', error);
      }
    };

    fetchData();
  }, []);

  return (
    <div>
      <h2>Users</h2>
      <ul>{users.map(user => <li key={user.id}>{user.name}</li>)}</ul>
      <h2>Posts</h2>
      <ul>{posts.map(post => <li key={post.id}>{post.title}</li>)}</ul>
    </div>
  );
}

export default FetchMultipleData;
```

- (●) The component will fetch the users first and then fetch the posts. ✗
- ( ) The component will only fetch the users, not the posts.
- ( ) The component will fetch and display users and posts simultaneously.
- ( ) The component will throw an error because Promise.all() is not used correctly.

Correct answer

- (●) The component will fetch and display users and posts simultaneously.

This content is neither created nor endorsed by Google. - Contact form owner - Terms of Service - Privacy Policy

Does this form look suspicious? Report

Google Forms