# Large-scale structure of complex networks (Part 2)

Snehal M. Shekatkar

Centre for modeling and simulation, S.P. Pune University, Pune Large-scale structure of complex networks (Part 2)

Large-scale structure of complex networks (Part 2)


Suehal M. Shekotkor

Caste for modifieg and simulation.

S.P. Pane University, Pane

Hello

## Community structure in networks





Large-scale structure of complex networks (Part 2)  $\,$ 



Community structure in networks

Network of coauthorships in a university department

## Community structure in networks

#### What are communities?

- ► **Traditional definition**: Groups of nodes with a high internal link density
- ▶ Modern definition: Nodes with similar connection probabilities to the rest of the network

Large-scale structure of complex networks (Part 2)

Community structure in networks

Community structure in networks

What are communities?

 Traditional definition: Groups of nodes with a high internal link density

ties to the rest of the network

#### Communities in the real-world networks

#### Social networks:

- ► Friend-circles
- ► Research communities
- Co-workers

#### World Wide Web:

- ▶ Pages with similar contents
- ▶ Webpages under the same domain (e.g. Wikipedia)

#### ▶ Biological network:

▶ Proteins with similar roles in protein interaction networks

4 D > 4 A > 4 B > 4 B > B 9 Q (>

- Chemicals together taking part in chemical reactions in metabolic networks
- ▶ Communities in neuronal networks

Large-scale structure of complex networks (Part 2)

-Communities in the real-world networks

Communities in the real-world networks


Friend-rireles

- Research communities
- ▶ World Wide Web:
- · Pages with similar contents Webnares under the same domain (e.e. Wikinedia)
- · Proteins with similar roles in protein interaction networks · Chemicals together taking part in chemical reactions in metabolic networks
  - Communities in neuronal networks

## Community detection

#### Detecting communities is important!

- ▶ Communities are building blocks of networks
- ▶ Communities allow us to see "the big picture"
- ► Functional/Autonomous units
- ▶ Non-trivial effects on the processes on networks



Community detection


Community detection

Detecting communities is important!

- Communities are building blocks of netwo
- Communities allow us to see "the big pict
  - Functional/Autonomous units
- $\blacktriangleright$  Non-trivial effects on the processes on networks

#### Graph partitioning

Problem of dividing a graph in a given number of groups of given sizes such that the number of links between the groups (cut size) is minimized




Large-scale structure of complex networks (Part 2)

└─Graph partitioning



## Graph partitioning

Problem of dividing a graph in a given number of groups of given sizes such that the number of links between the groups (cut size) is minimized



Large-scale structure of complex networks (Part 2)

—Graph partitioning



Partitioning is hard!

▶ Number of ways:  $\frac{a!}{a \cdot b \cdot a!} \approx \frac{2^{a+1}}{a!}$ 


Partitioning is hard!

Heuristics are needed

- ightharpoonup Graph with n vertices
- Find two groups with sizes  $n_1$  and  $n_2$  such that the cut size is minimum
- Number of ways:  $\frac{n!}{n_1!n_2!} \approx \frac{2^{n+1}}{\sqrt{n}}$


Heuristics are needed!

cut size = 4




▶ Divide the vertices into two groups of the required sizes and calculate the cut size Large-scale structure of complex networks (Part 2)

└─Kernighan-Lin algorithm




cut size = 4



- ► Divide the vertices into two groups of the required sizes and calculate the cut size
- ► Find a pair of nodes which when switched, will reduce the cut size most and switch them


Large-scale structure of complex networks (Part 2)

└─Kernighan-Lin algorithm



Kernighan-Lin algorithm

cut size = 2



- ▶ Divide the vertices into two groups of the required sizes
- ► Find a pair of nodes which when switched, will reduce the cut size most and switch them

Large-scale structure of complex networks (Part 2)


—Kernighan-Lin algorithm

2017-12-29





cut size = 2



- ▶ Divide the vertices into two groups of the required sizes
- ► Find a pair of nodes which when switched, will reduce the cut size most and switch them
- ► If no such pair exists, select the pair which least increases the cut size

#### Large-scale structure of complex networks (Part 2)

-Kernighan-Lin algorithm


2017-12-29



Kernighan-Lin algorithm



cut size = 2



- ▶ Divide the vertices into two groups of the required sizes
- ► Find a pair of nodes which when switched, will reduce the cut size most and switch them
- ► If no such pair exists, select the pair which least increases the cut size
- ► Continue this such that the already switched pair is not switched again

Large-scale structure of complex networks (Part 2)



Kernighan-Lin algorithm

▶ If no such pair exists, select

the pair which least increases · Continue this such that the

already switched pair is not

-Kernighan-Lin algorithm

2017-12-29

- ▶ Go through all the states and select the one with the least cut size
- ▶ Start with this state and repeat the whole procedure
- ▶ Continue till the cut size no longer becomes smaller
- ▶ Starting with many random initial conditions is better

Large-scale structure of complex networks (Part 2)

-Kernighan-Lin algorithm


Kernighan-Lin algorithm

- Go through all the states and select the one with the leas cut size
- Start with this state and repeat the whole procedure
- Continue till the cut size no longer becomes smal
- Starting with many random initial conditions is b

Group sizes remain constant

#### Spectral paritioning

- ▶ Faster algorithm than Kernighan-Lin
- ▶ Uses properties of the graph Laplacian
- ▶ More complex to implement than Kernighan-Lin



\_Spectral paritioning

Spectral paritioning

- ▶ Faster algorithm than Kernighan-Lin
- Uses properties of the graph Laplace
- $\blacktriangleright$  More complex to implement than Kernighan-Lin

## Community detection is harder!

#### ► Graph partitioning

- well defined
- Number of groups is fixed
- Sizes of the groups are fixed
- ▶ Divide even if no good division exists

#### ► Community detection

- ▶ ill-defined
- ▶ Number of groups depends on the structure of the network
- ▶ Sizes of the groups depend on the structure of the network
- Discover natural fault lines

Large-scale structure of complex networks (Part 2)

-Community detection is harder!

12-29

7

Community detection is harder!


· Graph partitioning

- well defined
- Number of groups is fixed
- · Sizes of the groups are fixed Divide even if no rood division exists
- ► Community detection
- · Number of groups depends on the structure of the network
- · Discover natural fault lines

4 D > 4 A > 4 B > 4 B > B 9 Q (>

## Many definitions.. many algorithms!

- ▶ Girvan-Newman algorithm
- ► Kernighan-Lin-Newman algorithm
- ► Spectral decomposition
- ► Clique-percolation
- ▶ Radom walk methods
- ▶ Statistical inference
- ► Label propagation
- ► Hierarchical clustering



Many definitions.. many algorithms!

2017-12-29

Many definitions.. many algorithms!

- ► Kernighan-Lin-Newman algorithm
- ▶ Spectral decomposition Clique-percolation
- Radom walk method
- Statistical inference
- Label propagation
- Hierarchical clustering

I can go on.. These algorithms use different definitions/views of communities

#### Broad classification

#### ▶ Agglomerative algorithms:

- ► Hierarchical clustering
- ▶ Louvain method
- ► CNM algorithm

#### ▶ Divisive algorithms:

- ► Girvan-Newman algorithm
- ▶ Radichhi algorithm

#### ► Assignment algorithms:

- ▶ Label propagation
- ► Spectral partitioning
- ► Kernighan-Lin-Newman algorithm

Large-scale structure of complex networks (Part 2)

-Broad classification

7 - 12 - 29

Broad classification

Agglomerative algorithms

Hierarchical clustering

· Lorrain method CNM algorithm


Divisive algorithms:

 Radichhi algorithm Assignment algorithms

Label propagation

"The" simplest community detection problem

- ightharpoonup Bisecting a graph with n nodes
- ► Group sizes are not fixed
- ▶ Minimum cut size?





"The" simplest community detection problem


- ▶ Bisecting a graph with n nodes
   ▶ Group sizes are not fixed
- ► Minimum cut size?

Empty group

"The" simplest community detection problem

- ightharpoonup Bisecting a graph with n nodes
- ► Group sizes are not fixed
- ▶ Minimum cut size?

A different measure of the quality of division is required..



Different measure

Large-scale structure of complex networks (Part 2)  $\,$ 

Quantification of community structure


• Fewer than expected edges between the groups

2017-12-29

—Quantification of community structure

few edges = expected edges = not a good division

- ▶ Fewer than expected edges between the groups
- ▶ Equivalently, more than expected edges inside the groups




Quantification of community structure

Quantification of community structure

Fewer than expected edges detween the groups
 Equivalently, more than expected edges inside the

Remember assortativity

- ▶ Fewer than expected edges between the groups
- ▶ Equivalently, more than expected edges inside the groups
- ► Assortativity mixing and modularity



└─Quantification of community structure

Quantification of community structure

- Fewer than expected edges between the group
- Equivalently, more than expected edges inside the
- Assortativity mixing and modularity

Divide network using modularity

- ► Fewer than expected edges between the groups
- ▶ Equivalently, more than expected edges inside the groups
- ► Assortativity mixing and modularity
- ▶ Look for divisions with high modularity

Large-scale structure of complex networks (Part 2)

-Quantification of community structure

Quantification of community structure

- Fewer than expected edges between the group
- Equivalently, more than expected edges inside the g
  - Assortativity mixing and modul
  - Look for divisions with hi

Heuristics are needed

2017-12-29

- ▶ Fewer than expected edges between the groups
- ▶ Equivalently, more than expected edges inside the groups
- ► Assortativity mixing and modularity
- ▶ Look for divisions with high modularity
- ▶ Modularity maximization is hard

#### Large-scale structure of complex networks (Part 2)

└─Quantification of community structure

2017-12-29

Fewer than expected edges between the groups

Equivalently, more than expected edges inside the

Assortativity mixing and modularity


Quantification of community structure

Look for divisions with high mod

Modularity maximization is hard

## Newman-Girvan algorithm

- ▶ Look for edges between the communities
- ► Edge betweenness



Newman-Girvan algorithm


Look for edges between the communities

► Edge betweenness

Let's have a look at the edge betweenness

#### Edge betweenness

- ▶ Path between two nodes
- ► Shortest path between two nodes
- ▶ Number of shortest paths that go through a given edge



Large-scale structure of complex networks (Part 2)

LEdge betweenness



The algorithm

- ▶ Calculate betweenness for all edges
- ▶ Remove the edge with the highest betweenness
- ▶ Recalculate betweenness for all edges
- ► Repeat

└─The algorithm

4 D > 4 B > 4 E > 4 E > E 990