

2017-12-30

Large-scale structure of complex networks (Part 2)

Large-scale structure of complex networks
(Part 2)

Snehal M. Shekatkar
Centre for modeling and simulation,
S.P. Pune University, Pune


Large-scale structure of complex networks (Part 2)

Snehal M. Shekatkar

Centre for modeling and simulation,
S.P. Pune University, Pune

Hello

Community structure in networks




2017-12-30

Large-scale structure of complex networks (Part 2)

└ Community structure in networks

Network of coauthorships in a university department

Community structure in networks



Community structure in networks

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Community structure in networks

What are communities?

- **Traditional definition:** Groups of nodes with a high internal link density
- **Modern definition:** Nodes with similar connection probabilities to the rest of the network

What are communities?

- **Traditional definition:** Groups of nodes with a high internal link density
- **Modern definition:** Nodes with similar connection probabilities to the rest of the network

└ Communities in the real-world networks

- ▶ **Social networks:**
 - Friend-circles
 - Research communities
 - Co-workers
- ▶ **World Wide Web:**
 - Pages with similar contents
 - Webpages under the same domain (e.g. Wikipedia)
- ▶ **Biological networks:**
 - Proteins with similar roles in protein interaction networks
 - Chemicals together taking part in chemical reactions in metabolic networks
 - Communities in neuronal networks

- ▶ **Social networks:**
 - ▶ Friend-circles
 - ▶ Research communities
 - ▶ Co-workers
- ▶ **World Wide Web:**
 - ▶ Pages with similar contents
 - ▶ Webpages under the same domain (e.g. Wikipedia)
- ▶ **Biological networks:**
 - ▶ Proteins with similar roles in protein interaction networks
 - ▶ Chemicals together taking part in chemical reactions in metabolic networks
 - ▶ Communities in neuronal networks

Community detection

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Community detection

Detecting communities is important!


- ▶ Communities are building blocks of networks
- ▶ Communities allow us to see “the big picture”
- ▶ Functional/Autonomous units
- ▶ Non-trivial effects on the processes on networks

Detecting communities is important!

- ▶ Communities are building blocks of networks
- ▶ Communities allow us to see “the big picture”
- ▶ Functional/Autonomous units
- ▶ Non-trivial effects on the processes on networks

Graph partitioning

Problem of dividing a graph in a given number of groups of given sizes such that the number of links between the groups (**cut size**) is minimized



2017-12-30

Large-scale structure of complex networks (Part 2)

└ Graph partitioning


Graph partitioning

Problem of dividing a graph in a given number of groups of given sizes such that the number of links between the groups (**cut size**) is minimized



Graph partitioning

Problem of dividing a graph in a given number of groups of given sizes such that the number of links between the groups (**cut size**) is minimized



2017-12-30

Large-scale structure of complex networks (Part 2)

└ Graph partitioning

Graph partitioning

Problem of dividing a graph in a given number of groups of given sizes such that the number of links between the groups (**cut size**) is minimized

2017-12-30


- └ Partitioning is hard!

- ## Heuristics are needed!

Heuristics are needed!

Kernighan-Lin algorithm

cut size = 4



- Divide the vertices into two groups of the required sizes and calculate the cut size

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Kernighan-Lin algorithm

Kernighan-Lin algorithm


cut size = 4



- Divide the vertices into two groups of the required sizes and calculate the cut size

Kernighan-Lin algorithm

cut size = 4



- ▶ Divide the vertices into two groups of the required sizes and calculate the cut size
- ▶ Find a pair of nodes which when switched, will reduce the cut size most and switch them

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Kernighan-Lin algorithm

Kernighan-Lin algorithm


cut size = 4



- Divide the vertices into two groups of the required sizes and calculate the cut size
- Find a pair of nodes which when switched, will reduce the cut size most and switch them

Kernighan-Lin algorithm

cut size = 2



- ▶ Divide the vertices into two groups of the required sizes
- ▶ Find a pair of nodes which when switched, will reduce the cut size most and switch them

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Kernighan-Lin algorithm

Kernighan-Lin algorithm


cut size = 2



- ▶ Divide the vertices into two groups of the required sizes
- ▶ Find a pair of nodes which when switched, will reduce the cut size most and switch them

Kernighan-Lin algorithm

cut size = 2




- ▶ Divide the vertices into two groups of the required sizes
- ▶ Find a pair of nodes which when switched, will reduce the cut size most and switch them
- ▶ If no such pair exists, select the pair which least increases the cut size

2017-12-30

Large-scale structure of complex networks (Part 2)


└ Kernighan-Lin algorithm

Kernighan-Lin algorithm



Kernighan-Lin algorithm

cut size = 2



- ▶ Divide the vertices into two groups of the required sizes
- ▶ Find a pair of nodes which when switched, will reduce the cut size most and switch them
- ▶ If no such pair exists, select the pair which least increases the cut size
- ▶ Continue this such that the already switched pair is not switched again

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Kernighan-Lin algorithm


Kernighan-Lin algorithm

cut size = 2



- ▶ Divide the vertices into two groups of the required sizes
- ▶ Find a pair of nodes which when switched, will reduce the cut size most and switch them
- ▶ If no such pair exists, select the pair which least increases the cut size
- ▶ Continue this such that the already switched pair is not switched again

Kernighan-Lin algorithm



- ▶ Go through all the states and select the one with the least cut size
- ▶ Start with this state and repeat the whole procedure
- ▶ Continue till the cut size no longer becomes smaller
- ▶ Starting with many random initial conditions is better

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Kernighan-Lin algorithm

Group sizes remain constant

Kernighan-Lin algorithm



- Go through all the states and select the one with the least cut size
- Start with this state and repeat the whole procedure
- Continue till the cut size no longer becomes smaller
- Starting with many random initial conditions is better

Spectral partitioning

- ▶ Faster algorithm than Kernighan-Lin
- ▶ Uses properties of the graph Laplacian
- ▶ More complex to implement than Kernighan-Lin

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Spectral partitioning

Spectral partitioning

- ▶ Faster algorithm than Kernighan-Lin
- ▶ Uses properties of the graph Laplacian
- ▶ More complex to implement than Kernighan-Lin

Spectral partitioning

Cut size:

$$R = \frac{1}{2} \sum_{\substack{i,j \text{ in} \\ \text{different} \\ \text{groups}}} A_{ij}$$

Define

$$s_i = \begin{cases} +1 & \text{if vertex } i \text{ belongs to group 1} \\ -1 & \text{if vertex } i \text{ belongs to group 2} \end{cases}$$

Then

$$\frac{1}{2}(1 - s_i s_j) = \begin{cases} 1 & \text{if } i \text{ and } j \text{ are in different groups,} \\ 0 & \text{if } i \text{ and } j \text{ are in the same group} \end{cases}$$

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Spectral partitioning

Spectral partitioning

Cut size:

$$R = \frac{1}{2} \sum_{\substack{i,j \text{ in} \\ \text{different} \\ \text{groups}}} A_{ij}$$

Define

$$s_i = \begin{cases} +1 & \text{if vertex } i \text{ belongs to group 1} \\ -1 & \text{if vertex } i \text{ belongs to group 2} \end{cases}$$

Then

$$\frac{1}{2}(1 - s_i s_j) = \begin{cases} 1 & \text{if } i \text{ and } j \text{ are in different groups,} \\ 0 & \text{if } i \text{ and } j \text{ are in the same group} \end{cases}$$

Spectral partitioning

$$R = \frac{1}{4} \sum_{ij} A_{ij} (1 - s_i s_j)$$

First term,

$$\sum_{ij} A_{ij} = \sum_i k_i = \sum_i k_i s_i^2 = \sum_{ij} k_i \delta_{ij} s_i s_j$$

$$R = \frac{1}{4} \sum_{ij} (k_i \delta_{ij} - A_{ij}) s_i s_j = \frac{1}{4} \sum_{ij} L_{ij} s_i s_j$$

$$R = \frac{1}{4} \mathbf{s}^T \mathbf{L} \mathbf{s}$$

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Spectral partitioning

L is so imp that we have a name for it! Laplacian

·
s is a columnvector

·
L: structure, s: division

·
find s that minimizes R

·
Problem is hard, s takes only integer values

·

Spectral partitioning

$$R = \frac{1}{4} \sum_{ij} A_{ij} (1 - s_i s_j)$$

First term,

$$\sum_{ij} A_{ij} = \sum_i k_i = \sum_i k_i s_i^2 = \sum_{ij} k_i \delta_{ij} s_i s_j$$

$$R = \frac{1}{4} \sum_{ij} (k_i \delta_{ij} - A_{ij}) s_i s_j = \frac{1}{4} \sum_{ij} L_{ij} s_i s_j$$


$$R = \frac{1}{4} \mathbf{s}^T \mathbf{L} \mathbf{s}$$

Relaxation method

Two constraints:

- ▶ s_i can be only ± 1
- ▶ $\sum_i s_i = n_1 - n_2 \Rightarrow \mathbf{1}^T \mathbf{s} = n_1 - n_2$

Relax the first constraint



2017-12-30

Large-scale structure of complex networks (Part 2)

Relaxation method

hypercube

.

continuous s, differentiate

Relaxation method

Two constraints:

- ▶ s_i can be only ± 1
- ▶ $\sum_i s_i = n_1 - n_2 \Rightarrow \mathbf{1}^T \mathbf{s} = n_1 - n_2$

Relax the first constraint



Spectral partitioning

Minimization with constraints \Rightarrow Lagrange multipliers

$$\frac{\partial}{\partial s_i} \left[\sum_{jk} L_{jk} s_j s_k + \lambda \left(n - \sum_j s_j^2 \right) + 2\mu \left((n_1 - n_2) - \sum_j s_j \right) \right] = 0$$

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Spectral partitioning

Spectral partitioning

Minimization with constraints \Rightarrow Lagrange multipliers

$$\frac{\partial}{\partial s_i} \left[\sum_{jk} L_{jk} s_j s_k + \lambda \left(n - \sum_j s_j^2 \right) + 2\mu \left((n_1 - n_2) - \sum_j s_j \right) \right] = 0$$

Spectral partitioning

Minimization with constraints \Rightarrow Lagrange multipliers

$$\frac{\partial}{\partial s_i} \left[\sum_{jk} L_{jk} s_j s_k + \lambda \left(n - \sum_j s_j^2 \right) + 2\mu \left((n_1 - n_2) - \sum_j s_j \right) \right] = 0$$

$$\sum_j L_{ij} s_j = \lambda s_i + \mu$$

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Spectral partitioning

Spectral partitioning

Minimization with constraints \Rightarrow Lagrange multipliers

$$\frac{\partial}{\partial s_i} \left[\sum_{jk} L_{jk} s_j s_k + \lambda \left(n - \sum_j s_j^2 \right) + 2\mu \left((n_1 - n_2) - \sum_j s_j \right) \right] = 0$$
$$\sum_j L_{ij} s_j = \lambda s_i + \mu$$

Spectral partitioning

Minimization with constraints \Rightarrow Lagrange multipliers

$$\frac{\partial}{\partial s_i} \left[\sum_{jk} L_{jk} s_j s_k + \lambda \left(n - \sum_j s_j^2 \right) + 2\mu \left((n_1 - n_2) - \sum_j s_j \right) \right] = 0$$

$$\sum_j L_{ij} s_j = \lambda s_i + \mu$$

$$\mathbf{L}\mathbf{s} = \lambda\mathbf{s} + \mu\mathbf{1} = \lambda \left(\mathbf{s} + \frac{\mu}{\lambda}\mathbf{1} \right)$$

$$\mathbf{L} \left(\mathbf{s} + \frac{\mu}{\lambda}\mathbf{1} \right) = \lambda \left(\mathbf{s} + \frac{\mu}{\lambda}\mathbf{1} \right)$$

$\mathbf{1}$ is an eigenvector of the Laplacian with eigenvalue 0

$$\mathbf{L}\mathbf{x} = \lambda\mathbf{x}$$

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Spectral partitioning

Spectral partitioning

Minimization with constraints \Rightarrow Lagrange multipliers

$$\frac{\partial}{\partial s_i} \left[\sum_{jk} L_{jk} s_j s_k + \lambda \left(n - \sum_j s_j^2 \right) + 2\mu \left((n_1 - n_2) - \sum_j s_j \right) \right] = 0$$

$$\sum_j L_{ij} s_j = \lambda s_i + \mu$$

$$\mathbf{L}\mathbf{s} = \lambda\mathbf{s} + \mu\mathbf{1} = \lambda \left(\mathbf{s} + \frac{\mu}{\lambda}\mathbf{1} \right)$$

$$\mathbf{L} \left(\mathbf{s} + \frac{\mu}{\lambda}\mathbf{1} \right) = \lambda \left(\mathbf{s} + \frac{\mu}{\lambda}\mathbf{1} \right)$$

$\mathbf{1}$ is an eigenvector of the Laplacian with eigenvalue 0

$$\mathbf{L}\mathbf{x} = \lambda\mathbf{x}$$

Spectral partitioning

\mathbf{x} is an eigenvector of the Laplacian with eigenvalue λ

Which eigenvector to choose?

\mathbf{x} cannot be the eigenvector $\mathbf{1} = \begin{pmatrix} 1 \\ 1 \\ \cdot \\ \cdot \\ 1 \end{pmatrix}$

$$\mathbf{1}^T \mathbf{x} = \mathbf{1} \left(\mathbf{s} + \frac{\mu}{\lambda} \mathbf{1} \right) = (n_1 - n_2) + \frac{\mu}{\lambda} n = 0$$

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Spectral partitioning

\mathbf{x} is orthogonal to $\mathbf{1}$

.

\mathbf{x} is eigenvector but not $\mathbf{1}$

Spectral partitioning

\mathbf{x} is an eigenvector of the Laplacian with eigenvalue λ

Which eigenvector to choose?

\mathbf{x} cannot be the eigenvector $\mathbf{1} = \begin{pmatrix} 1 \\ 1 \\ \cdot \\ \cdot \\ 1 \end{pmatrix}$

$\mathbf{1}^T \mathbf{x} = \mathbf{1} \left(\mathbf{s} + \frac{\mu}{\lambda} \mathbf{1} \right) = (n_1 - n_2) + \frac{\mu}{\lambda} n = 0$

Which eigenvector to choose?

$$R = \frac{1}{4} \mathbf{s}^T \mathbf{L} \mathbf{s} = \frac{1}{4} \mathbf{x}^T \mathbf{x} = \frac{n_1 n_2}{n} \lambda$$

Choose the eigenvector with smallest possible eigenvalue!

Eigenvalues of the Laplacian are non-negative and smallest is always 0

$\mathbf{v}_1 = \mathbf{1}$ is ruled out already. So choose \mathbf{v}_2 with the smallest positive eigenvalue

└ Spectral partitioning

Which eigenvector to choose?
 $R = \frac{1}{4} \mathbf{s}^T \mathbf{L} \mathbf{s} = \frac{1}{4} \mathbf{x}^T \mathbf{x} = \frac{n_1 n_2}{n} \lambda$
Choose the eigenvector with smallest possible eigenvalue!
Eigenvalues of the Laplacian are non-negative and smallest is always 0
 $\mathbf{v}_1 = \mathbf{1}$ is ruled out already. So choose \mathbf{v}_2 with the smallest positive eigenvalue

Spectral partitioning

$$\mathbf{s} = x + \frac{n_1 - n_2}{n} \mathbf{1}$$

OR

$$s_i = x_i + \frac{n_1 - n_2}{n}$$

But s_i can be only ± 1

Thus, we want \mathbf{x} to be as close as possible to \mathbf{s}

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Spectral partitioning

Spectral partitioning

$$\mathbf{s} = x + \frac{n_1 - n_2}{n} \mathbf{1}$$

OR

$$s_i = x_i + \frac{n_1 - n_2}{n}$$

But s_i can be only ± 1

Thus, we want \mathbf{x} to be as close as possible to \mathbf{s}

Spectral partitioning

Maximize:

$$\mathbf{s}^T \left(\mathbf{x} + \frac{n_1 - n_2}{n} \mathbf{1} \right) = \sum_i s_i \left(x_i + \frac{n_1 - n_2}{n} \right)$$

Equivalently, maximize:

$$\sum_i s_i x_i$$

Simply put the n_1 vertices with most positive elements in group 1 and the rest ones in group 2

Group assignments are arbitrary

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Spectral partitioning

Choose the assignment with the smaller cut size

Spectral partitioning

Maximize:

$$\mathbf{s}^T \left(\mathbf{x} + \frac{n_1 - n_2}{n} \mathbf{1} \right) = \sum_i s_i \left(x_i + \frac{n_1 - n_2}{n} \right)$$

Equivalently, maximize:

$$\sum_i s_i x_i$$

Simply put the n_1 vertices with most positive elements in group 1 and the rest ones in group 2

Group assignments are arbitrary

2017-12-30

- Spectral partitioning

- Calculate v_2 of the Laplacian
- Put vertices corresponding to largest n_1 elements in group 1 and others in group 2. Calculate the cut size
- Put vertices corresponding to smallest n_1 elements in group 1 and others in group 2. Calculate the cut size
- Choose the division with the smallest cut size among the two

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Community detection is harder!

► **Graph partitioning**

- well defined
- Number of groups is fixed
- Sizes of the groups are fixed
- Divide even if no good division exists

► **Community detection**

- ill-defined
- Number of groups depends on the structure of the network
- Sizes of the groups depend on the structure of the network
- Discover natural fault lines

- **Graph partitioning**
 - well defined
 - Number of groups is fixed
 - Sizes of the groups are fixed
 - Divide even if no good division exists
- **Community detection**
 - ill-defined
 - Number of groups depends on the structure of the network
 - Sizes of the groups depend on the structure of the network
 - Discover natural fault lines

Many definitions.. many algorithms!

- ▶ Girvan-Newman algorithm
- ▶ Kernighan-Lin-Newman algorithm
- ▶ Spectral decomposition
- ▶ Clique-percolation
- ▶ Random walk methods
- ▶ Statistical inference
- ▶ Label propagation
- ▶ Hierarchical clustering

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Many definitions.. many algorithms!

I can go on.. These algorithms use different definitions/views of communities

- ▶ Girvan-Newman algorithm
- ▶ Kernighan-Lin-Newman algorithm
- ▶ Spectral decomposition
- ▶ Clique-percolation
- ▶ Random walk methods
- ▶ Statistical inference
- ▶ Label propagation
- ▶ Hierarchical clustering

Broad classification

- ▶ **Agglomerative algorithms:**
 - ▶ Hierarchical clustering
 - ▶ Louvain method
 - ▶ CNM algorithm
- ▶ **Divisive algorithms:**
 - ▶ Girvan-Newman algorithm
 - ▶ Radicchi algorithm
- ▶ **Assignment algorithms:**
 - ▶ Label propagation
 - ▶ Spectral partitioning
 - ▶ Kernighan-Lin-Newman algorithm

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Broad classification

- ▶ **Agglomerative algorithms:**
 - Hierarchical clustering
 - Louvain method
 - CNM algorithm
- ▶ **Divisive algorithms:**
 - Girvan-Newman algorithm
 - Radicchi algorithm
- ▶ **Assignment algorithms:**
 - Label propagation
 - Spectral partitioning
 - Kernighan-Lin-Newman algorithm

- ▶ Bisecting a graph with n nodes
- ▶ Group sizes are not fixed
- ▶ Minimum cut size?

2017-12-30

Large-scale structure of complex networks (Part 2)

└ “The” simplest community detection problem

Empty group

- ▶ Bisecting a graph with n nodes
- ▶ Group sizes are not fixed
- ▶ Minimum cut size?

“The” simplest community detection problem

- ▶ Bisecting a graph with n nodes
- ▶ Group sizes are not fixed
- ▶ Minimum cut size?

A different measure of the quality of division is required..

2017-12-30

Large-scale structure of complex networks (Part 2)

└ “The” simplest community detection problem

“The” simplest community detection problem

- ▶ Bisecting a graph with n nodes
- ▶ Group sizes are not fixed
- ▶ Minimum cut size?

A different measure of the quality of division is required..

Different measure

Quantification of community structure

- Fewer than expected edges between the groups

2017-12-30

Large-scale structure of complex networks (Part 2)

- └ Quantification of community structure

few edges = expected edges = not a good division

- Fewer than expected edges between the groups

Quantification of community structure

- ▶ Fewer than expected edges between the groups
- ▶ Equivalently, more than expected edges inside the groups

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Quantification of community structure

- ▶ Fewer than expected edges between the groups
- ▶ Equivalently, more than expected edges inside the groups

Remember assortativity

Quantification of community structure

- ▶ Fewer than expected edges between the groups
- ▶ Equivalently, more than expected edges inside the groups
- ▶ Assortativity mixing and modularity

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Quantification of community structure

Divide network using modularity

- ▶ Fewer than expected edges between the groups
- ▶ Equivalently, more than expected edges inside the groups
- ▶ Assortativity mixing and modularity

Quantification of community structure

- ▶ Fewer than expected edges between the groups
- ▶ Equivalently, more than expected edges inside the groups
- ▶ Assortativity mixing and modularity
- ▶ Look for divisions with high modularity

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Quantification of community structure

Heuristics are needed

- ▶ Fewer than expected edges between the groups
- ▶ Equivalently, more than expected edges inside the groups
- ▶ Assortativity mixing and modularity
- ▶ Look for divisions with high modularity

Quantification of community structure

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Quantification of community structure

- ▶ Fewer than expected edges between the groups
- ▶ Equivalently, more than expected edges inside the groups
- ▶ Assortativity mixing and modularity
- ▶ Look for divisions with high modularity
- ▶ Modularity maximization is hard

- ▶ Fewer than expected edges between the groups
- ▶ Equivalently, more than expected edges inside the groups
- ▶ Assortativity mixing and modularity
- ▶ Look for divisions with high modularity
- ▶ Modularity maximization is hard

Newman-Girvan algorithm

2017-12-30

Large-scale structure of complex networks (Part 2)

└ Newman-Girvan algorithm

Let's have a look at the edge betweenness


- ▶ Look for edges between the communities
- ▶ Edge betweenness

Newman-Girvan algorithm

- Look for edges between the communities
- Edge betweenness

Edge betweenness

- ▶ Path between two nodes
- ▶ Shortest path between two nodes
- ▶ Number of shortest paths that go through a given edge



2017-12-30

Large-scale structure of complex networks (Part 2)

└ Edge betweenness

Edge betweenness

- ▶ Path between two nodes
- ▶ Shortest path between two nodes
- ▶ Number of shortest paths that go through a given edge



└ The algorithm

- ▶ Calculate betweenness for all edges
- ▶ Remove the edge with the highest betweenness
- ▶ Recalculate betweenness for all edges
- ▶ Repeat

- ▶ Calculate betweenness for all edges
- ▶ Remove the edge with the highest betweenness
- ▶ Recalculate betweenness for all edges
- ▶ Repeat