1.Write a PL/SQL block that declares two variables: one for a user's name (VARCHAR2) and one for their age (NUMBER). Assign values and print both using DBMS_OUTPUT.PUT_LINE.

```
    DECLARE
 name varchar2(100):='sneha';
 age int:=25;
BEGIN
 dbms_output.put_line(name);
  dbms_output.put_line(age);


END;
/
```

Output:

```
sneha
25
```

2. Create a PL/SQL block that uses an IF statement to check if a given order amount is above 500. If yes, print 'Eligible for free delivery', else print 'Delivery charges apply'.

```
  DECLARE
 amount float:=2200;


BEGIN
 if amount >500 then
   dbms_output.put_line('Eligible');
 else
  dbms_output.put_line(' Not Eligible');
  END if;
END;
/
```

Output:

```
Eligible
```

3. Write a PL/SQL block that uses a simple LOOP to print the numbers 1 to 5 using DBMS_OUTPUT.PUT_LINE.

Hint: Use a counter variable and EXIT WHEN condition inside the loop.

DELIMITER //

```
CREATE PROCEDURE getPnameByRow()
BEGIN
   DECLARE cpid INT;
   DECLARE cname VARCHAR(100);
   DECLARE done INT DEFAULT 0;

   DECLARE productcursor CURSOR FOR
      SELECT pid, pname FROM product;

   DECLARE CONTINUE HANDLER FOR NOT FOUND
      SET done = 1;

   OPEN productcursor;

   ploop: LOOP
      FETCH productcursor INTO cpid, cname;

      IF done = 1 THEN
         LEAVE ploop;
      END IF;

      SELECT cpid AS Product_ID, cname AS Product_Name;

   END LOOP;

   CLOSE productcursor;
END //

DELIMITER ;
```

Product_ID	Product_Name
1	tv

Product_ID	Product_Name
2	TV

Product_ID	Product_Name
3	Washing Machine

Product_ID	Product_Name
4	Refrigerator

Product_ID	Product_Name
5	Kurti

Product_ID	Product_Name
6	Jeans

Product_ID	Product_Name
7	T-Shirt

Product_ID	Product_Name
8	Sofa

Product_ID	Product_Name
9	Dining Table

Product_ID	Product_Name
10	Office Chair

Product_ID	Product_Name
11	JavaScript Book

Product_ID	Product_Name