

1. Create a SQL table called Restaurants with columns: id (INT, auto-increment), name (VARCHAR), cuisine (VARCHAR), rating (DECIMAL), and city (VARCHAR). Insert 5 sample restaurants into the table, each with a different cuisine and rating.

[CREATE TABLE](#) Restaurants (id int PRIMARY KEY AUTO_INCREMENT, name varchar(100), cuisine varchar(100), rating decimal, city varchar(50));

INSERT INTO Restaurants (name, cuisine, rating, city) VALUES ("testy", "chinese", 4.5, "Ahmedabad");

INSERT INTO Restaurants (name, cuisine, rating, city) VALUES ("kathiyawadi", "gujrati dishes", 4.0, "surat");

INSERT INTO Restaurants (name, cuisine, rating, city) VALUES ("pizza hut", "italian", 5.0, "bardoli");

INSERT INTO Restaurants (name, cuisine, rating, city) VALUES ("Spice Garden", "Indian", 4.2, "rajkot");

INSERT INTO Restaurants (name, cuisine, rating, city) VALUES ("Burger Point", "American", 3.9, "Gandhinagar");

2. Write a SQL UPDATE statement to change the rating of the restaurant named 'Spice Villa' to 4.7 in the Restaurants table.

UPDATE restaurants SET name = "spice villa", rating = 4.7 WHERE id=1;

3. Delete all restaurants from the Restaurants table where the rating is less than 3.5 using a SQL DELETE statement.

[DELETE](#) FROM restaurants WHERE rating < 3.5;

4. Use a SELECT query with WHERE and LIMIT to fetch the top 2 restaurants in the city 'Ahmedabad' with a rating above 4.0 from the Restaurants table.
Hint: Combine WHERE for city and rating, and LIMIT to restrict the number of results.

SELECT * FROM Restaurants WHERE city = 'Ahmedabad' AND rating > 4.0 LIMIT 2;