

Chapter 8 - Characters and Strings

Outline

8.1 Introduction

8.2 Fundamentals of Strings

8.3 Character Handling Library

8.4 String Functions

8.5 String Manipulation Functions of the String Handling Library

8.6 Comparison Functions of the String Handling Library

8.7 Other Functions

8.8 Exercises



8.1 Introduction

- Strings
 - A **string** in **C** is an array of **characters**.
 - The length of a **string** is determined by a terminating null **character**: `'\0'`.
 - So, a **string** with the contents, say, “hello” has six **characters**: `'h'`, `'e'`, `'l'`, `'l'`, `'o'` and the terminating null (`'\0'`) **character**.
 - The terminating null **character** has the value zero.

<code>char str[6] = "Hello";</code>						
index	0	1	2	3	4	5
value	H	e	l	l	o	\0
address	1000	1001	1002	1003	1004	1005



8.1 Introduction

- Series of characters treated as a single unit
 - Can include letters, digits and special characters (*, /, \$)
- String literal (string constant) - written in double quotes
 - "Hello"
- String a pointer to first character
- Value of string is the address of first character



8.2 Fundamentals of Strings

- String definitions
 - Define as a character array or a variable of type `char *`

```
char color[] = "blue";  
char *colorPtr = "blue";
```
 - Remember that strings represented as character arrays end with `'\0'`
 - `color` has 5 elements
- Inputting strings
 - Use `scanf`

```
scanf("%s", word);
```

 - Copies input into `word[]`
 - Do not need `&` (because a string is a pointer)
 - Remember to leave room in the array for `'\0'`



```
#include "stdafx.h"
void main()
{
    char colour[] = "blue";
    printf("colour=%s", colour);
}
```

```
#include "stdafx.h"
void main()
{
    char *colour = "blue";
    printf("colour=%s", colour);
}
```

```
#include "stdafx.h"
void main()
{
    char *colour = "blue";
    puts(colour);
}
```



```
#include "stdafx.h"
void main()
{
    char colour[] = "blue";
    int i = 0;
    while (colour[i] != '\0')
    {
        printf("%c", colour[i]);
        i++;
    }
}
```

```
#include "stdafx.h"
void main()
{
    char *color = "blue";
    while (*color != '\0')
    {
        printf("%c", *color); //or putchar(*color);
        color++;
    }
}
```



8.3 Character Handling Library

- Character handling library
 - Includes functions to perform useful tests and manipulations of character data
- The following slide contains a table of all the functions in `<ctype.h>`



8.3 Character Handling Library

Prototype	Description
<code>int isdigit(int c);</code>	Returns <code>true</code> if <code>c</code> is a digit and <code>false</code> otherwise.
<code>int isalpha(int c);</code>	Returns <code>true</code> if <code>c</code> is a letter and <code>false</code> otherwise.
<code>int isalnum(int c);</code>	Returns <code>true</code> if <code>c</code> is a digit or a letter and <code>false</code> otherwise.
<code>int isxdigit(int c);</code>	Returns <code>true</code> if <code>c</code> is a hexadecimal digit character and <code>false</code> otherwise.
<code>int islower(int c);</code>	Returns <code>true</code> if <code>c</code> is a lowercase letter and <code>false</code> otherwise.
<code>int isupper(int c);</code>	Returns <code>true</code> if <code>c</code> is an uppercase letter; <code>false</code> otherwise.
<code>int tolower(int c);</code>	If <code>c</code> is an uppercase letter, <code>tolower</code> returns <code>c</code> as a lowercase letter. Otherwise, <code>tolower</code> returns the argument unchanged.
<code>int toupper(int c);</code>	If <code>c</code> is a lowercase letter, <code>toupper</code> returns <code>c</code> as an uppercase letter. Otherwise, <code>toupper</code> returns the argument unchanged.
<code>int isspace(int c);</code>	Returns <code>true</code> if <code>c</code> is a white-space character—newline (<code>'\n'</code>), space (<code>' '</code>), form feed (<code>'\f'</code>), carriage return (<code>'\r'</code>), horizontal tab (<code>'\t'</code>), or vertical tab (<code>'\v'</code>)—and <code>false</code> otherwise.
<code>int iscntrl(int c);</code>	Returns <code>true</code> if <code>c</code> is a control character and <code>false</code> otherwise.
<code>int ispunct(int c);</code>	Returns <code>true</code> if <code>c</code> is a printing character other than a space, a digit, or a letter and <code>false</code> otherwise.
<code>int isprint(int c);</code>	Returns <code>true</code> value if <code>c</code> is a printing character including space (<code>' '</code>) and <code>false</code> otherwise.
<code>int isgraph(int c);</code>	Returns <code>true</code> if <code>c</code> is a printing character other than space (<code>' '</code>) and <code>false</code> otherwise.




```
#include "stdafx.h"
#include "ctype.h"

void main()
{
    char c;

    printf("Enter a character: ");
    scanf_s("%c", &c, 1); // or c = getchar();

    if (isdigit(c) )
        printf("%c is a digit.\n", c);
    else
        printf("%c is not a digit.\n", c);
}
```

Enter a character: 4
4 is a digit.

Having to put a 1 as the size of a single character.



Characters

- Characters are simple alphabets like a, b, c, d...., A, B, C, D,....., any single digit number like 0, 1, 2,....and special characters like \$, %, +, -.... etc., are also treated as characters and to assign them in a character type variable,
- you simply need to put them inside **single quotes**.
- For example, the following statement defines a character type variable **ch** and we assign a value 'a' to it –

char ch = 'a';



```
#include "stdafx.h"
void main()
{
    char c;
    printf("Input No.1\n");
    scanf_s("%c", &c,1);
    printf("c = %c\n", c);

    printf("Input No.2\n");
    scanf_s("%c", &c,1);
    printf("c = %c\n", c);

    printf("Input No.3\n");
    scanf_s("%c", &c,1);
    printf("c = %c\n", c);
}
```

Input No.1

s

c = s

Input No.2

c =

Input No.3

a

c = a

As you see, the input No.2 was skipped. As a result, first scanf will read the s. Second scanf will read the enter! That's why, the second printf of the value of c leaves just a newline after "c=". Then the third scanf waits for a key press. You input a and then you hit enter. a is been assigned to variable c and enter remains in the stdin buffer, ready to be read by the next scanf. If we had a fourth scanf, then it would read the enter.



So, just change `scanf_s("%c", &c,1);` to `scanf_s(" %c", &c,1);` and you will be just fine. You can see in the code below:

```
#include "stdafx.h"
void main()
{
    char c;
    printf("Input No.1\n");
    scanf_s("%c", &c,1);
    printf("c = %c\n", c);

    printf("Input No.2\n");
    scanf_s(" %c", &c,1);
    printf("c = %c\n", c);

    printf("Input No.3\n");
    scanf_s(" %c", &c,1);
    printf("c = %c\n", c);
}
```

```
Input No.1
s
c = s
Input No.2
a
c = a
Input No.3
m
c = m
```



8.4 String Functions

- Used to manipulate character and string data

Function	Function description
<code>get char</code>	Inputs the next character from the standard input and returns it as an integer.
<code>get s</code>	Inputs characters from the standard input into the array <code>s</code> until a newline or end-of-file character is encountered. A terminating null character is appended to the array.
<code>put char</code>	Prints the character stored in <code>c</code> .
<code>put s</code>	Prints the string <code>s</code> followed by a newline character.
<code>spri nt f _s</code>	Equivalent to <code>pr i nt f</code> , except the output is stored in the array <code>s</code> instead of printing it on the screen.
<code>sscanf _s</code>	Equivalent to <code>scanf</code> , except the input is read from the array <code>s</code> instead of reading it from the keyboard.



```
#include "stdafx.h"
#include "string.h"
void main()
{
    char c;          /* variable to hold character input by user */
    char sentence[80]; /* create char array */
    int i = 0;

    /* prompt user to enter line of text */
    puts("Enter a line of text:");

    /* use getchar to read each character */
    while ((c = getchar()) != '\n') {
        sentence[i++] = c;
    }

    sentence[i] = '\0'; /* terminate string */

    /* use puts to display sentence */
    puts("\nThe line entered was:");
    puts(sentence);
}
```

Enter a line of text:
This is a test.

The line entered was:
This is a test.



```
#include "stdafx.h"

void main()
{
    char s[80]; /* create char array */
    int x;      /* x value to be input */
    double y;   /* y value to be input */

    printf("Enter an integer and a double:\n");
    scanf_s("%d%lf", &x, &y);

    sprintf_s(s, "integer:%6d\ndouble:%8.2f", x, y);

    printf("%s\n%s\n", "The formatted output stored in  
array s is:", s);
}
```

```
Enter an integer and a double:
298 87.375
The formatted output stored in array s is:
integer:    298
double:    87.38
```



```
#include "stdafx.h"

void main()
{
    char s[] = "31298 87.375"; /* initialize array s */
    int x;    /* x value to be input */
    double y; /* y value to be input */

    sscanf_s(s, "%d%lf", &x, &y);

    printf("%s\n%s%6d\n%s%8.3f\n", "The values stored in character  
array s are:", "integer:", x, "double:", y);
}
```

```
The values stored in character array s are:
integer: 31298
double:  87.375
```



8.5 String Manipulation Functions of the String Handling Library

- String handling library has functions to
 - Manipulate string data

Function prototype	Function description
<code>strcpy_s(s1, s2)</code>	Copies string s2 into array s1. The value of s1 is returned.
<code>strncpy_s(s1, s2, n)</code>	Copies at most n characters of string s2 into array s1. The value of s1 is returned.
<code>strcat_s(s1, s2)</code>	Appends string s2 to array s1. The first character of s2 overwrites the terminating null character of s1. The value of s1 is returned.
<code>strncat_s(s1, s2, n)</code>	Appends at most n characters of string s2 to array s1. The first character of s2 overwrites the terminating null character of s1. The value of s1 is returned.



```
#include "stdafx.h"
#include "string.h"
void main()
{
    char x[] = "Happy Birthday to You";
    char y[25];
    char z[15];

    printf("%s%s\n", "The string in array x is: ", x);
    /* copy contents of x into y */
    strcpy_s(y, x);
    printf("The string in array y is: %s\n", y);

    /* copy first 14 characters of x into z. Does not copy null
    character */
    strncpy_s(z, x, 14);

    z[14] = '\0'; /* terminate string in z */
    printf("The string in array z is: %s\n", z);
}
```

```
The string in array x is: Happy Birthday to You
The string in array y is: Happy Birthday to You
The string in array z is: Happy Birthday
```



```

#include "stdafx.h"
#include "string.h"
void main()
{
    char s1[20] = "Happy ";
    char s2[] = "New Year ";
    char s3[40] = "";          /* initialize char array s3 to empty */

    printf("s1 = %s\ns2 = %s\n", s1, s2);

    /* concatenate s2 to s1 */
    strcat_s(s1, s2);
    printf("strcat( s1, s2 ) = %s\n",s1 );

    /* concatenate first 6 characters of s1 to s3. Place '\0' after last character */
    strncat_s(s3, s1, 6);
    printf("strncat( s3, s1, 6 ) = %s\n",s3 );

    /* concatenate s1 to s3 */
    strcat_s(s3, s1);
    printf("strcat( s3, s1 ) = %s\n",s3 );
}

```

```

s1 = Happy
s2 = New Year
strcat( s1, s2 ) = Happy New Year
strncat( s3, s1, 6 ) = Happy
strcat( s3, s1 ) = Happy Happy New Year

```



8.6 Comparison Functions of the String Handling Library

- Comparing strings
 - Computer compares numeric ASCII codes of characters in string

`strcmp(s1, s2);`

- Compares string s1 to s2
- Returns a negative number if $s1 < s2$, zero if $s1 == s2$ or a positive number if $s1 > s2$

`strncmp(s1, s2, n);`

- Compares up to n characters of string s1 to s2
- Returns values as above



```

#include "stdafx.h"
#include "string.h"
void main()
{
    char s1[] = "Happy New Year";
    char s2[] = "Happy New Year";
    char s3[] = "Happy Holidays";

    printf("%s%s\n%s%s\n%s%s\n\n%s%2d\n%s%2d\n%s%2d\n\n",
        "s1 = ", s1, "s2 = ", s2, "s3 = ", s3,
        "strcmp(s1, s2) = ", strcmp(s1, s2),
        "strcmp(s1, s3) = ", strcmp(s1, s3),
        "strcmp(s3, s1) = ", strcmp(s3, s1));

    printf("%s%2d\n%s%2d\n%s%2d\n",
        "strncmp(s1, s3, 6) = ", strncmp(s1, s3, 6),
        "strncmp(s1, s3, 7) = ", strncmp(s1, s3, 7),
        "strncmp(s3, s1, 7) = ", strncmp(s3, s1, 7));
}

```

```

s1 = Happy New Year
s2 = Happy New Year
s3 = Happy Holidays

```

```

strcmp(s1, s2) = 0
strcmp(s1, s3) = 1
strcmp(s3, s1) = -1

```

```

strncmp(s1, s3, 6) = 0
strncmp(s1, s3, 7) = 1
strncmp(s3, s1, 7) = -1

```



8.7 Other Functions

- `strlen(s)`;
 - Returns the number of characters (before NULL) in string `s`
- `_strrev(s)` function
 - `strrev()` function reverses a given string `s`.



```
#include "stdafx.h"
#include "string.h"
void main()
{
    char s[30] = "Hello";

    printf("String before reverse : %s\n", s);

    printf("String after reverse  : %s\n", _strrev(s));
}
```

```
String before reverse : Hello
String after reverse  : olleH
```



```
#include "stdafx.h"
void main()
{
    char input[64];
    int size, c;

    printf("enter a common earth phrase:");
    gets(input);

    puts("\nHere is how we say that on backward
planet:");
    size = strlen(input);
    for (c = size - 1; c >= 0; c--)
        putchar(input[c]);
    printf("\n");
}
```

enter a common earth phrase:Just Do It

Here is how we say that on backward planet:
tI oD tsuJ



8.8 Exercises

This program reads the word character by character and then prints out the string

```
#include "stdafx.h"
void main()
{
    char str[20] = "hello";
    int i = 0;
    while (str[i] != '\0')
    {
        putchar(str[i]);
        i++;
    }
    printf("\n");
}
```



This program reads characters until a newline, stores them in an array and terminates the string with a NULL character. It then prints out the string.

```
#include "stdafx.h"
void main()
{
    char str[20], ch;
    int i = 0;
    printf("enter some characters:\n");
    ch = getchar();
    while (ch != '\n')
    {
        str[i] = ch;    /*(str+i)=ch;
        i++;
        ch = getchar();
    }
    str[i] = '\0'; // *(str+i)=NULL; or *(str+i)=0;

    printf("\nthe string is:\n");
    i = 0;
    while (str[i] != '\0')
    {
        putchar(str[i]); // putchar(*(str+i));
        i++;
    }
    printf("\n");
}
```



Passing array to a function

```
#include "stdafx.h"
void func(char *p)
{
    int i = 0;
    while (*(p + i) != '\0')
    {
        putchar(*(p + i));
        i++;
    }
    printf("\n");
}
void main()
{
    char str[25];
    printf("enter a message:\n");
    gets(str);
    func(str);
}
```



```
#include "stdafx.h"
void main()
{
    char *article[] = { "the", "a", "one", "some", "any" };
    for (int i = 0; i<5; i++)

        printf("%s\n", *(article + i));
}
```

the
a
one
some
any



```
#include "stdafx.h"
void main()
{
    char *name[] = { "usman", "reza", "metin" };
    char *task[] = { "task1", "task2", "task3" };
    char sentence[50] = "";
    srand(time(NULL));
    for (int i = 0; i <= 2; i++)
    {
        strcat(sentence, name[i]);
        strcat(sentence, "==>");
        strcat(sentence, task[rand() % 3]);
        printf("%s\n\n", sentence);
        sentence[0] = NULL;
    }
}
```

usman==>task2

reza==>task1

metin==>task3

