FastSpeech 2 for English and Telugu: Technical Report

Snehitha Andapally · Research Assistant assignment, Speech Processing Lab, LTRC, IIIT Hyderabad · November 2026

Code: https://github.com/snehithareddy28/fastspeech2-assignment. Every number in this report is read from the files in `Results/` produced by the training and inference runs; none is estimated. Listening observations are the author's (a native Telugu speaker).

1. Summary

Two FastSpeech 2 models were trained from scratch, one on ~5 h of Indian-accented English (Svarah) and one on ~5 h of single-speaker Telugu (IndicTTS Telugu), starting from the ming024 PyTorch implementation. The architecture is unchanged. The work is in the data pipeline (selection, alignment, Telugu G2P, normalisation), compatibility fixes, and training/inference tooling. Both models produce intelligible speech for all ten test sentences. Telugu sounds clean and natural, including numbers and phrase-final lengthening; English is intelligible but audibly noisy. The most notable failures come from text processing, not from the acoustic model: without a fix "rhyth m" is read as "rye-th em" (a join rule in the frontend now gives "rhythm"), "andaroo" gets English timing, and the Telugu loanword in T1 keeps the long vowels of its spelling. The English model also does not realise the lexical stress contrast in E2a/E2b, although the frontend supplies it. Validation loss stops improving after about 10k steps in both languages while training loss keeps falling, which shows overfitting to ~5 h of data.

2. Implementation

2.1 Components used from ming024

Unchanged: Transformer encoder (4 FFT blocks) and decoder (6 FFT blocks), hidden size 256, 2 heads, conv1d FFN (kernel 9, filter 1024); variance adaptor with duration, pitch and energy predictors (2 conv layers, kernel 3, dropout 0.5); phoneme-level pitch and energy, quantised into 256 linear bins with learned embeddings; length regulator; PostNet; losses (L1 on mel before and after PostNet, MSE on log-duration, pitch, energy); Noam warm-up LR schedule with step annealing; pretrained HiFi-GAN "universal" vocoder. About 35 M parameters (35,081,025 for Telugu and 35,118,401 for English, which has the larger symbol table and a speaker embedding table; counted by the training script).

2.2 Changes common to both languages

Full list with reasons: `docs/CHANGES.md`; the first commit is the pristine upstream code, so every change is a reviewable diff.

- **Compatibility.** librosa >= 0.10 keyword-only APIs; a hard-coded `.cuda()` in the STFT removed (preprocessing needed a GPU); `torch.load(weights_only=False)` for torch >= 2.6.
- **Bug fixes.** The energy predictor received `p_control` instead of `e_control`. MFA >= 2 writes silences as empty intervals; upstream read TextGrids without them, which loses silence frames from the duration sum. Unknown phones were silently dropped, which would desynchronise phones and durations; they now raise.
- **Per-language symbol tables.** Upstream used one table (ARPAbet + pinyin) for all data. Each model now has its own table and embedding size.

- **Fixed, documented split.** The split is decided at data-selection time and grouped by transcript, so the same sentence never appears in both train and validation (upstream took a random `val_size` cut). Pitch/energy normalisation statistics come from the training split only.
- **Training infrastructure.** Resumable checkpoints (model, optimizer, step, RNG) every 1000 steps, best-by-validation checkpoint, CSV loss logs, wall-clock budget, single-GPU device selection.
- **Inference.** A sentence file is read verbatim; the frontend normalises and converts to phones; the script saves audio, duration/pitch/energy plots and a JSON of every predicted value with the G2P source of each word.

2.3 English-specific

- **G2P.** Upstream looked each word up in a lexicon and took the first pronunciation, so heteronyms could never be distinguished. Here g2p_en runs on the whole normalised sentence: its POS tagger selects between homograph pronunciations, CMUdict covers known words, and its neural model handles out-of-vocabulary words.
- **Alignment lexicon.** All LibriSpeech/CMU variants for in-vocabulary words plus g2p_en pronunciations for OOV words, so MFA chooses the variant that matches the audio and no training word is unknown.
- **Normalisation** (`fastspeech2/text/english.py`): `H:MM` -> hour + minutes (":00" -> "o'clock", "05" -> "oh five"); AM/PM -> letter names; `<day> <Month> <year>` -> ordinal day, month, year read in pairs ("12 November 2026" -> "twelfth November twenty twenty six"); other 4-digit numbers 1000 to 2099 as years; remaining digits as cardinals.
- **Split words** (inference only): two adjacent alphabetic tokens are joined when the join is a CMUdict word and at least one part is not a word by itself (not in CMUdict, or a single letter other than "a"/"i"). "rhyth m" -> "rhythm"; "in to" and "a way" stay split. Known false positive: "a m an" -> "am an". `--no_join` disables it. Training and alignment are unaffected.
- **Added after training** (inference frontend only; the trained models are unchanged): clitics split off by NLTK's tokenizer are re-attached ("orchestra" + "'s" -> "orchestra's", read with /z/; before, "'s" was read as the letter `S`), with an `S`, `Z` or `IH0 Z` rule for possessives not in CMUdict; `$` and `Rs` amounts; "1,000" as a cardinal (it was read as the year "ten hundred"); digit strings of 7 or more digits read digit by digit; hyphenated words not in CMUdict read part by part; a pause at an ellipsis. Telugu: "%" -> శాతం, and a warning when non-Telugu text (e.g. a Latin-script word) is dropped. These came from probing the frontends with general edge cases; among the test sentences only E2a changes.
- **Multi-speaker.** Svarah has many speakers with a few minutes each, so a speaker embedding table is used (upstream `multi_speaker: True`). Test sentences use the speaker with the most training data.

2.4 Telugu-specific

- **Phone set.** 50 ASCII phones (vowels with length, aspirated and retroflex consonants, homorganic nasals) plus `sp`/`spn`/`sil`. Retroflexes carry an `x` suffix (`tx`, `dx`, `nx`, `lx`, `sx`).
- **Rule-based G2P** (`fastspeech2/text/telugu.py`). Telugu script is close to phonemic, so rules suffice: every consonant carries the inherent /a/ unless followed by a vowel sign or virama; conjuncts follow from the virama rule (పట్టు -> `p a tx tx u`); anusvara becomes the nasal homorganic with the next consonant (బలంగా -> `b a l a ng g aa`, ఉంది -> `u n d i`) and /m/ word-finally (సమావేశం -> `... sh a m`); visarga -> /h/. Not modelled: word-initial e -> ye glide, sandhi across words, loanword pronunciation. The normaliser output and the phone strings for all Telugu test sentences were checked by a native Telugu speaker (the author) and judged correct.
- **Number normalisation.** Telugu digits are mapped to ASCII; cardinals use Indian grouping with combining forms (2026 -> రెండు వేల ఇరవై ఆరు); `<n>వ` becomes an ordinal (12వ -> పన్నెండవ); `HH:MM` is read as two cardinals (10:45 -> పది నలభై ఐదు).

- **Alignment.** No pretrained Telugu MFA model exists. Two options were considered: (a) train an MFA (GMM-HMM, speaker-adapted) acoustic model on the selected subset with the rule-based lexicon, or (b) character input with a learned/CTC aligner. (a) was chosen: it keeps the upstream duration pipeline unchanged, and a phonemic script with one speaker and ~6 h is enough for a GMM-HMM to align well. (b) would need architectural changes (an alignment module and its loss) with no time to tune them. Fallback if MFA training failed: CTC forced alignment with a multilingual wav2vec2 model (torchaudio MMS) over romanised characters, implemented in `scripts/ctc_align.py` (MMS-300m forced-alignment model, own Viterbi pass, same TextGrid output). On 4 real IndicTTS utterances it aligned 4/4, with intervals it labelled as silence averaging -42 dB relative to peak versus -13 dB for phone intervals. It was not needed: the final Telugu alignments come from the trained MFA model (MFA 3.4.3), which aligned 1501 of 1528 selected utterances; the 27 failures were dropped. MFA splits work by speaker, so a single-speaker corpus silently ran on one CPU core (about 3.5 h for acoustic model training) until `--single_speaker` was passed.
- **Chunking long utterances.** IndicTTS Telugu utterances are long (in a 500-utterance sample: median 18.9 s, 95th percentile 46.4 s; only 7 % of audio is in utterances of 11 s or less). Utterances up to 30 s are selected and aligned whole, then split at MFA pauses of at least 0.15 s into training items of at most 10 s (the decoder's positional table covers 1000 frames = 11.6 s). Chunks inherit their source utterance's split.

3. Data

	English (Svarah)	Telugu (IndicTTS Telugu)
Source	`ai4bharat/Svarah`, split `test` (the only split; 6656 utterances, 9.61 h)	`SPRINGLab/IndicTTS_Telugu`, split `train` (8576 utterances, 36.71 h)
Native sample rate	16 kHz (all selected files)	16 kHz (all selected files)
Speakers used	49 of 115 recovered (67 had >= 3 min)	1 (female; 13.3 h usable vs 11.4 h male)
Speaker identity	metadata tuple (no speaker-id column; file names carry no ID)	`gender` label (two speakers)
Duration filter	1 to 30 s, then chunked to <= 10 s	1 to 30 s, then chunked to <= 10 s
Text filter	plain English characters, >= 2 words	pure Telugu script after normalisation, G2P covers every character, >= 2 words
Selected (before trimming)	train 5.47 h (3087 utts) / val 1.17 h (637 utts)	train 5.50 h (1273 utts) / val 1.10 h (255 utts)
After alignment + trimming	train 5.01 h (3510 items) / val 1.07 h (729 items)	train 4.81 h (2408 items) / val 0.96 h (475 items)
Alignment coverage	3724 / 3724 (pretrained `english_us_arpa`)	1501 / 1528 (MFA trained on the subset)
Lexicon	6521 words, 1118 OOV via g2p_en (many are Indian names, places and words)	13011 words, all by rule

Selection strategy. English: Svarah has no speaker-id column and its file names carry no speaker ID, so speakers are recovered from the tuple of speaker metadata columns (gender, age group, first language, state, district, qualification, job, occupation). The recovered identity is an approximation and is recorded in the summary. Speakers with at least 3 minutes of usable audio are ranked by amount of audio and taken in order until ~6.6 h is reached; fewer speakers with more audio each give better-trained speaker embeddings than many speakers with a minute each. Telugu: a single speaker for stability (`speaker: auto`

picks the one with more usable audio), random sampling with a fixed seed. In both cases the validation share (1/6) is taken within each speaker and grouped by normalised transcript; the script asserts that no transcript appears in both splits. The selection target is 10 % above 5 h + 1 h because leading/trailing silence trimming and chunking remove audio; the final hours are in the table. Lists of selected utterances: `Results/<Lang>/data_selection.tsv`.

Preprocessing. Mono, resampled to 22.05 kHz (both sources are upsampled, so the mel bands above 8 kHz are empty; the HiFi-GAN mel range is 0 to 8 kHz anyway), peak-normalised. 80-band log-mel, 1024-point FFT, hop 256. F0 with WORLD DIO + StoneMask (65 to 500 Hz), unvoiced frames linearly interpolated, averaged per phone. Energy = L2 norm of the STFT magnitude frame, averaged per phone. Both z-normalised with training-set statistics.


4. Training configuration

	English	Telugu
Steps	65,000 (planned total reached)	62,211 of 65,000 (stopped by the 5.1 h budget)
Batch size	16	16
Optimiser	Adam (0.9, 0.98), eps 1e-9, Noam warm-up 4000, x0.3 at 60/80/90 % of steps	same
Gradient clip	1.0	1.0
Precision	fp16 mixed precision (AMP)	same
GPU, wall-clock	1 x Tesla T4 (Kaggle), 4.72 h	1 x Tesla T4 (Kaggle), 5.10 h
Throughput	4.06 it/s (median)	3.52 it/s (median)
Checkpoint used for results	best validation total loss, step 10,000	best validation total loss, step 14,000


The two languages were trained one after the other in one 10.5 h Kaggle session. Running them in parallel on the two T4s was tried first and was CPU-bound on the 4-core machine (about 1.1 it/s each, against about 3.8 it/s for one run alone), so sequential training gave more steps per language. fp16 AMP was measured at 3.8 it/s against 1.7 it/s in fp32 on the same GPU, with matching validation loss in a short smoke test. Two bugs only appeared on GPU and were fixed: energy targets reached the loss as float64 (the CUDA backward pass rejects mixed dtypes), and torch 2.11 rejects `set_device("cuda")` without an index. The final-step checkpoints were also synthesised; they sounded the same as the best ones.


5. Loss curves


English: training losses (logged every 100 steps)





English: validation losses (full validation set)




Telugu: training losses (logged every 100 steps)
train total loss
raw
EMA 0.9
train mel loss
train mel_postnet loss
train pitch loss
train energy loss
train duration loss
step


Telugu: validation losses (full validation set)
val total loss
val mel loss
val mel_postnet loss
val pitch loss
val energy loss
val duration loss
step





Loss	EN train (last 1k steps)	EN val best (step)	EN val final	TE train (last 1k steps)	TE val best (step)	TE val final
total	0.798	2.494 (10k)	2.521	0.622	1.810 (14k)	1.832
mel	0.382	0.725 (12k)	0.741	0.299	0.559 (14k)	0.567
pitch	0.013	0.393 (1k)	0.403	0.011	0.495 (14k)	0.504
energy	0.015	0.374 (28k)	0.380	0.009	0.153 (22k)	0.155
duration	0.008	0.247 (5k)	0.254	0.004	0.039 (7k)	0.041

- **Convergence.** Validation mel loss flattens by about 8k to 10k steps in both languages and changes by less than 3 % afterwards. Training loss keeps falling until the end.
- **Overfitting.** Clear in the variance predictors: training pitch, energy and duration losses fall to about 0.01, while validation stays at 0.04 to 0.50, roughly 10 to 45 times higher, and is flat or slightly rising after its minimum. Validation mel loss rises slowly (English 0.725 at 12k to 0.741 at 65k; Telugu 0.559

to 0.567). The best checkpoints are therefore early ones; with ~5 h of data, more steps do not help generalisation.
- **Stability.** No spikes in training loss and no non-finite-loss skips in either run (`train_stdout.log`). The Telugu validation pitch loss has one spike at 4k (0.62) during warm-up. The first LR anneal at 39k gives a small step down in training loss (English 0.899 to 0.852, Telugu 0.673 to 0.647, mean over the 2k steps before and after) and no change in validation loss.
- **English vs Telugu.** English validation losses are higher for mel (0.73 vs 0.56), energy (0.37 vs 0.15) and especially duration (0.25 vs 0.04). This fits 49 speakers with varied recording conditions and speaking styles, where duration and energy are much less predictable from phones alone, against one studio speaker reading in a consistent style. Telugu pitch loss is higher (0.50 vs 0.39), plausibly because the female voice has a wider F0 range in absolute terms (the test outputs span 147 to 332 Hz vs 109 to 182 Hz).

6. Test sentences: generated speech

Audio: `Results/<Lang>/test_generated_audios/<ID>.wav`. The normalised text and phone sequence below are produced by the frontend (copied from the per-utterance JSON). Listening observations are the author's, made on the generated files.

English

ID	Frontend output (deterministic, verified)	Listening observations
E1	"antidisestablishmentarianism" is in CMUdict: `AE2 N T AY0 D IH0 S AH0 S T AE2 B L IH0 SH M AH0 N T EH1 R IY0 AH0 N IH0 Z AH0 M` (28 phones)	The long word is clear and intact. As in all English outputs, the audio has audible background noise (see Section 8).
E2a	"conduct" tagged NN -> `K AA1 N D AH0 K T` (noun stress). "orchestra's" -> CMUdict `... AH0 Z`	Sounds natural, but no stress is audible on either syllable (see E2b). Predicted: AA1 46 ms / 137 Hz, AH0 104 ms / 130 Hz; the stressed vowel is shorter than the unstressed one and the pitch step is only 7 Hz. The first run split off "'s" and read it as the letter name `EH1 S`, because NLTK's word_tokenize separates clitics; the frontend now re-attaches them (Section 2.3). The corrected version was judged right by listening; the earlier output is kept in `Results/English/e2a_before_clitic_fix/` (there the AA1/AH0 values were 58 ms / 140 Hz and 104 ms / 130 Hz, same conclusion).
E2b	"conduct" tagged VB -> `K AA0 N D AH1 K T` (verb stress)	Sounds natural, but no stress contrast with E2a is audible. Predicted: AA0 58 ms / 130 Hz, AH1 35 ms / 133 Hz, i.e. the stressed vowel is again the shorter one and pitch is flat. The frontend does choose the correct stress (the phone symbols differ: AA1/AH0 vs AA0/AH1), but the model has not learned to realise lexical stress as duration or pitch. Plausible reasons: Indian English, the variety in Svarah, marks lexical stress weakly and less consistently than US English, the CMUdict stress labels are US English, and 5 h of data gives few contrasting examples.
E3	With the split-word rule: "rhyth m" -> "rhythm" -> CMUdict `R IH1 DH AH0 M`. Without it (`--no_join`, kept in `Results/English/e3_without_join/`): "rhyth" is OOV -> neural G2P `R AY1 DH`, "m" -> letter name `EH1 M`	With the rule it sounds like "rhythm". Without it, heard as "rye-th em", as predicted by the phones: the model speaks what the frontend gives it, so the error was entirely in text processing, not in the acoustic model. In the fixed version the F0 peak falls on the unstressed AH0 (158 Hz, 58 ms) rather than IH1 (135 Hz, 46 ms), the same missing-stress pattern as E2a/E2b.
E4	normalised to "ten forty five {A M} on twelfth November twenty twenty six, so andaroo ..."; AM as letter names `EY1 EH1 M`; "andaroo" OOV -> `AE0 N D AA1 R OW0`	Time and date sound perfect. "andaroo" sounds rushed: its predicted vowels (AE0 70, AA1 58, OW0 70 ms) are no longer than the sentence's average vowel (63 ms), whereas Telugu అందరూ ends in a long /uu/ (the Telugu model predicts about 100 to 120 ms for long vowels). The English G2P reads it with English vowels (AE, OW) and English stress, so a Telugu word in an English sentence gets English timing.

Telugu

ID	Frontend output (deterministic, verified)	Listening observations
T1	న్యూరోఫార్మకోలాజికల్ -> `n y uu r oo ph aa r m a k oo l aa j i k a l` (19 phones, a loanword; ఫ is read as aspirated /ph/, while Telugu speakers often say /f/)	The "-colo-" part is heard as "koolaa". Predicted durations confirm both vowels are long (oo 116 ms, aa 104 ms), as written in కోలా: the English reduced/short vowels (/kəˈlɒ/) are lost because the rule-based G2P reads the script literally and has no loanword handling. ఫ is realised as /ph/, not /f/.
T2a	పట్టు -> `p a tx tx u` (grip)	See T2b.
T2b	పట్టు -> `p a tx tx u` (silk): identical phones to T2a, so any difference can only come from context through the encoder	T2a and T2b sound the same. Predictions for పట్టు differ only slightly (total 325 vs 313 ms; mean F0 206 vs 212 Hz), consistent with its different position in the sentence (phone 11 of 31 vs 3 of 37) rather than with meaning. The encoder does see the neighbouring phones (e.g. `c ii r a` of చీరను in T2b), but word boundaries are dropped before the model and nothing in training links a sense to a pronunciation. Here that is the correct behaviour: a native speaker confirms the two senses of పట్టు are pronounced the same, so this homograph needs no disambiguation (unlike English E2a/E2b).
T3	"అడ విలో" -> `a dx a + v i l oo`: exactly the phones of అడవిలో, because the model has no word-boundary symbol	No break is audible: it sounds like అడవిలో. Predicted durations across the split are ordinary (a 46 ms, v 58 ms) with no pause, because the space never reaches the model.
T4	2026 -> రెండు వేల ఇరవై ఆరు; 12వ -> పన్నెండవ; 10:45 -> పది నలభై ఐదు; comma -> pause	Sounds natural. The comma gives a 650 ms pause, preceded by a lengthened vowel (i 139 ms) and the sentence ends with a lengthened final vowel (i 174 ms): phrase-final lengthening learned from the data. Total 9.27 s.

7. Variance adaptor analysis

Plots: `Results/<Lang>/variance_adaptor_plots/{duration,pitch,energy}/<ID>.png` (per-phone predictions; word boundaries dashed; Telugu words labelled by their phones because matplotlib cannot shape Telugu script), plus `overview/<ID>.png` (mel with F0 and energy). The exact values are in `<ID>.json`.

Summary per sentence (speech phones only; F0 is the predicted per-phone value):

ID	Length	Phones/s	Mean F0, first third -> last third	F0 on final vowel	Mean vowel / final vowel	Energy, vowels vs consonants
E1	5.47 s	15.9	145 -> 127 Hz	123 Hz	53 / 46 ms	98 vs 64
E2a	3.44 s	14.8	137 -> 121 Hz	118 Hz	64 / 70 ms	103 vs 58
E2b	3.77 s	14.8	133 -> 126 Hz	117 Hz	61 / 58 ms	102 vs 52
E3	2.40 s	15.4	138 -> 129 Hz	118 Hz	62 / 116 ms	105 vs 48
E3, no join	2.63 s	14.0	152 -> 135 Hz	119 Hz	75 / 116 ms	103 vs 50
E4	6.71 s	12.1	153 -> 130 Hz	114 Hz	63 / 93 ms	93 vs 53
T1	5.18 s	12.7	223 -> 194 Hz	166 Hz	77 / 116 ms	68 vs 45
T2a	2.45 s	12.7	229 -> 188 Hz	157 Hz	81 / 151 ms	66 vs 35
T2b	2.63 s	14.0	210 -> 188 Hz	149 Hz	66 / 151 ms	69 vs 36
T3	2.16 s	14.4	256 -> 178 Hz	156 Hz	67 / 162 ms	71 vs 40
T4	9.27 s	12.8	224 -> 197 Hz	185 Hz	73 / 174 ms	72 vs 47

- **Duration.** No phone was predicted zero frames in any sentence. Telugu shows strong phrase-final lengthening: the final vowel is 116 to 174 ms, about twice the mean vowel. English final vowels in E1, E2a and E2b are not lengthened (46 to 70 ms, close to each sentence's mean vowel); E3 and E4 do lengthen. The T4 comma gives a 650 ms pause with a lengthened vowel before it (139 ms). The geminate in పట్టు is realised as two `tx` intervals totalling 116 to 128 ms (closure plus release) against 35 to 46 ms for its single /a/ and /u/. E1 is not compressed: the long word keeps ordinary phone durations and the sentence rate (15.9 phones/s) is close to E2a/E2b.
- **Pitch.** Every sentence shows declination (F0 falls from the first to the last third by 7 to 78 Hz) and ends low, as expected for declaratives. "conduct" shows no stress-related peak in either E2a or E2b (Section 6). In E3 without the join rule the isolated letter "m" (`EH1 M`) gets the sentence's F0 maximum (182 Hz) and highest energy, so the stray letter is emphasised rather than absorbed. With the rule, the maximum (158 Hz) is on the unstressed AH0 of "rhythm".
- **Energy.** Vowels carry clearly more energy than consonants in every sentence (ratio about 1.5 to 2.2). English values are higher than Telugu because each model is normalised with its own data statistics. "andaroo" shows ordinary energy (80 to 88 on its vowels), so its problem is timing, not loudness.

8. English vs Telugu

Listening. All English outputs sound somewhat noisy, while words remain clear. The Telugu outputs do not have this problem. This agrees with the validation mel loss, which is clearly higher for English (best 0.727 vs 0.559 for Telugu). Likely causes, not separately tested: Svarah is not studio TTS data (varied microphones and rooms, background noise that the model learns to reproduce), 49 speakers with only 4 to 25 minutes each, so the decoder averages across voices and channels, and the universal HiFi-GAN vocoder was not fine-tuned on these speakers or on upsampled 16 kHz audio.

- **Data.** One studio speaker reading long sentences (Telugu) against 49 speakers with 4 to 25 minutes each in varied conditions (English). As expected, Telugu is cleaner and more consistent: lower validation loss on every term except pitch, much lower duration loss, clear phrase-final lengthening.
- **Frontend.** Telugu G2P is near-deterministic from the script. English depends on CMUdict, a POS tagger and a neural G2P for unseen words; the English failures (E3 before the join rule, E4) are in words the neural G2P had to guess, and the first E2a run had a tokenisation bug (the possessive "'s"

read as a letter). The one Telugu failure (T1) is a loanword whose spelling does not match its usual pronunciation.
- **Heteronyms.** English: the frontend picks the right stress for "conduct", but the model does not realise it. Telugu: పట్టు has the same phones and, as confirmed by a native speaker, the same pronunciation in both senses, so identical output is correct.
- **Broken tokens.** In English the space in "rhyth m" changes the pronunciation completely unless the frontend re-joins it (now done by the split-word rule). In Telugu the space in "అడ విలో" changes nothing, because the phones are the same and no word-boundary symbol reaches the model.
- **Numbers.** Both normalisers handle the test patterns and both sound right. The reading conventions (ordinal day in English, two cardinals for the time in Telugu) are rules, not learned.
- **Code-mixing.** "andaroo" goes through an English G2P trained on English spelling and gets English vowels and timing.

Limitations. ~5 h per language and a few hours of GPU training; vocoder not fine-tuned on these speakers (upsampled 16 kHz sources, Indian speakers unseen by the universal HiFi-GAN); English speaker identities approximated; Telugu G2P ignores loanword phonology; no word-boundary or punctuation symbols beyond pauses.

Improvements tied to the test sentences. E3: the "join if the join is in the lexicon" rule is implemented (Section 2.3); it can still join real words ("a m an" -> "am an"), so a language-model or spelling-correction check would make it safer. E4: a code-mixed G2P that detects Indic words in Latin script and transliterates them (andaroo -> అందరూ -> Telugu phones with Telugu durations). T1: a loanword lexicon or rules for English-origin Telugu words (/f/ for ఫ, reduced or short vowels). E2a/E2b: explicit stress features or more data with contrasting stress; the stress labels are already correct in the input. General: fine-tune HiFi-GAN on ground-truth-aligned mels (expected to help the English noise most), cleaner or speaker-balanced English data, and early stopping or stronger regularisation of the variance predictors given the overfitting in Section 5.

9. Reproducibility

- Software (training): Python 3.13.16, PyTorch 2.11.0+cu130, librosa 0.11.0, numpy 2.1.3, MFA 3.4.3. `requirements.txt` gives lower bounds; the exact environment of each stage is in `Results/environment_*.txt` (`pip freeze`).
- Configs: `English/config.yaml`, `Telugu/config.yaml` (copied into `Results/<Lang>/logs/config_used.yaml` at training time).
- Commands (from the repository root):

```
pip install -r requirements.txt && bash scripts/setup_mfa.sh && export HF_TOKEN=...
bash scripts/run_pipeline.sh data english   && bash scripts/run_pipeline.sh data telugu
bash scripts/run_pipeline.sh train-seq 5.1   # English then Telugu, 5.1 h each
bash scripts/run_pipeline.sh results english && bash scripts/run_pipeline.sh results telugu
python scripts/build_report.py
```

- Seeds: data selection and training use seed 1234; DataLoader shuffling and cuDNN are not fully deterministic, so loss values can differ slightly between runs.