

CS 453/698: Software and Systems Security

Module: Bug Finding Tools and Practices

Lecture: Fuzz testing (a.k.a., fuzzing)

Meng Xu (*University of Waterloo*)

Winter 2025

Outline

- 1 Introduction
- 2 Testing with concrete inputs
- 3 Fuzzing overview
- 4 Program state coverage: “natural selection” in the fuzzing world
- 5 Conclusion

Program assurance

An eternal question behind all software developers' mind:
how do I know that my code is correct and secure?

Program assurance

An eternal question behind all software developers' mind:
how do I know that my code is correct and secure?

- Existing practice: testing with manual effort
 - a.k.a., unit tests, E2E tests, quality assurance, etc.

Program assurance

An eternal question behind all software developers' mind:
how do I know that my code is correct and secure?

- Existing practice: testing with manual effort
 - a.k.a., unit tests, E2E tests, quality assurance, etc.
- Emerging trend in practice: coverage-guided fuzzing
 - i.e., **automated**, **evolutionary**, and **random** generation of test cases

Program assurance

An eternal question behind all software developers' mind:
how do I know that my code is correct and secure?

- Existing practice: testing with manual effort
 - a.k.a., unit tests, E2E tests, quality assurance, etc.
- Emerging trend in practice: coverage-guided fuzzing
 - i.e., **automated**, **evolutionary**, and **random** generation of test cases
- In research pipeline: symbolic execution
 - i.e., **automated**, **systematic**, and **deterministic** exploration of search space

Program assurance

An eternal question behind all software developers' mind:
how do I know that my code is correct and secure?

- Existing practice: testing with manual effort
 - a.k.a., unit tests, E2E tests, quality assurance, etc.
- Emerging trend in practice: coverage-guided fuzzing
 - i.e., **automated**, **evolutionary**, and **random** generation of test cases
- In research pipeline: symbolic execution
 - i.e., **automated**, **systematic**, and **deterministic** exploration of search space
- Latest development: **concolic execution**
 - i.e., **automated**, **efficient**, and **practical** exploration of search space

Running example

Running example

```
1 // implementation of `calc`  
2 fn calc(  
3   x: u64, y: u64, n: u64  
4 ) -> (u64, u64, u64) {  
5   /*  
6    *  
7    * code omitted for now  
8    *  
9    */  
10 }
```

calc is the function we want to check for vulnerabilities.

Running example

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   /*
6    *
7    * code omitted for now
8    *
9    */
10 }
```


calc is the function we want to check for vulnerabilities.

We know how to use calc (as shown in the main function).

```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   // use the results
6   // .....
7 }
```

Running example

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   /*
6    *
7    * code omitted for now
8    *
9    */
10 }
```

```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```


calc is the function we want to check for vulnerabilities.

We know how to use calc (as shown in the main function).

More importantly, we know when calc is **wrong** (by the **assertion** the main function).

Running example

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   /*
6    *
7    * code omitted for now
8    *
9    */
10 }
```

```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```

calc is the function we want to check for vulnerabilities.

We know how to use calc (as shown in the main function).

More importantly, we know when calc is **wrong** (by the **assertion** the main function).


Real-world software is of course more complicated than this simple example.

Running example: open-box analysis

Running example: open-box analysis

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   let a = x, b = y, i = 0;
6   while (a < n) {
7     if (b > a) {
8       a++;
9     } else {
10      b++;
11    }
12    i++;
13  }
14  return (a, b, i);
15 }
```

Q: Now we have the source code of the calc function, how do we know it is correct?


```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```

Running example: open-box analysis

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   let a = x, b = y, i = 0;
6   while (a < n) {
7     if (b > a) {
8       a++;
9     } else {
10      b++;
11    }
12    i++;
13  }
14  return (a, b, i);
15 }
```

Q: Now we have the source code of the `calc` function, how do we know it is correct?

A: Just try it with some concrete inputs and see if the results match with our expectations.


```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```

Outline

- 1 Introduction
- 2 Testing with concrete inputs
- 3 Fuzzing overview
- 4 Program state coverage: “natural selection” in the fuzzing world
- 5 Conclusion

Testing the running example


```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   let a = x, b = y, i = 0;
6   while (a < n) {
7     if (b > a) {
8       a++;
9     } else {
10      b++;
11    }
12    i++;
13  }
14  return (a, b, i);
15 }
```

```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```

Testing the running example

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   let a = x, b = y, i = 0;
6   while (a < n) {
7     if (b > a) {
8       a++;
9     } else {
10      b++;
11    }
12    i++;
13  }
14  return (a, b, i);
15 }
```

• $x=0, y=1, n=2 \rightarrow a=2, b=2, i=3$


```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```

Testing the running example

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   let a = x, b = y, i = 0;
6   while (a < n) {
7     if (b > a) {
8       a++;
9     } else {
10      b++;
11    }
12    i++;
13  }
14  return (a, b, i);
15 }
```

• $x=0, y=1, n=2 \rightarrow a=2, b=2, i=3$


• $x=1, y=0, n=2 \rightarrow a=2, b=2, i=3$

```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```

Testing the running example

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   let a = x, b = y, i = 0;
6   while (a < n) {
7     if (b > a) {
8       a++;
9     } else {
10      b++;
11    }
12    i++;
13  }
14  return (a, b, i);
15 }
```


- $x=0, y=1, n=2 \rightarrow a=2, b=2, i=3$
- $x=1, y=0, n=2 \rightarrow a=2, b=2, i=3$
- $x=0, y=2, n=1 \rightarrow a=1, b=2, i=1$
- $x=1, y=2, n=0 \rightarrow a=1, b=2, i=0$

```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```

Testing the running example

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   let a = x, b = y, i = 0;
6   while (a < n) {
7     if (b > a) {
8       a++;
9     } else {
10      b++;
11    }
12    i++;
13  }
14  return (a, b, i);
15 }
```


- $x=0, y=1, n=2 \rightarrow a=2, b=2, i=3$
- $x=1, y=0, n=2 \rightarrow a=2, b=2, i=3$
- $x=0, y=2, n=1 \rightarrow a=1, b=2, i=1$
- $x=1, y=2, n=0 \rightarrow a=1, b=2, i=0$
- $x=2, y=0, n=1 \rightarrow a=2, b=0, i=0$
- $x=2, y=1, n=0 \rightarrow a=2, b=1, i=0$
-

```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```

Testing the running example

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   let a = x, b = y, i = 0;
6   while (a < n) {
7     if (b > a) {
8       a++;
9     } else {
10      b++;
11    }
12    i++;
13  }
14  return (a, b, i);
15 }
```


- $x=0, y=1, n=2 \rightarrow a=2, b=2, i=3$
- $x=1, y=0, n=2 \rightarrow a=2, b=2, i=3$
- $x=0, y=2, n=1 \rightarrow a=1, b=2, i=1$
- $x=1, y=2, n=0 \rightarrow a=1, b=2, i=0$
- $x=2, y=0, n=1 \rightarrow a=2, b=0, i=0$
- $x=2, y=1, n=0 \rightarrow a=2, b=1, i=0$
-

```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```

Q: When should the testing end?

Testing the running example

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   let a = x, b = y, i = 0;
6   while (a < n) {
7     if (b > a) {
8       a++;
9     } else {
10      b++;
11    }
12    i++;
13  }
14  return (a, b, i);
15 }
```

```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```

- $x=0, y=1, n=2 \rightarrow a=2, b=2, i=3$
- $x=1, y=0, n=2 \rightarrow a=2, b=2, i=3$
- $x=0, y=2, n=1 \rightarrow a=1, b=2, i=1$
- $x=1, y=2, n=0 \rightarrow a=1, b=2, i=0$
- $x=2, y=0, n=1 \rightarrow a=2, b=0, i=0$
- $x=2, y=1, n=0 \rightarrow a=2, b=1, i=0$
-


Q: When should the testing end?

A: The *de facto* answer is: when achieved 100% code coverage.

CFG and code coverage

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   let a = x, b = y, i = 0;
6   while (a < n) {
7     if (b > a) {
8       a++;
9     } else {
10      b++;
11    }
12    i++;
13  }
14  return (a, b, i);
15 }
```

Figure: the control-flow graph (CFG) of function calc(..)



```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   XXXXXXXXXXXXXXXXXXXXXXXXXXXX
7 }
```


CFG and code coverage

```
1 // implementation of `calc`  
2 fn calc(  
3   x: u64, y: u64, n: u64  
4 ) -> (u64, u64, u64) {  
5   let a = x, b = y, i = 0;  
6   while (a < n) {  
7     if (b > a) {  
8       a++;  
9     } else {  
10      b++;  
11    }  
12    i++;  
13  }  
14  return (a, b, i);  
15 }
```



```
1 // use the `calc` function  
2 pub fn main() {  
3   let (x, y, n) = /* input */;  
4   let (a, b, i) = calc(x, y, n);  
5   assert!(n-a-b+i != 42);  
6     
7 }
```

Figure: the control-flow graph (CFG) of function calc(..)




100% code coverage usually means:

- all nodes in the CFG, or
- all edges in the CFG


100% coverage does not imply a worry-free program

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   let a = x, b = y, i = 0;
6   while (a < n) {
7     if (b > a) {
8       a++;
9     } else {
10      b++;
11    }
12    i++;
13  }
14  return (a, b, i);
15 }
```

```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```


100% coverage does not imply a worry-free program

```
1 // implementation of `calc`
2 fn calc(
3   x: u64, y: u64, n: u64
4 ) -> (u64, u64, u64) {
5   let a = x, b = y, i = 0;
6   while (a < n) {
7     if (b > a) {
8       a++;
9     } else {
10      b++;
11    }
12    i++;
13  }
14  return (a, b, i);
15 }
```


```
1 // use the `calc` function
2 pub fn main() {
3   let (x, y, n) = /* input */;
4   let (a, b, i) = calc(x, y, n);
5   assert!(n-a-b+i != 42);
6   
7 }
```

- $x=0, y=1, n=2 \rightarrow a=2, b=2, i=3$
- $x=1, y=0, n=2 \rightarrow a=2, b=2, i=3$
- $x=0, y=2, n=1 \rightarrow a=1, b=2, i=1$
- $x=1, y=2, n=0 \rightarrow a=1, b=2, i=0$
- $x=2, y=0, n=1 \rightarrow a=2, b=0, i=0$
- $x=2, y=1, n=0 \rightarrow a=2, b=1, i=0$


Reason: loop unrolling yields new components in CFG



Reason: loop unrolling yields new components in CFG



Reason: loop unrolling yields new components in CFG



Manual enumeration is impossible

In reality, it is infeasible to manually construct test cases that cover every new node / edge in the loop-unrolled CFG.

Manual enumeration is impossible

In reality, it is infeasible to manually construct test cases that cover every new node / edge in the loop-unrolled CFG.

A genetic programming solution: coverage-guided fuzzing.

Manual enumeration is impossible

In reality, it is infeasible to manually construct test cases that cover every new node / edge in the loop-unrolled CFG.

A genetic programming solution: coverage-guided fuzzing.

- ① Randomly selects a seed s from a pool of test cases (seed pool)
 - e.g., seed test case $s = \{ x=0, y=1, n=2 \}$
- ② Mutate seed s to produce a new test case t
 - e.g., test case $t = \{ x=0, y=42, n=2 \}$
- ③ Execute t and collect coverage on the CFG during execution
 - if t yields new coverage, save t to the seed pool
 - otherwise, discard t
- ④ Go back to step 1 — completing one round of evolution

Outline

- 1 Introduction
- 2 Testing with concrete inputs
- 3 Fuzzing overview**
- 4 Program state coverage: “natural selection” in the fuzzing world
- 5 Conclusion

History: why do we call it “fuzzing”?

History: why do we call it “fuzzing”?

In 80's, someone remotely logged into a unix system over a dial-up network link **during a storm**.

The rain caused a lot of **random noise** on the dial-up link.

And these noise caused applications that were using data off the dial-up network line to **crash**.

History: why do we call it “fuzzing”?

In 80's, someone remotely logged into a unix system over a dial-up network link **during a storm**.

The rain caused a lot of **random noise** on the dial-up link.

And these noise caused applications that were using data off the dial-up network line to **crash**.

Gist of the story? — The rain tests the program way better than human beings.


Evolution: from the rain-fuzzer to modern fuzzing

Evolution: from the rain-fuzzer to modern fuzzing


The key is **genetic algorithm**.

Training a program to play the snake game with genetic algorithm

Feedback-guided evolution process



Feedback-guided evolution process



Natural selection — survival of the fittest

Demo with AFL++

Acknowledgement: this demo is based on one of the examples used in the “[Fuzzing with AFL](#)” workshop by Michael Macnair.

Outline

- 1 Introduction
- 2 Testing with concrete inputs
- 3 Fuzzing overview
- 4 Program state coverage: “natural selection” in the fuzzing world
- 5 Conclusion

Intuition: what makes a high-quality seed?

Intuition: what makes a high-quality seed?

```
1 pub fn foo(a: num, b: num) {  
2   let c = if (a >= 0) {  
3     1  
4   } else {  
5     2  
6   };  
7  
8   // irrelevant operations  
9  
10  let d = if (b >= 0) {  
11    2  
12  } else {  
13    3  
14  };  
15  
16  // irrelevant operations  
17  
18  assert!(c != d);  
19 }
```

Q: What is the testing plan?

Intuition: what makes a high-quality seed?

```
1 pub fn foo(a: num, b: num) {  
2   let c = if (a >= 0) {  
3     1  
4   } else {  
5     2  
6   };  
7  
8   // irrelevant operations  
9  
10  let d = if (b >= 0) {  
11    2  
12  } else {  
13    3  
14  };  
15  
16  // irrelevant operations  
17  
18  assert!(c != d);  
19 }
```

Q: What is the testing plan?

- Cover every line?
- Cover every if-else branch?
- Cover every exit status?
- Cover every path?

Intuition: what makes a high-quality seed?

```
1 pub fn foo(a: num, b: num) {  
2     let c = if (a >= 0) {  
3         1  
4     } else {  
5         2  
6     };  
7  
8     // irrelevant operations  
9  
10    let d = if (b >= 0) {  
11        2  
12    } else {  
13        3  
14    };  
15  
16    // irrelevant operations  
17  
18    assert!(c != d);  
19 }
```

Q: What is the testing plan?

- Cover every line?
- Cover every if-else branch?
- Cover every exit status?
- Cover every path?

⇒ if the fuzzer generates an input that **expands the coverage**, that input is a good seed.

Illustration of different coverage metrics

```
1 pub fn foo(a: num, b: num) {  
2   let c = if (a >= 0) {  
3     1  
4   } else {  
5     2  
6   };  
7  
8   // irrelevant operations  
9  
10  let d = if (b >= 0) {  
11    2  
12  } else {  
13    3  
14  };  
15  
16  // irrelevant operations  
17  
18  assert!(c != d);  
19 }
```




Illustration of different coverage metrics

- Cover every line?
 - Block coverage
- Cover every if-else branch?
 - Branch coverage
- Cover every exit status?
 - Return coverage
- Cover every path?
 - Path coverage





Illustration of different coverage metrics

- Cover every line?
 - Block coverage
- Cover every if-else branch?
 - Branch coverage
- Cover every exit status?
 - Return coverage
- Cover every path?
 - Path coverage




Path coverage: a theoretical optimum

Claim: A program is **saturately tested** if we obtain a set of inputs that covers **every feasible path** of the program CFG.


NOTE: feasible paths include paths that leads to explicit and implicit panics.

Path coverage demo




Path coverage demo

- $a = 1, b = 1$




Path coverage demo

- $a = 1, b = 1$
- $a = 1, b = -1$




Path coverage demo

- $a = 1, b = 1$
- $a = 1, b = -1$
- $a = -1, b = 1$



Path coverage demo


- $a = 1, b = 1$
- $a = 1, b = -1$
- $a = -1, b = 1$
- $a = -1, b = -1$



Path coverage demo

- $a = 1, b = 1$
- $a = 1, b = -1$
- $a = -1, b = 1$
- $a = -1, b = -1$

No new program behaviors can be discovered \implies the program is saturately tested



Why not path coverage in practice?

Why not path coverage in practice?

Short answer: I don't know... AFL (American Fuzzy Lop) didn't adopt path coverage, so everyone follows suite...

Long answer:

- tracking block / branch coverage is **stateless** while tracking path coverage requires **stateful** instrumentations.
- different parts of the execution are not necessarily related, i.e., a new path does not necessarily mean interesting findings.
- it is hard to quantitatively measure the completeness of path coverage (because of infeasible paths). But by default, all branches should be somewhat feasible.

Why not path coverage in practice?

Short answer: I don't know... AFL (American Fuzzy Lop) didn't adopt path coverage, so everyone follows suite...

Long answer:

- tracking block / branch coverage is **stateless** while tracking path coverage requires **stateful** instrumentations.
- different parts of the execution are not necessarily related, i.e., a new path does not necessarily mean interesting findings.
- it is hard to quantitatively measure the completeness of path coverage (because of infeasible paths). But by default, all branches should be somewhat feasible.


In practice, branch coverage hits a nice balance between effectiveness and easiness of instrumentation.

What's wrong with branch coverage?

What's wrong with branch coverage?

- $a = 1, b = 1$
- $a = -1, b = -1$

Two seeds already covered most of the branches.




What's wrong with branch coverage?

- $a = 1, b = 1$
- $a = -1, b = -1$

Two seeds already covered most of the branches.

- $a = 1, b = -1$

A seed that yields new path but is considered as a bad seed as it yields no new branch coverage.



What's wrong with branch coverage?


- $a = 1, b = 1$
- $a = -1, b = -1$

Two seeds already covered most of the branches.

- $a = 1, b = -1$

A seed that yields new path but is considered as a bad seed as it yields no new branch coverage.

⇒ fuzzer is not rewarded by mutating a and b , hence, lowering their priorities and the panic case may never be found,



What's wrong with branch coverage?


- $a = 1, b = 1$
- $a = -1, b = -1$

Two seeds already covered most of the branches.

- $a = 1, b = -1$

A seed that yields new path but is considered as a bad seed as it yields no new branch coverage.

⇒ fuzzer is not rewarded by mutating a and b , hence, lowering their priorities and the panic case may never be found, especially when fuzzing **complex** CFGs



Outline

- 1 Introduction
- 2 Testing with concrete inputs
- 3 Fuzzing overview
- 4 Program state coverage: “natural selection” in the fuzzing world
- 5 Conclusion

The goal of fuzzing

Q: What is fuzzing doing essentially? Try to describe it in a way that is as abstract/general as possible.

The goal of fuzzing

Q: What is fuzzing doing essentially? Try to describe it in a way that is as abstract/general as possible.

A: To **drive** the execution of a **system** into **desired states**.

Elaborating on the definition

- What is special about the target **system**?
 - Do we know the source code?
 - Do we know the input format?
 - What are the challenges when executing the “system”?
- What do we mean by a **state**?
 - How can we tell that one state is different from another?
- What do we mean by **desired**?
 - New/unseen behavior?
 - Closeness to targeted execution points?
- What do we mean by **driving** the execution?
 - What can possibly be one mutation?
 - How do you select the next mutation?

〈 End 〉