

ANGULAR 2

Angular v2.2.1

[Home](#)

[Why Angular2?](#)

[Components](#)

[Inputs](#)

[Outputs](#)

[Lifecycle](#)

[Templates](#)

[Events](#)

[Forms](#)

[ViewChild](#)

ES6/TypeScript

1/1/2017

COMPONENTS

[Suggest improvements](#)

[Tweet](#)

In Angular 2, “everything is a component.” Components are the main way we build and specify elements and logic on the page, through both custom elements and attributes that add functionality to our existing components.

A SIMPLE COMPONENT

Here’s a simple [Component](#) that renders our name, and a button that triggers a method to print our name to the console:

APP.COMPONENT.TS

```
import { Component } from '@angular/core';

@Component({
  selector: 'my-component',
  template: `
```

[vvalr](#)

[Variables](#)

[Classes](#)

[Template Strings](#)

[Arrow Functions](#)

[Promises](#)

```
<div>Hello my name is {{name}}.  
  <button (click)="sayMyName()">Say my name</button>  
</div>  
,  
  })  
  export class MyComponent {  
    name: string;  
    constructor() {  
      this.name = 'Max'  
    }  
    sayMyName() {  
      console.log('My name is', this.name)  
    }  
  }
```

When we use the `<my-component></my-component>` tag in our HTML, this component will be created, our constructor called, and rendered.

Built by the [Ionic](#) Team. Licensed under Apache 2.

