

ANGULAR 2

Angular v2.2.1

[Home](#)

[Why Angular2?](#)

[Components](#)

[Inputs](#)

[Outputs](#)

[Lifecycle](#)

[Templates](#)

[Events](#)

[Forms](#)

[ViewChild](#)

ES6/TypeScript

ANGULAR 2 EVENTS

[Suggest improvements](#)

[Tweet](#)

Events in Angular 2 use the parentheses notation in templates, and trigger methods in a component's class. For example, assume we have this component class:

```
@Component(...)  
class MyComponent {  
  clicked(event) {  
  }  
}
```

And this template:

```
<button (click)="clicked()">Click</button>
```

Our `clicked()` method will be called when the button is clicked.

[Wat?](#)

[Variables](#)

[Classes](#)

[Template Strings](#)

[Arrow Functions](#)

[Promises](#)

DELEGATION

Events in Angular 2 behave like normal DOM events. They can bubble up and propagate down. Nothing special to do here!

EVENT OBJECT

To capture the event object, pass `$event` as a parameter in the event callback from the template:

```
<button (click)="clicked($event)"></button>
```

This is an easy way to modify the event, such as calling `preventDefault` :

```
@Component(...)  
class MyComponent {  
  clicked(event) {  
    event.preventDefault();  
  }  
}
```

Built by the [Ionic](#) Team. Licensed under Apache 2.