Chapter VI	Big O								
	Asymptotic notations								
	O(Big O)	Describes an upper bound on time		on the runtime; similar to a less-	then we also say that X<=	In industry, O and theta have been put together and we have to give the tightest description of runtime			
	Omega(n)	Describes the lower bound	for example: printing the values in an array is Omega (n) as well as Omega(logn) as well as Omega(1)						
	Theta(n)	Describes the tight bound on runtime	Theta here means both O and Omega; in this example, it would be Theta(n)						
	Best Case, Worst Case and Expected Case								
	Best Case:	For example, in Quick Sort, if all the elements are equal, then quick sort will, on average, just traverse through the array once - O(N) time	elements greater than pivot - this gives partial sort. then it recursively sorts the left and						
	Worst Case:	The pivot could be repeatedly the biggest element in the array. If pivot is the first element in a reversely sorted array. In this cae, our recursion does not divide the array in half and recurse on other half. Instead, it justs shrinks the subarray by 1 element.	Time taken would O(N^2)						
		both the above best and worst conditions would rarely happen; thus we can expect a runtime of O(nlogn)							
		etween Asymptotic notations , Worst Case and Expected							

There is no particular relationship between the two concepts										
	10 15 110									
Best Case, Wor	st Case and Expected Case act	ually describe the big O or big	g Theta time for part	ticular scenarios w	hereas these asy	mptotic notations	describe the upp	er, lower and tigh	t bounds for the ru	ıntime
Space complexity										
Memory or space required by an algorithm	to create an array - if it is unidimensional, O(N) space complexity; for a 2-D array, O (N^2)									
Stack space in recursive calls counts too. Each call adds a level tot he stack and takes up actual memory.	However, just because you have N calls does not mean it will take O(N) time: check the example on Page 41 for more details									
Drop the constants										
O(2N) is actually O(N)										
Drop the non- dominant terms										
O(N^2 + N) becomes O (N^2)										
O(N + logN) becomes O(N)										
O(5*2^N + 1000N^100) becomes O (2^N)										
$O(x!) > O(2^x) > 0$	$O(x^2) > O(x\log x) > O(x)$									
Multi-Parts algorithms: add versus mutiply										
Add:	Non-nested chunk of work A and B	O(A + B)	"DO THIS THEN WHEN YOU ARE ALL DONE, DO THAT"							

Multiply	Nested A and B	O(AB)	"DO THIS FOR EACH TIME YOU DO THAT"				
Multiply	Nesteu A anu B	O(AB)	TOO DO THAT				
Amortized time							
	That copying might take additional O(N) time after accounting for initial O(N) time of adding the elements	into a new array does not	that the worst ca every once in a happens it won't				
Adding X more space to an array takes additional O(X) time; thus the amortized time for each adding is O(1)	X + X/2 + X/4 + X/8 = 2X						
logN runtimes							
Example:							
Binary search. We are looking for an element x in a sorted array. We first compare to the midpoint. If x == middle, then we return else if x < middle, we search on the left side of array		The total runtime is then a matter of how many steps we can take before it becomes 1	$2^k = N \Rightarrow k = \log N$ with base 2	Basically, when you see a problem with logN runtime, the problem space gets halved in each step			
Recursive runtimes							
Program:	int f(int n){						
	if(n <= 1){						
	return 1}						
	return f(n -1) + f(n -1);}						
How many calls in the tree?							
Do not count and say 2							

It will have recursive calls with a depth N and 2^N nodes at the bottom most level	More genrically, 2 ⁰ + 2 ¹ + 2 ² +2 ⁿ -1 = 2 ⁿ - 1 nodes	O(branches^depth) where branches is the number of times each recursive call branches	The space complexity would still be O (n) - even though we have O(2^n) nodes in tree total, only O(n) exists at a time				
Examples and Exercises							
Example 1	O(n) time as we iterate through array once in each loop which are non-nested						
Example 2	O(N^2) time as we have two nested loops						
Example 3	j basically runs for N-1 steps in first iteration, N-2 steps in second iteration and so on.	1 + 2 + 3 ++ N-1 = N(N - 1)/2 ~ N^2	O(N^2)				
Example 4	For each element of array A, the inner loop goes through b iterations where b is the length of array B. Thus, time complexity is O(ab)						
Example 5	Similar to example 4, 100,000 units of work is still constant; so the run time is O(ab)						
Example 6	O(N) time as the array is iterated even if half of it (constant 1/2 can be ignored)						
Example 7	There is no established relationship between N and M , thus all but the last one are equivalent to O(N)						
Example 8	s = length of the longest string Sorting each string would take elements of the array; thus O(a array would take O(s * aloga) a would take O(s) time in additio take O(aloga); thus adding the aloga) = O(a *s (log a + log s)	O(slogs) and we do this for a a * slogs). Now, sorting the as each string comparison in to array sorting that would					
Example 9	Approach 1: for summing up the nodes in a BST, each node is exactly traversed once, thus O(N) time complexity						
	Approach 2: The number of recursive calls is 2 and the depth is logN in a BST> O (branches ^ depth) = O(2 ^ logN) where the base of logN is also 2 => time complexity = O(N) after simpllifying						

Example	O(root(N)) as the for loop does constant time and runs at 10 in O(root(N)) time		
Example	O(N) as the recursive process calls from N to N-1 to e 11 N-2 and so on until 1		
Example	Approach 1 : We make a tree for an example string say 'abcd' and we see that we brand 4 times at the root , then 3 times, then 2 times, and then 1 tir this gives us $4*3*2*1$ leaf nodes. We could say n! leaf nodes for n length string. So, total nodes would be $n*n!$ as each leaf node is attached to a path with n nodes. Also, string concatenation will also take $O(n)$ time. Thus the final time complexity in worst case would be $O(n*n*n!) = O((n+2)!)$	ne.	
	Approach 2: At level 6, we have 6! / 0! nodes; at level 5 we have 6! / 1! nodes; at level 4 we have 6!/2! nodesat level 0, we have 6!/6! nodes. so, total nodes in the tree in terms of n can be: n!(1/0! + 1/1! + 1/2! + 1/3!+ 1/n!). Now, the term in the bracket can be defined in terms of Euler's numb n! * e whose value is around 2.718. The constant e can be dropped further. Thus, the time complexity would be O(n! * n) where n is due to permutation thus, time complexity: O((n+1)!)	per:	