

```

snigdha@Snigdha:~$ cat skill2.c
#include <stdio.h>
#include <string.h>

int main() {
    char input[100];

    while (1) {
        printf("shell> ");
        fgets(input, sizeof(input), stdin);

        // Remove newline character
        input[strcspn(input, "\n")] = '\0';

        // Check exit condition
        if (strcmp(input, "exit") == 0) {
            printf("Exiting shell...\n");
            break;
        }

        // Handle user input
        if (strlen(input) > 0) {
            printf("You entered: %s\n", input);
        }
    }

    return 0;
}

```

```

snigdha@Snigdha:~$ nano skill2.c
snigdha@Snigdha:~$ gcc skill2.c -o skill2
snigdha@Snigdha:~$ ./skill2
shell> hello
You entered: hello
shell> help
You entered: help
shell> ls
You entered: ls
shell> exit
Exiting shell...

```

```

snigdha@Snigdha:~$ cat skill2a.c
#include <stdio.h>
#include <unistd.h>
#include <termios.h>
#include <string.h>

#define BUFFER_SIZE 100

int main() {
    struct termios oldt, newt;
    char buffer[BUFFER_SIZE];
    int index = 0;
    char ch;

    // Get current terminal settings
    tcgetattr(STDIN_FILENO, &oldt);

    // Copy current settings
    newt = oldt;

    // Disable canonical mode and echo
    newt.c_lflag &= ~(ICANON | ECHO);

    // Apply new settings
    tcsetattr(STDIN_FILENO, TCSANOW, &newt);

    while (1) {
        printf("\rshell> %s", buffer);
        fflush(stdout);

        // Read one character
        read(STDIN_FILENO, &ch, 1);

        // Handle Enter
        if (ch == '\n' || ch == '\r') {
            buffer[index] = '\0';

            printf("\n");

            // Check exit command
            if (strcmp(buffer, "exit") == 0) {
                printf("Exiting shell...\n");
                break;
            }

```

```

        if (index > 0) {
            printf("Command received: %s\n", buffer);
        }

        // Clear buffer
        index = 0;
        buffer[0] = '\0';
    }

    // Handle Backspace
    else if (ch == 127 || ch == 8) {
        if (index > 0) {
            index--;

            buffer[index] = '\0';

            // Erase character from screen
            printf("\b \b");
            fflush(stdout);
        }
    }

    // Handle normal characters
    else if (ch >= 32 && ch <= 126) {
        if (index < BUFFER_SIZE - 1) {
            buffer[index++] = ch;
            buffer[index] = '\0';

            printf("%c", ch);
            fflush(stdout);
        }
    }
}

// Restore terminal settings
tcsetattr(STDIN_FILENO, TCSANOW, &oldt);

return 0;
}

```

```
snigdha@Snigdha:~$ nano skill2a.c
snigdha@Snigdha:~$ gcc skill2a.c -o skill2a
snigdha@Snigdha:~$ ./skill2a
shell> hello
Command received: hello
shell> help
Command received: help
shell>
shell> exit
Exiting shell...
```