

Phase 1: Introduction to Golang (Sessions 1-8)

Objective: Build a strong foundation in Golang basics.

Session 4: Functions



Discussion Points

- Function declarations and returns
- Multiple return values
- Recursion
- Variadic functions
- Defer, panic, and recover





Function declarations and returns

What is Function?

We use functions to divide our code into smaller chunks to make our code looks clean and easier to understand.

Basically, a function is a block of code that performs a specific task. For example, suppose we want to write code to create a circle and rectangle and color them.

In this case, we can organize our code by creating three different functions:

- function to create a circle
- function to create a rectangle
- function to color

```
func addNumbers() {  
    // code  
}  
  
addNumbers()
```





Function declarations and returns

What is Parameters?

Parameters provided in a function call are called **arguments**

```
func addNumbers(parameters) {  
    // code  
}  
  
addNumbers(parameters)
```

Note: Go doesn't support default parameter values.






Function declarations and returns

What is Return value?

If a function should return some value, the data type of the value should be specified right after function parameter parentheses

```
func addNumbers(parameters) int {  
    // code  
    return sum  
}  
  
result := addNumbers(parameters)
```





Function declarations and returns

What is Multiple Return value?

Multiple values can be returned from a function by specifying the return types separated by commas

If we do not need some of the values after the function call, we should assign it as `_` (blank identifier)

```
func addNumbers(parameters) (int, string) {  
    // code  
    return sum, str  
}  
  
int1, str1 := addNumbers(parameters)  
  
int2, _ := addNumbers(parameters)
```





Function declarations and returns

What is Named return values?

Explicitly mentioned return variables in function definition is a different way of returning values in Go

```
func addMultiply(parameters) (add int, mul int) {  
    add = ...  
    mul = ...  
    return  
}  
  
add1, mul1 := addMultiply(parameters)
```






Function declarations and returns

What is Recursion?

Sometimes, the solution for bigger instances depends on the solution of smaller instances. A function calls itself for smaller instances until the problem is solved. This approach is called recursion.

```
func fibonacci(n int)(res int) {  
    if n <= 1 {  
        res = 1  
    } else {  
        res = fibonacci(n - 1) + fibonacci(n - 2) // recursive call  
    }  
    return  
}
```

Fibonacci Spirals





Function declarations and returns

What is Function as a type?

A function in Golang is also a **type**. If two function accepts the same parameters and returns the same values, these two functions are of the same type

We can pass a function as an argument to another function or a function can return another function as a type

Same type

```
func add(a, b int) int {}  
  
func subtract(a, b int) int {}
```

Different type

```
func add(a string) string {}  
  
func subtract(a, b int) int {}
```

```
func calc(a, b int, fn func(int, int) int) int {  
    r := fn(a, b)  
    return r  
}  
  
calc(5, 10, add)  
calc(10, 4, subtract)
```





Function declarations and returns

What is Anonymous function?

A function in Go can also be a value. This means you can assign a function to a variable, return an anonymous function and etc.

Use cases:

Short-lived functions, Passing functions as arguments, Closures with state, Deferred execution, Concurrency with Goroutines

```
var var1 = func(n1, n2 int) int {  
    ...  
}  
  
var1(5, 3)
```

```
func displayNumber() func() int {  
    return func() int {  
        ...  
    }  
}
```





Function declarations and returns

What is Closure?

Go closure is a nested function that allows us to access variables of the outer function even after the outer function is closed.

Before we learn about closure, let's first revise the following concepts:

- Nested Functions
- Returning a function

```
func greet() func() {  
  
    return func() {  
        ...  
    }  
}  
  
func main() {  
  
    g1 := greet()  
    g1()  
}
```

```
// outer function  
func greet() func() string {  
  
    // variable defined outside the inner function  
  
    // return a nested anonymous function  
    return func() string {  
        ...  
    }  
}  
  
func main() {  
  
    // call the outer function  
    message := greet()  
  
    // call the inner function  
    fmt.Println(message())  
}
```





Function declarations and returns

What is Immediately-invoked function?

In Golang, we can create an anonymous function that can be defined and executed at the same time:

```
func main() {  
    addRes := func(a, b int) int {  
        return a + b  
    }(10, 50)  
  
    fmt.Println("10 + 50 =", addRes)  
}
```





Function declarations and returns

What is Variadic functions?

Variadic functions are functions can take an infinite or variable number of arguments

A typical syntax of a variadic function looks like this. ... (unpack operator) called as pack operator instructs to store all arguments of type **Type** in **elem** parameter

IMPORTANT Note: Only the last argument of a function is allowed to be variadic

```
func print(elem ...Type)
```

```
func print(a int, arg ...int) []int {  
    ...  
    return arg  
}
```





Defer, Panic, Recover

What is Defer?

In Go, we use defer, panic and recover statements to handle errors.

We use **defer** to delay the execution of functions that might cause an error. The **panic** statement terminates the program immediately and **recover** is used to recover the message during panic.

```
defer fmt.Println("I'm quit")
```

```
defer func() {  
    fmt.Println("I'm quit")  
}()
```





Defer, Panic, Recover

What is Recover?

The **panic** statement immediately terminates the program. However, sometimes it might be important for a program to complete its execution and get some required results.

In such cases, we use the **recover** statement to handle **panic** in Go. The **recover** statement prevents the termination of the program and recovers the program from **panic**.

```
defer func() {  
    if a := recover() ; a != nil {  
        fmt.Println("RECOVER", a)  
    }  
}()  

```



Session Quiz Go?



Join at
slido.com
3213656

Thank you.

Questions?

- Function declarations and returns
- Multiple return values
- Recursion
- Variadic functions
- Defer, panic, and recover

“Learn from yesterday, live for today, hope for tomorrow. The important thing is not to stop questioning.”

- Albert Einstein

