



Crown 250/350 Triplex Pump

Application:

- Underground stope cleaning.
- Drilling applications.
- General industrial high pressure cleaning.
- Sewer and pipe line cleaning.
- Abrasive water blasting – removal of graffiti, paint etc.
- Cleaning of rolling stock – earthmoving equipment.
- Vortex jet mud sucking attachment available

Mechanical Features:

- Alloy steel fluid end design.
- All stainless steel valve assemblies and relief valve.
- Nodular iron connecting rods.
- Forged steel crankshaft.
- Nodular iron connecting rods.
- Integral gearbox with helical gear set.
- Hard chromed or tungsten coated plungers.
- Self tensioning gland assembly.
- Skid mounted with tubular protection frame.
- Stainless steel epoxy coated control panel.
- All stainless steel fasteners – wet end.
- Available in dump type or dry shut off system.
- 95 % Volumetric efficiency.
- Electric or diesel drive 15kW – 55kW.
- Compact design for use in confined area.

Tel: +27 618-2003 E-Mail: sales@cemo.co.za

Physical Address: Crown Building, 64 Hanau Street, Jeppestown, JHB
Standard Trading Terms, Conditions and Warranties Apply And Are Available On request



- Pressure range 8 – 20 Mpa.
- Flows from 136 – 220 L/min.

Our high pressure CROWN brand of triplex pump ranges are perfect for use on underground and mining opencast operations. These pumps are also used extensively in reverse osmosis plants as well as plate descaling in the steel mill industry. The CROWN 350 medium to high pressure triplex pump has become a standard within the South African and North and South American mining operations. Its ability to operate at pressures of up to 20 MPa and with flows ranging from 130 - 210 l/min have made this the industry's first choice for water jetting, general descaling, plant cleaning as well as micro-hydro-power mining systems which include rock drills, roof bolters, rock and ore loaders which would have previously been powered pneumatically. The CROWN 250 triplex high pressure pump is a compact version of the robust Crown 350. These are used primarily on municipal drain cleaning and honey-sucker type equipment used for unblocking sewer lines as well as drain cleaning. These are also used in the coal mining industry as a high pressure pump used in conjunction with a scrubber for dust suppression. Their compact size and light weight have made the CROWN 250 the preferred mobile, trailer mounted, diesel driven high pressure pump for building contractors, fire-fighters, plumbers and plant excavators. Pressures of up to 25 MPa and flows of up to 150 l/min are achievable with this all nodular iron and steel construction.

SI Units							US Imperial Units				
Plunger Diameter (mm)	Pinion (T)	Gear (T)	Flowrate (l/s)	Maximum Head (m)	Pressure (bar)	Power (kW)	Plunger Diameter (in.)	Flowrate (gpm)	Head (ft)	Pressure (psi)	Power (hp)
22.225	19	44	0.78	3063	300	30	¾	12.42	10049	4355	40
28	19	44	1.23	3063	300	55	1.1	19.55	10049	4355	74
31.75	19	44	1.6	2552.5	250	55	1¼	25.36	8374	3630	74
38.1	19	44	2.3	1939.9	190	55	1½	36.46	6365	2758	74
41.275	19	44	2.7	1837.8	180	55	1¾	42.8	6030	2613	74
45	19	44	3.2	1327.3	130	55	1¾	50.73	4355	1887	74
50.8	19	44	4.08	1225.2	120	55	2	64.73	4020	1742	74

Tel: +27 618-2003 E-Mail: sales@cemo.co.za

Physical Address: Crown Building, 64 Hanau Street, Jeppestown, JHB

Standard Trading Terms, Conditions and Warranties Apply And Are Available On request