



Crown 767 Triplex Mud Pump

Typical Applications:

- Underground mining mud and slurry pumping
- Backfill pumping
- Raw sewage pumping
- Petro-Chemical bi-product and viscous product pumping
- High flow medium pressure pump

Technical features:

- Split type fabricated steel casing for ease of jackshaft removal and replacement
- Robust cast steel one piece fluid end with simple access to valve assemblies for easy valve service & replacement with minimum skill requirements eliminating pump downtime.

NB: Crown 767 type fluid end is not interchangeable with standard Crown 120 Triplex mud pump fluid end

- Custom designed suction and delivery valve configurations and materials to suit particular fluid or medium being pumped. (On special request only)
- All parts i.e. crankcase/casing, all rotating spares, lubrication system, jackshaft gear sets and eccentric assemblies within the crankcase are

Tel: +27 618-2003 E-Mail: sales@cemo.co.za

Physical Address: Crown Building, 64 Hanau Street, Jeppestown, JHB

Standard Trading Terms, Conditions and Warranties Apply And Are Available On request



fully interchangeable with Crown120 type triplex pump and alternate mud pump models currently available within the mining

- Compact pump base plate dimensions identical to Crown 120 Triplex Pump
- Typical SG of fluids from 1.05 to 1.20 readily achievable
- Input power from 90kW to 132kW dependent on pump duty required
- Heavy duty and heat treated ring gear and pinion sets
- Crown heavy duty Nitrile/Urethane combo Mission Piston with 316 S/S piston rods and bronze piston guides
- Pushrods: Hard Chrome plated with Ramiex packed adjustable glands
- Connecting Rod/Crossheads and Eccentric: SG Nodular Iron
- Connecting Rod Liners and Crosshead Pin Bushes: Leadaded gun metal
- Oil Stop Heads: Single piece gland packed with bronze guide rings
- Electrically controlled independent oil pump lubrication or jackshaft driven oil pump
- Oil over-temperature cut out probe fitted as standard equipment
- Piston diameters from 5" – 7" (127mm to 178mm), to achieve high flows that this model is designed for
- 316 S/S Mission piston sleeves with hard chrome plated bores for extra wear resistance
- Ancillary equipment and components supplied with pump

Full set maintenance spanners

Mission Piston seal kit installation tools

Accumulator

Shear Relief Valve

2 x 2" High Pressure Isolation/Start-up Cock (Manually or actuator operated)

Non-Return Valve

Tel: +27 618-2003 E-Mail: sales@cemo.co.za

Physical Address: Crown Building, 64 Hanau Street, Jeppestown, JHB

Standard Trading Terms, Conditions and Warranties Apply And Are Available On request



Full set operating and maintenance manual in both hard copy and digital format

On site commissioning both locally and globally

Options:-

DOL motor control centres and enclosures or VSD drives and enclosures available on request (525V-1000V)

Piston Size	Flow l/sec	m ³ / hr	Max head	Power
5"	12.87	46.33	800m	132kW
5½"	15.57	56.05	670m	132kW
6"	18.53	66.71	560m	132kW
6½"	21.75	78.30	480m	132kW
7"	25.22	90.79	420m	132kW

Pulley Ratio : 315:1000
Jackshaft speed : 469 RPM
Eccentric speed : 100 RPM
Recommended NPSH : 9.5 → 10 KPa

Based on 95% volumetric efficiency @ 20°C (maximum), mechanical efficiency rated at 97% (maximum)

All above data quoted are rated at motor speeds of 1490 RPM and SG content of 1.01 → 1.05. Motor pulley diameters to be selected and determined as per flow requested by client

Tel: +27 618-2003 E-Mail: sales@cemo.co.za

Physical Address: Crown Building, 64 Hanau Street, Jeppestown, JHB

Standard Trading Terms, Conditions and Warranties Apply And Are Available On request