

MFG-EX-SH-01 • v0.8 MANUFACTURING DRAWING


TOP X-Y



FRONT X-Z



SIDE Y-Z



Drawing MFG-EX-SH-01 | Part EX-SH-01 — Three-panel hot-zone shield | Qty 1

Rev final-design-fabrication-closure-v0.8 | Units mm | Scale NTS, dimensions govern | Third-angle projection | source commit 5008ee78988e17bcd38904df27b48af28fd8c594

Material: 2 mm 5052 aluminum | Process/finish: laser + two 90deg bends; bond PE

Overall: X 335.000 × Y 75.000 × Z 85.000 mm | general tolerance ISO 2768-m unless noted

Critical: 335 x75 x85; open bottom/ends; feeder opening Ø50 at X314/Y37; >=10 mm ABS-duct gap; edge hem/deburr

GD&T/datums: A=frame mounting plane; B=primary edge; C=mounting-hole centreline; verify datum marking on supplier inspection report

Inspection: CMM/caliper against STEP and drawing; deburr and visual crack/warp inspection; fit-up, PE bond where metal, reach/access and interlock actuation inspection

Edges: remove burrs; break unspecified sharp edges C0.3–0.5. No unapproved material/tolerance substitution.

Artifact check: PASS only; fabrication HOLD pending full v0.8 gates. Physical NOT_RUN; machining USER_APPROVAL_REQUIRED.