


MFG-FD-BIN-01 • v0.8 MANUFACTURING DRAWING


TOP X-Y



FRONT X-Z



SIDE Y-Z



Drawing MFG-FD-BIN-01 | Part FD-BIN-01 — Removable flake bin | Qty 1

Rev final-design-fabrication-closure-v0.8 | Units mm | Scale NTS, dimensions govern | Third-angle projection | source commit d09fe9bc0a587c2aadf27557c7d2bed8bf3f9424

Material: 1.00 ±0.05 mm 304 stainless sheet | Process/finish: laser cut, fold and rivet/TIG seam

Overall: X 185.000 × Y 175.000 × Z 115.000 mm | general tolerance ISO 2768-m unless noted

Critical: 185 x175 x115 outside; sheet1.00 ±0.05; PPR-C03 slot1.40 ±0.30 gives clearance0.05–0.75; corner reliefs control; no inward burr/dead pocket; removable without cutter disassembly

GD&T/datums: A=material-flow axis; B=mounting face; C=drive/sensor centre plane; verify datum marking on supplier inspection report

Inspection: CMM/caliper against STEP and drawing; deburr and visual crack/warp inspection; dry assembly rotation and cleanout/dead-pocket inspection

Edges: remove burrs; break unspecified sharp edges C0.3–0.5. No unapproved material/tolerance substitution.

Artifact check: PASS only; fabrication HOLD pending full v0.8 gates. Physical NOT_RUN; machining USER_APPROVAL_REQUIRED.