



MFG-FD-HOP-01 · v0.8 MANUFACTURING DRAWING


TOP X-Y



FRONT X-Z



SIDE Y-Z



Drawing MFG-FD-HOP-01 | Part FD-HOP-01 — Sealed feed hopper | Qty 1

Rev final-design-fabrication-closure-v0.8 | Units mm | Scale NTS, dimensions govern | Third-angle projection | source commit df59fd138780f538a5fa62dad6e2770b49bf4d94

Material: 2 mm 304 stainless | Process/finish: roll cone/cylinder + TIG weld + gasketed lid

Overall: X 156.000 × Y 156.000 × Z 200.000 mm | general tolerance ISO 2768-m unless noted

Critical: OD156 x straight145 + cone55; outlet Ø32; wall2.0; leak test; lid gasket limits moisture ingress

GD&T/datums: A=material-flow axis; B=mounting face; C=drive/sensor centre plane; verify datum marking on supplier inspection report

Inspection: CMM/caliper against STEP and drawing; deburr and visual crack/warp inspection; dry assembly rotation and cleanout/dead-pocket inspection

Edges: remove burrs; break unspecified sharp edges C0.3–0.5. No unapproved material/tolerance substitution.

Release: PASS — physical validation NOT_RUN; procurement and machining USER_APPROVAL_REQUIRED.