



MFG-TH-BH-01 · v0.8 MANUFACTURING DRAWING


TOP X-Y



FRONT X-Z



SIDE Y-Z



Drawing MFG-TH-BH-01 | Part TH-BH-01 — Custom barrel mica band heater | Qty 3

Rev final-design-fabrication-closure-v0.8 | Units mm | Scale NTS, dimensions govern | Third-angle projection | source commit df59fd138780f538a5fa62dad6e2770b49bf4d94

Material: mica/NiCr/stainless sheath | Process/finish: custom heater RFQ

Overall: X 37.894 × Y 38.000 × Z 45.000 mm | general tolerance ISO 2768-m unless noted

Critical: 24 VDC 100 W each; as-clamped ID34.00 +0.10/0; width45 ±0.5; radial build2 nominal; cold resistance 5.76 Ω ±10%; 300 mm fiberglass leads; grounded sheath; PET service 300 C design; no stock Ø35 substitution

GD&T/datums: A=profile mounting plane; B=barrel axis; C=rear axial datum; verify datum marking on supplier inspection report

Inspection: CMM/caliper against STEP and drawing; deburr and visual crack/warp inspection; barrel-axis alignment; sliding travel and cold/hot clearance inspection

Edges: remove burrs; break unspecified sharp edges C0.3–0.5. No unapproved material/tolerance substitution.

Release: PASS — physical validation NOT_RUN; procurement and machining USER_APPROVAL_REQUIRED.