

MFG-TH-PTC-02 · v0.8 MANUFACTURING DRAWING

TOP X-Y



FRONT X-Z



SIDE Y-Z



Drawing MFG-TH-PTC-02 | Part TH-PTC-02 — Hopper PTC grounded keeper | Qty 1

Rev final-design-fabrication-closure-v0.8 | Units mm | Scale NTS, dimensions govern | Third-angle projection | source commit
df59fd138780f538a5fa62dad6e2770b49bf4d94

Material: 304 stainless t2 | Process/finish: laser + deburr

Overall: X 120.000 × Y 2.000 × Z 55.000 mm | general tolerance ISO 2768-m unless noted

Critical: 120 x55 x2; 4x Ø4.5; spring/compliant electrically-insulating pads prevent ceramic point load; PE bond

GD&T/datums: A=material-flow axis; B=mounting face; C=drive/sensor centre plane; verify datum marking on supplier inspection report

Inspection: CMM/caliper against STEP and drawing; deburr and visual crack/warp inspection; dry assembly rotation and cleanout/dead-pocket inspection

Edges: remove burrs; break unspecified sharp edges C0.3–0.5. No unapproved material/tolerance substitution.

Release: PASS — physical validation NOT_RUN; procurement and machining USER_APPROVAL_REQUIRED.