

MFG-SP-DA-01 • v0.8 MANUFACTURING DRAWING

TOP X-Y



FRONT X-Z



SIDE Y-Z



Drawing MFG-SP-DA-01 | Part SP-DA-01 — Dancer arm | Qty 1

Rev final-design-fabrication-closure-v0.8 | Units mm | Scale NTS, dimensions govern | Third-angle projection | source commit
df59fd138780f538a5fa62dad6e2770b49bf4d94

Material: 8 mm 6061-T6 | Process/finish: waterjet + ream

Overall: X 122.000 × Y 8.000 × Z 24.000 mm | general tolerance ISO 2768-m unless noted

Critical: 100 mm pivot centres; 12 mm arm; 2xØ8.2; edge R2; full -25..+25deg motion

GD&T/datums: A=frame mounting plane; B=primary edge; C=mounting-hole centreline; verify datum marking on supplier inspection report

Inspection: CMM/caliper against STEP and drawing; deburr and visual crack/warp inspection; fit-up, PE bond where metal, reach/access and interlock actuation inspection

Edges: remove burrs; break unspecified sharp edges C0.3–0.5. No unapproved material/tolerance substitution.

Release: PASS — physical validation NOT_RUN; procurement and machining USER_APPROVAL_REQUIRED.