



MFG-DRV-F01A · v0.8 MANUFACTURING DRAWING


TOP X-Y



FRONT X-Z



SIDE Y-Z



Drawing MFG-DRV-F01A | Part DRV-F01A — Motor-side fuse inner hub | Qty 1
Rev final-design-fabrication-closure-v0.8 | Units mm | Scale NTS, dimensions govern | Third-angle projection | source commit
df59fd138780f538a5fa62dad6e2770b49bf4d94

Material: S45C | Process/finish: turn + keyway + radial drill

Overall: X 20.000 × Y 20.000 × Z 16.000 mm | general tolerance ISO 2768-m unless noted

Critical: Ø12.2 bore matched to received GMP60 Ø12 keyed shaft; OD20 x16; radial Ø3.2; no set-screw-only torque path

GD&T/datums: A=shaft bore axis; B=stack face; C=key/dowel angular datum; verify datum marking on supplier inspection report

Inspection: CMM/caliper against STEP and drawing; deburr and visual crack/warp inspection; CMM centre distance; blue-check backlash/contact; verify keyed torque path

Edges: remove burrs; break unspecified sharp edges C0.3–0.5. No unapproved material/tolerance substitution.

Release: PASS — physical validation NOT_RUN; procurement and machining USER_APPROVAL_REQUIRED.