


MFG-FM-AX-01 • v0.8 MANUFACTURING DRAWING

TOP X-Y



FRONT X-Z



SIDE Y-Z



Drawing MFG-FM-AX-01 | Part FM-AX-01 — Puller roller spindle | Qty 2

Rev final-design-fabrication-closure-v0.8 | Units mm | Scale NTS, dimensions govern | Third-angle projection | source commit 93ec6a9c0c2afa3ad72288a967f07b7c8d03c99e

Material: Ø8 h6 stainless shaft | Process/finish: cut/face + collar flats

Overall: X 8.000 × Y 8.000 × Z 80.000 mm | general tolerance ISO 2768-m unless noted

Critical: Ø8 h6 x80; TIR0.03; two metal collars; driven spindle interface remains donor-specific

GD&T/datums: A=common journal axis; B=drive-end shoulder/face; C=keyway or retaining feature plane; verify datum marking on supplier inspection report

Inspection: CMM/caliper against STEP and drawing; deburr and visual crack/warp inspection; micrometer bearing seats; dial-indicator TIR/runout between centres

Edges: remove burrs; break unspecified sharp edges C0.3–0.5. No unapproved material/tolerance substitution.

Artifact check: PASS only; fabrication HOLD pending full v0.8 gates. Physical NOT_RUN; machining USER_APPROVAL_REQUIRED.