


MFG-FM-GC-01 · v0.8 MANUFACTURING DRAWING

TOP X-Y



FRONT X-Z



SIDE Y-Z



Drawing MFG-FM-GC-01 | Part FM-GC-01 — Guide roller 625 outer-ring retainer | Qty 2

Rev final-design-fabrication-closure-v0.8 | Units mm | Scale NTS, dimensions govern | Third-angle projection | source commit
b287f07f7a55ba61e39c0a5cbe8e45515c9e53ec

Material: 1 mm 304 stainless sheet | Process/finish: laser cut + deburr

Overall: X 32.000 × Y 32.000 × Z 1.000 mm | general tolerance ISO 2768-m unless noted

Critical: Ø32 x1; bore Ø15.00 +0.10/0 gives outer-ring radial overlap0.446-0.500; 3xØ3.4 PCD26; flatness0.05; bearing face burr-free; install flush in FM-GR-01 recess

GD&T/datums: A=frame mounting face; B=primary bearing axis; C=secondary bearing/fastener axis; verify datum marking on supplier inspection report

Inspection: CMM/caliper against STEP and drawing; deburr and visual crack/warp inspection; bore gauge; matched-pair centre distance and axis parallelism

Edges: remove burrs; break unspecified sharp edges C0.3–0.5. No unapproved material/tolerance substitution.

Artifact check: PASS only; fabrication HOLD pending full v0.8 gates. Physical NOT_RUN; machining USER_APPROVAL_REQUIRED.