


MFG-SP-SH-01 • v0.8 MANUFACTURING DRAWING

TOP X-Y



FRONT X-Z



SIDE Y-Z



Drawing MFG-SP-SH-01 | Part SP-SH-01 — Spool spindle | Qty 1

Rev final-design-fabrication-closure-v0.8 | Units mm | Scale NTS, dimensions govern | Third-angle projection | source commit b287f07f7a55ba61e39c0a5cbe8e45515c9e53ec

Material: Ø12 h6 S45C | Process/finish: cut/turn faces + collar flats

Overall: X 12.000 × Y 12.000 × Z 143.000 mm | general tolerance ISO 2768-m unless noted

Critical: Ø12 h6=11.989-12.000 x143; straightness0.05; two SKF6001-2RSH bore11.992-12.000; axial collars carry spool load

GD&T/datums: A=common journal axis; B=drive-end shoulder/face; C=keyway or retaining feature plane; verify datum marking on supplier inspection report

Inspection: CMM/caliper against STEP and drawing; deburr and visual crack/warp inspection; micrometer bearing seats; dial-indicator TIR/runout between centres

Edges: remove burrs; break unspecified sharp edges C0.3–0.5. No unapproved material/tolerance substitution.

Artifact check: PASS only; fabrication HOLD pending full v0.8 gates. Physical NOT_RUN; machining USER_APPROVAL_REQUIRED.