

# MFG-ExtruderSupportRailRear · v0.8 MANUFACTURING DRAWING



Drawing MFG-ExtruderSupportRailRear | Part ExtruderSupportRailRear — ExtruderSupportRailRear | Qty 1

Rev final-design-fabrication-closure-v0.8 | Units mm | Scale NTS, dimensions govern | Third-angle projection | source commit df59fd138780f538a5fa62dad6e2770b49bf4d94

Material: 2020 aluminum profile L390 | Process/finish: saw cut, face and deburr

Overall: X 390.000 × Y 20.000 × Z 20.000 mm | general tolerance ISO 2768-m unless noted

Critical: length 390.0 ±0.5 mm; end squareness 0.3; front/rear support height difference ≤0.20 mm; axis parallelism ≤0.20/390

GD&T/datums: A=profile mounting plane; B=barrel axis; C=rear axial datum; verify datum marking on supplier inspection report

Inspection: CMM/caliper against STEP and drawing; deburr and visual crack/warp inspection; barrel-axis alignment; sliding travel and cold/hot clearance inspection

Edges: remove burrs; break unspecified sharp edges C0.3–0.5. No unapproved material/tolerance substitution.

Release: PASS — physical validation NOT\_RUN; procurement and machining USER\_APPROVAL\_REQUIRED.