

Parameters and choices for AddiVortes

Lewis Maltby

July 12, 2026

Choice/parameter	Symb	Default value	Search range
Metric to use	d	Euclidean	
Number of tessellations	m	200	[20, 500]
Variance of noise	σ	$\propto \frac{\nu\lambda^1}{\chi_\nu^2}$	
Noise degrees of freedom hyperparam	ν	3 – 10(6)	[1, 10]
Noise alignment hyperparam	q	0.7 – 0.99(0.85)	[0.6, 0.999]
Number of covariates in T_j	d_j	$d_j - 1 \sim \text{Bin}(p - 1, \frac{\omega}{p})$	
Number of centers in T_j	b_j	$b_j - 1 \sim \text{Po}(\lambda_c)$	
Covariates included in T_j	—	Uniformly at random	
Coordinates of centers of T_j	—	$\mathcal{N}(0, \sigma_c^2)^2$	
Number of covariates hyperparam	ω	$\min(3, p)$	[1, 7] (depends on p)
Number of centers hyperparam	λ_c		[1, 50]
Center coordinates hyperparam	σ_c		[0.1, 3]
Mean response of cell i under tess j	μ_{ij}	$\mathcal{N}(\mu_\mu, \sigma_\mu^2)$	
Mean response center hyperparam	μ_μ	0^3	
Mean response spread hyperparam	σ_μ	$\frac{0.5}{k\sqrt{m}}^4$	
Mean response alignment hyperparam	k	3	
Prob of adding/removing a center	—	0.2	
Prob of adding/removing a covariate	—	0.2	
Prob of swapping a covariate	—	0.1	
Prob of changing position of a center	—	0.1	
Number of MCMC iterations	—	1200	[500, 100000]
Number of MCMC burn-ins	—	200	[0.01, 0.5] (as a proportion)

¹Two plausible choices for $\hat{\sigma}$ are considered. The first is the “naive” option, wherein $\hat{\sigma}$ corresponds to the sample standard deviation of the transformed training response values. The second is the “linear model” choice, where $\hat{\sigma}$ is based on the residual standard deviation from a least-squares linear regression of scaled Y on the scaled X variables. Subsequently, a value for ν within the range of 3–10 is selected to shape the prior appropriately. Additionally, a suitable λ value is determined such that the q th quantile of the prior on σ aligns with $\hat{\sigma}$, that is $P(\sigma < \hat{\sigma}) = q$. A suitable range for q is values between 0.7 and 0.99.

²Drawn independently for each dimension

³Given the prior centered at 0, representing our zero-centered transformed data

⁴These hyper-parameters are set such that $m\mu_\mu - k\sqrt{m}\sigma_\mu = -0.5$ and $m\mu_\mu + k\sqrt{m}\sigma_\mu = 0.5$, where k is a preselected hyperparameter determining the prior probability of $E[Y \mid \mathbf{x}, \mathbf{y}_{\text{train}}, \mathbf{X}_{\text{train}}]$