

Wavelets, Sparsity and their Applications

Session 1: Introduction

Pier Luigi Dragotti
Imperial College London
p.dragotti@imperial.ac.uk

Overview


- **Material Provided**
 - Slides
 - Lecture notes
 - Matlab Mini-project
- **Assessment**
 - Final exam consisting of four compulsory questions each carrying equal mark
 - Matlab mini-project due on Monday 18th of December at 5:00pm (25% of final mark)
- **Material and recommended textbooks available on Blackboard**

Motivation

- **Data Data Data**
- Where is all this data coming from?
- 90% of the data exchanged over Internet is non-textual
- Understanding the origin of the data and its formation is key (biomedical data, multimedia data, physical measurements from sensor networks)
- Proper **Signal/Data Representation** is fundamental to **restructure** the original data in a more **revealing** form (*sparse signal representation*)

The Signal Representation Problem

Signal processing aims to
decompose complex signals
using elementary functions which
are then easier to manipulate




$$x(t) = \sum_{i=-\infty}^{\infty} \alpha_i \varphi_i(t)$$



- Wavelets and the wavelet transform - in much the same way as the Fourier transform - is an advanced signal processing tool that helps us to make things easy.
- This is achieved by decomposing a signal in elementary constituents and analysing or processing these constituents independently before reconstruction (re-synthesising the signal).


Signal Representation: Fourier Series



Any signal defined on a finite interval is represented by a sum of sinusoids at different frequencies.

What has Fourier ever done for us?


- Fourier Transform and Fourier series make things easy, e.g.,
 - Fast computation of convolution
 - Essential in LTI filter design and in filtering in general
 - Essential in communication
 - Valid signal analysis tool
- Can we do better? Is FT good at analysing the signal below?



Signal Representation: Haar Wavelet

finite interval \rightarrow Fourier series

finite energy \rightarrow Haar function



Any function of **finite energy** is given by the sum of the Haar function and its translated and scaled versions.


Haar function is the first example of a **wavelet!**

L^p space: f must be p -integrable for f to be in L_p .

Signal Representation: Haar Wavelet

$$L^p \text{ norm: } \|f\|_p = \left(\sum_i |f_i|^p \right)^{\frac{1}{p}}$$

1910: Alfred Haar discovers the Haar wavelet
dual to the Fourier construction



Why do this? What makes it work?

- basic atoms form an orthonormal set

Note

- sines/cosines and Haar functions are ON bases for $L_2(\mathbb{R})$
- both are structured orthonormal bases
- they have different time and frequency behavior

The Haar Decomposition

Basis functions

$$\psi(0) = 1 \rightarrow \psi(0.5) = -1$$


$$\psi(t) = \begin{cases} 1 & 0 \leq t < 0.5 \\ -1 & 0.5 \leq t < 1 \\ 0 & \text{else} \end{cases}$$

$$\psi_{mn}(t) = 2^{-m/2} \psi(2^{-m}t - n)$$


$$\psi_{00}(t) = \psi(t)$$

$$\begin{aligned} \psi_{10}(t) &= 2^{-\frac{1}{2}} \psi(2^{-1}t) \\ &= \frac{1}{\sqrt{2}} \psi\left(\frac{t}{2}\right) \end{aligned}$$

$$\begin{aligned} \psi_{-10}(t) &= 2^{\frac{1}{2}} \psi(2^1 t) \\ &= \sqrt{2} \psi(2t) \end{aligned}$$



Basis functions across scales (note orthogonality)



Series expansions from iterated filter banks- 11

Signal Representations

$$x(t) = \sum_{i=-\infty}^{\infty} \alpha_i \varphi_i(t)$$

Key Ingredients:

- a set of ‘atoms’: $\{\varphi_i\}$
- a inner product: $\langle x, \varphi_i \rangle = \int x(t) \varphi_i(t) dt$
- a synthesis formula: $x(t) = \sum_{i=-\infty}^{\infty} \alpha_i \varphi_i(t)$

Many choices of $\{\varphi_i\}$

- orthonormal bases (e.g., Fourier series, Haar wavelet, Daubechies wavelets)
- biorthogonal bases (e.g., splines)
- overcomplete expansions or frames


Key Questions: How can I find new sets of atoms? Which set is better?

Sparse Signal Representations


- Given two competing signal representations, which one is better?
- Signal Processing uses **Occam's razor** to answer this question:
“among competing *representations* that predict equally well,
the one with the *fewest number of components* should be selected.”
- Wavelets are *better* because they provide **sparse representations** of most natural signals
- This is why wavelets are used successfully in many signal processing applications (e.g., image compression)
- The **Sparse Representation Principle** is now the cornerstone of ‘Data Analysis’

Wavelets vs Fourier

Coefficients used: 2%



Wavelets




Fourier

Wavelets vs Fourier: Time-Frequency Tiling


Time-frequency tiling

Basis functions have some spread in time and frequency

- leads to time-frequency tile or atom
- the area in which most of the signal's energy resides




- to represent signals, the tiling cannot have “holes”




Wavelets vs Fourier: Time-Frequency Tiling

1945: Gabor localizes the Fourier transform \Rightarrow STFT

1980: Morlet proposes the continuous wavelet transform



short-time Fourier transform





wavelet transform

Wavelets vs Fourier

Which one looks like music?

(a)  **Equal time divisions at all frequencies – like STFT**

(b)  **Finer time divisions at lower frequencies – possible w/wavelet packets**

(c)  **Finer time divisions at higher frequencies – like DWT**

Wavelets vs Fourier

Preview 1: Approximation

Consider signals in the vector space \mathbb{R}^N

There are many orthonormal expansions


$$x = \sum_{i=1}^N \alpha_i \varphi_i$$

How do they differ for *approximation*?


$$x \approx \hat{x}_K = \sum_{i=1}^K \beta_i \varphi_{j_i}, \quad K < N$$

- Different bases $\{\varphi_i\}_{i=1}^N$
- Different orders j_1, j_2, j_3, \dots


Wavelets vs Fourier




Original signal, $N=1024$




$M=64$, linear
Fourier



$M=64$, nonlinear
Fourier



$M=64$, linear
Daubechies wavelet




$M=64$, nonlinear
Daubechies wavelet


5

Why Sparsity?

Coefficients used: 2%



Wavelets



Fourier

Why Sparsity?

Image Compression



Original Lena Image
(256×256 pixels)



JPEG (Compression Ratio
43:1)



JPEG2000 (Compression
Ratio 43:1)

Note: images courtesy of dspworx.com

Why Sparsity?

- In signal processing we often have to solve ill-conditioned inverse problems
- Approach: given partial and noisy knowledge of your signal, amongst all possible valid solutions, pick the sparsest one
- This sparsity-driven principle has lead to state-of-the-art algorithms in denoising, inpainting, deconvolution, sampling etc.

Why Sparsity? Inpainting



The usual suspect

Why Sparsity? Inpainting



Inpainting based on [Scholefield-Dragotti. IEEE Trans. Image Processing 2014](#)

Wavelets vs Fourier

Preview 2: Estimation

Consider signal x observed through noisy observation

$$y = x + d \quad d \sim \mathcal{N}(0, \sigma^2 I)$$

minimum mean square error

MMSE estimate $\hat{x}_{\text{MMSE}} = E[x | y]$ can be complicated
(if even known)


For simplicity, we often insist on a diagonal estimator in
a transform domain:

$$\hat{x} = T^{-1}D(Ty), \quad D(\cdot) \text{ diagonal}$$

What are good choices for T and D ?

Wavelets vs Fourier

Original image



Original image +
i.i.d. Gaussian noise



Denoised in
Fourier domain




Denoised in
Wavelet domain



Wavelets vs Fourier

1-D Example



Wavelets vs Fourier


Fourier	Wavelet
linear, time invariant	not linear, time invariant
Gaussian	non-Gaussian
stationary	non-stationary
continuous	discontinuous
smooth	containing edges
known structure	(partly) unknown structure
global	locally “adaptive”
single resolution	multiple resolutions
modeled by sinusoids	modeled by piecewise polynomials

10


Implementation of the Wavelet Transform

- Two-channel filter-bank

-




- How can I achieve perfect reconstruction?




Implementation of the Wavelet Transform


1984: Lena gets critical
(subband coding)




Implementation of the 2-D Wavelet Transform



Implementation of the 2-D Wavelet Transform



Wavelet Theory: A Unifying Framework



Introduction - 12


Course Aims and Course Outline

- **Course aim:** find systematic ways to design new signal representations (e.g., new wavelets beyond the Haar wavelet). This is achieved
 - using the geometry of Hilbert spaces
 - learning about filter banks (for fast implementation of new bases)
 - connecting ideas in approximation theory and spline theory with filter banks
- Wavelets had impact in many **applications**. We will touch upon:
 - Image/Video Compression
 - Super-Resolution Imaging
 - Neuroscience
- **Conceptually** wavelets:
 - provide a bridge between discrete-time and continuous-time processing
 - give us an understanding of the importance of compact representation (**sparsity**) in both signal processing and data analysis (e.g., sparse regression)
 - provide the tools to build new representations to tackle the applications at hand

Wavelets and Beyond: Image Super-Resolution



(a) Original (512 x 512)



(b) Low-res. (64 x 64)



(c) Super-res (PSNR=24.2dB)

- *Forty low-resolution and shifted versions of the original.*
- *Accurate registration is achieved by retrieving the continuous moments of the 'Tiger' from the samples.*
- *The registered images are interpolated to achieve super-resolution.*