

ROLLPACK

Self-supporting cast iron roller


Société Nouvelle
RAZOL //



ROLLPACK

Self-supporting cast iron roller

Strong points



Standard equipments

- CHASSIS steel beam 100 x 100 x 10 mm
- 2 SIDE ELEMENTS steel beams 100 x 100 x 8 mm (Rollpack 5,25 and 6,25 m)
- 2 SIDE ELEMENTS steel beams 150 x 100 x 8 mm (Rollpack 7,25 and 8,25 m)
- DRAWBAR steel beams 150 x 100 x 8 mm
- HITCH RING fixed Ø51 adjustable 4 positions
- LOAD TRANSFER steel beams 150 x 100 x 8 mm
- 2 WHEELS 260/70 - 15.3 FL+
- HYDRAULIC FOLDING 2DA controled from the tractor
- BEARING with self-aligning bearings
- LOCKING of side elements in transport mode
- LED LIGHTING as standard




- Hydraulic connection : 2 DA output
- Good weight distribution
- Land's shape monitoring
- Transport width 2,45 m
- 3 elements

The heavy self-supporting roller ROLLPACK has been designed for tamping, crumbling and soil levelling. It is especially made to improve soil-seed contact after sowing or soil-root after a frost, to avoid evaporation and erosion, to crumble soil after plowing or between two seedbed preparations.

HITCH

Fixed ring adjustable 4 positions.
Optional raised ring.



CROSSING AXLE

Square of 60 mm.

WHEELS 260/70 - 15.3 FL+

Or wheels 300/80 - 15.3 FL+ in option.

ARRAYS

1 fixed middle element and 2 side elements to better suit the land's shape.
Adjustable rollers' tightening rings.

TRANSPORT MODE

Safe. The lifters stay in place in the cradle thanks to an anchor.



ROLLPACK

Working width	5,25 m	6,25 m	7,25 m	8,25 m
Power	80 to 100 cv	90 to 110 cv	100 to 130 cv	120 to 150 cv


Roller

CAMBRIDGE Ø520 mm	Weight	2 650 kg	3 050 kg	3 500 kg	3 800 kg
CORRUGATED-CAMBRIDGE Ø520 mm	Weight	2 500 kg	2 900 kg	3 300 kg	3 600 kg
CROSSKILL Ø550 mm	Weight	2 650 kg	3 000 kg	3 500 kg	3 800 kg
CORRUGATED Ø500 mm	Weight	2 550 kg	2 850 kg	3 300 kg	3 650 kg

Options and accessories :

- Stone bins
- Hectare counter
- Wheels 300/80 - 15,3 FL+
- Wheels 13.0/55 R 16 - 14 ply
- Raised ring Ø41 (for exportation only)
- Retractable hydraulic lift
- Wheels chocks

ROLLER



CROSSING AXLE Ø70 mm

Ensuring optimum sturdiness and rolling quality.



STOPPING RING

To keep the cast iron rollers tight.



CONVEX WASHER

To avoid contact between bearings and the axle turning.



BEARING

Roller mounted on self-aligning triple sealed bearing Ø60 mm.

The type of cast iron chosen for the roller doesn't impact its assembly process.

CAST IRON ROLLERS



CAMBRIDGE Ø520 mm 5 YEARS WARRANTY

Its aggressive shape can make effective soil crumbling during seedbed preparation. With a weight of more than 500 kg per meter, it offers excellent quality tamping.


Suitable for heavy and sticky soils.



CORRUGATED-CAMBRIDGE Ø520 mm 5 YEARS WARRANTY

The alternation between Cambridge and Corrugated elements makes it highly versatile.

Suitable for work in clay land or spring tamping.



CORRUGATED Ø500 mm 5 YEARS WARRANTY

This type of wheel can make furrow in the soil, which limits soil slaking.

Suitable for post-sowing tamping and spring rolling.



CROSSKILL Ø550 mm 5 YEARS WARRANTY

This type of cast iron is perfect for light soils and seedbed preparation.



Devices with INDEPENDENT DISCS

- SKYRON fixed independent disc harrow
- SKYRON folding independent disc harrow
- SKYRON self-supporting independent disc harrow



Devices with DISCS X

- ORBYS self-supporting X combining sprayer
- ZÉNITH RGH self-supporting X combining sprayer
- ZÉNITH RZH self-supporting X combining sprayer
- ZÉNITH RJH self-supporting X combining sprayer
- PHÉNIXTGX self-supporting X sprayer
- PHÉNIXTBX self-supporting X sprayer



Devices with DISCS V

- CWH - CWHR super heavy self-supporting V Cover Crop
- SYNCHRONIC CIN self-supporting V Cover Crop
- CLH - CVH heavy self-supporting V Cover Crop
- CIH - CJH self-supporting V Cover Crop



Devices with SUPPORTED DISCS

- VITICROP mounted X sprayer
- VINIDISC mounted disc harrow
- TXL mounted X sprayer
- TRW heavy-duty mounted reversible sprayer
- CCW - CCU mounted reversible sprayer



Devices for ROLLING

- ROLLPACK self-supporting cast iron roller
- TORO - RVH self-supporting cast iron roller
- RVH EVO self-supporting steel smooth roller



Devices with TINES

- KILIS - KILIS R combined cultivator with flexible tines
- TÉOS - TÉOS R stubble cultivator with curved tines 3 rows



Devices for LOOSENING

- ARASOL AVLE supported subsoiler
- ARASOL AVS - AVR supported subsoiler
- ARAPLOW ACV supported decompactor
- ARAPLOW ACM - ACMH supported decompactor
- ARAMULCH ADM - ADMH supported decompactor
- DVV supported subsoiler for vineyard and orchards



Devices for SPRING

- BLI - BMI - BSI folding and fixed mounted cultivator