clang-format

2026.03.26

SWPP Practice Session

Seunghyeon Nam

Why Format the Code?

- Improves readability
- Minimize diffs due to minor editing
- Looks more professional ☺

clang-format

- C/C++ formatter
- Reads C++ code via stdin, prints formatted code via stdout
  - `clang-format < unformatted.cpp > formatted.cpp`
  - `clang-format -i unformatted.cpp`
- Customize formatting rules using `.clang-format` file
  - `clang-format --dump-config` will print the template config file

clang-format with vscode

- You can use vscode command `format document`
  - In case of C++ source files, clangd will be called
  - Extension will then call clang-format to format the code
- You can provide `.clang-format` file in the source directory

File Edit Selection View Go Run Terminal Help — inst.cpp - swpp-compiler - Visual Studio Code

RUN ... Debug

inst.cpp M | result.h

src > lib > backend > assembly > inst.cpp > {} `anony

```
  // remove trailing whitespace
  joined_string.pop_back();
  return joined_string;
}

using namespace sc::backend::assembly::ins

std::string getToken(const IcmpCondition
  switch (__cond) {
  case IcmpCondition::EQ:
    return "eq"s;
  case IcmpCondition::NE:
    return "ne"s;
  case IcmpCondition::UGT:
    return "ugt"s;        You, 2 months ago
  case IcmpCondition::UGE:
    return "uge"s;
  case IcmpCondition::ULT:
    return "ult"s;
  case IcmpCondition::ULE:
    return "ule"s;
  case IcmpCondition::SGT:
    return "sgt"s;
  case IcmpCondition::SGE:
    return "sge"s;
  case IcmpCondition::SLT:
    return "slt"s;
  case IcmpCondition::SLE:
    return "sle"s;
  default: // unreachable
    return ";"s;
  }
}

std::string getToken(const std::string_view __name) noexcept {
  return std::string(__name);
```

>

CMake: Build Target	Shift + F7 recently used
CMake: Debug	Ctrl + F5
Developer: Reload Window	Ctrl + R
Git: Checkout to...	
Format Document	Shift + Alt + F
CMake: Delete Cache and Reconfigure	
Git: Merge Branch...	
Git: Checkout to (Detached)...	
Git: Fetch	
Git: Pull	
Git: Create Branch...	
Git: Delete Branch...	
Git: Push	
Git: Revert Selected Ranges	Ctrl + K Ctrl + R
Git: Rebase Branch...	
Git: Rename Branch...	
Git: Rename	
Git: Pop Latest Stash	

Open the command palette (Ctrl/Cmd+Shift+P)

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS GITLENS

swpp-compiler main ±

VARIABLES

WATCH

CALL STACK

BREAKPOINTS
- C++: on throw
- C++: on catch

MODULES

SSH: main* 0 0 0 Debug (swpp-compiler) CMake: [Debug]: Ready [Clang 14.0.0 x86_64-unknown-linux-gnu] Build [all] [swpp-compiler] You, 2 months ago Ln 39, Col 19 Spaces: 2 UTF-8 LF C++ Linux

File Edit Selection View Go Run Terminal Help — inst.cpp - swpp-compiler - Visual Studio Code

RUN ... Debug

inst.cpp M | result.h

src > lib > backend > assembly > inst.cpp > {} `anonym

```
  // remove trailing whitespace
  joined_string.pop_back();
  return joined_string;
}

using namespace sc::backend::assembly::ins

std::string getToken(const IcmpCondition _
  switch (__cond) {
  case IcmpCondition::EQ:
    return "eq"s;
  case IcmpCondition::NE:
    return "ne"s;
  case IcmpCondition::UGT:
    return "ugt"s;        You, 2 months ago
  case IcmpCondition::UGE:
    return "uge"s;
  case IcmpCondition::ULT:
    return "ult"s;
  case IcmpCondition::ULE:
    return "ule"s;
  case IcmpCondition::SGT:
    return "sgt"s;
  case IcmpCondition::SGE:
    return "sge"s;
  case IcmpCondition::SLT:
    return "slt"s;
  case IcmpCondition::SLE:
    return "sle"s;
  default: // unreachable
    return ";"s;
  }
}

std::string getToken(const std::string_view __name) noexcept {
  return std::string(__name);
```

>format

- Format Document — Shift + Alt + F — recently used
- C/C++: Generate EditorConfig contents from VC Format settings — other commands
- File: Save without Formatting — Ctrl + K Ctrl + Shift + S
- Format Document With...
- Format Modified Lines
- Format Selection — Ctrl + K Ctrl + F
- LLDB: Display Format ...
- Terminal: Show Environment Information

Search for the command,
then press enter or click

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS GITLENS

swpp-compiler main ±

VARIABLES
WATCH
CALL STACK
BREAKPOINTS
- C++: on throw
- C++: on catch

MODULES

SSH: main* 0 0 0 Debug (swpp-compiler) CMake: [Debug]: Ready [Clang 14.0.0 x86_64-unknown-linux-gnu] Build [all] [swpp-compiler] You, 2 months ago Ln 39, Col 19 Spaces: 2 UTF-8 LF C++ Linux

File Edit Selection View Go Run Terminal Help — inst.cpp - swpp-compiler - Visual Studio Code

RUN ... Debug

VARIABLES

WATCH

CALL STACK

BREAKPOINTS
- C++: on throw
- C++: on catch

MODULES

inst.cpp M | result.h

src > lib > backend > assembly > inst.cpp > {} `anonym

```
  // remove trailing whitespace
  joined_string.pop_back();
  return joined_string;
}

using namespace sc::backend::assembly::ins

std::string getToken(const IcmpCondition _
  switch (__cond) {
  case IcmpCondition::EQ:
    return "eq"s;
  case IcmpCondition::NE:
    return "ne"s;
  case IcmpCondition::UGT:
    return "ugt"s;        You, 2 months ago
  case IcmpCondition::UGE:
    return "uge"s;
  case IcmpCondition::ULT:
    return "ult"s;
  case IcmpCondition::ULE:
    return "ule"s;
  case IcmpCondition::SGT:
    return "sgt"s;
  case IcmpCondition::SGE:
    return "sge"s;
  case IcmpCondition::SLT:
    return "slt"s;
  case IcmpCondition::SLE:
    return "sle"s;
  default: // unreachable
    return ";"s;
  }
}

std::string getToken(const std::string_view __name) noexcept {
  return std::string(__name);
```

>format

- Format Document — Shift + Alt + F — recently used
- C/C++: Generate EditorConfig contents from VC Format settings — other commands
- File: Save without Formatting — Ctrl + K Ctrl + Shift + S
- Format Document With...
- Format Modified Lines
- Format Selection — Ctrl + K Ctrl + F
- LLDB: Display Format ...
- Terminal: Show Environment Information

You can also use the shortcut without opening the palette

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS GITLENS

swpp-compiler main ±

SSH: main* 0 0 0 Debug (swpp-compiler) CMake: [Debug]: Ready [Clang 14.0.0 x86_64-unknown-linux-gnu] Build [all] [swpp-compiler] You, 2 months ago Ln 39, Col 19 Spaces: 2 UTF-8 LF C++ Linux