

Search operations

Form

GET {tenant}/forms

FormSubmission

GET {tenant}/submissions

Jobs

GET {tenant}/jobs/attachment/{id}

POST {tenant}/jobs/{id}/attachments

GET {tenant}/jobs/{jobId}/attachments

## Forms

API definition

### Jobs\_GetJobAttachments

Gets Attachments on the specified Job

#### Request

##### Production Environment

GET https://api.servicetitan.io/forms/v2/tenant/{tenant}/jobs/{jobId}/attachments[?createdBefore]&created0n0rAfter]&sort]&page]&pageSize]&includeTotal]

##### Integration Environment

GET https://api-integration.servicetitan.io/forms/v2/tenant/{tenant}/jobs/{jobId}/attachments[?createdBefore]&created0n0rAfter]&sort]&page]&pageSize]&includeTotal]

#### Request parameters

Name	In	Required	Type	Description
jobId	template	true	integer	Format - int64. Job Id
tenant	template	true	integer	Format - int64. Tenant ID
createdBefore	query	false	string	Format - date-time (as date-time in RFC3339).
created0n0rAfter	query	false	string	Format - date-time (as date-time in RFC3339).
sort	query	false	string	
page	query	false	integer	Format - int32.
pageSize	query	false	integer	Format - int32.
includeTotal	query	false	boolean	

#### Response: 200 OK

The request has succeeded

#### Response: 400 Bad Request

The request cannot be processed, check validation errors or request format

application/json

#### ApiErrorResponse

Detailed error response, following RFC 7807 recommendations (<https://tools.ietf.org/html/rfc7807>).

{}

Name	Required	Type	Description
type	true	string	A URI reference that identifies the problem type
title	true	string	A short, human-readable summary of the problem type
status	true	integer (int32)	The HTTP status code generated by server
traceId	true	string	Internal trace ID for advanced diagnostics
errors	true	object	Provides more details about errors occurred, which can potentially be used for visual display
data	true	object	Provides additional data, intended for programmatical usage

#### default

DEFAULT - JSON

```
{  "type": "string",  "title": "string",  "status": 0,  "traceId": "string",  "errors": {},  "data": {} }
```

Copy

#### Definitions

Name	Description
ApiErrorResponse	Detailed error response, following RFC 7807 recommendations ( <a href="https://tools.ietf.org/html/rfc7807">https://tools.ietf.org/html/rfc7807</a> ).

#### ApiErrorResponse

Detailed error response, following RFC 7807 recommendations (<https://tools.ietf.org/html/rfc7807>).

{}

Name	Required	Type	Description
type	true	string	A URI reference that identifies the problem type
title	true	string	A short, human-readable summary of the problem type
status	true	integer (int32)	The HTTP status code generated by server
traceId	true	string	Internal trace ID for advanced diagnostics
errors	true	object	Provides more details about errors occurred, which can potentially be used for visual display
data	true	object	Provides additional data, intended for programmatical usage