Search operations

Export
GET (tenant)/exports/appointments
GET (tenant)/exports/job-canceled-logs
GET (tenant)/exports/job-history
GET (tenant)/exports/job-notes
GET (tenant)/exports/jobs
GET (tenant)/exports/project-notes
GET (tenant)/exports/projects

Appointments
GET (tenant)/appointments
POST (tenant)/appointments
GET (tenant)/appointments/{id}
DEL (tenant)/appointments/{id}
DEL (tenant)/appointments/{id}/confirmation
PUT (tenant)/appointments/{id}/confirmation
DEL (tenant)/appointments/{id}/hold
PUT (tenant)/appointments/{id}/hold
PATCH (tenant)/appointments/{id}/reschedule
GET (tenant)/appointments/{id}/special-instructions

Budget Codes
GET (tenant)/work-breakdown-structure/budget-codes
POST (tenant)/work-breakdown-structure/budget-codes
POST (tenant)/work-breakdown-structure/budget-codes/batch
GET (tenant)/work-breakdown-structure/budget-codes/search?n=...
PATCH (tenant)/work-breakdown-structure/budget-codes/{id}
POST (tenant)/work-breakdown-structure/budget-codes/{id}/activa...
GET (tenant)/work-breakdown-structure/projects/{id}/budget-...
GET (tenant)/work-breakdown-structure/projects/{id}/budget-...
GET (tenant)/work-breakdown-structure/projects/{id}/budget-...
GET (tenant)/work-breakdown-structure/projects/{id}/budget-...
GET (tenant)/work-breakdown-structure/projects/{id}/budget-...
GET (tenant)/work-breakdown-structure/segments
GET (tenant)/work-breakdown-structure/segments/{segmentId}/...
GET (tenant)/work-breakdown-structure/segments/{segmentId}/...

Job Cancel Reasons
GET (tenant)/job-cancel-reasons

Job Hold Reasons
GET (tenant)/job-hold-reasons

Jobs
GET (tenant)/jobs
POST (tenant)/jobs
GET (tenant)/jobs/cancel-reasons/bb-id(s)
GET (tenant)/jobs/custom-fields
PATCH (tenant)/jobs/bb-id(s)
GET (tenant)/jobs/bb-id(s)
GET (tenant)/jobs/bb-id(s)/booked-log
PUT (tenant)/jobs/bb-id(s)/cancel
GET (tenant)/jobs/bb-id(s)/canceled-log
GET (tenant)/jobs/bb-id(s)/history
GET (tenant)/jobs/bb-id(s)/notes
POST (tenant)/jobs/bb-id(s)/notes
PUT (tenant)/jobs/bb-id(s)/remove-cancellation

Job Types
GET (tenant)/job-types
POST (tenant)/job-types
PATCH (tenant)/job-types/bb-id(s)
GET (tenant)/job-types/bb-id(s)

Projects
GET (tenant)/projects
POST (tenant)/projects
GET (tenant)/projects/custom-fields
POST (tenant)/projects/detach-job/jobId(s)
PATCH (tenant)/projects/bb-id(s)
GET (tenant)/projects/bb-id(s)
POST (tenant)/projects/bb/attach-job/jobId(s)
GET (tenant)/projects/bb/notes
POST (tenant)/projects/bb/notes

Project Statuses
GET (tenant)/project-statuses
GET (tenant)/project-statuses/bb-id(s)

Project Substatuses
GET (tenant)/project-substatuses
GET (tenant)/project-substatuses/bb-id(s)

Project Types
GET (tenant)/project-types
GET (tenant)/project-types/bb-id(s)

Job Planning and Management

API definition

Appointments_Reschedule

Reschedule job appointment

Request

Production Environment

```
PATCH https://api.servicetitan.io/jpm/v2/tenant/{tenant}/appointments/{id}/reschedule
```

Integration Environment

```
PATCH https://api-integration.servicetitan.io/jpm/v2/tenant/{tenant}/appointments/{id}/reschedule
```

Request parameters

Name	In	Required	Type	Description
id	template	true	integer	
tenant	template	true	integer	Tenant ID

Request body

application/json

{ }

Name	Required	Type	Description
start	false	string (date-time)	New start date/time (in UTC) for appointment
end	false	string (date-time)	New end date/time (in UTC) for appointment
arrivalWindowStart	false	string (date-time)	New arrival window start date/time (in UTC) for appointment, if configured
arrivalWindowEnd	false	string (date-time)	New arrival window end date/time (in UTC) for appointment, if configured

default

DEFAULT JSON

```
{
  "type": "string",
  "title": "string",
  "status": 0,
  "arrivalWindowStart": "string",
  "arrivalWindowEnd": "string"
}
```

Response: 200 OK

The request has succeeded

application/json

Jpm.V2.AppointmentResponse

Appointment response model

{ }

Name	Required	Type	Description
id	true	integer (int64)	Appointment ID
jobId	true	integer (int64)	ID of the job that the appointment was created for
appointmentNumber	false	string	Appointment number
start	true	string (date-time)	Appointment's start date/time (in UTC)
end	true	string (date-time)	Appointment's end date/time (in UTC)
arrivalWindowStart	false	string (date-time)	Arrival window start date/time (in UTC), if configured
arrivalWindowEnd	false	string (date-time)	Arrival window end date/time (in UTC), if configured
status	true	One of: Jpm.V2.Base.AppointmentStatus	Appointment's status
specialInstructions	false	string (multiline)	Special instructions associated to the appointment
createdOn	true	string (date-time)	When the appointment was created (in UTC)
modifiedOn	true	string (date-time)	When the appointment was modified (in UTC)
customerId	true	integer (int64)	Id of a customer that the appointment was created for
unused	true	boolean	Returns true if the appointment is unused
createdById	true	integer (int64)	ID of the user that created the appointment
isConfirmed	true	boolean	Returns true if the appointment is confirmed

default

DEFAULT JSON

```
{
  "id": 0,
  "jobId": 0,
  "appointmentNumber": "string",
  "start": "string",
  "end": "string",
  "arrivalWindowStart": "string",
  "arrivalWindowEnd": "string",
  "status": 1,
  "specialInstructions": "string",
  "createdOn": "string",
  "modifiedOn": "string",
  "customerId": 0,
  "unused": true,
  "createdById": 0,
  "isConfirmed": true
}
```

Response: 400 Bad Request

The request cannot be processed, check validation errors or request format

application/json

ApiErrorResponse

Detailed error response, following RFC 7807 recommendations (https://tools.ietf.org/html/rfc7807).

{ }

Name	Required	Type	Description
type	true	string	A URI reference that identifies the problem type
title	true	string	A short, human-readable summary of the problem type
status	true	integer (int32)	The HTTP status code generated by server
traceId	true	string	Internal trace ID for advanced diagnostics
errors	true	object	Provides more details about errors occurred, which can potentially be used for visual display
data	true	object	Provides additional data, intended for programmatical usage

default

DEFAULT JSON

```
{
  "type": "string",
  "title": "string",
  "status": 0,
  "traceId": "string",
  "errors": {},
  "data": {}
}
```

Response: 404 Not Found

Job appointment was not found

application/json

ApiErrorResponse

Detailed error response, following RFC 7807 recommendations (https://tools.ietf.org/html/rfc7807).

{ }

Name	Required	Type	Description
type	true	string	A URI reference that identifies the problem type
title	true	string	A short, human-readable summary of the problem type
status	true	integer (int32)	The HTTP status code generated by server
traceId	true	string	Internal trace ID for advanced diagnostics
errors	true	object	Provides more details about errors occurred, which can potentially be used for visual display
data	true	object	Provides additional data, intended for programmatical usage

default

DEFAULT JSON

```
{
  "type": "string",
  "title": "string",
  "status": 0,
  "traceId": "string",
  "errors": {},
  "data": {}
}
```

Response: 409 Conflict

Some conflict occurred while executing the request

application/json

ApiErrorResponse

Detailed error response, following RFC 7807 recommendations (https://tools.ietf.org/html/rfc7807).

{ }

Name	Required	Type	Description
type	true	string	A URI reference that identifies the problem type
title	true	string	A short, human-readable summary of the problem type
status	true	integer (int32)	The HTTP status code generated by server
traceId	true	string	Internal trace ID for advanced diagnostics
errors	true	object	Provides more details about errors occurred, which can potentially be used for visual display
data	true	object	Provides additional data, intended for programmatical usage

default

DEFAULT JSON

```
{
  "type": "string",
  "title": "string",
  "status": 0,
  "traceId": "string",
  "errors": {},
  "data": {}
}
```

Definitions

Name	Description
Jpm.V2.AppointmentResponse	Appointment response model
Jpm.V2.Base.AppointmentStatus	Indicates the status of a job Appointment.
ApiErrorResponse	Detailed error response, following RFC 7807 recommendations (https://tools.ietf.org/html/rfc7807).
Jpm.V2.AppointmentRescheduleRequest	

Jpm.V2.AppointmentResponse

Appointment response model

{ }

Name	Required	Type	Description
id	true	integer (int64)	Appointment ID
jobId	true	integer (int64)	ID of the job that the appointment was created for
appointmentNumber	false	string	Appointment number
start	true	string (date-time)	Appointment's start date/time (in UTC)
end	true	string (date-time)	Appointment's end date/time (in UTC)
arrivalWindowStart	false	string (date-time)	Arrival window start date/time (in UTC), if configured
arrivalWindowEnd	false	string (date-time)	Arrival window end date/time (in UTC), if configured
status	true	One of: Jpm.V2.Base.AppointmentStatus	Appointment's status
specialInstructions	false	string (multiline)	Special instructions associated to the appointment
createdOn	true	string (date-time)	When the appointment was created (in UTC)
modifiedOn	true	string (date-time)	When the appointment was modified (in UTC)
customerId	true	integer (int64)	Id of a customer that the appointment was created for
unused	true	boolean	Returns true if the appointment is unused
createdById	true	integer (int64)	ID of the user that created the appointment
isConfirmed	true	boolean	Returns true if the appointment is confirmed

Jpm.V2.Base.AppointmentStatus

Indicates the status of a job Appointment.

{ }

Type	Values
string	Scheduled,Dispatched,Working,Hold,Done,Canceled

ApiErrorResponse

Detailed error response, following RFC 7807 recommendations (https://tools.ietf.org/html/rfc7807).

{ }

Name	Required	Type	Description
type	true	string	A URI reference that identifies the problem type
title	true	string	A short, human-readable summary of the problem type
status	true	integer (int32)	The HTTP status code generated by server
traceId	true	string	Internal trace ID for advanced diagnostics
errors	true	object	Provides more details about errors occurred, which can potentially be used for visual display
data	true	object	Provides additional data, intended for programmatical usage

Jpm.V2.AppointmentRescheduleRequest

{ }

Name	Required	Type	Description
start	false	string (date-time)	New start date/time (in UTC) for appointment
end	false	string (date-time)	New end date/time (in UTC) for appointment
arrivalWindowStart	false	string (date-time)	New arrival window start date/time (in UTC) for appointment, if configured
arrivalWindowEnd	false	string (date-time)	New arrival window end date/time (in UTC) for appointment, if configured