Search operations...

Tenant
- GET Get a tenant by id
- GET Get a tenant by id in a collection
- GET Get a tenant by id in a collection by a parent id
- GET Get a tenant by id in a parent id
- GET Get a tenant by id in a parent id in a collection
- GET Get a tenant by id in a parent id in a collection in a parent id

Accounting Integration
- GET Get a Accounting provider mapping
- PATCH Update a Accounting provider mapping
- PUT Create or update a Accounting provider mapping

Accounting Integration Log
- GET Get a Accounting provider log
- PATCH Update a Accounting provider log
- PUT Create or update a Accounting provider log

Accounting
- PATCH Update a Accounting id
- PUT Create or update a Accounting id

Accounting Customers
- GET Get a Accounting customer id
- PATCH Update a Accounting customer id
- PUT Create or update a Accounting customer id

Accounting Customers Mapping
- GET Get a Accounting customer id mapping
- PATCH Update a Accounting customer id mapping
- PUT Create or update a Accounting customer id mapping

Accounting Customers Mapping Log
- GET Get a Accounting customer id mapping log

Accounting Customers Log
- GET Get a Accounting customer id log

Accounting Log
- GET Get a Accounting id log

Accounting Mapping
- GET Get a Accounting id mapping
- PATCH Update a Accounting id mapping
- PUT Create or update a Accounting id mapping

Accounting Mapping Log
- GET Get a Accounting id mapping log

Customers
- GET Get a Customers
- PATCH Update a Customers
- PUT Create or update a Customers
- PATCH Update a Customers Custom Fields
- PUT Create or update a Customers Custom Fields
- PATCH Update a Customers id
- PUT Create or update a Customers id
- PATCH Update a Customers id Contacts
- PUT Create or update a Customers id Contacts
- PATCH Update a Customers id Contacts id
- PUT Create or update a Customers id Contacts id
- PATCH Update a Customers id Contacts id Contacts Log
- PUT Create or update a Customers id Contacts id Contacts Log
- GET Get a Customers id Contacts id Log
- GET Get a Customers id Contacts Log
- GET Get a Customers id Log
- GET Get a Customers id Notes
- PATCH Update a Customers id Notes id
- PUT Create or update a Customers id Notes id
- GET Get a Customers id Notes id Log
- GET Get a Customers Log

Locations
- GET Get a Locations
- PATCH Update a Locations
- PUT Create or update a Locations
- PATCH Update a Locations Custom Fields
- PUT Create or update a Locations Custom Fields
- PATCH Update a Locations id
- PUT Create or update a Locations id
- GET Get a Locations id Log
- GET Get a Locations Log

Events
- GET Get a Events
- PATCH Update a Events
- PUT Create or update a Events
- GET Get a Events Feed
- PATCH Update a Events id
- PUT Create or update a Events id
- GET Get a Events id Log
- GET Get a Events Log

Geolocation
- POST Geocode Locations
- GET Get a Geolocation Source
- PATCH Update a Geolocation Source
- PUT Create or update a Geolocation Source
- GET Get a Geolocation Source Log
- GET Get a Geolocation Verification
- PATCH Update a Geolocation Verification
- PUT Create or update a Geolocation Verification
- GET Get a Geolocation Verification Log
- POST Get a Geolocation Verification by Coordinates
- POST Get a Geolocation Verification by Coordinates Log
- POST Get a Geolocation Verification by Id
- POST Get a Geolocation Verification by Id Log
- POST Get a Geolocation Verification by Id and Coordinates
- POST Get a Geolocation Verification by Id and Coordinates Log

Jobs
- GET Get a Jobs
- PATCH Update a Jobs
- PUT Create or update a Jobs
- GET Get a Jobs Log

CRM

GET /crm/v2/tenant/{...}/...

Locations_Create

Creates a new location.

Request

Production Environment

`POST https://api.servicetitan.io/crm/v2/tenant/{tenant}/locations`

Sandbox Environment

`POST https://capi-integration.servicetitan.io/crm/v2/tenant/{tenant}/locations`

Request parameters

Name	In	Required	Type	Description
tenant	template	true	integer	Tenant ID

Request body

application/json

Crm.V2.Locations.CreateLocationRequest

{ }

Name	Required	Type	Description
name	true	string	Name of the location
address	true	One of: Crm.Shared.v2.CustomerAddress	Address of the location record
contacts	false	One of: Crm.V2.Locations.LocationContact[]	Contacts for the location
customFields	false	Crm.V2.Customers.CustomFieldModel[]	Location record's custom fields
tagTypeIds	false	integer[]	Tag type ids for the location
externalData	false	One of: Crm.V2.ExternalData.ExternalRequest	External reference records of external data items that should be attached to this location
coordinateSource	false	One of: GeolocationCoordinateSource	Sets or sets the verification status of the coordinates
coordinateVerification	false	One of: GeolocationVerificationStatus	Sets or sets the verification status of the coordinates
customerId	true	integer (Int64)	ID of the location's customer

default

application/json

Copy

```
{
  "type": "string",
  "detail": {
    "errors": {
      "property1": "string",
      "property2": "string"
    },
    "traceId": "string",
    "status": 0,
    "title": "string",
    "instance": "string"
  }
}
```

Response: 200 OK

The request has succeeded

application/json

Crm.V2.Locations.CreateLocationResponse

{ }

Name	Required	Type	Description
successful	true	boolean	All of the location has come
id	true	integer (Int64)	ID of the location
customerId	true	integer (Int64)	ID of the location's customer
active	true	boolean	If false, the record has been deactivated.
name	true	string	Name of the location
address	true	One of: Crm.Shared.v2.CustomerAddress	Location's address
customFields	true	Crm.V2.Customers.CustomFieldModel[]	Location record's custom fields
createdOn	true	string (date-time)	Date/Time (UTC) that location record was created
createdBy	true	integer (Int64)	User ID who created the record
modifiedOn	true	string (date-time)	Modified On (UTC) for the record
mergedTo0	false	integer (Int64)	Tells you which location record the record was merged into.
zoneId	false	integer (Int64)	ID of the location's Zone
taxExempt	true	boolean	Tax Exempt status of the location
tagTypeIds	true	integer[]	Tag Type IDs of the location
externalData	true	One of: Crm.V2.ExternalData.ExternalD	List of external data attached to this location, which corresponds to the external data records passed in the request.
contacts	true	Crm.V2.LocationContact.LocationContact[]	

default

application/json

Copy

```
{
  "successful": 0,
  "id": 0,
  "customerId": 0,
  "active": true,
  "name": "string",
  "address": {
    "street": "string",
    "unit": "string",
    "city": "string",
    "state": "string",
    "zip": "string",
    "country": "string",
    "latitude": 0,
    "longitude": 0
  },
  "customFields": [
    {
      "typeId": 0,
      "name": "string",
      "value": "string"
    }
    ...
  ],
  "createdOn": "2022-01-01T00:00:00.0000000Z",
  "createdBy": 0,
  "modifiedOn": "2022-01-01T00:00:00.0000000Z",
  "mergedTo0": 0,
  "zoneId": 0,
  "taxExempt": true,
  "tagTypeIds": [
    0
    ...
  ],
  "externalData": [
    {
      "key": "string",
      "value": "string"
    }
    ...
  ],
  "contacts": [
    {
      "id": 0,
      "customerId": 0,
      "type": "string",
      "value": "string",
      "memo": "string",
      "phoneSettings": {
        "phoneNumber": "string",
        "doNotText": true,
        "doNotCall": true
      },
      "modifiedOn": "2022-01-01T00:00:00.0000000Z",
      "active": true
    }
    ...
  ]
}
```

Response: 400 Bad Request

The request cannot be processed, check validation errors or request format

application/json

ApiErrorResponse

Standard error response, following RFC 7807 recommendations (https://tools.ietf.org/html/rfc7807).

{ }

Name	Required	Type	Description
type	true	string	A URI reference that identifies the problem type
title	true	string	A short, human-readable summary of the problem type
status	true	integer (Int32)	The HTTP status code generated by server
traceId	true	string	Internal trace ID for advanced diagnostics
errors	true	object	Provides more details about errors occurred, which can potentially be used for visual display
data	true	object	Provides additional data, intended for programmatical usage

default

application/json

Copy

```
{
  "type": "string",
  "title": "string",
  "status": 0,
  "traceId": "string",
  "errors": {
    "property1": "string",
    "property2": "string"
  },
  "data": {
    "property1": "string",
    "property2": "string"
  }
}
```

Response: 409 Conflict

Unknown customer

application/json

ApiErrorResponse

Standard error response, following RFC 7807 recommendations (https://tools.ietf.org/html/rfc7807).

{ }

Name	Required	Type	Description
type	true	string	A URI reference that identifies the problem type
title	true	string	A short, human-readable summary of the problem type
status	true	integer (Int32)	The HTTP status code generated by server
traceId	true	string	Internal trace ID for advanced diagnostics
errors	true	object	Provides more details about errors occurred, which can potentially be used for visual display
data	true	object	Provides additional data, intended for programmatical usage

default

application/json

Copy

```
{
  "type": "string",
  "title": "string",
  "status": 0,
  "traceId": "string",
  "errors": {
    "property1": "string",
    "property2": "string"
  },
  "data": {
    "property1": "string",
    "property2": "string"
  }
}
```

Definitions

Name	Description
ApiErrorResponse	Standard error response, following RFC 7807 recommendations (https://tools.ietf.org/html/rfc7807).
Crm.V2.ContactType	
Crm.V2.Customers.LocationAddress	
Crm.V2.Customers.CustomFieldModel	
Crm.V2.ExternalDataModel	
Crm.V2.Locations.CreateLocationResponse	
Crm.V2.Locations.LocationContact	
Crm.V2.Locations.NewCustomerContact	
Crm.V2.Locations.CustomFieldUpdateModel	
Crm.V2.ExternalDataCreateRequest	
GeolocationCoordinateSource	Specifies the source of geolocation coordinates.
GeolocationVerificationStatus	Represents the status of geolocation verification for a set of coordinates.
Crm.V2.Locations.CreateLocationRequest	

ApiErrorResponse

Standard error response, following RFC 7807 recommendations (https://tools.ietf.org/html/rfc7807).

{ }

Name	Required	Type	Description
type	true	string	A URI reference that identifies the problem type
title	true	string	A short, human-readable summary of the problem type
status	true	integer (Int32)	The HTTP status code generated by server
traceId	true	string	Internal trace ID for advanced diagnostics
errors	true	object	Provides more details about errors occurred, which can potentially be used for visual display
data	true	object	Provides additional data, intended for programmatical usage

Crm.V2.ContactType

{ }

Type	Values
string	Phone, Phone - Work 1, Fax, Mobile Cell Phone

Crm.V2.Customers.LocationAddress

{ }

Name	Required	Type	Description
street	true	string	Street
unit	false	string	Unit
city	true	string	City
state	true	string	State
zip	true	string	Zip
country	true	string	Country
latitude	false	nullable<double>	Latitude
longitude	false	nullable<double>	Longitude

Crm.V2.Customers.CustomFieldModel

{ }

Name	Required	Type	Description
typeId	true	integer (Int64)	ID of the custom field
name	false	string	Name/label of the custom field
value	false	string	Value of the custom field

Crm.V2.ExternalDataModel

{ }

Name	Required	Type	Description
key	true	string	External data key
value	true	string	External data value

Crm.V2.Locations.CreateLocationResponse

{ }

Name	Required	Type	Description
successful	true	boolean	All of the location has come
id	true	integer (Int64)	ID of the location
customerId	true	integer (Int64)	ID of the location's customer
active	true	boolean	If false, the record has been deactivated.
name	true	string	Name of the location
address	true	One of: Crm.Shared.v2.CustomerAddress	Location's address
customFields	true	Crm.V2.Customers.CustomFieldModel[]	Location record's custom fields
createdOn	true	string (date-time)	Date/Time (UTC) that location record was created
createdBy	true	integer (Int64)	User ID who created the record
modifiedOn	true	string (date-time)	Modified On (UTC) for the record
mergedTo0	false	integer (Int64)	Tells you which location record the record was merged into.
zoneId	false	integer (Int64)	ID of the location's Zone
taxExempt	true	boolean	Tax Exempt status of the location
tagTypeIds	true	integer[]	Tag Type IDs of the location
externalData	true	One of: Crm.V2.ExternalData.ExternalD	List of external data attached to this location, which corresponds to the external data records passed in the request.
contacts	true	Crm.V2.LocationContact.LocationContact[]	

Crm.V2.Locations.LocationContact

{ }

Name	Required	Type	Description
id	true	integer (Int64)	ID of the contact
type	true	One of: Crm.V2.ContactType	Landline, mobile, e-mail, or fax.
value	true	string	The email, phone number, or fax number for the contact.
memo	false	string	Short description about the contact, for example, "work id" or "Tatum's daughter nicky."

Crm.V2.Customers.NewCustomerContact

{ }

Name	Required	Type	Description
type	true	One of: Crm.V2.ContactType	Landline, mobile, e-mail, or fax.
value	true	string	The email, phone number, or fax number for the contact.
memo	false	string	Short description about the contact, for example, "work id" or "Tatum's daughter nicky."

Crm.V2.Customers.CustomFieldUpdateModel

{ }

Name	Required	Type	Description
typeId	true	integer (Int64)	ID of the custom field
value	true	string	Value of the custom field

Crm.V2.ExternalDataCreateRequest

{ }

Name	Required	Type	Description
applicationGuid	true	string (guid)	Same GUID as in created with a specific grant, could be "00000000-0000-0000-0000-000000000000" for cases when system grant is provided
externalData	true	Crm.V2.ExternalData.ExternalRequest	External data key

GeolocationCoordinateSource

Specifies the source of geolocation coordinates.

{ }

Type	Values
string	Basic, Tsunami, Esri, DeepMind

GeolocationVerificationStatus

Represents the status of geolocation verification for a set of coordinates.

{ }

Type	Values
string	GreenFlight, RedFlagNoMatch, PartialMatch, NotFlagged

Crm.V2.Locations.CreateLocationRequest

{ }

Name	Required	Type	Description
name	true	string	Name of the location
address	true	One of: Crm.Shared.v2.CustomerAddress	Address of the location record
contacts	false	One of: Crm.V2.Locations.LocationContact[]	Contacts for the location
customFields	false	Crm.V2.Customers.CustomFieldModel[]	Location record's custom fields
tagTypeIds	false	integer[]	Tag type ids for the location
externalData	false	One of: Crm.V2.ExternalData.ExternalRequest	External reference records of external data items that should be attached to this location
coordinateSource	false	One of: GeolocationCoordinateSource	Sets or sets the source of the coordinates
coordinateVerification	false	One of: GeolocationVerificationStatus	Sets or sets the verification status of the coordinates
customerId	true	integer (Int64)	ID of the location's customer