



Artificial Neural Networks

Machine Learning and Pattern Recognition

Prof. Sandra Avila

Institute of Computing (IC/Unicamp)

MC886/MO444, September 15, 2017

**What does an
artificial neuron do?**



It calculates a “weighted sum” of its input, adds a bias and then decides whether it should be “fired” or not.

**How do we decide whether
the neuron should fire or not?**

We decided to add “activation functions” for this purpose.

Step Function

Its output is **1 (activated)** when value > 0 (threshold) and outputs a **0 (not activated)** otherwise.



Step Function: **Problem?**

Step Function: **Problem?**


- Binary classifier (“yes” or “no”, activate or not activate). A Step function could do that for you!

Step Function: **Problem?**

- Binary classifier (“yes” or “no”, activate or not activate). A Step function could do that for you!
- Multi classifier (class1, class2, class3, etc). What will happen if more than 1 neuron is “activated”?

Sigmoid Function

- The output of the activation function is always going to be in range **(0,1)**.
- It is nonlinear in nature.
- Combinations of this function are also nonlinear! Great!!



$$\sigma(x) = \frac{1}{1+e^{-x}}$$

Sigmoid Function: **Problem?**

Sigmoid Function: Problem?


- Towards either end of the sigmoid function, the $\sigma(x)$ values tend to respond very less to changes in x .

Sigmoid Function: Problem?

- Towards either end of the sigmoid function, the $\sigma(x)$ values tend to respond very less to changes in x .
- The problem of “vanishing gradients”.
 - Cannot make significant change because of the extremely small value.

Tanh Function

- The output of the activation function is always going to be in range **$(-1,1)$** .
- It is nonlinear in nature.
- Combinations of this function are also nonlinear! Great!!




$$\tanh(x) = \frac{2}{1+e^{-2x}} - 1$$

Tanh Function: **Problem?**

- Like sigmoid, tanh also has the vanishing gradient problem.

ReLU Function

- It gives an output x if x is positive and 0 otherwise. The range is **[0, inf)**.
- It is nonlinear in nature. Combinations of this function are also nonlinear!
- Sparsity of the activation!



$$\text{ReLU}(x) = \max(0, x)$$


ReLU Function: **Problem?**

ReLU Function: Problem?

- Because of the horizontal line in ReLU(for negative x), the gradient can go towards 0.
- “Dying ReLU problem”: several neurons can just die and not respond making a substantial part of the network passive.

Leaky ReLU Function

- It gives an output x if x is positive and 0 otherwise. The range is $[0, \infty)$.
- (Leaky) ReLU is less computationally expensive than *tanh* and *sigmoid* because it involves simpler mathematical operations.



$$\begin{aligned}\text{Leaky ReLU}(x) &= \\ &= \begin{cases} x & \text{if } x > 0 \\ 0.01x & \text{otherwise} \end{cases}\end{aligned}$$

Ok! Which One Do We Use?

Ok! Which One Do We Use?


- If you don't know the nature of the function you are trying to learn, start with ReLU.

Ok! Which One Do We Use?


- If you don't know the nature of the function you are trying to learn, start with ReLU.
- You can use your own custom functions too!

Neural Network Representation


Neural Network



$a_i^{(j)}$ “activation” of unit i in layer j
 $\Theta^{(j)}$ matrix of weights controlling function mapping from layer j to layer $j + 1$




$a_i^{(j)}$ “activation” of unit i in layer j
 $\Theta^{(j)}$ matrix of weights controlling
function mapping from layer j
to layer $j + 1$



$a_i^{(j)}$ “activation” of unit i in layer j
 $\Theta^{(j)}$ matrix of weights controlling
 function mapping from layer j
 to layer $j + 1$

$$a_1^{(2)} = g(\Theta_{10}^{(1)}x_0 + \Theta_{11}^{(1)}x_1 + \Theta_{12}^{(1)}x_2 + \Theta_{13}^{(1)}x_3)$$




$a_i^{(j)}$ “activation” of unit i in layer j

$\Theta^{(j)}$ matrix of weights controlling function mapping from layer j to layer $j + 1$

$$a_1^{(2)} = g(\Theta_{10}^{(1)}x_0 + \Theta_{11}^{(1)}x_1 + \Theta_{12}^{(1)}x_2 + \Theta_{13}^{(1)}x_3)$$

$$a_2^{(2)} = g(\Theta_{20}^{(1)}x_0 + \Theta_{21}^{(1)}x_1 + \Theta_{22}^{(1)}x_2 + \Theta_{23}^{(1)}x_3)$$




$a_i^{(j)}$ “activation” of unit i in layer j

$\Theta^{(j)}$ matrix of weights controlling function mapping from layer j to layer $j + 1$

$$a_1^{(2)} = g(\Theta_{10}^{(1)}x_0 + \Theta_{11}^{(1)}x_1 + \Theta_{12}^{(1)}x_2 + \Theta_{13}^{(1)}x_3)$$

$$a_2^{(2)} = g(\Theta_{20}^{(1)}x_0 + \Theta_{21}^{(1)}x_1 + \Theta_{22}^{(1)}x_2 + \Theta_{23}^{(1)}x_3)$$

$$a_3^{(2)} = g(\Theta_{30}^{(1)}x_0 + \Theta_{31}^{(1)}x_1 + \Theta_{32}^{(1)}x_2 + \Theta_{33}^{(1)}x_3)$$



$a_i^{(j)}$ “activation” of unit i in layer j


$\Theta^{(j)}$ matrix of weights controlling function mapping from layer j to layer $j + 1$

$$a_1^{(2)} = g(\Theta_{10}^{(1)}x_0 + \Theta_{11}^{(1)}x_1 + \Theta_{12}^{(1)}x_2 + \Theta_{13}^{(1)}x_3)$$

$$a_2^{(2)} = g(\Theta_{20}^{(1)}x_0 + \Theta_{21}^{(1)}x_1 + \Theta_{22}^{(1)}x_2 + \Theta_{23}^{(1)}x_3)$$

$$a_3^{(2)} = g(\Theta_{30}^{(1)}x_0 + \Theta_{31}^{(1)}x_1 + \Theta_{32}^{(1)}x_2 + \Theta_{33}^{(1)}x_3)$$


$$h_\Theta(x) = a_1^{(3)} = g(\Theta_{10}^{(2)}a_0^{(2)} + \Theta_{11}^{(2)}a_1^{(2)} + \Theta_{12}^{(2)}a_2^{(2)} + \Theta_{13}^{(2)}a_3^{(2)})$$



$a_i^{(j)}$ “activation” of unit i in layer j
 $\Theta^{(j)}$ matrix of weights controlling
 function mapping from layer j
 to layer $j + 1$

Feedforward Neural Network (forward propagating)


$$h_{\Theta}(x) = a_1^{(3)} = g(\Theta_{10}^{(2)}a_0^{(2)} + \Theta_{11}^{(2)}a_1^{(2)} + \Theta_{12}^{(2)}a_2^{(2)} + \Theta_{13}^{(2)}a_3^{(2)})$$



$a_i^{(j)}$ “activation” of unit i in layer j
 $\Theta^{(j)}$ matrix of weights controlling
 function mapping from layer j
 to layer $j + 1$


If network has s_j units in layer j , s_{j+1} units in layer $j+1$,
 then $\Theta^{(j)}$ will be of dimension $s_{j+1} \times (s_j + 1)$.

Other Network Architectures




Neural Network Zoo

<http://www.asimovinstitute.org/neural-network-zoo/>




Neural Network Intuition







Layer 1



Layer 2



Layer 3



<http://yosinski.com/deepvis>


<https://youtu.be/AgkflQ4lGaM>




Neural Network Intuition

Toy 2d classification with 2-layer neural network


<http://cs.stanford.edu/people/karpathy/convnetjs/demo/classify2d.html>



3 hidden neurons



6 hidden neurons



20 hidden neurons

Multi-class Classification



Cat




Dog



Frog



Car





Cat




Dog



Frog



Car



Want $h_{\Theta}(x) \approx \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$, when cat


$h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$, when dog

$h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$, when frog

$h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}$, when car



Softmax Classification

The **output layer** is typically modified by replacing the individual activation functions by a **shared softmax** function.




Softmax Classification

The **output layer** is typically modified **by replacing** the individual activation functions **by a shared softmax** function.




Softmax Classification

The **output layer** is typically modified by replacing the individual activation functions **by a shared softmax** function.



$$f(\mathbf{z})_k = \frac{e^{z_k}}{\sum_{j=1}^K e^{z_j}}$$

Softmax Classification




$$f(\mathbf{z})_k = \frac{e^{z_k}}{\sum_{j=1}^K e^{z_j}}$$

Softmax Classification




Cat	5.1
Dog	3.2
Frog	-1.7
Car	-2.0



$$f(\mathbf{z})_k = \frac{e^{z_k}}{\sum_{j=1}^K e^{z_j}}$$


Softmax Classification



Cat	5.1		164.0
Dog	3.2	➡	24.5
Frog	-1.7		0.18
Car	-2.0		0.13

$$f(\mathbf{z})_k = \frac{e^{z_k}}{\sum_{j=1}^K e^{z_j}}$$

Softmax Classification



Cat	5.1	164.0	0.87
Dog	3.2	24.5	0.13
Frog	-1.7	0.18	0.00
Car	-2.0	0.13	0.00

$$f(\mathbf{z})_k = \frac{e^{z_k}}{\sum_{j=1}^K e^{z_j}}$$

Cost Function

Cost Function

Let's first define a few variables that we will need to use:

- L = total number of **layers** in the network
- s_l = number of **units** (not counting bias unit) in layer l
- K = number of **output** units/classes

Cost Function

Let's first define a few variables that we will need to use:

- L = total number of **layers** in the network
- s_l = number of **units** (not counting bias unit) in layer l
- K = number of **output** units/classes

Our cost function for neural networks is going to be a generalization of the one we used for **logistic regression**.

Logistic Regression:

$$J(\theta) = -\frac{1}{m} \left[\sum_{i=1}^m y^{(i)} \log h_{\theta}(x^{(i)}) + (1-y^{(i)}) \log(1-h_{\theta}(x^{(i)})) \right]$$

Logistic Regression:

$$J(\theta) = -\frac{1}{m} \left[\sum_{i=1}^m y^{(i)} \log h_{\theta}(x^{(i)}) + (1-y^{(i)}) \log(1-h_{\theta}(x^{(i)})) \right]$$

Neural Network: $h_{\Theta}(x) \in \mathbb{R}^K$ $(h_{\Theta}(x))_i = i^{th}$ output

$$J(\Theta) = -\frac{1}{m} \left[\sum_{i=1}^m \sum_{k=1}^K y_k^{(i)} \log(h_{\Theta}(x^{(i)}))_k + (1-y_k^{(i)}) \log(1-(h_{\Theta}(x^{(i)}))_k) \right]$$

Logistic Regression:

$$J(\theta) = -\frac{1}{m} \left[\sum_{i=1}^m y^{(i)} \log h_{\theta}(x^{(i)}) + (1-y^{(i)}) \log(1-h_{\theta}(x^{(i)})) \right] + \frac{\lambda}{2m} \sum_{j=1}^n \theta^2$$

Neural Network: $h_{\Theta}(x) \in \mathbb{R}^K$ $(h_{\Theta}(x))_i = i^{th}$ output

$$J(\Theta) = -\frac{1}{m} \left[\sum_{i=1}^m \sum_{k=1}^K y_k^{(i)} \log(h_{\Theta}(x^{(i)}))_k + (1-y_k^{(i)}) \log(1-(h_{\Theta}(x^{(i)}))_k) \right] \\ + \frac{\lambda}{2m} \sum_{l=1}^{L-1} \sum_{i=1}^{s_l} \sum_{j=1}^{s_{l+1}} (\Theta_{ji}^{(l)})^2$$

Backpropagation

A Simple Example

Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$

$$\text{e.g., } x = -2, y = 5, z = -4$$

Backpropagation: A Simple Example

$$f(x, y, z) = (x + y)z$$

e.g., $x = -2$, $y = 5$, $z = -4$



Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$

e.g., $x = -2$, $y = 5$, $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1 \quad \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z \quad \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}$, $\frac{\partial f}{\partial y}$, $\frac{\partial f}{\partial z}$



Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$

e.g., $x = -2$, $y = 5$, $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1 \quad \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z \quad \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}$, $\frac{\partial f}{\partial y}$, $\frac{\partial f}{\partial z}$



Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$

e.g., $x = -2$, $y = 5$, $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1 \quad \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z \quad \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}$, $\frac{\partial f}{\partial y}$, $\frac{\partial f}{\partial z}$



Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$

e.g., $x = -2$, $y = 5$, $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1 \quad \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z \quad \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}$, $\frac{\partial f}{\partial y}$, $\frac{\partial f}{\partial z}$



Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$

e.g., $x = -2$, $y = 5$, $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1 \quad \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z \quad \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}$, $\frac{\partial f}{\partial y}$, $\frac{\partial f}{\partial z}$



Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$

e.g., $x = -2$, $y = 5$, $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1 \quad \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z \quad \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}$, $\frac{\partial f}{\partial y}$, $\frac{\partial f}{\partial z}$



Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$

e.g., $x = -2$, $y = 5$, $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1 \quad \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z \quad \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}$, $\frac{\partial f}{\partial y}$, $\frac{\partial f}{\partial z}$



Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$

e.g., $x = -2$, $y = 5$, $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1 \quad \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z \quad \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}$, $\frac{\partial f}{\partial y}$, $\frac{\partial f}{\partial z}$



Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$

$$\text{e.g., } x = -2, y = 5, z = -4$$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1 \quad \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z \quad \frac{\partial f}{\partial z} = q$$

$$\text{Want: } \frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$$



Chain rule

$$\frac{\partial f}{\partial y} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial y}$$

Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$

$$\text{e.g., } x = -2, y = 5, z = -4$$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1 \quad \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z \quad \frac{\partial f}{\partial z} = q$$

$$\text{Want: } \frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$$



Chain rule

$$\frac{\partial f}{\partial y} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial y}$$

Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$

$$\text{e.g., } x = -2, y = 5, z = -4$$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1 \quad \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z \quad \frac{\partial f}{\partial z} = q$$

$$\text{Want: } \frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$$



Backpropagation: A Simple Example


$$f(x, y, z) = (x + y)z$$


e.g., $x = -2$, $y = 5$, $z = -4$


$$q = x + y \quad \frac{\partial q}{\partial x} = 1 \quad \frac{\partial q}{\partial y} = 1$$


$$f = qz \quad \frac{\partial f}{\partial q} = z \quad \frac{\partial f}{\partial z} = q$$


Want: $\frac{\partial f}{\partial x}$, $\frac{\partial f}{\partial y}$, $\frac{\partial f}{\partial z}$

















To be continued ...

References

— — —

Machine Learning Books

- Hands-On Machine Learning with Scikit-Learn and TensorFlow, Chap. 10
- Pattern Recognition and Machine Learning, Chap. 5
- Pattern Classification, Chap. 6
- Free online book: <http://neuralnetworksanddeeplearning.com>

Machine Learning Courses

- <https://www.coursera.org/learn/machine-learning>, Week 4 & 5
- <https://www.coursera.org/learn/neural-networks>