To achieve a $\pm\ 0.5cm$ **accuracy target** on soft tissue, complete capture in **under 60 seconds**, fit inside a compact Japanese retail fitting room, and output data securely over a store VPN toward the December 2026 **3DBG** and April 2027 **Electronic Record** launches, the problem must be framed not as a graphics problem, but as a **metrology and biomechanical calibration problem**.

Visual 3D meshes fail in corrective underwear fitting because optical sensors capture the **uncompressed outer perimeter (P_{rigid})**, whereas an experienced fitter applies specific circumferential tension (T_{tape}) that compresses subcutaneous adipose tissue, alters local curvature, and shifts landmarks.

Below are the **top 5 technical product architectures** that fit these requirements, followed by the mathematical and architectural strategies to overcome previous PoC limitations, solve the tape-pressure problem, and guarantee zero-trust privacy.

Top 5 Technical Product Architectures

1. Fixed Multi-Sensor Active IR / ToF Edge Pod + Parametric AI Prior (Recommended Primary PoC)

This architecture pairs 4 to 8 synchronized Time-of-Flight (ToF) or Active IR Stereo depth pods (e.g., Orbbec Femto Bolt / Intel RealSense D455 / Sony DepthSense) mounted on vertical corner columns inside the fitting room, wired to a small fanless local Edge GPU box (e.g., NVIDIA Jetson AGX Orin).

- **Technical Pipeline:**

1. **Synchronized Multi-View Capture (< 2 seconds):** Hardware-triggered shutters capture synchronized RGB-D frames simultaneously, eliminating non-rigid human breathing and sway artifacts.
2. **Point-Cloud Fusion & Implicit Surface Reconstruction:** Extrinsic calibration matrices merge the 4–8 point clouds into a single coordinate space. Instead of noisy Poisson meshing, a **Neural Pull / Implicit SDF (Signed Distance Function)** network fits a watertight surface.
3. **Anatomical Prior Registration (SMPL-X / STAR):** A learned statistical human body model (such as **STAR**—Sparse Trained Articulated Human Body Regressor, or an Asian-body-tuned **SMPL-X** variant) is registered to the dense point cloud via Iterative Closest Point (ICP) + 3D skeletal keypoints. This guarantees topological consistency even in self-occluded zones (crotch/in-seam, underbust fold).
4. **Geodesic Slice & Soft-Tissue Regression:** Cross-sectional planes are sliced orthogonal to the local skeletal bone vector (critical for separating left/right thighs cleanly), and passed through a **Soft-Tissue Compression Regressor** to output tape-equivalent values.

- **Why it wins:** Simultaneous capture solves the 1-minute limit (actual scan is ~2 seconds; total guidance-to-JSON is ~35 seconds). Zero moving parts means almost zero maintenance.

2. Automated Vertical-Travel Structured-Light / Laser Column

(High-Precision Reference / Benchmark)

Modeled after industrial metrology leaders (**Humanetics Vitronic Vitusa / SafeSize / Size Stream**), this architecture uses 2 to 3 slim vertical towers or a rotating/sliding sensor mast projecting high-frequency sinusoidal fringe patterns (White/Blue Structured Light) or Class-1 eye-safe laser lines.

- **Technical Pipeline:**

1. **Phase-Shifting Profilometry:** Projectors cast phase-shifted fringe patterns onto the body; industrial monochrome global-shutter CMOS cameras calculate phase unwrapping to compute sub-millimeter 3D coordinates ($\pm\ 0.2mm$ sensor-level Z-accuracy).
2. **Direct Topological Slicing:** Because the raw point cloud is dense (1M+ vertices), the system does not rely on heavy AI hallucination. It directly locates geometric inflection points (e.g., the acute dihedral angle at the inframammary fold for the underbust) and calculates horizontal and orthogonal perimeter loops.

- **Why it wins:** Highest raw geometric fidelity ($\pm\ 0.2to0.4cm$ on rigid mannequins). Ideal as the **Ground Truth Reference System** in flagship stores or R&D labs to train the tape-pressure compensation model, though hardware cost ($15k$–40k per unit) and footprint make chain-wide rollout harder.

3. Dual-View / Multi-View 2D Silhouette + NeRF/Gaussian Splatting to 3D Mesh (Minimal Hardware Footprint)

Inspired by mobile-first leaders (**3DLOOK**, **Prism Labs**, **Meshcapade**), but hardened for a fixed fitting room using **two fixed wall-mounted tablets or PoE RGB cameras** positioned orthogonally (Front + Side) at a 1.2m–1.5m distance, avoiding the handheld operator walk-around error.

- **Technical Pipeline:**

1. **Sub-Pixel Silhouette & DensePose Extraction:** High-resolution RGB frames are segmented immediately in RAM using **SAM-2 (Segment Anything Model 2)** or **DensePose** to extract UV surface coordinates and 2D sub-pixel contours, immediately discarding the raw RGB texture for privacy.
2. **3D Human Mesh Recovery (HMR 2.0 / SHAPY):** A Vision Transformer (ViT) backbone (like **HMR 2.0** or **SHAPY**—Shape-Aware Parametric Models) regresses the β shape parameters and θ pose parameters of a parametric mesh constrained by the exact pixel heights derived from camera intrinsics and an ultrasonic/ToF floor-to-head height sensor.

- **Why it wins:** Lowest hardware cost and zero footprint (mounts flush on existing fitting room walls).
- **Critical Limitation:** Because it infers 3D depth from 2D contours via statistical priors, unusual adipose distribution or localized asymmetries (e.g., a 1.5 cm difference between left and right thigh, or ptotic/unsupported vs. supported bust geometry) get smoothed out toward the population mean, making true $\pm\ 0.5cm$ across all outliers very risky without at least one depth sensor.

4. Millimeter-Wave (mmWave) 60–77 GHz MIMO Radar Array

(Zero-Camera / Privacy-First Architecture)

A bleeding-edge architecture utilizing solid-state flat-panel **mmWave MIMO Radar panels** (similar to miniature airport security/retail scanners like Rohde & Schwarz QPS or TI Cascade Radar arrays) concealed behind thin non-conductive wall panels.

- **Technical Pipeline:**

1. **Synthetic Aperture Radar (SAR) Beamforming:** Electronic steering across a 2D antenna array transmits FMCW (Frequency-Modulated Continuous Wave) chirps that reflect completely off the skin surface (water content in skin reflects 60–77 GHz RF waves completely, while thin fabrics are 100% transparent).
2. **Point-Cloud Deep Learning Reconstruction:** Multi-static radar returns are processed via 3D CNNs to generate a dense skin-surface mesh.

- **Why it wins: Absolute privacy guarantee**—there is literally no optical camera in the fitting room, eliminating customer psychological discomfort (Objective 2.5) and GDPR/APPI image storage concerns. It also sees right through underwear without fabric bunching artifacts.
- **Critical Limitation:** Specular reflection on curved body surfaces causes sparse returns on high-angle slopes (like the inner thigh and underbust crease), currently limiting standalone commercial accuracy to $\sim\pm\ 0.8to1.2cm$ unless fused with an optical silhouette.

5. Handheld Tablet LiDAR + Automated Acoustic/Visual Guided Gimbal (Low-CapEx PoC Bridge)

This upgrades your **Option 1 (iPad Pro / iPhone Pro dToF LiDAR)** to overcome operator-induced fusion drift. Instead of a staff member walking around the customer holding an iPad manually, the iPad is mounted on a **compact motorized 180° arc arm or column slider**, or constrained via **Real-Time AR Trajectory Locking**.

- **Technical Pipeline:**

1. **dToF LiDAR + Photometric Stereo Fusion:** Combines Apple's direct Time-of-Flight (dToF) depth map (which is low-resolution 256×192) with high-res RGB normal maps using **Neural RGB-D Surface Reconstruction (e.g., MonoSDF / BakedSDF)**.
2. **Non-Rigid SLAM (DynamicFusion / SurfelWarp):** Compensates for minor postural sway during a 10-second sweep by tracking a canonical skeletal warp field alongside the TSDF (Truncated Signed Distance Function) volume.

- **Why it wins:** Reuses existing iOS/3DBG development knowledge and connects effortlessly to an iPad UI. However, handheld operator scanning should be restricted to early algorithm prototyping; a fixed multi-sensor array (Architecture 1) is far superior for production stores.

Evaluation Against the 17 RFI Criteria

#	RFI Evaluation	Arch 1: Fixed Multi-De	Arch 2: Structured-Light	Arch 3: Dual Fixed	Arch 4: mmWave Radar	Arch 5: Guided iPad Pro

	Criterion	pth Pod + AI (Recommended)	/ Laser Booth (Humanetics/Vitronic)	RGB + ViT Mesh (3DLOOK/SHAPY)	Array	LiDAR
1	**Measures all 11 items?**	**Yes** (with digital weight scale via BLE)	**Yes** (with integrated floor scale)	**Yes** (requires BLE scale + height sensor)	**Partial** (struggles on sharp creases)	**Yes** (requires BLE scale)
2	**Separate R/L thighs?**	**Yes** (via orthogonal skeletal slicing)	**Yes** (native high-res mesh slicing)	**Weak** (priors tend to symmetrize thighs)	**Yes** (requires wide-stance posture)	**Moderate** (inner-thigh occlusion risk)
3	**Custom anatomical defs?**	**Yes** (programmable 3D landmark definitions)	**Partial** (often locked in vendor SDK)	**Yes** (trainable on custom keypoints)	**Yes** (custom ML pipeline)	**Yes** (full access to custom code)
4	$\pm 0.5cm$ **demonstrated?**	**Achievable** *only* with Soft-Tissue ML model	**Yes** (ISO 20685 certified on rigid forms)	**No** (typically $\pm 1.0to1.5$ MAE)	**No** ($\pm 0.8to1.2$ current state)	**No** ($\pm 0.8to1.5$ due to drift)
5	**Validation benchmark**	IEEE/CVPR benchmarks ($N = 500 +$ scans)	ISO 20685-1 anthropometric validation	Commercial apparel studies ($N = 1,000$)	Academic IEEE Radar/ArXiv studies (2025–2026)	Academic clinical trials ($N = 50–200$)

6	**Capture time**	**1.5 – 3 seconds** (instant multi-shot)	**2 – 6 seconds**	**2 seconds** (2 photos)	**1 – 2 seconds**	**15 – 30 seconds** (sweep required)
7	**Time to result display**	**15 – 25 seconds** (Local Edge GPU)	**20 – 40 seconds**	**10 – 20 seconds** (Cloud or Edge)	**15 – 30 seconds**	**25 – 45 seconds**
8	**Space required**	**1.2m × 1.2m** (Corner-mounted pods)	**1.5m × 1.5m** (Dedicated booth)	**1.2m × 1.0m** (Wall mounted)	**1.2m × 1.2m** (Wall panels)	**1.5m × 1.5m** (Operator clearance)
9	**Expert operator needed?**	**No** (1-tap iPad trigger)	**No** (1-tap trigger)	**No** (Voice/Tablet guided)	**No** (1-tap trigger)	**Yes** (Requires steady sweep technique)
10	**API / CSV / JSON output?**	**Yes** (Native REST API, JSON, CSV)	**Yes** (Vendor SDK / CSV export)	**Yes** (REST API / JSON)	**Yes** (Custom Edge API)	**Yes** (Native iOS JSON/CSV)
11	**Raw 3D data (.OBJ/.PLY)?**	**Yes** (Full vertex/mesh ownership)	**Yes** (Usually licensed per unit)	**Yes** (Parametric SMPL/OBJ mesh)	**Yes** (Sparse/Dense point cloud)	**Yes** (USDZ / OBJ / PLY)
12	**Local / Edge**	**Yes** (100%	**Yes** (Local	**Usually Cloud**	**Yes** (Local	**Yes** (On-devi

	execution?	On-Prem Edge GPU)	workstation PC)	(Edge container costs extra)	DSP + Edge GPU)	ce Apple Neural Engine)
13	**Image storage & deletion**	**RAM-only ephemeral** (Zero disk write)	Configurable local wipe	Risk if cloud-based; safe if Edge-deployed	**No optical images captured**	On-device ephemeral sandbox wipe
14	**Ready for Nov 2026 Demo?**	**Yes** (Using off-the-shelf RGB-D + SMPL)	**Yes** (COTS rental/demo unit)	**Yes** (Immediate SDK availability)	**No** (Requires custom hardware integration)	**Yes** (Immediate prototype ready)
15	**Approx. Hardware Cost**	**$2,500 – $4,500** / fitting room	**$15,000 – $35,000** / booth	**$800 – $1,500** / room (+ SaaS fee)	**$6,000 – $12,000** / room	**$1,200 – $2,000** / room
16	**3DBG & Electronic Record?**	**Seamless** (Exports rigged 3D mesh + JSON)	**Moderate** (Heavy mesh needs decimation)	**High** (Native parametric mesh matches 3DBG)	**Low** (Mesh lacks visual smoothness)	**High** (Direct iOS ecosystem match)
17	**Major Limitations**	Needs initial calibration & paired tape dataset	High CapEx, large footprint, proprietary defs	Cannot hit $\pm\ 0.5cm$ on atypical bodies	Lower spatial resolution on creases	Operator fatigue, motion drift, occlusion

How to Win the Technical Evaluation: Bleeding-Edge Solutions to Core Risks

Quoting the following specific methodologies, patents, and mathematical formulations in your RFI response will set your technical proposal apart from generic scanner vendors.

1. Solving the "Tape-Pressure vs. Non-Contact Surface" Problem (The #1 Differentiator)

A non-contact scanner measures the **Zero-Tension Optical Perimeter (P_{opt})**. When a staff member measures the waist, hip, or thigh with a tape, they apply a tension T (typically $0.5Nto1.5N$), which indents soft tissue according to local biomechanical compliance.
In your RFI response, propose a **Two-Stage Physics-Informed Biomechanical Calibration Model**:

Mathematical Formulation: Model the tape-equivalent circumference C_{tape} at body cross-section i not as a simple linear offset, but as a non-linear function of the optical perimeter P_{opt}, local Gaussian/Mean surface curvature (κ_G, κ_H), cross-sectional eccentricity ($e = \sqrt{1 - b^2/a^2}$), and estimated regional soft-tissue compliance (σ_i):

$$C_{tape}^{(i)} = P_{opt}^{(i)} - \Delta C_{compression}\left(P_{opt}^{(i)}, \kappa_H^{(i)}, e^{(i)}, BMI, Age, Posture\right)$$

- **Convex Hull "Bridging" Emulation:** A physical tape measure cannot dip into concavities (such as the gluteal cleft at the hips or the sternum valley between the breasts). Before applying soft-tissue compression, the algorithm must compute the **2D Convex Hull** of the cross-sectional slice to mathematically simulate how a physical tape bridges across valleys:

$$P_{opt}^{(i)} = \oint_{\partial Conv(S_i)} ds$$

-
- **Bleeding-Edge Research & Patents to Cite:**
  - **HIT (Human Implicit Tissues - CVPR 2024 / Max Planck Institute for Intelligent Systems):** Introduces compressive biomechanical tissue layers inside parametric human models (SMPL), differentiating rigid skeletal structures (ribcage at underbust, iliac crest) from compressible subcutaneous adipose layers (waist, thighs).
  - **SHAPY (Shape-Aware Parametric Models - CVPR 2022) & Anthropometric-CNN Regressors:** Demonstrates that regressing anthropometric tape measurements via learned surface descriptors outperforms raw geometric slicing on noisy scans.
  - **Patent Precedents (e.g., US10929998B2 / US11468608B2 / WO2021173680A1):** Cover

methods for adjusting optical 3D body circumference measurements using learned tissue-deformation coefficients trained on paired optical scan + expert tailor tape datasets.

2. Overcoming Previous PoC Limitations (< 60-Second Turnaround & Zero Motion Blur)

The previous technology verification failed primarily because **capture + processing took too long** and required customer stillness.

- **Hardware Fix (Global Sync Capture):** By replacing sequential scanning (walking around with an iPad or waiting for a slow mechanical turntable) with **4 synchronized multi-view RGB-D pods**, the physical capture time drops from 45 seconds to **< 2 seconds** (a single breath-hold).
- **Software Fix (TensorRT Edge Acceleration):** Previous pipelines ran heavy Poisson surface reconstruction and CPU-bound ICP registration (taking 2–4 minutes). By compiling the point-cloud fusion and landmark detection models into **FP16 TensorRT engines** running locally on an **NVIDIA Jetson Orin NX/AGX** inside the fitting room, full 3D mesh reconstruction + 11-item extraction completes in **12 to 18 seconds**.
- **Automated Floor-Scale Pairing:** Place a Bluetooth Low Energy (BLE) / RS-232 digital weight plate directly as the **foot-positioning mat** in the center of the booth. When the customer steps onto the foot decals, **Body Weight (to $0.1kg$)** is captured simultaneously during the 2-second scan, solving the 11th requirement with zero extra time and enforcing exact foot separation for **Left/Right Thigh** disambiguation.

3. Solving Company-Specific Landmarks (Top Bust, Underbust, Waist, and Thighs)

Standard ISO-7250 / ISO-20685 definitions used by off-the-shelf scanners (like Size Stream or 3DLOOK) **do not match** Japanese corrective lingerie definitions (such as Maruko's specific waist height or supported vs. unsupported bust geometry).

- **Underbust & Supported Bust:** In an undergarment or scanning bra, the **inframammary fold (underbust)** is often occluded in front-facing cameras by breast ptosis. Fix this by mounting the lower sensor pods at a **low upward-looking angle (30° upward tilt at $60cm$ height)** so the infrared structured light directly illuminates the underbust crease, combined with **surface normal divergence ($\nabla \cdot n$)** detection to find the exact crease line.
- **Left & Right Thigh Separation:** Instead of slicing thighs with a global horizontal plane (which fails if the customer shifts weight to one leg), fit an internal 3D skeleton (via **MediaPipe 3D / MMPose**) and slice each thigh **orthogonal to the respective femur vector** at a fixed geodesic ratio below the crotch landmark (ischial tuberosity / perineum point).

Cyber Security & Zero-Trust Privacy Architecture (Critical for Submission)

Because customers are scanned in corrective underwear, **cybersecurity and visual privacy**

are board-level gating criteria under Japan's APPI (Act on the Protection of Personal Information). Highlighting a **Zero-Persistence RAM-Only Edge Architecture** will give your proposal a massive advantage:

1. **Ephemeral RAM-Only Image Processing (Zero Disk Write):** Raw RGB and Infrared frames captured in the fitting room are written exclusively to an encrypted **volatile RAM disk (tmpfs)** on the local Edge unit. No raw photographic images are ever written to an SSD/SD card or transmitted over the store network.
2. **Immediate Destructive Feature Extraction:** Within **5 seconds** of capture, the local pipeline converts the RGB-D frames into an anonymized, textureless 3D point cloud / parametric mesh and 11 numerical floats. A cryptographic memory-scrubbing routine (memset_s / zero-fill) overwrites the volatile RAM buffer holding the raw camera frames before the result even appears on the staff tablet.
3. **Tokenized Pseudonymization at the Edge:** The fitting-room Edge unit never stores customer names, phone numbers, or PII. The staff tablet passes an ephemeral **Session_UUID** and **Customer_Hash_ID** via local mTLS.
4. **Store VPN & Network Hardening:**
   - **Outbound-Only REST API over mTLS (TLS 1.3):** The Edge unit communicates exclusively with the internal Electronic Record / Core System gateway over the existing Store VPN via **Port 443 (HTTPS with mutual certificate authentication)**.
   - **Strict Payload Contract:** The transmitted JSON payload is < 50 KB (or < 2 MB if including the decimated, textureless .OBJ/.GLTF 3D mesh for the **3DBG** system), ensuring zero strain on store VPN bandwidth.

Interactive Architecture Explorer

Use the interactive matrix below to filter, sort, and compare the five architectures across the 17 RFI requirements, accuracy thresholds, and phased rollout stages (PoC Option A → Integrated Option B → Unified 3DBG Option C).

Phased Architecture Roadmap for the October 27 RFI Submission

To align with your **Short / Medium / Long-term strategy** and protect the **December 2026 3DBG launch**:

1. **Phase 1: Dual-Track PoC (Option A — Nov 2026 to March 2027)**
   - **Benchmark Track:** Rent or partner with **1 Industrial Structured-Light Scanner (Architecture 2, e.g., Humanetics)** at a single flagship/lab location to capture high-precision ground-truth 3D meshes alongside experienced fitter tape measurements ($N \geq 300$ subjects across body types).
   - **Store Deployment Candidate Track:** Build **Architecture 1 (4-Pod Synchronized Depth Array + Edge GPU)** alongside the benchmark scanner. Use the paired dataset (3D scan + expert tape + soft-tissue indicators) to train the **Soft-Tissue Tape-Pressure Compensation Model** and custom landmark definitions (top bust, underbust, company-specific waist, separate thighs).
   - **Integration:** Standalone tablet UI with customer-ID barcode/QR scan and automated

CSV/JSON export.

2. **Phase 2: Electronic Record Modular Integration (Option B — April 2027)**
   - Connect the Edge GPU unit via **REST API over Store VPN** to the new Electronic Record system. The Electronic Record initiates the measurement session (POST /api/v1/session/start with Customer_ID), and the Edge pod returns the 11 compensated measurements (0.1 cm / 0.1 kg precision) within 20 seconds.
3. **Phase 3: Unified 3DBG + Measurement Convergence (Option C — Late 2027+)**
   - Once the $\pm\ 0.5cm$ accuracy and tape-pressure model pass statistical validation (e.g., $ICC > 0.98, MAE \leq 0.4cm$), feed the rigged parametric 3D mesh from Architecture 1 directly into the **3DBG visualization engine**, achieving single-capture counseling visualization and precision sizing.