

QLog

Quick logging for Windows Azure .NET applications

Version: 1.4.1.0

Configuration

Author: Adam Sobaniec (sobanieca@gmail.com)

Connection string:

```
<add name="QLogDataSource"
      connectionString="{ -Connection string for logs database-}"
/>
```

QLog area:

```
<add key="QLogArea"
      value="*None*|All|QTrace|QDebug|QInfo|QWarn|QError|
QCritical|Accept:{ -areas names separated with comma-}|Ignore:
{-areas names separated with comma-}" />
```

QLog async:

```
<add key="QLogAsync"
      value="True|*False*|Accept:{ -areas names separated with
comma-}|Ignore:{ -areas names separated with comma-}" />
```

QLog silent mode:

```
<add key="QLogSilentMode"
      value="*True*|False" />
```

QLog stacktrace:

```
<add key="QLogStacktrace"
      value="*True*|False" />
```

QLog postfix:

```
<add key="QLogPostfix"
      value="{ -Postfix that will be added to table name-}" />
```

QLog buffer max count (capacity):

```
<add key="QLogBufferMaxCount"
      value="*100*|{-Any Int32 valid value-}" />
```

All values surrounded by "*" are the default values that are being used by QLog if no specific setting was found in the application configuration.