

Make the website with nicer font and gradient colors, and interactive premium elements. Use the given components across the website, I have given basic labeling on where you gotta use them. It needs to have a tech-y vibe and feel to it, it should be high converting

Do changes to the text of these components according to the narrative of the website and ensure high quality website copy

Components:

Body Component:

You are given a task to integrate an existing React component in the codebase

The codebase should support:

- shadcn project structure
- Tailwind CSS
- Typescript

If it doesn't, provide instructions on how to setup project via shadcn CLI, install Tailwind or Typescript.

Determine the default path for components and styles.

If default path for components is not /components/ui, provide instructions on why it's important to create this folder

Copy-paste this component to /components/ui folder:

```
``tsx
features-10.tsx
import { Card, CardContent, CardHeader } from '@components/ui/card'
import { cn } from '@lib/utils'
import { Calendar, LucideIcon, MapIcon } from 'lucide-react'
import { ReactNode } from 'react'

export function Features() {
  return (
    <section className="bg-zinc-50 py-16 md:py-32 dark:bg-transparent">
      <div className="mx-auto max-w-2xl px-6 lg:max-w-5xl">
        <div className="mx-auto grid gap-4 lg:grid-cols-2">
          <FeatureCard>
            <CardHeader className="pb-3">
              <CardHeading
                icon={MapIcon}
                title="Real time location tracking"
                description="Advanced tracking system, Instantly locate all your assets."
              />
            </CardHeader>

            <div className="relative mb-6 border-t border-dashed sm:mb-0">
              <div className="absolute inset-0
[background:radial-gradient(125%_125%_at_50%_0%,transparent_40%,hsl(var(--muted)),white_1
25%)]"></div>

              <div className="aspect-[76/59] p-1 px-6">
                <DualModelImage
```

darkSrc="https://tailark.com/_next/image?url=%2Fpayments.png&w=3840&q=75"

lightSrc="https://tailark.com/_next/image?url=%2Fpayments-light.png&w=3840&q=75"

alt="payments illustration"

width={1207}

height={929}

/>

</div>

</div>

</FeatureCard>

<FeatureCard>

<CardHeader className="pb-3">

<CardHeading

icon={Calendar}

title="Advanced Scheduling"

description="Scheduling system, Instantly locate all your assets."

/>

</CardHeader>

<CardContent>

<div className="relative mb-6 sm:mb-0">

<div className="absolute -inset-6

[background:radial-gradient(50%_50%_at_75%_50%,transparent,hsl(var(--background))_100%)]"

></div>

<div className="aspect-[76/59] border">

<DualModelImage

darkSrc="https://tailark.com/_next/image?url=%2Forigin-cal-dark.png&w=3840&q=75"

lightSrc="https://tailark.com/_next/image?url=%2Forigin-cal.png&w=3840&q=75"

alt="calendar illustration"

width={1207}

height={929}

/>

</div>

</div>

</CardContent>

</FeatureCard>

<FeatureCard className="p-6 lg:col-span-2">

<p className="mx-auto my-6 max-w-md text-balance text-center text-2xl font-semibold">Smart scheduling with automated reminders for maintenance.</p>

<div className="flex justify-center gap-6 overflow-hidden">

<CircularUI

label="Inclusion"

circles={[{ pattern: 'border' }, { pattern: 'border' }]}

/>

<CircularUI

```

        label="Inclusion"
        circles={{ pattern: 'none' }, { pattern: 'primary' }}}
    />

    <CircularUI
        label="Join"
        circles={{ pattern: 'blue' }, { pattern: 'none' }}}
    />

    <CircularUI
        label="Exclusion"
        circles={{ pattern: 'primary' }, { pattern: 'none' }}}
        className="hidden sm:block"
    />
</div>
</FeatureCard>
</div>
</div>
</section>
)
}

interface FeatureCardProps {
    children: ReactNode
    className?: string
}

const FeatureCard = ({ children, className }: FeatureCardProps) => (
    <Card className={cn('group relative rounded-none shadow-zinc-950/5', className)}>
        <CardDecorator />
        {children}
    </Card>
)

const CardDecorator = () => (
    <>
        <span className="border-primary absolute -left-px -top-px block size-2 border-l-2 border-t-2"></span>
        <span className="border-primary absolute -right-px -top-px block size-2 border-r-2 border-t-2"></span>
        <span className="border-primary absolute -bottom-px -left-px block size-2 border-b-2 border-l-2"></span>
        <span className="border-primary absolute -bottom-px -right-px block size-2 border-b-2 border-r-2"></span>
    </>
)

interface CardHeadingProps {
    icon: LucideIcon
    title: string
    description: string
}

```

```
const CardHeading = ({ icon: Icon, title, description }: CardHeadingProps) => (
  <div className="p-6">
    <span className="text-muted-foreground flex items-center gap-2">
      <Icon className="size-4" />
      {title}
    </span>
    <p className="mt-8 text-2xl font-semibold">{description}</p>
  </div>
)
```

```
interface DualModelImageProps {
  darkSrc: string
  lightSrc: string
  alt: string
  width: number
  height: number
  className?: string
}
```

```
const DualModelImage = ({ darkSrc, lightSrc, alt, width, height, className }:
DualModelImageProps) => (
  <>
    <img
      src={darkSrc}
      className={cn('hidden dark:block', className)}
      alt={` ${alt} dark`}
      width={width}
      height={height}
    />
    <img
      src={lightSrc}
      className={cn('shadow dark:hidden', className)}
      alt={` ${alt} light`}
      width={width}
      height={height}
    />
  </>
)
```

```
interface CircleConfig {
  pattern: 'none' | 'border' | 'primary' | 'blue'
}
```

```
interface CircularUIProps {
  label: string
  circles: CircleConfig[]
  className?: string
}
```

```
const CircularUI = ({ label, circles, className }: CircularUIProps) => (
  <div className={className}>
```

```

    <div className="bg-gradient-to-b from-border size-fit rounded-2xl to-transparent p-px">
      <div className="bg-gradient-to-b from-background to-muted/25 relative flex
aspect-square w-fit items-center -space-x-4 rounded-[15px] p-4">
        {circles.map((circle, i) => (
          <div
            key={i}
            className={cn('size-7 rounded-full border sm:size-8', {
              'border-primary': circle.pattern === 'none',
              'border-primary
bg-[repeating-linear-gradient(-45deg,hsl(var(--border)),hsl(var(--border))_1px,transparent_1px,trans
parent_4px)]: circle.pattern === 'border',
              'border-primary bg-background
bg-[repeating-linear-gradient(-45deg,hsl(var(--primary)),hsl(var(--primary))_1px,transparent_1px,tra
nsparent_4px)]: circle.pattern === 'primary',
              'bg-background z-1 border-blue-500
bg-[repeating-linear-gradient(-45deg,theme(colors.blue.500),theme(colors.blue.500)_1px,transpar
ent_1px,transparent_4px)]: circle.pattern === 'blue',
            })}></div>
          )})
        </div>
      </div>
      <span className="text-muted-foreground mt-1.5 block text-center text-sm">{label}</span>
    </div>
  )

```

demo.tsx

```
import { Features } from "@components/blocks/features-10"
```

```
export const Demo = () => {
  return <Features />
}

```

Copy-paste these files for dependencies:

```
```tsx
```

```
shadcn/card
```

```
import * as React from "react"
```

```
import { cn } from "@lib/utils"
```

```
const Card = React.forwardRef<
 HTMLDivElement,
 React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
 <div
 ref={ref}
 className={cn(
 "rounded-lg border bg-card text-card-foreground shadow-sm",
 className,
)}
 {...props}
 >

```

```

 />
))
 Card.displayName = "Card"

 const CardHeader = React.forwardRef<
 HTMLDivElement,
 React.HTMLAttributes<HTMLDivElement>
 >(({ className, ...props }, ref) => (
 <div
 ref={ref}
 className={cn("flex flex-col space-y-1.5 p-6", className)}
 {...props}
 />
))
 CardHeader.displayName = "CardHeader"

 const CardTitle = React.forwardRef<
 HTMLParagraphElement,
 React.HTMLAttributes<HTMLHeadingElement>
 >(({ className, ...props }, ref) => (
 <h3
 ref={ref}
 className={cn(
 "text-2xl font-semibold leading-none tracking-tight",
 className,
)}
 {...props}
 />
))
 CardTitle.displayName = "CardTitle"

 const CardDescription = React.forwardRef<
 HTMLParagraphElement,
 React.HTMLAttributes<HTMLParagraphElement>
 >(({ className, ...props }, ref) => (
 <p
 ref={ref}
 className={cn("text-sm text-muted-foreground", className)}
 {...props}
 />
))
 CardDescription.displayName = "CardDescription"

 const CardContent = React.forwardRef<
 HTMLDivElement,
 React.HTMLAttributes<HTMLDivElement>
 >(({ className, ...props }, ref) => (
 <div ref={ref} className={cn("p-6 pt-0", className)} {...props} />
))
 CardContent.displayName = "CardContent"

 const CardFooter = React.forwardRef<

```

```

HTMLDivElement,
React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
 <div
 ref={ref}
 className={cn("flex items-center p-6 pt-0", className)}
 {...props}
 />
))
CardFooter.displayName = "CardFooter"

export { Card, CardHeader, CardFooter, CardTitle, CardDescription, CardContent }

'''

```

Install NPM dependencies:

```

'''bash
lucide-react
'''

```

#### Implementation Guidelines

1. Analyze the component structure and identify all required dependencies
2. Review the component's arguments and state
3. Identify any required context providers or hooks and install them
4. Questions to Ask
  - What data/props will be passed to this component?
  - Are there any specific state management requirements?
  - Are there any required assets (images, icons, etc.)?
  - What is the expected responsive behavior?
  - What is the best place to use this component in the app?

#### Steps to integrate

0. Copy paste all the code above in the correct directories
1. Install external dependencies
2. Fill image assets with Unsplash stock images you know exist
3. Use lucide-react icons for svgs or logos if component requires them

#### 2nd Component (Card):

You are given a task to integrate an existing React component in the codebase

The codebase should support:

- shadcn project structure
- Tailwind CSS
- Typescript

If it doesn't, provide instructions on how to setup project via shadcn CLI, install Tailwind or Typescript.

Determine the default path for components and styles.

If default path for components is not /components/ui, provide instructions on why it's important to create this folder

Copy-paste this component to /components/ui folder:

```
``tsx
gradient-card.tsx
'use client'
import React, { useRef, useState, useEffect } from "react";
import { motion } from "framer-motion";

export const GradientCard = () => {
 const cardRef = useRef<HTMLDivElement>(null);
 const [isHovered, setIsHovered] = useState(false);
 const [mousePosition, setMousePosition] = useState({ x: 0, y: 0 });
 const [rotation, setRotation] = useState({ x: 0, y: 0 });

 // Handle mouse movement for 3D effect
 const handleMouseMove = (e: React.MouseEvent<HTMLDivElement>) => {
 if (cardRef.current) {
 const rect = cardRef.current.getBoundingClientRect();

 // Calculate mouse position relative to card center
 const x = e.clientX - rect.left - rect.width / 2;
 const y = e.clientY - rect.top - rect.height / 2;

 setMousePosition({ x, y });

 // Calculate rotation (limited range for subtle effect)
 const rotateX = -(y / rect.height) * 5; // Max 5 degrees rotation
 const rotateY = (x / rect.width) * 5; // Max 5 degrees rotation

 setRotation({ x: rotateX, y: rotateY });
 }
 };

 // Reset rotation when not hovering
 const handleMouseLeave = () => {
 setIsHovered(false);
 setRotation({ x: 0, y: 0 });
 };

 return (
 <div className="w-full h-screen flex items-center justify-center bg-black">
 {/* Card container with realistic 3D effect */}
 <motion.div
 ref={cardRef}
 className="relative rounded-[32px] overflow-hidden"
 style={{
```



```

width: "360px",
height: "450px",
transformStyle: "preserve-3d",
backgroundColor: "#0e131f",
boxShadow: "0 -10px 100px 10px rgba(78, 99, 255, 0.25), 0 0 10px 0 rgba(0, 0, 0, 0.5)",
}}
initial={{ y: 0 }}
animate={{
 y: isHovered ? -5 : 0,
 rotateX: rotation.x,
 rotateY: rotation.y,
 perspective: 1000,
}}
transition={{
 type: "spring",
 stiffness: 300,
 damping: 20
}}
onMouseEnter={() => setIsHovered(true)}
onMouseLeave={handleMouseLeave}
onMouseMove={handleMouseMove}
>
{/* Subtle glass reflection overlay */}
<motion.div
 className="absolute inset-0 z-35 pointer-events-none"
 style={{
 background: "linear-gradient(135deg, rgba(255,255,255,0.08) 0%, rgba(255,255,255,0)
40%, rgba(255,255,255,0) 80%, rgba(255,255,255,0.05) 100%)",
 backdropFilter: "blur(2px)",
 }}
 animate={{
 opacity: isHovered ? 0.7 : 0.5,
 rotateX: -rotation.x * 0.2,
 rotateY: -rotation.y * 0.2,
 z: 1,
 }}
 transition={{
 duration: 0.4,
 ease: "easeOut"
 }}
/>

{/* Dark background with black gradient like in the image */}
<motion.div
 className="absolute inset-0 z-0"
 style={{
 background: "linear-gradient(180deg, #000000 0%, #000000 70%)",
 }}
 animate={{
 z: -1
 }}
/>

```

```

 { /* Noise texture overlay */
 <motion.div
 className="absolute inset-0 opacity-30 mix-blend-overlay z-10"
 style={{
 backgroundImage: `url("data:image/svg+xml,%3Csvg viewBox='0 0 200 200'
xmlns='http://www.w3.org/2000/svg'%3E%3Cfilter id='noise'%3E%3CfeTurbulence
type='fractalNoise' baseFrequency='0.65' numOctaves='5'
stitchTiles='stitch'/%3E%3C/filter%3E%3Crect width='100%25' height='100%25'
filter='url(%23noise)'/%3E%3C/svg%3E")`,
 }}
 animate={{
 z: -0.5
 }}
 />

 { /* Subtle finger smudge texture for realism */
 <motion.div
 className="absolute inset-0 opacity-10 mix-blend-soft-light z-11 pointer-events-none"
 style={{
 backgroundImage: `url("data:image/svg+xml,%3Csvg viewBox='0 0 400 400'
xmlns='http://www.w3.org/2000/svg'%3E%3Cfilter id='smudge'%3E%3CfeTurbulence
type='fractalNoise' baseFrequency='0.01' numOctaves='3' seed='5'
stitchTiles='stitch'/%3E%3CfeGaussianBlur stdDeviation='10'/%3E%3C/filter%3E%3Crect
width='100%25' height='100%25' filter='url(%23smudge)'/%3E%3C/svg%3E")`,
 backdropFilter: "blur(1px)",
 }}
 animate={{
 z: -0.25
 }}
 />

 { /* Purple/blue glow effect matching the image */
 <motion.div
 className="absolute bottom-0 left-0 right-0 h-2/3 z-20"
 style={{
 background: `
 radial-gradient(ellipse at bottom right, rgba(172, 92, 255, 0.7) -10%, rgba(79, 70, 229, 0)
70%),
 radial-gradient(ellipse at bottom left, rgba(56, 189, 248, 0.7) -10%, rgba(79, 70, 229, 0)
70%)
 `,
 filter: "blur(40px)",
 }}
 animate={{
 opacity: isHovered ? 0.9 : 0.8,
 y: isHovered ? rotation.x * 0.5 : 0,
 z: 0
 }}
 transition={{
 duration: 0.4,
 ease: "easeOut"
 }}
 />

```

```
}}
/>
```

```
 { /* Central purple glow as seen in the image */
 <motion.div
 className="absolute bottom-0 left-0 right-0 h-2/3 z-21"
 style={{
 background: `
60%) radial-gradient(circle at bottom center, rgba(161, 58, 229, 0.7) -20%, rgba(79, 70, 229, 0)
 ,
 filter: "blur(45px)",
 }}
 animate={{
 opacity: isHovered ? 0.85 : 0.75,
 y: isHovered ? `calc(10% + ${rotation.x * 0.3}px)` : "10%",
 z: 0
 }}
 transition={{
 duration: 0.4,
 ease: "easeOut"
 }}
 }
 />
```

```
 { /* Enhanced bottom border glow for premium look */
 <motion.div
 className="absolute bottom-0 left-0 right-0 h-[2px] z-25"
 style={{
 background: "linear-gradient(90deg, rgba(255, 255, 255, 0.05) 0%, rgba(255, 255, 255,
0.7) 50%, rgba(255, 255, 255, 0.05) 100%)",
 }}
 animate={{
 boxShadow: isHovered
 ? "0 0 20px 4px rgba(172, 92, 255, 0.9), 0 0 30px 6px rgba(138, 58, 185, 0.7), 0 0 40px
8px rgba(56, 189, 248, 0.5)"
 : "0 0 15px 3px rgba(172, 92, 255, 0.8), 0 0 25px 5px rgba(138, 58, 185, 0.6), 0 0 35px
7px rgba(56, 189, 248, 0.4)",
 opacity: isHovered ? 1 : 0.9,
 z: 0.5
 }}
 transition={{
 duration: 0.4,
 ease: "easeOut"
 }}
 }
 />
```

```
 <motion.div
 className="absolute bottom-0 left-0 h-1/4 w-[1px] z-25 rounded-full"
 style={{
 background: "linear-gradient(to top, rgba(255, 255, 255, 0.7) 0%, rgba(255, 255, 255, 0.5)
20%, rgba(255, 255, 255, 0.3) 40%, rgba(255, 255, 255, 0.1) 60%, rgba(255, 255, 255, 0) 80%)",
 }}
 animate={{
```

```

 boxShadow: isHovered
 ? "0 0 20px 4px rgba(172, 92, 255, 0.9), 0 0 30px 6px rgba(138, 58, 185, 0.7), 0 0 40px
8px rgba(56, 189, 248, 0.5)"
 : "0 0 15px 3px rgba(172, 92, 255, 0.8), 0 0 25px 5px rgba(138, 58, 185, 0.6), 0 0 35px
7px rgba(56, 189, 248, 0.4)",
 opacity: isHovered ? 1 : 0.9,
 z: 0.5
 }}
 transition={{
 duration: 0.4,
 ease: "easeOut"
 }}
/>
<motion.div
 className="absolute bottom-0 left-0 h-1/4 z-25"
 style={{
 background: "linear-gradient(to top, rgba(255, 255, 255, 0.7) 0%, rgba(255, 255, 255, 0.55)
15%, rgba(255, 255, 255, 0.4) 30%, rgba(255, 255, 255, 0.25) 45%, rgba(255, 255, 255, 0.1) 70%,
rgba(255, 255, 255, 0) 85%)",
 }}
 animate={{
 boxShadow: isHovered
 ? "0 0 20px 4px rgba(172, 92, 255, 0.9), 0 0 30px 6px rgba(138, 58, 185, 0.7), 0 0 40px
8px rgba(56, 189, 248, 0.5)"
 : "0 0 15px 3px rgba(172, 92, 255, 0.8), 0 0 25px 5px rgba(138, 58, 185, 0.6), 0 0 35px
7px rgba(56, 189, 248, 0.4)",
 opacity: isHovered ? 1 : 0.9,
 z: 0.5
 }}
 transition={{
 duration: 0.4,
 ease: "easeOut"
 }}
/>
<motion.div
 className="absolute bottom-0 right-0 h-1/4 w-[1px] z-25 rounded-full"
 style={{
 background: "linear-gradient(to top, rgba(255, 255, 255, 0.7) 0%, rgba(255, 255, 255, 0.5)
20%, rgba(255, 255, 255, 0.3) 40%, rgba(255, 255, 255, 0.1) 60%, rgba(255, 255, 255, 0) 80%)",
 }}
 animate={{
 boxShadow: isHovered
 ? "0 0 20px 4px rgba(172, 92, 255, 0.9), 0 0 30px 6px rgba(138, 58, 185, 0.7), 0 0 40px
8px rgba(56, 189, 248, 0.5)"
 : "0 0 15px 3px rgba(172, 92, 255, 0.8), 0 0 25px 5px rgba(138, 58, 185, 0.6), 0 0 35px
7px rgba(56, 189, 248, 0.4)",
 opacity: isHovered ? 1 : 0.9,
 z: 0.5
 }}
 transition={{
 duration: 0.4,
 ease: "easeOut"
 }}

```

```

 }}
 />
 <motion.div
 className="absolute bottom-0 right-0 h-1/3 z-25"
 style={{
 background: "linear-gradient(to top, rgba(255, 255, 255, 0.7) 0%, rgba(255, 255, 255, 0.55)
15%, rgba(255, 255, 255, 0.4) 30%, rgba(255, 255, 255, 0.25) 45%, rgba(255, 255, 255, 0.1) 70%,
rgba(255, 255, 255, 0) 85%)",
 }}
 animate={{
 boxShadow: isHovered
 ? "0 0 20px 4px rgba(172, 92, 255, 0.9), 0 0 30px 6px rgba(138, 58, 185, 0.7), 0 0 40px
8px rgba(56, 189, 248, 0.5)"
 : "0 0 15px 3px rgba(172, 92, 255, 0.8), 0 0 25px 5px rgba(138, 58, 185, 0.6), 0 0 35px
7px rgba(56, 189, 248, 0.4)",
 opacity: isHovered ? 1 : 0.9,
 z: 0.5
 }}
 transition={{
 duration: 0.4,
 ease: "easeOut"
 }}
 />

 {/ * Card content */}
 <motion.div
 className="relative flex flex-col h-full p-8 z-40"
 animate={{
 z: 2
 }}
 >
 {/ * Icon circle with shadow - making it dark like in the image */}
 <motion.div
 className="w-12 h-12 rounded-full flex items-center justify-center mb-6"
 style={{
 background: "linear-gradient(225deg, #171c2c 0%, #121624 100%)",
 position: "relative",
 overflow: "hidden"
 }}
 initial={{ filter: "blur(3px)", opacity: 0.7 }}
 animate={{
 filter: "blur(0px)",
 opacity: 1,
 boxShadow: isHovered
 ? "0 8px 16px -2px rgba(0, 0, 0, 0.3), 0 4px 8px -1px rgba(0, 0, 0, 0.2), inset 2px 2px
5px rgba(255, 255, 255, 0.15), inset -2px -2px 5px rgba(0, 0, 0, 0.7)"
 : "0 6px 12px -2px rgba(0, 0, 0, 0.25), 0 3px 6px -1px rgba(0, 0, 0, 0.15), inset 1px 1px
3px rgba(255, 255, 255, 0.12), inset -2px -2px 4px rgba(0, 0, 0, 0.5)",
 z: isHovered ? 10 : 5,
 y: isHovered ? -2 : 0,
 rotateX: isHovered ? -rotation.x * 0.5 : 0,
 rotateY: isHovered ? -rotation.y * 0.5 : 0
 }}
 />

```

```

 }}
 transition={{
 duration: 0.4,
 ease: "easeOut"
 }}
 >
 {/ * Top-left highlight for realistic lighting */}
 <div
 className="absolute top-0 left-0 w-2/3 h-2/3 opacity-40"
 style={{
 background: "radial-gradient(circle at top left, rgba(255, 255, 255, 0.5), transparent
80%)",
 pointerEvents: "none",
 filter: "blur(10px)"
 }}
 />

 {/ * Bottom shadow for depth */}
 <div
 className="absolute bottom-0 left-0 w-full h-1/2 opacity-50"
 style={{
 background: "linear-gradient(to top, rgba(0, 0, 0, 0.4), transparent)",
 pointerEvents: "none",
 backdropFilter: "blur(3px)"
 }}
 />

 {/ * Star icon matching the image */}
 <div className="flex items-center justify-center w-full h-full relative z-10">
 <svg width="20" height="20" viewBox="0 0 16 16" fill="none"
xmlns="http://www.w3.org/2000/svg">
 <path
 d="M8 0L9.4 5.4L14.8 5.4L10.6 8.8L12 14.2L8 10.8L4 14.2L5.4 8.8L1.2 5.4L6.6 5.4L8
0Z"
 fill="white"
 />
 </svg>
 </div>
</motion.div>

 {/ * Content positioning to match the image */}
 <motion.div
 className="mb-auto"
 animate={{
 z: isHovered ? 5 : 2,
 rotateX: isHovered ? -rotation.x * 0.3 : 0,
 rotateY: isHovered ? -rotation.y * 0.3 : 0
 }}
 transition={{
 duration: 0.4,
 ease: "easeOut"
 }}
 />

```

```

>
<motion.h3
 className="text-2xl font-medium text-white mb-3"
 style={{
 letterSpacing: "-0.01em",
 lineHeight: 1.2,
 }}
 initial={{ filter: "blur(3px)", opacity: 0.7 }}
 animate={{
 textShadow: isHovered ? "0 2px 4px rgba(0,0,0,0.2)" : "none",
 filter: "blur(0px)",
 opacity: 1,
 transition: { duration: 1.2, delay: 0.2 }
 }}
>
 AI-Powered Inbox Sorting
</motion.h3>

<motion.p
 className="text-sm mb-6 text-gray-300"
 style={{
 lineHeight: 1.5,
 fontWeight: 350,
 }}
 initial={{ filter: "blur(3px)", opacity: 0.7 }}
 animate={{
 textShadow: isHovered ? "0 1px 2px rgba(0,0,0,0.1)" : "none",
 filter: "blur(0px)",
 opacity: 0.85,
 transition: { duration: 1.2, delay: 0.4 }
 }}
>
 OpenMail revolutionizes email management with AI-driven sorting,
 boosting productivity and accessibility
</motion.p>

{/* Learn More with arrow - matching the image */}
<motion.a
 href="#"
 className="inline-flex items-center text-white text-sm font-medium group"
 initial={{ filter: "blur(3px)", opacity: 0.7 }}
 animate={{
 filter: "blur(0px)",
 opacity: 0.9,
 transition: { duration: 1.2, delay: 0.6 }
 }}
 whileHover={{
 filter: "drop-shadow(0 0 5px rgba(255, 255, 255, 0.5))"
 }}
>
 Learn More
</motion.svg

```

```

 className="ml-1 w-4 h-4"
 width="8"
 height="8"
 viewBox="0 0 16 16"
 fill="none"
 xmlns="http://www.w3.org/2000/svg"
 animate={{
 x: isHovered ? 4 : 0
 }}
 transition={{
 duration: 0.6,
 ease: "easeOut"
 }}
 >
 <path
 d="M1 8H15M15 8L8 1M15 8L8 15"
 stroke="white"
 strokeWidth="1.5"
 strokeLinecap="round"
 strokeLinejoin="round"
 />
 </motion.svg>
 </motion.a>
</motion.div>
</motion.div>
</div>
);
};

demo.tsx
import { GradientCard } from "@components/ui/gradient-card"

export const Demo = () => {
 return <GradientCard />
}

```

Install NPM dependencies:

```

`bash
framer-motion
`

```

### Implementation Guidelines

1. Analyze the component structure and identify all required dependencies
2. Review the component's arguments and state
3. Identify any required context providers or hooks and install them
4. Questions to Ask
  - What data/props will be passed to this component?
  - Are there any specific state management requirements?
  - Are there any required assets (images, icons, etc.)?
  - What is the expected responsive behavior?



- What is the best place to use this component in the app?

Steps to integrate

0. Copy paste all the code above in the correct directories
1. Install external dependencies
2. Fill image assets with Unsplash stock images you know exist
3. Use lucide-react icons for svgs or logos if component requires them

Make the website with nicer font and gradient colors, and interactive premium elements. Use the given components across the website, I have given basic labeling on where you gotta use them. It needs to have a tech-y vibe and feel to it, it should be high converting

Do changes to the text of these components according to the narrative of the website and ensure high quality website copy

Hero:

You are given a task to integrate an existing React component in the codebase

The codebase should support:

- shadcn project structure
- Tailwind CSS
- Typescript

If it doesn't, provide instructions on how to setup project via shadcn CLI, install Tailwind or Typescript.

Determine the default path for components and styles.

If default path for components is not /components/ui, provide instructions on why it's important to create this folder

Copy-paste this component to /components/ui folder:

```
``tsx
```

```
hero-1.tsx
```

```
"use client"
```

```
import { ChevronRight } from "lucide-react"
```

```
import { Button } from "@/components/ui/button"
```

```
interface HeroProps {
```

```
 eyebrow?: string
```

```
 title: string
```

```
 subtitle: string
```

```
 ctaLabel?: string
```

```
 ctaHref?: string
```

```
}
```

```
export function Hero({
```

```
 eyebrow = "Innovate Without Limits",
```

```
 title,
```

```
 subtitle,
```

```
 ctaLabel = "Explore Now",
```

```
 ctaHref = "#",
```

```
}: HeroProps) {
```

```

return (
 <section
 id="hero"
 className="relative mx-auto w-full pt-40 px-6 text-center md:px-8
 min-h-[calc(100vh-40px)] overflow-hidden
 bg-[linear-gradient(to_bottom,#fff,#fffff_50%,#e8e8e8_88%)]
 dark:bg-[linear-gradient(to_bottom,#000,#0000_30%,#898e8e_78%,#ffffff_99%_50%)]
 rounded-b-xl"
 >
 {/ * Grid BG */}
 <div
 className="absolute -z-10 inset-0 opacity-80 h-[600px] w-full

 bg-[linear-gradient(to_right,#f0f0f0_1px,transparent_1px),linear-gradient(to_bottom,#f0f0f0_1px,tra
 nsparent_1px)]

 dark:bg-[linear-gradient(to_right,#333_1px,transparent_1px),linear-gradient(to_bottom,#333_1px,tr
 ansparent_1px)]
 bg-[size:6rem_5rem]
 [mask-image:radial-gradient(ellipse_80%_50%_at_50%_0%,#000_70%,transparent_110%)]"
 />

 {/ * Radial Accent */}
 <div
 className="absolute left-1/2 top-[calc(100%-90px)] lg:top-[calc(100%-150px)]
 h-[500px] w-[700px] md:h-[500px] md:w-[1100px] lg:h-[750px] lg:w-[140%]
 -translate-x-1/2 rounded-[100%] border-[#B48CDE] bg-white dark:bg-black
 bg-[radial-gradient(closest-side,#fff_82%,#000000)]
 dark:bg-[radial-gradient(closest-side,#000_82%,#ffffff)]
 animate-fade-up"
 />

 {/ * Eyebrow */}
 {eyebrow && (

 <span
 className="text-sm text-gray-600 dark:text-gray-400 font-geist mx-auto px-5 py-2
 bg-gradient-to-tr from-zinc-300/5 via-gray-400/5 to-transparent
 border-[2px] border-gray-300/20 dark:border-white/5
 rounded-3xl w-fit tracking-tight uppercase flex items-center justify-center"
 >
 {eyebrow}
 <ChevronRight className="inline w-4 h-4 ml-2 transition-transform duration-300
group-hover:translate-x-1" />

)}

 {/ * Title */}
 <h1
 className="animate-fade-in -translate-y-4 text-balance
 bg-gradient-to-br from-black from-30% to-black/40

```

```

 bg-clip-text py-6 text-5xl font-semibold leading-none tracking-tighter
 text-transparent opacity-0 sm:text-6xl md:text-7xl lg:text-8xl
 dark:from-white dark:to-white/40"
 >
 {title}
 </h1>

 {/ * Subtitle */}
 <p
 className="animate-fade-in mb-12 -translate-y-4 text-balance
 text-lg tracking-tight text-gray-600 dark:text-gray-400
 opacity-0 md:text-xl"
 >
 {subtitle}
 </p>

 {/ * CTA */}
 {ctaLabel && (
 <div className="flex justify-center">
 <Button
 asChild
 className="mt-[-20px] w-fit md:w-52 z-20 font-geist tracking-tighter text-center text-lg"
 >
 {ctaLabel}
 </Button>
 </div>
)}

 {/ * Bottom Fade */}
 <div
 className="animate-fade-up relative mt-32 opacity-0 [perspective:2000px]
 after:absolute after:inset-0 after:z-50
 after:[background:linear-gradient(to_top,hsl(var(--background))_10%,transparent)]"
 />
</section>
)
}

```

demo.tsx

```

import { Hero } from "@/components/ui/hero-1";

export default function DemoOne() {
 return (
 <Hero title="Build smarter tools for modern teams"
 subtitle="Streamline your workflow and boost productivity with intuitive solutions. Security,
 speed, and simplicity—all in one platform."
 eyebrow="Next-Gen Productivity"
 ctaLabel="Get Started"
 ctaHref="#" />
);
}

```

```
}
```

```
...
```

Copy-paste these files for dependencies:

```
```tsx
```

```
shadcn/button
```

```
import * as React from "react"
```

```
import { Slot } from "@radix-ui/react-slot"
```

```
import { cva, type VariantProps } from "class-variance-authority"
```

```
import { cn } from "@lib/utils"
```

```
const buttonVariants = cva(
```

```
  "inline-flex items-center justify-center whitespace-nowrap rounded-md text-sm font-medium
```

```
  ring-offset-background transition-colors focus-visible:outline-none focus-visible:ring-2
```

```
  focus-visible:ring-ring focus-visible:ring-offset-2 disabled:pointer-events-none
```

```
  disabled:opacity-50",
```

```
{
```

```
  variants: {
```

```
    variant: {
```

```
      default: "bg-primary text-primary-foreground hover:bg-primary/90",
```

```
      destructive:
```

```
        "bg-destructive text-destructive-foreground hover:bg-destructive/90",
```

```
      outline:
```

```
        "border border-input bg-background hover:bg-accent hover:text-accent-foreground",
```

```
      secondary:
```

```
        "bg-secondary text-secondary-foreground hover:bg-secondary/80",
```

```
      ghost: "hover:bg-accent hover:text-accent-foreground",
```

```
      link: "text-primary underline-offset-4 hover:underline",
```

```
    },
```

```
    size: {
```

```
      default: "h-10 px-4 py-2",
```

```
      sm: "h-9 rounded-md px-3",
```

```
      lg: "h-11 rounded-md px-8",
```

```
      icon: "h-10 w-10",
```

```
    },
```

```
  },
```

```
  defaultVariants: {
```

```
    variant: "default",
```

```
    size: "default",
```

```
  },
```

```
},
```

```
)
```

```
export interface ButtonProps
```

```
  extends React.ButtonHTMLAttributes<HTMLButtonElement>,
```

```
  VariantProps<typeof buttonVariants> {
```

```
  asChild?: boolean
```

```
}
```

```
const Button = React.forwardRef<HTMLButtonElement, ButtonProps>(
```

```

({ className, variant, size, asChild = false, ...props }, ref) => {
  const Comp = asChild ? Slot : "button"
  return (
    <Comp
      className={cn(buttonVariants({ variant, size, className })))
      ref={ref}
      {...props}
    />
  )
},
)
Button.displayName = "Button"

export { Button, buttonVariants }

...

```

Install NPM dependencies:

```

```bash
lucide-react, @radix-ui/react-slot, class-variance-authority
```

```

Extend existing Tailwind 4 index.css with this code (or if project uses Tailwind 3, extend tailwind.config.js or globals.css):

```

```css
@import "tailwindcss";
@import "tw-animate-css";

@keyframes fade-in {
 0% {
 opacity: 0;
 transform: translateY(20px);
 }
 100% {
 opacity: 1;
 transform: translateY(0);
 }
}

@keyframes fade-up {
 0% {
 opacity: 0;
 transform: translateY(40px);
 }
 100% {
 opacity: 1;
 transform: translateY(0);
 }
}
```

```

Implementation Guidelines

1. Analyze the component structure and identify all required dependencies
2. Review the component's arguments and state
3. Identify any required context providers or hooks and install them
4. Questions to Ask
 - What data/props will be passed to this component?
 - Are there any specific state management requirements?
 - Are there any required assets (images, icons, etc.)?
 - What is the expected responsive behavior?
 - What is the best place to use this component in the app?

Steps to integrate

0. Copy paste all the code above in the correct directories
1. Install external dependencies
2. Fill image assets with Unsplash stock images you know exist
3. Use lucide-react icons for svgs or logos if component requires them

Make the website with nicer font and gradient colors, and interactive premium elements. Use the given components across the website, I have given basic labeling on where you gotta use them. It needs to have a tech-y vibe and feel to it, it should be high converting

Do changes to the text of these components according to the narrative of the website and ensure high quality website copy

Section Component:

You are given a task to integrate an existing React component in the codebase

The codebase should support:

- shadcn project structure
- Tailwind CSS
- Typescript

If it doesn't, provide instructions on how to setup project via shadcn CLI, install Tailwind or Typescript.

Determine the default path for components and styles.

If default path for components is not /components/ui, provide instructions on why it's important to create this folder

Copy-paste this component to /components/ui folder:

```
``tsx
```

```
orbiting-circles.tsx
```

```
import { cn } from "@lib/utils"
```

```
export interface OrbitingCirclesProps {  
  className?: string  
  children?: React.ReactNode  
  reverse?: boolean  
  duration?: number  
  delay?: number  
  radius?: number  
  path?: boolean  
}
```

```
export function OrbitingCircles({  
  className,  
  children,  
  reverse,  
  duration = 20,  
  delay = 10,  
  radius = 50,  
  path = true,  
}: OrbitingCirclesProps) {  
  return (  
    <>  
      {path && (  
        <svg
```



```

    xmlns="http://www.w3.org/2000/svg"
    version="1.1"
    className="pointer-events-none absolute inset-0 size-full"
  >
    <circle
      className="stroke-black/10 stroke-1 dark:stroke-white/10"
      cx="50%"
      cy="50%"
      r={radius}
      fill="none"
    />
  </svg>
)}

<div
  style={
    {
      "--duration": duration,
      "--radius": radius,
      "--delay": -delay,
    } as React.CSSProperties
  }
  className={cn(
    "absolute flex transform-gpu animate-orbit items-center justify-center rounded-full border
    bg-black/10 [animation-delay:calc(var(--delay)*1000ms)] dark:bg-white/10",
    { "[animation-direction:reverse]": reverse },
    className,
  )}
  >
    {children}
  </div>
</>
)
}

```

demo.tsx

```
import { OrbitingCircles } from "@components/ui/orbiting-circles"
```

```
export function OrbitingCirclesDemo() {
```

```
  return (
```

```
    <div className="relative flex h-[500px] w-full flex-col items-center justify-center
    overflow-hidden rounded-lg border bg-background md:shadow-xl">
```

```
      <span className="pointer-events-none whitespace-pre-wrap bg-gradient-to-b from-black
    to-gray-300 bg-clip-text text-center text-8xl font-semibold leading-none text-transparent
    dark:from-white dark:to-black">
```

```
        Circles
```

```
      </span>
```

```
      { /* Inner Circles */ }
```

```
      <OrbitingCircles
```

```
        className="size-[30px] border-none bg-transparent"
```

```

    duration={20}
    delay={20}
    radius={80}
  >
    <Icons.whatsapp />
  </OrbitingCircles>
</OrbitingCircles>
  className="size-[30px] border-none bg-transparent"
  duration={20}
  delay={10}
  radius={80}
  >
    <Icons.notion />
  </OrbitingCircles>

  { /* Outer Circles (reverse) */ }
<OrbitingCircles>
  className="size-[50px] border-none bg-transparent"
  radius={190}
  duration={20}
  reverse
  >
    <Icons.googleDrive />
  </OrbitingCircles>
<OrbitingCircles>
  className="size-[50px] border-none bg-transparent"
  radius={190}
  duration={20}
  delay={20}
  reverse
  >
    <Icons.gitHub />
  </OrbitingCircles>
</div>
)
}

```

```

const Icons = {
  gitHub: () => (
    <svg width="100" height="100" viewBox="0 0 438.549 438.549">
      <path
        fill="currentColor"
        d="M409.132
114.573c-19.608-33.596-46.205-60.194-79.798-79.8-33.598-19.607-70.277-29.408-110.063-29.
408-39.781 0-76.472 9.804-110.063 29.408-33.596 19.605-60.192 46.204-79.8 79.8C9.803
148.168 0 184.854 0 224.63c0 47.78 13.94 90.745 41.827 128.906 27.884 38.164 63.906 64.572
108.063 79.227 5.14.954 8.945.283 11.419-1.996 2.475-2.282 3.711-5.14 3.711-8.562
0-.571-.049-5.708-.144-15.417a2549.81 2549.81 0 01-.144-25.406l-6.567
1.136c-4.187.767-9.469 1.092-15.846
1-6.374-.089-12.991-.757-19.842-1.999-6.854-1.231-13.229-4.086-19.13-8.559-5.898-4.473-10.
085-10.328-12.56-17.556l-2.855-6.57c-1.903-4.374-4.899-9.233-8.992-14.559-4.093-5.331-8.23
2-8.945-12.419-10.848l-1.999-1.431c-1.332-.951-2.568-2.098-3.711-3.429-1.142-1.331-1.997-2.

```

```

663-2.568-3.997-.572-1.335-.098-2.43 1.427-3.289 1.525-.859 4.281-1.276
8.28-1.276l5.708.853c3.807.763 8.516 3.042 14.133 6.851 5.614 3.806 10.229 8.754 13.846
14.842 4.38 7.806 9.657 13.754 15.846 17.847 6.184 4.093 12.419 6.136 18.699 6.136 6.28 0
11.704-.476 16.274-1.423 4.565-.952 8.848-2.383 12.847-4.285 1.713-12.758 6.377-22.559
13.988-29.41-10.848-1.14-20.601-2.857-29.264-5.14-8.658-2.286-17.605-5.996-26.835-11.14-9.
235-5.137-16.896-11.516-22.985-19.126-6.09-7.614-11.088-17.61-14.987-29.979-3.901-12.374-
5.852-26.648-5.852-42.826 0-23.035 7.52-42.637 22.557-58.817-7.044-17.318-6.379-36.732
1.997-58.24 5.52-1.715 13.706-.428 24.554 3.853 10.85 4.283 18.794 7.952 23.84 10.994 5.046
3.041 9.089 5.618 12.135 7.708 17.705-4.947 35.976-7.421 54.818-7.421s37.117 2.474 54.823
7.421l10.849-6.849c7.419-4.57 16.18-8.758 26.262-12.565 10.088-3.805 17.802-4.853
23.134-3.138 8.562 21.509 9.325 40.922 2.279 58.24 15.036 16.18 22.559 35.787 22.559 58.817
0 16.178-1.958 30.497-5.853 42.966-3.9 12.471-8.941 22.457-15.125 29.979-6.191 7.521-13.901
13.85-23.131 18.986-9.232 5.14-18.182 8.85-26.84 11.136-8.662 2.286-18.415 4.004-29.263
5.146 9.894 8.562 14.842 22.077 14.842 40.539v60.237c0 3.422 1.19 6.279 3.572 8.562 2.379
2.279 6.136 2.95 11.276 1.995 44.163-14.653 80.185-41.062 108.068-79.226 27.88-38.161
41.825-81.126 41.825-128.906-.01-39.771-9.818-76.454-29.414-110.049z"
/>
</svg>
),
notion: () => (
  <svg
    width="100"
    height="100"
    viewBox="0 0 100 100"
    fill="none"
    xmlns="http://www.w3.org/2000/svg"
  >
    <path
      d="M6.017 4.313l55.333 -4.087c6.797 -0.583 8.543 -0.19 12.817 2.917l17.663 12.443c2.913
2.14 3.883 2.723 3.883 5.053v68.243c0 4.277 -1.553 6.807 -6.99 7.193l24.467 99.967c-4.08
0.193 -6.023 -0.39 -8.16 -3.113l3.3 79.94c-2.333 -3.113 -3.3 -5.443 -3.3 -8.167v11.113c0 -3.497
1.553 -6.413 6.017 -6.8z"
      fill="#ffffff"
    />
    <path
      d="M61.35 0.227l-55.333 4.087C1.553 4.7 0 7.617 0 11.113v60.66c0 2.723 0.967 5.053 3.3
8.167l13.007 16.913c2.137 2.723 4.08 3.307 8.16 3.113l64.257 -3.89c5.433 -0.387 6.99 -2.917
6.99 -7.193V20.64c0 -2.21 -0.873 -2.847 -3.443 -4.733l74.167 3.143c-4.273 -3.107 -6.02 -3.5
-12.817 -2.917zM25.92 19.523c-5.247 0.353 -6.437 0.433 -9.417 -1.99l8.927 11.507c-0.77 -0.78
-0.383 -1.753 1.557 -1.947l53.193 -3.887c4.467 -0.39 6.793 1.167 8.54 2.527l9.123 6.61c0.39
0.197 1.36 1.36 0.193 1.36l-54.933 3.307 -0.68 0.047zM19.803 88.3V30.367c0 -2.53 0.777 -3.697
3.103 -3.893l86 22.78c2.14 -0.193 3.107 1.167 3.107 3.693v57.547c0 2.53 -0.39 4.67 -3.883
4.863l-60.377 3.5c-3.493 0.193 -5.043 -0.97 -5.043 -4.083zm59.6 -54.827c0.387 1.75 0 3.5 -1.75
3.7l-2.91 0.577v42.773c-2.527 1.36 -4.853 2.137 -6.797 2.137 -3.107 0 -3.883 -0.973 -6.21
-3.887l-19.03 -29.94v28.967l6.02 1.363s0 3.5 -4.857 3.5l-13.39 0.777c-0.39 -0.78 0 -2.723 1.357
-3.113l3.497 -0.97v-38.3l30.48 40.667c-0.39 -1.75 0.58 -4.277 3.3 -4.473l14.367 -0.967 19.8
30.327v-26.83l-5.047 -0.58c-0.39 -2.143 1.163 -3.7 3.103 -3.89l13.4 -0.78z"
      fill="#000000"
      fillRule="evenodd"
      clipRule="evenodd"
    />
  </svg>

```

```

),
openai: () => (
  <svg
    width="100"
    height="100"
    viewBox="0 0 24 24"
    xmlns="http://www.w3.org/2000/svg"
  >
    <path d="M22.2819 9.8211a5.9847 5.9847 0 0 0-.5157-4.9108 6.0462 6.0462 0 0
0-6.5098-2.9A6.0651 6.0651 0 0 0 4.9807 4.1818a5.9847 5.9847 0 0 0-3.9977 2.9 6.0462 6.0462
0 0 0 .7427 7.0966 5.98 5.98 0 0 0 .511 4.9107 6.051 6.051 0 0 0 6.5146 2.9001A5.9847 5.9847 0
0 0 13.2599 24a6.0557 6.0557 0 0 0 5.7718-4.2058 5.9894 5.9894 0 0 0 3.9977-2.9001 6.0557
6.0557 0 0 0-.7475-7.0729zm-9.022 12.6081a4.4755 4.4755 0 0 1-2.8764-1.0408l.1419-.0804
4.7783-2.7582a.7948.7948 0 0 0 .3927-.6813v-6.7369l2.02 1.1686a.071.071 0 0 1
.038.052v5.5826a4.504 4.504 0 0 1-4.4945 4.4944zm-9.6607-4.1254a4.4708 4.4708 0 0
1-.5346-3.0137l.142.0852 4.783 2.7582a.7712.7712 0 0 0 .7806
0l5.8428-3.3685v2.3324a.0804.0804 0 0 1-.0332.0615L9.74 19.9502a4.4992 4.4992 0 0
1-6.1408-1.6464zM2.3408 7.8956a4.485 4.485 0 0 1 2.3655-1.9728V11.6a.7664.7664 0 0 0
.3879.6765l5.8144 3.3543-2.0201 1.1685a.0757.0757 0 0 1-.071 0l-4.8303-2.7865A4.504 4.504 0
0 1 2.3408 7.872zm16.5963 3.8558L13.1038 8.364 15.1192 7.2a.0757.0757 0 0 1 .071 0l4.8303
2.7913a4.4944 4.4944 0 0 1-.6765 8.1042v-5.6772a.79.79 0 0
0-.407-.667zm2.0107-3.0231l-.142-.0852-4.7735-2.7818a.7759.7759 0 0 0-.7854 0L9.409
9.2297V6.8974a.0662.0662 0 0 1 .0284-.0615l4.8303-2.7866a4.4992 4.4992 0 0 1 6.6802
4.66zM8.3065 12.863l-2.02-1.1638a.0804.0804 0 0 1-.038-.0567V6.0742a4.4992 4.4992 0 0 1
7.3757-3.4537l-.142.0805L8.704 5.459a.7948.7948 0 0
0-.3927.6813zm1.0976-2.3654l2.602-1.4998 2.6069 1.4998v2.9994l-2.5974
1.4997-2.6067-1.4997Z" />
  </svg>
),
googleDrive: () => (
  <svg
    width="100"
    height="100"
    viewBox="0 0 87.3 78"
    xmlns="http://www.w3.org/2000/svg"
  >
    <path
      d="m6.6 66.85 3.85 6.65c.8 1.4 1.95 2.5 3.3 3.3l13.75-23.8h-27.5c0 1.55.4 3.1 1.2 4.5z"
      fill="#0066da"
    />
    <path
      d="m43.65 25-13.75-23.8c-1.35-.8-2.5-1.9-3.3-3.3l-25.4 44a9.06 9.06 0 0 0 -1.2 4.5h27.5z"
      fill="#00ac47"
    />
    <path
      d="m73.55 76.8c1.35-.8 2.5-1.9 3.3-3.3l1.6-2.75 7.65-13.25c.8-1.4 1.2-2.95
1.2-4.5h-27.502l5.852 11.5z"
      fill="#ea4335"
    />
    <path
      d="m43.65 25 13.75-23.8c-1.35-.8-2.9-1.2-4.5-1.2h-18.5c-1.6 0-3.15.45-4.5 1.2z"
      fill="#00832d"
    />
  >

```

```

/>
<path
  d="m59.8 53h-32.3l-13.75 23.8c1.35.8 2.9 1.2 4.5 1.2h50.8c1.6 0 3.15-.45 4.5-1.2z"
  fill="#2684fc"
/>
<path
  d="m73.4 26.5-12.7-22c-.8-1.4-1.95-2.5-3.3-3.3l-13.75 23.8 16.15
28h27.45c0-1.55-.4-3.1-1.2-4.5z"
  fill="#ffba00"
/>
</svg>
),
whatsapp: () => (
  <svg
    width="100"
    height="100"
    viewBox="0 0 175.216 175.552"
    xmlns="http://www.w3.org/2000/svg"
  >
    <defs>
      <linearGradient
        id="b"
        x1="85.915"
        x2="86.535"
        y1="32.567"
        y2="137.092"
        gradientUnits="userSpaceOnUse"
      >
        <stop offset="0" stopColor="#57d163" />
        <stop offset="1" stopColor="#23b33a" />
      </linearGradient>
      <filter
        id="a"
        width="1.115"
        height="1.114"
        x="-.057"
        y="-.057"
        colorInterpolationFilters="sRGB"
      >
        <feGaussianBlur stdDeviation="3.531" />
      </filter>
    </defs>
    <path
      d="m54.532 138.45 2.235 1.324c9.387 5.571 20.15 8.518 31.126 8.523h.023c33.707 0
61.139-27.426 61.153-61.135.006-16.335-6.349-31.696-17.895-43.251A60.75 60.75 0 0 0 87.94
25.983c-33.733 0-61.166 27.423-61.178 61.13a60.98 60.98 0 0 0 9.349 32.535l1.455 2.312-6.179
22.558zm-40.811 23.544L24.16 123.88c-6.438-11.154-9.825-23.808-9.821-36.772.017-40.556
33.021-73.55 73.578-73.55 19.681.01 38.154 7.669 52.047 21.572s21.537 32.383 21.53
52.037c-.018 40.553-33.027 73.553-73.578
73.553h-.032c-12.313-.005-24.412-3.094-35.159-8.954zm0 0"
      fill="#b3b3b3"
      filter="url(#a)"
    >

```

```

    />
    <path
      d="m12.966 161.238 10.439-38.114a73.42 73.42 0 0 1-9.821-36.772c.017-40.556
33.021-73.55 73.578-73.55 19.681.01 38.154 7.669 52.047 21.572s21.537 32.383 21.53
52.037c-.018 40.553-33.027 73.553-73.578
73.553h-.032c-12.313-.005-24.412-3.094-35.159-8.954z"
      fill="#ffffff"
    />
    <path
      d="M87.184 25.227c-33.733 0-61.166 27.423-61.178 61.13a60.98 60.98 0 0 0 9.349
32.535l1.455 2.312-6.179 22.559 23.146-6.069 2.235 1.324c9.387 5.571 20.15 8.518 31.126
8.524h.023c33.707 0 61.14-27.426 61.153-61.135a60.75 60.75 0 0 0-17.895-43.251 60.75 60.75
0 0 0-43.235-17.929z"
      fill="url(#linearGradient1780)"
    />
    <path
      d="M87.184 25.227c-33.733 0-61.166 27.423-61.178 61.13a60.98 60.98 0 0 0 9.349
32.535l1.455 2.313-6.179 22.558 23.146-6.069 2.235 1.324c9.387 5.571 20.15 8.517 31.126
8.523h.023c33.707 0 61.14-27.426 61.153-61.135a60.75 60.75 0 0 0-17.895-43.251 60.75 60.75
0 0 0-43.235-17.928z"
      fill="url(#b)"
    />
    <path
      d="M68.772 55.603c-1.378-3.061-2.828-3.123-4.137-3.176l-3.524-.043c-1.226
0-3.218.46-4.902 2.3s-6.435 6.287-6.435 15.332 6.588 17.785 7.506 19.013 12.718 20.381
31.405 27.75c15.529 6.124 18.689 4.906 22.061 4.6s10.877-4.447 12.408-8.74 1.532-7.971
1.073-8.74-1.685-1.226-3.525-2.146-10.877-5.367-12.562-5.981-2.91-.919-4.137.921-4.746
5.979-5.819 7.206-2.144
1.381-3.984.462-7.76-2.861-14.784-9.124c-5.465-4.873-9.154-10.891-10.228-12.73s-.114-2.835
.808-3.751c.825-.824 1.838-2.147 2.759-3.22s1.224-1.84
1.836-3.065.307-2.301-.153-3.22-4.032-10.011-5.666-13.647"
      fill="#ffffff"
      fillRule="evenodd"
    />
  </svg>
),
}
...

```

Extend existing tailwind.config.js with this code:

```

```js
/** @type {import('tailwindcss').Config} */
module.exports = {
 theme: {
 extend: {
 animation: {
 orbit: "orbit calc(var(--duration)*1s) linear infinite",
 },
 keyframes: {
 orbit: {
 "0%": {

```

```

 transform:
 "rotate(0deg) translateY(calc(var(--radius) * 1px)) rotate(0deg)",
 },
 "100%": {
 transform:
 "rotate(360deg) translateY(calc(var(--radius) * 1px)) rotate(-360deg)",
 },
 },
},
},
},
},
};
'''

```

### Implementation Guidelines

1. Analyze the component structure and identify all required dependencies
2. Review the component's arguments and state
3. Identify any required context providers or hooks and install them
4. Questions to Ask
  - What data/props will be passed to this component?
  - Are there any specific state management requirements?
  - Are there any required assets (images, icons, etc.)?
  - What is the expected responsive behavior?
  - What is the best place to use this component in the app?

### Steps to integrate

0. Copy paste all the code above in the correct directories
1. Install external dependencies
2. Fill image assets with Unsplash stock images you know exist
3. Use lucide-react icons for svgs or logos if component requires them

### Footer or Near:

You are given a task to integrate an existing React component in the codebase

The codebase should support:

- shadcn project structure
- Tailwind CSS
- Typescript

If it doesn't, provide instructions on how to setup project via shadcn CLI, install Tailwind or Typescript.

Determine the default path for components and styles.

If default path for components is not /components/ui, provide instructions on why it's important to create this folder

Copy-paste this component to /components/ui folder:

```
``tsx
lamp.tsx
"use client";
import React from "react";
import { motion } from "framer-motion";
import { cn } from "@/lib/utils";

export function LampDemo() {
 return (
 <LampContainer>
 <motion.h1
 initial={{ opacity: 0.5, y: 100 }}
 whileInView={{ opacity: 1, y: 0 }}
 transition={{
 delay: 0.3,
 duration: 0.8,
 ease: "easeInOut",
 }}
 className="mt-8 bg-gradient-to-br from-slate-300 to-slate-500 py-4 bg-clip-text text-center
text-4xl font-medium tracking-tight text-transparent md:text-7xl"
 >
 Build lamps
 the right way
 </motion.h1>
 </LampContainer>
);
}

export const LampContainer = ({
 children,
 className,
}: {
 children: React.ReactNode;
 className?: string;
}) => {
 return (
 <div
 className={cn(
 "relative flex min-h-screen flex-col items-center justify-center overflow-hidden bg-slate-950
w-full rounded-md z-0",
 className
)}
 >
 <div className="relative flex w-full flex-1 scale-y-125 items-center justify-center isolate z-0"
 >
 <motion.div
 initial={{ opacity: 0.5, width: "15rem" }}
 whileInView={{ opacity: 1, width: "30rem" }}
 transition={{
 delay: 0.3,
 duration: 0.8,
 ease: "easeInOut",
 }}
 >
```



```

 }}
 style={{
 backgroundImage: `conic-gradient(var(--conic-position), var(--tw-gradient-stops))`,
 }}
 className="absolute inset-auto right-1/2 h-56 overflow-visible w-[30rem]
bg-gradient-conic from-cyan-500 via-transparent to-transparent text-white
[--conic-position:from_70deg_at_center_top]"
 >
 <div className="absolute w-[100%] left-0 bg-slate-950 h-40 bottom-0 z-20
[mask-image:linear-gradient(to_top,white,transparent)]" />
 <div className="absolute w-40 h-[100%] left-0 bg-slate-950 bottom-0 z-20
[mask-image:linear-gradient(to_right,white,transparent)]" />
 </motion.div>
<motion.div
 initial={{ opacity: 0.5, width: "15rem" }}
 whileInView={{ opacity: 1, width: "30rem" }}
 transition={{
 delay: 0.3,
 duration: 0.8,
 ease: "easeInOut",
 }}
 style={{
 backgroundImage: `conic-gradient(var(--conic-position), var(--tw-gradient-stops))`,
 }}
 className="absolute inset-auto left-1/2 h-56 w-[30rem] bg-gradient-conic
from-transparent via-transparent to-cyan-500 text-white
[--conic-position:from_290deg_at_center_top]"
 >
 <div className="absolute w-40 h-[100%] right-0 bg-slate-950 bottom-0 z-20
[mask-image:linear-gradient(to_left,white,transparent)]" />
 <div className="absolute w-[100%] right-0 bg-slate-950 h-40 bottom-0 z-20
[mask-image:linear-gradient(to_top,white,transparent)]" />
 </motion.div>
 <div className="absolute top-1/2 h-48 w-full translate-y-12 scale-x-150 bg-slate-950
blur-2xl"></div>
 <div className="absolute top-1/2 z-50 h-48 w-full bg-transparent opacity-10
backdrop-blur-md"></div>
 <div className="absolute inset-auto z-50 h-36 w-[28rem] -translate-y-1/2 rounded-full
bg-cyan-500 opacity-50 blur-3xl"></div>
 <motion.div
 initial={{ width: "8rem" }}
 whileInView={{ width: "16rem" }}
 transition={{
 delay: 0.3,
 duration: 0.8,
 ease: "easeInOut",
 }}
 className="absolute inset-auto z-30 h-36 w-64 -translate-y-[6rem] rounded-full
bg-cyan-400 blur-2xl"
 ></motion.div>
 <motion.div
 initial={{ width: "15rem" }}

```

```

whileInView={{ width: "30rem" }}
transition={{
 delay: 0.3,
 duration: 0.8,
 ease: "easeInOut",
}}
className="absolute inset-auto z-50 h-0.5 w-[30rem] -translate-y-[7rem] bg-cyan-400 "
></motion.div>

<div className="absolute inset-auto z-40 h-44 w-full -translate-y-[12.5rem] bg-slate-950
"></div>
</div>

<div className="relative z-50 flex -translate-y-80 flex-col items-center px-5">
 {children}
</div>
</div>
);
};

demo.tsx
"use client";
import React from "react";
import { motion } from "framer-motion";
import { LampContainer } from "@/components/ui/lamp";

export function LampDemo() {
 return (
 <LampContainer>
 <motion.h1
 initial={{ opacity: 0.5, y: 100 }}
 whileInView={{ opacity: 1, y: 0 }}
 transition={{
 delay: 0.3,
 duration: 0.8,
 ease: "easeInOut",
 }}
 className="mt-8 bg-gradient-to-br from-slate-300 to-slate-500 py-4 bg-clip-text text-center
text-4xl font-medium tracking-tight text-transparent md:text-7xl"
 >
 Build lamps
 the right way
 </motion.h1>
 </LampContainer>
);
}

...

```

Install NPM dependencies:

```

```bash
framer-motion

```

...

Implementation Guidelines

1. Analyze the component structure and identify all required dependencies
2. Review the component's arguments and state
3. Identify any required context providers or hooks and install them
4. Questions to Ask
 - What data/props will be passed to this component?
 - Are there any specific state management requirements?
 - Are there any required assets (images, icons, etc.)?
 - What is the expected responsive behavior?
 - What is the best place to use this component in the app?

Steps to integrate

0. Copy paste all the code above in the correct directories
1. Install external dependencies
2. Fill image assets with Unsplash stock images you know exist
3. Use lucide-react icons for svgs or logos if component requires them

Testimonials Component:

You are given a task to integrate an existing React component in the codebase

The codebase should support:

- shadcn project structure
- Tailwind CSS
- Typescript

If it doesn't, provide instructions on how to setup project via shadcn CLI, install Tailwind or Typescript.

Determine the default path for components and styles.

If default path for components is not /components/ui, provide instructions on why it's important to create this folder

Copy-paste this component to /components/ui folder:

```
``tsx
```

```
testimonials-columns-1.tsx
```

```
"use client";
```

```
import React from "react";
```

```
import { motion } from "motion/react";
```

```
export const TestimonialsColumn = (props: {  
  className?: string;  
  testimonials: typeof testimonials;  
  duration?: number;  
}) => {  
  return (  
    <div className={props.className}>  
      <motion.div
```

```

    animate={{
      translateY: "-50%",
    }}
    transition={{
      duration: props.duration || 10,
      repeat: Infinity,
      ease: "linear",
      repeatType: "loop",
    }}
    className="flex flex-col gap-6 pb-6 bg-background"
  >
    {[
      ...new Array(2).fill(0).map( (_, index) => (
        <React.Fragment key={index}>
          {props.testimonials.map(({ text, image, name, role }, i) => (
            <div className="p-10 rounded-3xl border shadow-lg shadow-primary/10 max-w-xs
w-full" key={i}>
              <div>{text}</div>
              <div className="flex items-center gap-2 mt-5">
                <img
                  width={40}
                  height={40}
                  src={image}
                  alt={name}
                  className="h-10 w-10 rounded-full"
                />
                <div className="flex flex-col">
                  <div className="font-medium tracking-tight leading-5">{name}</div>
                  <div className="leading-5 opacity-60 tracking-tight">{role}</div>
                </div>
              </div>
            </div>
          ))}
        </React.Fragment>
      )],
    ]}
  </motion.div>
</div>
);
};
;

```

demo.tsx

```

import { TestimonialsColumn } from "@components/ui/testimonials-columns-1";
import { motion } from "motion/react";

```

```

const testimonials = [
  {
    text: "This ERP revolutionized our operations, streamlining finance and inventory. The
cloud-based platform keeps us productive, even remotely.",
    image: "https://randomuser.me/api/portraits/women/1.jpg",
  }
]

```

```
name: "Briana Patton",
role: "Operations Manager",
},
{
  text: "Implementing this ERP was smooth and quick. The customizable, user-friendly interface
made team training effortless.",
  image: "https://randomuser.me/api/portraits/men/2.jpg",
  name: "Bilal Ahmed",
  role: "IT Manager",
},
{
  text: "The support team is exceptional, guiding us through setup and providing ongoing
assistance, ensuring our satisfaction.",
  image: "https://randomuser.me/api/portraits/women/3.jpg",
  name: "Saman Malik",
  role: "Customer Support Lead",
},
{
  text: "This ERP's seamless integration enhanced our business operations and efficiency. Highly
recommend for its intuitive interface.",
  image: "https://randomuser.me/api/portraits/men/4.jpg",
  name: "Omar Raza",
  role: "CEO",
},
{
  text: "Its robust features and quick support have transformed our workflow, making us
significantly more efficient.",
  image: "https://randomuser.me/api/portraits/women/5.jpg",
  name: "Zainab Hussain",
  role: "Project Manager",
},
{
  text: "The smooth implementation exceeded expectations. It streamlined processes, improving
overall business performance.",
  image: "https://randomuser.me/api/portraits/women/6.jpg",
  name: "Aliza Khan",
  role: "Business Analyst",
},
{
  text: "Our business functions improved with a user-friendly design and positive customer
feedback.",
  image: "https://randomuser.me/api/portraits/men/7.jpg",
  name: "Farhan Siddiqui",
  role: "Marketing Director",
},
{
  text: "They delivered a solution that exceeded expectations, understanding our needs and
enhancing our operations.",
  image: "https://randomuser.me/api/portraits/women/8.jpg",
  name: "Sana Sheikh",
  role: "Sales Manager",
},
},
```

```
{
  text: "Using this ERP, our online presence and conversions significantly improved, boosting
business performance.",
  image: "https://randomuser.me/api/portraits/men/9.jpg",
  name: "Hassan Ali",
  role: "E-commerce Manager",
},
];
```

```
const firstColumn = testimonials.slice(0, 3);
const secondColumn = testimonials.slice(3, 6);
const thirdColumn = testimonials.slice(6, 9);
```

```
const Testimonials = () => {
  return (
    <section className="bg-background my-20 relative">

      <div className="container z-10 mx-auto">
        <motion.div
          initial={{ opacity: 0, y: 20 }}
          whileInView={{ opacity: 1, y: 0 }}
          transition={{ duration: 0.8, delay: 0.1, ease: [0.16, 1, 0.3, 1] }}
          viewport={{ once: true }}
          className="flex flex-col items-center justify-center max-w-[540px] mx-auto"
        >
          <div className="flex justify-center">
            <div className="border py-1 px-4 rounded-lg">Testimonials</div>
          </div>

          <h2 className="text-xl sm:text-2xl md:text-3xl lg:text-4xl xl:text-5xl font-bold
tracking-tighter mt-5">
            What our users say
          </h2>
          <p className="text-center mt-5 opacity-75">
            See what our customers have to say about us.
          </p>
        </motion.div>

        <div className="flex justify-center gap-6 mt-10
[mask-image:linear-gradient(to_bottom,transparent,black_25%,black_75%,transparent)]
max-h-[740px] overflow-hidden">
          <TestimonialsColumn testimonials={firstColumn} duration={15} />
          <TestimonialsColumn testimonials={secondColumn} className="hidden md:block"
duration={19} />
          <TestimonialsColumn testimonials={thirdColumn} className="hidden lg:block"
duration={17} />
        </div>
      </div>
    </section>
  );
};
```

```
};  
  
export default { Testimonials };  
'''
```

Install NPM dependencies:

```
'''bash  
motion  
'''
```

Implementation Guidelines

1. Analyze the component structure and identify all required dependencies
2. Review the component's arguments and state
3. Identify any required context providers or hooks and install them
4. Questions to Ask
 - What data/props will be passed to this component?
 - Are there any specific state management requirements?
 - Are there any required assets (images, icons, etc.)?
 - What is the expected responsive behavior?
 - What is the best place to use this component in the app?

Steps to integrate

0. Copy paste all the code above in the correct directories
1. Install external dependencies
2. Fill image assets with Unsplash stock images you know exist
3. Use lucide-react icons for svgs or logos if component requires them

Component Robot:

You are given a task to integrate an existing React component in the codebase

The codebase should support:

- shadcn project structure
- Tailwind CSS
- Typescript

If it doesn't, provide instructions on how to setup project via shadcn CLI, install Tailwind or Typescript.

Determine the default path for components and styles.

If default path for components is not /components/ui, provide instructions on why it's important to create this folder

Copy-paste this component to /components/ui folder:

```
'''tsx  
splite.tsx  
'use client'
```

```

import { Suspense, lazy } from 'react'
const Spline = lazy(() => import('@splinetool/react-spline'))

interface SplineSceneProps {
  scene: string
  className?: string
}

export function SplineScene({ scene, className }: SplineSceneProps) {
  return (
    <Suspense
      fallback={
        <div className="w-full h-full flex items-center justify-center">
          <span className="loader"></span>
        </div>
      }
    >
      <Spline
        scene={scene}
        className={className}
      />
    </Suspense>
  )
}

```

demo.tsx
'use client'

```

import { SplineScene } from "@components/ui/splite";
import { Card } from "@components/ui/card"
import { Spotlight } from "@components/ui/spotlight"

```

```

export function SplineSceneBasic() {
  return (
    <Card className="w-full h-[500px] bg-black/[0.96] relative overflow-hidden">
      <Spotlight
        className="-top-40 left-0 md:left-60 md:-top-20"
        fill="white"
      />

      <div className="flex h-full">
        {/* Left content */}
        <div className="flex-1 p-8 relative z-10 flex flex-col justify-center">
          <h1 className="text-4xl md:text-5xl font-bold bg-clip-text text-transparent
            bg-gradient-to-b from-neutral-50 to-neutral-400">
            Interactive 3D
          </h1>
          <p className="mt-4 text-neutral-300 max-w-lg">
            Bring your UI to life with beautiful 3D scenes. Create immersive experiences
            that capture attention and enhance your design.
          </p>
        </div>
      </div>
    </Card>
  )
}

```



```

</div>

  { /* Right content */
  <div className="flex-1 relative">
    <SplineScene
      scene="https://prod.spline.design/kZDDjO5HuC9GJUM2/scene.splinecode"
      className="w-full h-full"
    />
  </div>
</div>
</Card>
)
}
...

```

Copy-paste these files for dependencies:

```
``tsx
```

```
acernity/spotlight
```

```
import React from "react";
```

```
import { cn } from "@lib/utils";
```

```

type SpotlightProps = {
  className?: string;
  fill?: string;
};

```

```

export const Spotlight = ({ className, fill }: SpotlightProps) => {
  return (
    <svg
      className={cn(
        "animate-spotlight pointer-events-none absolute z-[1] h-[169%] w-[138%] lg:w-[84%]
        opacity-0",
        className
      )}
      xmlns="http://www.w3.org/2000/svg"
      viewBox="0 0 3787 2842"
      fill="none"
    >
      <g filter="url(#filter)">
        <ellipse
          cx="1924.71"
          cy="273.501"
          rx="1924.71"
          ry="273.501"
          transform="matrix(-0.822377 -0.568943 -0.568943 0.822377 3631.88 2291.09)"
          fill={fill || "white"}
          fillOpacity="0.21"
        ></ellipse>
      </g>
      <defs>
        <filter
          id="filter"

```

```

    x="0.860352"
    y="0.838989"
    width="3785.16"
    height="2840.26"
    filterUnits="userSpaceOnUse"
    colorInterpolationFilters="sRGB"
  >
    <feFlood floodOpacity="0" result="BackgroundImageFix"></feFlood>
    <feBlend
      mode="normal"
      in="SourceGraphic"
      in2="BackgroundImageFix"
      result="shape"
    ></feBlend>
    <feGaussianBlur
      stdDeviation="151"
      result="effect1_foregroundBlur_1065_8"
    ></feGaussianBlur>
  </filter>
</defs>
</svg>
);
};

...
```tsx
ibelick/spotlight
'use client';
import React, { useRef, useState, useCallback, useEffect } from 'react';
import { motion, useSpring, useTransform, SpringOptions } from 'framer-motion';
import { cn } from '@lib/utls';

type SpotlightProps = {
 className?: string;
 size?: number;
 springOptions?: SpringOptions;
};

export function Spotlight({
 className,
 size = 200,
 springOptions = { bounce: 0 },
}: SpotlightProps) {
 const containerRef = useRef<HTMLDivElement>(null);
 const [isHovered, setIsHovered] = useState(false);
 const [parentElement, setParentElement] = useState<HTMLElement | null>(null);

 const mouseX = useSpring(0, springOptions);
 const mouseY = useSpring(0, springOptions);

 const spotlightLeft = useTransform(mouseX, (x) => `${x - size / 2}px`);
 const spotlightTop = useTransform(mouseY, (y) => `${y - size / 2}px`);

```

```

useEffect(() => {
 if (containerRef.current) {
 const parent = containerRef.current.parentElement;
 if (parent) {
 parent.style.position = 'relative';
 parent.style.overflow = 'hidden';
 setParentElement(parent);
 }
 }
}, []);

```

```

const handleMouseMove = useCallback(
 (event: MouseEvent) => {
 if (!parentElement) return;
 const { left, top } = parentElement.getBoundingClientRect();
 mouseX.set(event.clientX - left);
 mouseY.set(event.clientY - top);
 },
 [mouseX, mouseY, parentElement]
);

```

```

useEffect(() => {
 if (!parentElement) return;

 parentElement.addEventListener('mousemove', handleMouseMove);
 parentElement.addEventListener('mouseenter', () => setIsHovered(true));
 parentElement.addEventListener('mouseleave', () => setIsHovered(false));

```

```

 return () => {
 parentElement.removeEventListener('mousemove', handleMouseMove);
 parentElement.removeEventListener('mouseenter', () => setIsHovered(true));
 parentElement.removeEventListener('mouseleave', () =>
 setIsHovered(false)
);
 };
}, [parentElement, handleMouseMove]);

```

```

return (
 <motion.div
 ref={containerRef}
 className={cn(
 'pointer-events-none absolute rounded-full
bg-[radial-gradient(circle_at_center,var(--tw-gradient-stops),transparent_80%)] blur-xl
transition-opacity duration-200',
 'from-zinc-50 via-zinc-100 to-zinc-200',
 isHovered ? 'opacity-100' : 'opacity-0',
 className
)}
 style={{
 width: size,
 height: size,

```

```

 left: spotlightLeft,
 top: spotlightTop,
 }}
 />
);
}

""
""tsx
shadcn/card
import * as React from "react"

import { cn } from "@/lib/utils"

const Card = React.forwardRef<
 HTMLDivElement,
 React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
 <div
 ref={ref}
 className={cn(
 "rounded-lg border bg-card text-card-foreground shadow-sm",
 className,
)}
 {...props}
 />
))
Card.displayName = "Card"

const CardHeader = React.forwardRef<
 HTMLDivElement,
 React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
 <div
 ref={ref}
 className={cn("flex flex-col space-y-1.5 p-6", className)}
 {...props}
 />
))
CardHeader.displayName = "CardHeader"

const CardTitle = React.forwardRef<
 HTMLParagraphElement,
 React.HTMLAttributes<HTMLHeadingElement>
>(({ className, ...props }, ref) => (
 <h3
 ref={ref}
 className={cn(
 "text-2xl font-semibold leading-none tracking-tight",
 className,
)}
 {...props}

```

```

 />
))
 CardTitle.displayName = "CardTitle"

 const CardDescription = React.forwardRef<
 HTMLParagraphElement,
 React.HTMLAttributes<HTMLParagraphElement>
 >(({ className, ...props }, ref) => (
 <p
 ref={ref}
 className={cn("text-sm text-muted-foreground", className)}
 {...props}
 />
))
 CardDescription.displayName = "CardDescription"

 const CardContent = React.forwardRef<
 HTMLDivElement,
 React.HTMLAttributes<HTMLDivElement>
 >(({ className, ...props }, ref) => (
 <div ref={ref} className={cn("p-6 pt-0", className)} {...props} />
))
 CardContent.displayName = "CardContent"

 const CardFooter = React.forwardRef<
 HTMLDivElement,
 React.HTMLAttributes<HTMLDivElement>
 >(({ className, ...props }, ref) => (
 <div
 ref={ref}
 className={cn("flex items-center p-6 pt-0", className)}
 {...props}
 />
))
 CardFooter.displayName = "CardFooter"

 export { Card, CardHeader, CardFooter, CardTitle, CardDescription, CardContent }

```

...

Install NPM dependencies:

```

""bash
@splinetool/runtime, @splinetool/react-spline, framer-motion
""

```

### Implementation Guidelines

1. Analyze the component structure and identify all required dependencies
2. Review the component's arguments and state
3. Identify any required context providers or hooks and install them
4. Questions to Ask
  - What data/props will be passed to this component?
  - Are there any specific state management requirements?

- Are there any required assets (images, icons, etc.)?
- What is the expected responsive behavior?
- What is the best place to use this component in the app?

#### Steps to integrate

0. Copy paste all the code above in the correct directories
1. Install external dependencies
2. Fill image assets with Unsplash stock images you know exist
3. Use lucide-react icons for svgs or logos if component requires them

