

AI-Driven Test Automation Framework

For Web Applications · Powered by Kiro + Playwright

Client Deliverables Package

Milestone Technologies — QA Automation Team

August 2026

Contents

1. Case Study / Point of View
2. Demo / Presentation
3. Metrics Report
4. Workflow Walkthrough
5. Framework Documentation

1. Case Study / Point of View

Executive Summary

We built a **general-purpose, AI-orchestrated test automation framework** using **Kiro** and **Playwright** that automates functional testing for **any web application**. The

framework converts requirements — from Jira tickets, user stories, or documents — into working, self-healing automated tests in minutes rather than days.

To prove its capability, we applied it to one of the hardest automation targets in the industry: a **Salesforce Experience Cloud application**. If the framework can handle Salesforce's complex Shadow DOM, it can handle virtually any web application.

The Problem (Universal Across Web Apps)

Challenge	Impact
Manual test authoring	1–2 days per user story
Complex DOM (SPAs, Shadow DOM, iframes)	Standard locators fail to find elements
Locator fragility	Tests break with every UI change
Fragmented tooling	Requirement → test involves 5+ manual handoffs
Maintenance burden	60%+ of automation effort spent fixing broken tests

The Solution

An AI-orchestrated pipeline where Kiro acts as the automation engineer:

1. **Reads the requirement** — from Jira, a document, or chat
2. **Creates test cases** — in Zephyr Scale, linked to the source
3. **Generates the feature file** — business-readable Gherkin
4. **Discovers locators live** — Playwright MCP navigates the real app, pierces Shadow DOM, and verifies each locator by interacting with it
5. **Builds the automation** — Page Object + test spec following POM best practices
6. **Runs and self-heals** — executes the test; if a locator breaks, it re-inspects the live page and fixes itself
7. **Reports back** — posts results on the Jira ticket

Key Innovation: The Self-Healing Locator

The breakthrough is **not generating code from guesswork** — it's navigating the live application to discover and confirm locators.

Traditional Approach	Our Approach
Guess locators from DevTools	Healer interacts with the live page
Can't pierce Shadow DOM	Pierces Shadow DOM natively
Breaks on DOM changes	Self-heals by re-inspecting
Manual fixes needed	Auto-discovers working alternatives

Proof of Value — Salesforce Case Study

We chose Salesforce Experience Cloud because it represents a **worst-case difficulty**: Lightning Web Components with deeply nested Shadow DOM, dynamic dependent form fields, and custom widgets with no accessible text.

#	Scenario	Source	Status
1	Incident Creation	Jira ticket	Passing
2	Certificate of Insurance Request	Jira ticket	Passing
3	Expense Request	Document	Passing
4	Request Assessments	Document	Passing
5	Facilities Request	Document	Passing
6	Security Exception Request	Jira ticket	Passing

The takeaway: If it works on Salesforce, it works on your web application — whether that's a public website, a customer portal, an internal tool, or a SaaS product.

What the Framework Can Automate

Application Type	Supported
Public websites & marketing sites	Yes
Single Page Apps (React, Angular, Vue)	Yes
Salesforce & Lightning apps	Yes (proven)
Customer portals & dashboards	Yes
E-commerce & checkout flows	Yes
Banking / insurance web platforms	Yes
Mobile web (responsive)	Yes
Multi-browser (Chromium, Firefox, WebKit)	Yes

Business Impact

Metric	Traditional	AI-Driven	Improvement
Time per user story	1–2 days	6–10 minutes	~95% faster
Locator maintenance	1–4 hours per break	2 minutes (auto-heal)	~97% faster
Requirement → test	Multiple handoffs	Single conversation	Streamlined
First-run pass rate	Low (Salesforce)	High (verified live)	Significantly higher

2. Demo / Presentation

The following sections are structured as presentation slides. Each heading represents one slide.

Slide 1 — The Problem

- Manual test authoring: **1–2 days** per user story
- Complex DOM (SPAs, **Shadow DOM**, iframes) breaks standard locators
- Locators break with **every UI update**
- **60%+** of effort spent on maintenance

Slide 2 — The Solution

- **Kiro** as the AI automation engineer
- **Playwright** for browser automation (pierces Shadow DOM)
- **Self-healing locators** via live page inspection
- **4 flexible workflows** for any entry point

Slide 3 — Proof of Value (Salesforce Case Study)

Tested against Salesforce Experience Cloud — worst-case difficulty (Shadow DOM, dynamic forms):

Scenario	Status
Incident Creation	✓
COI Request	✓
Expense Request	✓
Request Assessments	✓
Facilities Request	✓
Security Exception	✓

100% pass rate

 — if it works on Salesforce, it works on your web app

Slide 4 — Time Savings

Activity	Traditional	AI-Driven
Understand requirement	30 min	5 sec
Create test cases	2 hours	15 sec
Discover locators	4 hours	3 min
Build Page Object	2 hours	30 sec
Write test	2 hours	20 sec
Total per story	1–2 days	6–10 min

Slide 5 — Live Demo Plan

1. **"Automate KD-10"** → watch full pipeline execute
2. **Attach a user story doc** → watch it become a test
3. **"Run all smoke tests"** → watch execution report
4. **Break a locator** → watch the healer fix it

Slide 6 — Key Takeaways

1. **95% faster** — days to minutes
2. **Self-healing** locators eliminate #1 maintenance cost
3. **Salesforce Shadow DOM** fully supported
4. **4 flexible workflows** for any entry point
5. **Full traceability** — requirement to test to report

3. Metrics Report

Framework Capability

Metric	Value
Automation Workflows	4
Steering Documents	12
Supported App Types	Any web app
Supported Browsers	Chromium, Firefox, WebKit
Page Objects (case study)	8

Case Study Execution Results

Scenario	Status
Incident — Create	PASS
Incident — Validation	PASS
COI Request	PASS
Expense Request	PASS
Request Assessments	PASS
Facilities Request	PASS
Security Exception	PASS

Overall Pass Rate: 100%

Performance

Test	Avg Duration
Incident Creation	~31 seconds
COI Request	~35 seconds
Expense Request	~33 seconds
Security Exception	~35 seconds
Average per test	~33 seconds

Efficiency — Time Savings

Activity	Traditional	AI-Driven	Savings
Understand requirement	30 min	5 sec	99%
Create test cases	2 hours	15 sec	99%
Write feature file	1 hour	10 sec	99%
Discover locators	4 hours	3 min	98%
Build Page Object	2 hours	30 sec	99%
Write test spec	2 hours	20 sec	99%
Heal broken locator	1–4 hours	2 min	97%
Total per story	1–2 days	6–10 min	~95%

4. Workflow Walkthrough

Overview of the 4 Workflows

#	Workflow	Trigger	Jira	Zephyr	Automates
1	Jira Automation	"Automate KD-7"	—	✓	✓
2	User Story Automation	Paste story / doc	—	—	✓
3	Story → Jira → Zephyr → Test	"Create in Jira and automate"	✓	✓	✓
4	Test Execution & Reporting	"Run smoke tests"	—	—	Runs existing

Workflow 1: Automate from Jira

1. Read Jira ticket

2. Create Zephyr test cases

3. Generate feature file

4. Discover locators

5. Build Page Object

6. Write test spec

7. Run & heal

8. Post Jira comment

→ getJiraIssue

→ linked to ticket

→ Gherkin with tags

→ Playwright MCP healer (live page)

→ extends BasePage

→ uses fixtures

→ execute, fix, re-run

→ results summary

Workflow 2: User Story to Automation

Paste a requirement in chat or attach a Word/PDF document. Kiro parses it, structures a user story, then generates the feature file, discovers locators, builds the Page Object, writes the test, and runs it. No Jira needed.

Workflow 3: Story → Jira → Zephyr → Automation

The most comprehensive flow. Kiro creates a new Jira ticket, creates Zephyr test cases linked to it, generates the feature file, automates the test, runs it, and posts results back on the ticket — all from a single conversation.

Workflow 4: Test Execution & Reporting

```
npx playwright test --project=chromium --grep @smoke  
npx playwright test --project=chromium --grep @regression  
npx playwright test --project=chromium --grep @e2e
```

Runs the suite, collects results, generates a structured report, and optionally posts to Jira.

5. Framework Documentation

Technology Stack

Layer	Technology
AI Orchestration	Kiro IDE + Steering Documents
Test Runner	Playwright (@playwright/test ^1.45)
Locator Discovery	Playwright MCP (live page inspection)
Test Management	Zephyr Scale (Jira-integrated)
Project Tracking	Jira (Atlassian Cloud)
Language	TypeScript (strict mode)
Reporting	Allure + Playwright HTML
Runtime	Node.js >= 18

Project Structure

```
ai-test-framework/
├── .kiro/steering/           # 12 AI behavior guides
├── src/
│   ├── config/              # .env.dev, .env.staging
│   ├── test-case-management/
│   │   ├── features/istm/    # Gherkin feature files
│   │   └── user-stories/     # Structured user stories
│   ├── playwright/
│   │   ├── pages/           # Page Objects (POM)
│   │   ├── fixtures/        # Test DI
│   │   ├── object-repository/ # Verified locators
│   │   └── tests/            # smoke / regression / e2e
│   └── reporting/           # Reports & artifacts
└── docs/                   # Documentation
```

```
├─ playwright.config.ts
├─ package.json
```

Locator Strategy (Any Web App)

DOM Type	Strategy
Standard HTML	<code>getByRole</code> , <code>getByLabel</code> , <code>getByTestId</code>
Shadow DOM (Web Components)	Playwright native piercing + deep query
iframes	Frame locators
Dynamic SPAs	Auto-waiting + explicit visibility waits
Custom widgets	Attribute selectors (<code>data-value</code> , <code>aria-label</code>)
Native dropdowns	<code>selectOption()</code>

Setup Guide

```
# Install
cd ai-test-framework
npm install
npx playwright install chromium

# Configure src/config/.env.dev
BASE_URL=https://your-application-url
APP_USERNAME=your-username
APP_PASSWORD=your-password
```

Note: Use `APP_USERNAME` / `APP_PASSWORD` (not `username` / `password`) to avoid conflict with Windows system environment variables.

Running Tests

```
npm run test:smoke
npm run test:regression
npm run test:e2e
```

```
# Specific spec
npx playwright test src/playwright/tests/smoke/incident-creation.spec.ts --project=chromium
```

Troubleshooting

Issue	Cause	Fix
Login fills wrong username	Windows env var conflict	Use APP_USERNAME
networkidle timeout	Salesforce background requests	Use domcontentloaded
Locator not found	Element in Shadow DOM	Use healer / data-value
Combobox option not clickable	Text empty in Shadow DOM	Use [data-value]
Missing browsers	Not installed	npx playwright install chromium

Security Considerations

- Kiro runs **locally** — code never leaves your machine
- Credentials in `.env` files (gitignored)
- Use **sandbox** environments only — never production
- Use **synthetic test data** — never real customer PII
- Rotate PATs (Jira, Zephyr) regularly