ATAC-seq Pipeline

Version 2.0.0

Overview

Samples were processed with the BIC ATAC-seq pipeline, which takes aligned, duplicate-marked BAM files and produces filtered alignments, normalized signal tracks (bigWig), MACS2 peak calls for each sample, a merged peak atlas with a raw fragment count matrix, QC metrics and, when the design has replicates, a differential accessibility analysis. The code is at https://github.com/soccin/ATAC-seq/releases/tag/v2.0.0.

Read filtering, the Tn5 shift and peak calling follow the ENCODE ATAC-seq pipeline (ENCODE-DCC/atac-seq-pipeline v2.2.3). The signal tracks, the peak atlas and the count normalization follow the methods of R. Koche (MSKCC Center for Epigenetics Research).

Reads were aligned to one of three reference genomes: GRCh37 (b37), GRCh38 (the GDC `GRCh38.d1.vd1` build, hg38) or GRCm38 (mm10). The build of a project is recorded in the BAM headers. Peaks, signal tracks and the atlas use the autosomes, X and Y only.

Methods

Alignment. Paired-end reads were aligned with BWA-MEM 0.7.19 (Li 2013) using the PEMapper pipeline (https://github.com/soccin/PEMapper), which trims adapters with cutadapt, aligns with `bwa mem -M`, merges lanes, sorts, and marks duplicates with Picard MarkDuplicates 2.25.5. Duplicates are marked in the BAM, not removed. The PEMapper version is in the `@PG` header line of each BAM.

Read filtering. With samtools 1.20 (Danecek 2021) each BAM was reduced to properly paired reads with mapping quality 10 or more, without unmapped reads, reads whose mate is unmapped, secondary alignments, reads failing vendor QC or duplicates (`-q 10 -f 3 -F 1804`). The reads were then name-sorted and passed through `samtools fixmate -r`, and the same flag filter was applied again, which removes a read whose mate did not pass the first filter. This is the filter of the ENCODE ATAC-seq pipeline. There is no filter on insert size. The result was coordinate-sorted with Picard SortSam 3.4.0; this filtered BAM is the input to every later step.

Tn5 shift. Each read was converted to a BED interval with bedtools 2.31.1 (Quinlan 2010) and shifted to place its 5' end at the Tn5 insertion site: +4 bp on the forward strand and -5 bp on the reverse strand (Buenrostro 2013). Reads on the mitochondrial contig and on unplaced, random, decoy and viral contigs were dropped at this step, as in the ENCODE pipeline; the fraction of mitochondrial reads is reported as a QC metric. This set of shifted reads is the input to the signal tracks and to peak calling.

Signal tracks. For each sample the coverage of the shifted reads was computed with bedtools genomecov, each read as its own interval with no extension, scaled to 10 million reads (the scale factor is 10 million divided by the number of shifted reads of the sample), and written as a bigWig with the UCSC wigToBigWig tool (Kent 2010). Tracks are therefore comparable between samples by sequencing depth; the DESeq2 scale factors below are not applied to them.

Peak calling. Peaks were called for each sample with MACS2 2.2.9.1 (Zhang 2008) on the shifted reads, with the settings of the ENCODE ATAC-seq pipeline: `--nomodel --shift -75 --extsize`

`150 --keep-dup all --call-summits -p 0.01` and the genome size `hs` or `mm`. Each read contributes a 150 bp window centered on its insertion site, every read is kept (duplicates were already removed by the filter), and peaks are called at a p-value of 0.01, a permissive cutoff chosen by ENCODE so that peaks can be ranked downstream. MACS2's own output (narrowPeak, summits, xls) is delivered unchanged. The peaks were then post-processed as ENCODE does: sorted by p-value, the 300,000 most significant kept, clipped to the contig ends, peaks overlapping the ENCODE blacklist of the genome removed (Amemiya 2019; Boyle lab blacklist v2 for hg38 and mm10, the DAC consensus excludable list for b37) and the score column capped at 1000. These `blacklistFiltered` peaks and summits are delivered beside MACS2's files and are the peaks used for the atlas.

Peak atlas. The blacklist-filtered peaks of all samples were pooled and merged with bedtools merge, joining peaks within 500 bp of each other into one region (R. Koche's method; ENCODE does not merge peaks). Any blacklisted region bridged by a merge was subtracted, so no atlas region overlaps the blacklist. The result is the peak atlas, one set of regions shared by every sample of the project, written in SAF format (1-based, inclusive coordinates) with the regions named `Peak_1`, `Peak_2`, … in genome order. Because peaks are merged and pooled over samples, the number of atlas regions grows with the number of samples and is not comparable to ENCODE's per-sample peak-count standards; the per-sample `narrowPeak` files are.

Counts. Fragments were counted over the atlas with featureCounts 2.1.1 (Liao 2014) from the filtered BAMs, counting read pairs as single fragments (`-p --countReadPairs`), with a fragment that overlaps two atlas regions counted in both (`-O`), and with the same mapping quality cutoff as the read filter (`-Q 10`). The counts were verified by two independent checks before use: each sample's fragment total must be half its mapped reads, within 5%, and the number of fragments in the atlas, counted a second time with samtools alone, must equal featureCounts' assigned total exactly. A run whose counts fail either check is stopped.

Normalization. Size factors were computed from the raw count matrix with DESeq2 (Love 2014; median-of-ratios method, Anders 2010). They are reported as scale factors, the reciprocal of the DESeq2 size factor, so that a normalized count is the raw count multiplied by the sample's scale factor.

QC. The insert-size distribution of the filtered BAM was computed with Picard CollectInsertSizeMetrics and plotted for all samples, to show the nucleosome-free and nucleosomal fragment populations. The mitochondrial fraction is the number of reads on the mitochondrial contig divided by all reads of the filtered BAM. TSS enrichment was computed with an R port of ENCODE's `encode_task_tss_enrich.py`: the coverage of the shifted reads in a window of 2 kb on each side of every unique protein-coding TSS (ENCODE's TSS sets: GENCODE v24 for hg38, v19 for b37, vM7 for mm10), averaged over TSSs in 400 bins and divided by the mean coverage of the outer 100 bp on each side; the score is the maximum of this profile. ENCODE's reading of the score is given with the output. The fraction of fragments in the atlas and a principal component analysis of the samples (edgeR TMM-normalized log2 CPM over the atlas, after filterByExpr) were plotted from the count matrix.

Differential accessibility. When the design has replicates, pairwise comparisons between groups were tested with edgeR (Robinson 2010; McCarthy 2012). For each comparison, the samples of its two groups were taken from the count matrix, atlas regions with too few counts removed with filterByExpr, library sizes normalized with TMM, dispersions estimated, and a negative binomial generalized linear model fitted and tested with the likelihood ratio test. P-values were adjusted with the Benjamini-Hochberg method (Benjamini 1995) and regions with FDR < 0.05 were called

significant. The sign of the log fold change is group 2 minus group 1 of the comparison: a positive value means more accessible in group 2. Significant regions were annotated with the nearest gene and genomic feature using ChIPseeker (Yu 2015) with the UCSC knownGene annotation of the build and a TSS region of 5 kb on each side.

Tool versions

Tool	Version
BWA-MEM (PEMapper)	0.7.19
Picard MarkDuplicates (PEMapper)	2.25.5
samtools	1.20
Picard SortSam, CollectInsertSizeMetrics	3.4.0
bedtools	2.31.1
UCSC wigToBigWig, bedClip	v369
MACS2	2.2.9.1
featureCounts (subread)	2.1.1
R	4.5.1
ENCODE ATAC-seq pipeline (settings followed)	2.2.3

References

Amemiya HM, Kundaje A, Boyle AP. The ENCODE Blacklist: identification of problematic regions of the genome. Sci Rep 2019;9:9354. doi:10.1038/s41598-019-45839-z

Anders S, Huber W. Differential expression analysis for sequence count data. Genome Biol 2010;11:R106. doi:10.1186/gb-2010-11-10-r106

Benjamini Y, Hochberg Y. Controlling the false discovery rate: a practical and powerful approach to multiple testing. J R Stat Soc B 1995;57:289-300.

Buenrostro JD, Giresi PG, Zaba LC, Chang HY, Greenleaf WJ. Transposition of native chromatin for fast and sensitive epigenomic profiling of open chromatin, DNA-binding proteins and nucleosome position. Nat Methods 2013;10:1213-1218. doi:10.1038/nmeth.2688

Danecek P, et al. Twelve years of SAMtools and BCFtools. GigaScience 2021;10:giab008. doi:10.1093/gigascience/giab008

ENCODE ATAC-seq pipeline. ENCODE Data Coordination Center. https://github.com/ENCOD E-DCC/atac-seq-pipeline. Data standards: https://www.encodeproject.org/atac-seq/

Kent WJ, Zweig AS, Barber G, Hinrichs AS, Karolchik D. BigWig and BigBed: enabling browsing of large distributed datasets. Bioinformatics 2010;26:2204-2207. doi:10.1093/bioinformatics/btq351

Li H. Aligning sequence reads, clone sequences and assembly contigs with BWA-MEM. arXiv 2013;1303.3997.

Liao Y, Smyth GK, Shi W. featureCounts: an efficient general purpose program for assigning sequence reads to genomic features. Bioinformatics 2014;30:923-930. doi:10.1093/bioinformatics/btt656

Love MI, Huber W, Anders S. Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2. Genome Biol 2014;15:550. doi:10.1186/s13059-014-0550-8

McCarthy DJ, Chen Y, Smyth GK. Differential expression analysis of multifactor RNA-Seq experiments with respect to biological variation. Nucleic Acids Res 2012;40:4288-4297. doi:10.1093/nar/gks042

Picard Toolkit. Broad Institute. http://broadinstitute.github.io/picard/

Quinlan AR, Hall IM. BEDTools: a flexible suite of utilities for comparing genomic features. Bioinformatics 2010;26:841-842. doi:10.1093/bioinformatics/btq033

Robinson MD, McCarthy DJ, Smyth GK. edgeR: a Bioconductor package for differential expression analysis of digital gene expression data. Bioinformatics 2010;26:139-140. doi:10.1093/bioinformatics/btp616

Yu G, Wang LG, He QY. ChIPseeker: an R/Bioconductor package for ChIP peak annotation, comparison and visualization. Bioinformatics 2015;31:2382-2383. doi:10.1093/bioinformatics/btv145

Zhang Y, et al. Model-based analysis of ChIP-Seq (MACS). Genome Biol 2008;9:R137. doi:10.1186/gb-2008-9-9-r137